



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH18

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839894.92
N 816538.77

DATE from 6/5/96 to 8/5/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.88 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX		80					PX		0.00			Concrete with red brick fragments. (FILL)
			60					PX		0.50			
			50					PX		1.00			
	PX 1.50m HX		80					PX		1.50			
2			30					HX		2.00			
3								HX		2.50			Wash Boring. (No Recovery)
								HX		3.00			
								HX		3.50			
4									1.38	4.00			
5										5.00			
6										6.00			
7										7.00			
8										8.00			
9										9.00			
10										10.00			

• SMALL DISTURBED SAMPLE	Δ WATER SAMPLE
○ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	□ STANDPIPE
▨ U76 UNDISTURBED SAMPLE	↓ STANDARD PENETRATION TEST
▨ U100 UNDISTURBED SAMPLE	⊥ PERMEABILITY TEST
▨ MAZIER SAMPLE (70mm)	∇ IN-SITU VANE SHEAR TEST
▨ PISTON SAMPLE	

LOGGED FRANK CHAN

DATE 09/05/96

APPROVED C.LUN

DATE 10/05/96

REMARKS

Hole termination depth at 29.71m



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH18

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839894.92

DATE from 6/5/96 to 8/5/96

N 816538.77

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.88 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.O.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11										11.00			Wash Boring. (No Recovery)
12										12.00			
13										13.00			
14										14.00			
15										15.00			
16										16.00			
17										17.00			
18										18.00			
19			50					T-74	-13.52 -13.82	18.40 18.70			
20										20.00			Sub-rounded COBBLES and GRAVELS of moderately decomposed tuff and granite with some silty sand. (ALLUVIUM) Wash boring at 18.70m-21.20m. (No Recovery)

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- ▲ WATER SAMPLE
- ▲ PIEZOMETER TIP
- ▲ STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 09/05/96

APPROVED C.LUN

DATE 10/05/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH18

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839894.92
N 816538.77

DATE from 6/5/96 to 8/5/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.88 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21	NX 23.77m		65					T-76	-16.32	21.20			Sub-rounded COBBLES and GRAVELS of moderately decomposed tuff and granite with some silty sand. (ALLUVIUM) Wash boring at 18.70m-21.20m. (No Recovery)
22									-17.62	22.50			
23									-18.89	23.77			
24			100	98	71	15.0		T-76				III	Moderately weak to moderately strong, brownish pink spotted black and white, moderately decomposed medium to coarse grained GRANITE with medium to closely spaced, very narrow, rough planar, limonite, manganese stained, kaolin and chlorite coated joints, dipping 10°-20°, 40°-50°, 65°-80° and vertical joints.
25			100	100	92	2.9		T-76		24.74			
26			100	70	25	20.0		T-76		25.23			
27			100	100	64	14.0		T-76		26.74			
28	08/05/96		100	100	89	6.0		T-76		28.24			
29										29.03			
30			100	100	88	2.9		T-76	-24.83	29.71			End of hole at 29.71m.

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 09/05/96

APPROVED C.LUN

DATE 10/05/96

REMARKS