



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH25

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839895.23

DATE from 20/4/96 to 23/4/96

N 816557.36

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.48 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX		18					PX	3.48	1.00			Wash Boring. (No Recovery)
2			63					T2-101		1.70			Angular COBBLES and GRAVELS of moderately decomposed granite with some brown, silty SAND and some red brick and concrete fragments. (FILL)
3			0					T2-101		2.50			
4										3.50			
5			50					T2-101		4.00			
6	PX 6.00m HX		33					T2-101		4.80			Wash Boring. (No Recovery)
7										6.00			
8													
9													
10													

• SMALL DISTURBED SAMPLE	▲ WATER SAMPLE
■ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	□ STANDPIPE
■ U76 UNDISTURBED SAMPLE	┆ STANDARD PENETRATION TEST
■ U100 UNDISTURBED SAMPLE	┆ PERMEABILITY TEST
▨ MAZIER SAMPLE (70mm)	┆ IN-SITU VANE SHEAR TEST
▨ PISTON SAMPLE	

LOGGED FRANK CHAN

DATE 24/04/96

APPROVED C.LUN

DATE 25/04/96

REMARKS
Hole termination depth at 29.80m



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH25

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839895.23
N 816557.36

DATE from 20/4/96 to 23/4/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.48 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11							(2, 3, 1, 7, 8, 9) N = 25	1	-6.02	10.00 10.45 10.50			Medium dense, grey, silty fine to medium SAND with occasionally some shell fragments. (MARINE DEPOSIT) Stiff, grey, sandy silty CLAY. (ALLUVIUM)
12													
13							(1, 2, 1, 1, 2, 5) N = 9	2		13.00 13.45			
14													
15													
16							(1, 1, 2, 1, 3, 5) N = 11	3	-11.52	16.00 16.45			Medium dense, grey, clayey silty fine to medium SAND. (ALLUVIUM)
17													
18													
19							(1, 3, 7, 2, 5, 3) N = 17	4	-15.12	19.00 19.45 19.60			
20			38					T2-101	-15.52	20.00			Sub-rounded COBBLES and GRAVELS of moderately

- | | |
|---------------------------|-----------------------------|
| • SMALL DISTURBED SAMPLE | ▲ WATER SAMPLE |
| ▮ LARGE DISTURBED SAMPLE | ■ PIEZOMETER TIP |
| ▨ SPT LINER SAMPLE | △ STANDPIPE |
| ▩ U76 UNDISTURBED SAMPLE | ↓ STANDARD PENETRATION TEST |
| ▪ U100 UNDISTURBED SAMPLE | ⊥ PERMEABILITY TEST |
| ▬ MAZIER SAMPLE (70mm) | ∇ IN-SITU VANE SHEAR TEST |
| ▮ PISTON SAMPLE | |

LOGGED FRANK CHAN

DATE 24/04/96

APPROVED C.LUN

DATE 25/04/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH25

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839895.23
N 816557.36

DATE from 20/4/96 to 23/4/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.48 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21												V	decomposed granite and tuff with some grey, silty SAND. (ALLUVIUM) Extremely weak, brownish pink spotted black and white, completely decomposed, medium to coarse grained GRANITE. (Very dense, gravelly silty medium to coarse SAND.)
22							(18, 22, 30, 30, 42, 50) N = 152	5		22.00			
23										22.45			
24	HX 24.04m								-19.56	24.04			
25			100	76	55	15.8		T2-101		24.33		III	Moderately weak to moderately strong, brownish pink spotted black and white, moderately decomposed medium to coarse grained GRANITE with medium spaced, extremely narrow, rough planar, limonite, manganese stained and kaolin coated joints, dipping 10°-20° and 40°-60°.
26			100	100	100	2.7		T2-101		24.92			
27			100	100	100			T2-101		25.44			Weak, highly decomposed zone at 24.23m-24.33m.
28			100	100	100	0.8		T2-101		26.94			
29			100	100	100			T2-101		28.44			
30			100	100	97	2.8		T2-101		29.80			End of hole at 29.80m.

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 24/04/96

APPROVED C.LUN

DATE 25/04/96

REMARKS