



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B6a

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. D-12

E 839910.71

DATE from 18/7/96 to 20/7/96

N 816492.51

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.60 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX							INSPECTION PIT					0.00-2.50m: wash boring
2									2.10	2.50			
3	PX 3.00m HX		88					PX	1.70	2.90			Rounded to subrounded, COBBLES and fine to coarse GRAVEL. No recovery assumed, finer material washed out. (FILL) 2.90-14.90m: wash boring.
4													
5													
6													
7													
8													
9													
10													

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED BENNY WONG

DATE 05/08/96

APPROVED C. LUN

DATE 06/08/96

REMARKS

Hole termination depth at 28.50m.
Inspection pit at 0.00m to 2.00m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B6a

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. D-12

E 839910.71
N 816492.51

DATE from 18/7/96 to 20/7/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.60 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11													
12													
13													
14													
15	HX 14.90m NX		81	75	52				-10.30	14.90	+	IV/III	Moderately strong to moderately weak, brownish grey, spotted black and white, moderately to highly decomposed, medium grained GRANITE with closely spaced, narrow to very narrow, rough undulating, limonite and manganese stained joints, dipping 15° to 35°.
16									-11.30	15.90	+		15.90-20.55m: wash boring
17													
18													
19													
20													

- SMALL DISTURBED SAMPLE
- ▬ LARGE DISTURBED SAMPLE
- ▨ SPT LIVER SAMPLE
- ▨ U76 UNDISTURBED SAMPLE
- ▨ U100 UNDISTURBED SAMPLE
- ▨ MAZIER SAMPLE (70mm)
- ▨ PISTON SAMPLE
- ▲ WATER SAMPLE
- ▲ PIEZOMETER TIP
- ▲ STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED BENNY WONG

DATE 05/08/96

APPROVED C. LUN

DATE 06/08/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B6a

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. D-12

E 839910.71
N 816492.51

DATE from 18/7/96 to 20/7/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.60 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21	NX 20.55m		90	90	90	5.8		T2 -101	-15.95	20.55	+	II/III	Moderately strong to strong, pinkish grey, spotted black and white, moderately to slightly decomposed medium grained GRANITE with closely to extremely closely spaced, narrow to very narrow, rough undulating, limonite and manganese stained joints, dipping 15° to 35°. 21.58-21.76m: no recovery assumed highly decomposed zone. 21.76-22.72m: moderately strong to weak, moderately to highly decomposed zone. Moderately strong to strong, pinkish grey, spotted black and white, moderately to slightly decomposed medium grained GRANITE with closely spaced, very narrow to extremely narrow, rough undulating, limonite and manganese stained joints, dipping 5° to 10°.
			98	98	72			T2 -101	-16.98	21.15	+		
			0	0	0	NR		T2 -101	-17.16	21.58	+	IV	
22			86	42	17	17.5		T2 -101	-17.16	21.76	+	III/IV	
						NI		T2 -101	-18.12	22.16	+		
23			100	97	70			T2 -101	-18.12	22.72	+	III/II	
24			100	100	70			T2 -101	-23.89	23.89	+		
25			100	100	100	4.8		T2 -101	-24.82	24.82	+		
26			100	100	93			T2 -101	-26.30	26.30	+		
27			100	100	100			T2 -101	-27.38	27.38	+		
28			100	100	100			T2 -101	-23.90	28.50	+		
29													End of hole at 28.50m.
30													

- SMALL DISTURBED SAMPLE
- ▬ LARGE DISTURBED SAMPLE
- ▬ SPT LINER SAMPLE
- ▬ U76 UNDISTURBED SAMPLE
- ▬ U100 UNDISTURBED SAMPLE
- ▬ MAZIER SAMPLE (70mm)
- ▬ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED BENNY WONG

DATE 05/08/96

APPROVED C. LUN

DATE 06/08/96

REMARKS