



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B5

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. SM400-04

E 839906.13
N 816512.28

DATE from 31/1/96 to 1/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	SX		80					▲ SX	4.24	0.20	▲ ▲		Concrete Slab.
2			100					▼ SX		1.00			Concrete with COBBLES and GRAVELS of moderately decomposed granite and some red bricks. (FILL)
3	SX 3.00m PX								2.64	1.80			Wash boring. (No recovery)
4													
5													
6													
7													
8													
9													
10													

- SMALL DISTURBED SAMPLE
- ▬ LARGE DISTURBED SAMPLE
- ▨ SPT LINER SAMPLE
- ▩ U76 UNDISTURBED SAMPLE
- ▩ U100 UNDISTURBED SAMPLE
- ▩ MAZIER SAMPLE (70mm)
- ▩ PISTON SAMPLE
- ▲ WATER SAMPLE
- ▲ PIEZOMETER TIP
- ▢ STANDPIPE
- ┆ STANDARD PENETRATION TEST
- ┆ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 02/02/96

APPROVED C.LUN

DATE 03/02/96

REMARKS
Hole termination depth at 29.96m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B5

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. SM400-04

E 839906.13

DATE from 31/1/96 to 1/2/96

N 816512.28

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/ end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11													AS SHEET 1 OF 3.
12	PX 12.00m HX												
13													
14													
15													
16													
17													
18													
19													
20			100	33	25	> 20.0		T2-101	-14.86 -15.46	19.30 19.90	IV/III		SEE SHEET 3 OF 3.

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 02/02/96

APPROVED C.LUN

DATE 03/02/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. B5

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. SM400-04

E 839906.13

DATE from 31/1/96 to 1/2/96

N 816512.28

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21	HX		100	33	25	NI		T2-101	-15.86	20.30	+	IV/III	Weak to moderately weak, brownish pink spotted black and white, highly to moderately decomposed, medium to coarse grained GRANITE with closely spaced, narrow, rough planar, limonite, manganese stained joints, dipping 10°-20°. Strong, pinkish grey spotted black and white, slightly decomposed, medium to coarse grained GRANITE with widely to medium spaced and occasionally closely spaced, extremely narrow to very narrow, rough planar, limonite, manganese stained joints, dipping 10°-20° & 40°-50°. 20.30m-20.75m & 22.48m-22.80m: moderately decomposed, medium to coarse grained GRANITE.
31/01/96	NX		100	100	89	4.3		T2-101	-16.31	20.75	+	III	
			100	100	65	10.0		T-74		21.23	+	II	
22			100	100	89	1.3		T-74		21.63	+		
	NX								-18.04	22.48	+		
23			100	100	97	3.8		T-74	-18.36	22.80	+	III	
											+	II	
24			100	100	92	2.9		T-74		23.98	+		
						11.1				24.66	+		
25			100	100	100	0.0		T-74		24.93	+		
										25.45	+		
26			100	100	97	9.4		T-74		25.91	+		
01/02/96										26.23	+		
27										26.94	+		
			100	100	100	1.3		T-74		28.46	+		
28											+		
29			100	100	100			T-74			+		
											+		
30									-25.52	29.96	+		End of hole at 29.96m.

• SMALL DISTURBED SAMPLE	△ WATER SAMPLE
□ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	□ STANDPIPE
▨ U76 UNDISTURBED SAMPLE	↓ STANDARD PENETRATION TEST
▨ U100 UNDISTURBED SAMPLE	⊥ PERMEABILITY TEST
▨ MAZIER SAMPLE (70mm)	∇ IN-SITU VANE SHEAR TEST
▨ PISTON SAMPLE	

LOGGED FRANK CHAN

DATE 02/02/96

APPROVED C.LUN

DATE 03/02/96

REMARKS