

		BACHY SOLETANCHE GROUP SOIL & FOUNDATIONS SPECIALISTS		DRILLHOLE RECORD CONTRACT		HOLE NO. DH15							
						SHEET 1 of 3							
PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY													
METHOD ROTARY				CO-ORDINATES E 839894.82 N 816531.09		W.O. W-518							
MACHINE & No. YBM-37						DATE from 20/3/96 to 22/3/96							
FLUSHING MEDIUM WATER				ORIENTATION Vertical		GROUND-LEVEL 4.52 mPD							
Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX		70					PX		1.00			Angular red bricks and concrete fragments with some grey, silty SAND. (FILL)
2			75					PX		2.00			
3	PX 3.00m HX		40					T2-101	1.52	3.00			
4													Wash boring. (No recovery)
5													
6													
7													
8													
9													
10													
20/03/96													
• SMALL DISTURBED SAMPLE ▬ LARGE DISTURBED SAMPLE ▨ SPT LINER SAMPLE ▩ U78 UNDISTURBED SAMPLE ▪ U100 UNDISTURBED SAMPLE ▧ MAZIER SAMPLE (70mm) ▦ PISTON SAMPLE								▲ WATER SAMPLE ▴ PIEZOMETER TIP □ STANDPIPE ↓ STANDARD PENETRATION TEST ⊥ PERMEABILITY TEST ∨ IN-SITU VANE SHEAR TEST		LOGGED <u>FRANK CHAN</u> DATE <u>23/03/96</u> APPROVED <u>C.LUN</u> DATE <u>25/03/96</u>		REMARKS Hole termination depth at 25.12m.	



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH15

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM-37

E 839894.82

DATE from 20/3/96 to 22/3/96

N 816531.09

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.52 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11													AS SHEET 1 OF 3.
12													
13													
14													
15													
16													
17													
18													Sub-rounded GRAVEL and COBBLES of moderately decomposed granite and tuff with some brown, silty sand. (ALLUVIUM)
19			100					T2-101	-13.48	18.00			
20								T2-101	-14.48	19.00			Weak to moderately weak, brownish pink spotted black and white, highly to moderately decomposed, medium to coarse grained GRANITE with medium spaced, very narrow, rough
			70	70	40	5.7			-14.83	19.35	IV/III		
						NR			-14.98	19.50	IV		
20									-15.48	20.00			

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- ▨ SPT LINER SAMPLE
- ▨ U76 UNDISTURBED SAMPLE
- ▨ U100 UNDISTURBED SAMPLE
- ▨ MAZIER SAMPLE (70mm)
- ▨ PISTON SAMPLE
- △ WATER SAMPLE
- ▲ PIEZOMETER TIP
- △ STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 23/03/96

APPROVED C.LUN

DATE 25/03/96

REMARKS

		BACHY SOLETANCHE GROUP SOIL & FOUNDATIONS SPECIALISTS		DRILLHOLE RECORD				HOLE NO. DH15					
				CONTRACT				SHEET 3 of 3					
PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY													
METHOD ROTARY				CO-ORDINATES E 839894.82 N 816531.09				W.O. W-518					
MACHINE & No. YBM-37								DATE from 20/3/96 to 22/3/96					
FLUSHING MEDIUM WATER				ORIENTATION Vertical				GROUND-LEVEL 4.52 mPD					
Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21			100	100	100			T-76		20.92	+	III/II	planar, limonite, manganese stained joints, dipping 20°-30°, 70°-80°. 19.35m-19.50m: no recovery. 19.50m-20.00m: wash boring. Moderately strong to strong, brownish pink spotted black and white, moderately to slightly decomposed, medium to coarse grained GRANITE, with medium to closely spaced, very narrow to extremely narrow, rough planar, limonite and manganese stained joints, dipping 10°-20°, 40°-60° & 70°-80°.
22			100	100	76	2.7		T-76		21.86	+		
			100	100	92	> 20.0		T-76		22.12	+		
23			100	100	85	5.0		T-76		22.72	+		
24			100	100	80	8.3		T-76		23.92	+		
25			100	100	80	8.3		T-76		25.12	+		
26													End of hole at 25.12m.
27													
28													
29													
30													
• SMALL DISTURBED SAMPLE ▮ LARGE DISTURBED SAMPLE ▨ SPT LINER SAMPLE ▩ U76 UNDISTURBED SAMPLE ▪ U100 UNDISTURBED SAMPLE ▧ MAZIER SAMPLE (70mm) ▦ PISTON SAMPLE								Δ WATER SAMPLE ▲ PIEZOMETER TIP ▽ STANDPIPE STANDARD PENETRATION TEST ⊥ PERMEABILITY TEST ∨ IN-SITU VANE SHEAR TEST		LOGGED <u>FRANK CHAN</u> DATE <u>23/03/96</u> APPROVED <u>C.LUN</u> DATE <u>25/03/96</u>		REMARKS	