



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH28

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-41

E 839895.46
N 816566.24

DATE from 2/2/96 to 5/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.55 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	SX							INSPECTION PIT	3.35	0.20			Concrete Slab.
2									1.55	1.80			Brown, gravelly silty medium to coarse SAND. (FILL)
3	SX 2.50m PX		42					T2 -101	1.05	2.50			Wash boring. (No recovery)
4								T2 -101		3.70			Angular Boulders, Cobbles and Gravels of moderately decomposed granite with some brown, silty SAND. (FILL)
5			32					T2 -101		5.10			3.50m-3.70m: boulder.
6			61					T2 -101		6.00			3.80m-4.08m: boulder.
7			42					T2 -101					5.63m-5.95m: boulder.
8									-4.25	7.80			Wash boring. (No recovery)
9													
10													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- △ STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 06/02/96

APPROVED C.LUN

DATE 07/02/96

REMARKS

Hole termination depth at 29.35m.
Inspection Pit from 0.00m to 1.80m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH28

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-41

E 839895.46
N 816566.24

DATE from 2/2/96 to 5/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.55 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11													AS SHEET 1 OF 3.
12													
13													
14													
15	PX 15.00m HX 03/02/96												
16													
17													
18			67				T2-101		-13.95 -14.55	17.50 18.10			
19													
20													

Sub-rounded Cobbles and Gravels of moderately decomposed granite and tuff with some brown, silty SAND. (ALLUVIUM)
Wash boring. (No recovery)

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ⊥ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 06/02/96

APPROVED C.LUN

DATE 07/02/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH28

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-41

E 839895.46

DATE from 2/2/96 to 5/2/96

N 816566.24

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.55 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21													AS SHEET 2 OF 3.
22													
23													
24	HX 23.67m		100	100	100	4.8		T2-101	-20.12	23.67	+	III/II	Moderately strong to strong, pinkish grey spotted black and white, moderately to slightly decomposed medium to coarse grained GRANITE with widely to medium spaced, very narrow to extremely narrow, rough planar, limonite, manganese stained, kaolin coated joints, dipping 10°-20°, 40°-50°, 60°-70°.
25			100	100	85			T2-101		24.10	+		
26			100	100	100	0.0		T2-101		24.72	+		
27			100	100	100			T2-101		24.95	+		
28			100	100	100			T2-101		25.50	+		
29			100	100	100	2.9		T2-101		26.24	+		
30			100	100	100			T2-101		26.44	+		
								T2-101		27.80	+		
								T2-101		27.80	+		
								T2-101		29.35	+		
									-25.80	29.35			End of hole at 29.35m.

• SMALL DISTURBED SAMPLE	Δ WATER SAMPLE
▬ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	□ STANDPIPE
▩ U76 UNDISTURBED SAMPLE	⊥ STANDARD PENETRATION TEST
▩ U100 UNDISTURBED SAMPLE	⊥ PERMEABILITY TEST
▩ MAZIER SAMPLE (70mm)	∇ IN-SITU VANE SHEAR TEST
▩ PISTON SAMPLE	

LOGGED FRANK CHAN

DATE 06/02/96

APPROVED C.LUN

DATE 07/02/96

REMARKS