



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH38

CONTRACT

SHEET 1 of 4

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. ACKER-35

E 839920.84
N 816562.25

DATE from 7/2/96 to 9/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.68 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	SX		100					INSPECTION PIT	3.48	0.20			Concrete Slab.
2									2.98	0.70			Brown, gravelly silty medium to coarse SAND. (FILL)
3	SX 3.00m HX		100					SX		1.70			Concrete with GRAVEL and COBBLES of moderately decomposed granite with some red bricks. (FILL)
4			100					T2 -101		3.00			
5			93					T2 -101		4.24			
6			61					T2 -101	-1.56	5.24			Angular GRAVEL, COBBLES and BOULDERS of moderately decomposed granite and tuff with some brown, silty SAND and some concrete fragments. (FILL)
7			75					T2 -101		6.06			6.26m-6.77m: boulder.
8			63					T2 -101	-4.32	8.00			
9													Wash boring. (No recovery)
10													

• SMALL DISTURBED SAMPLE	▲ WATER SAMPLE
▬ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▬ SPT LINER SAMPLE	▲ STANDPIPE
▬ U76 UNDISTURBED SAMPLE	▬ STANDARD PENETRATION TEST
▬ U100 UNDISTURBED SAMPLE	▬ PERMEABILITY TEST
▬ MAZIER SAMPLE (70mm)	▬ IN-SITU VANE SHEAR TEST
▬ PISTON SAMPLE	

LOGGED FRANK CHAN

DATE 10/02/96

APPROVED C.LUN

DATE 12/02/96

REMARKS

Hole termination depth at 30.05m.
Inspection Pit from 0.00m to 0.70m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH38

CONTRACT

SHEET 2 of 4

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. ACKER-35

E 839920.84
N 816562.25

DATE from 7/2/96 to 9/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.68 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11													AS SHEET 1 OF 4.
12													
13													
14													
15													
16													
17													
18			62					T2-101	-14.32	18.00			
19									-14.82	18.50			
20													

Sub-rounded GRAVEL and COBBLES of moderately decomposed granite and tuff with some brown, silty SAND. (ALLUVIUM)
Wash boring. (No recovery)

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 10/02/96

APPROVED C.LUN

DATE 12/02/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH38

CONTRACT

SHEET 3 of 4

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. ACKER-35

E 839920.84
N 816562.25

DATE from 7/2/96 to 9/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.68 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21													AS SHEET 2 OF 4.
22													
23													
24													
25	HX 24.65m		100	100	73	8.9		T2-101	-20.97	24.65	+	III	Moderately strong, brownish pink spotted black and white, moderately decomposed medium to coarse grained GRANITE with medium to closely spaced, very narrow, rough planar, limonite, manganese stained, kaolin and chlorite coated joints, dipping 10°-20°, 40°-50° & 60°-75°.
26	NX		100	100	88	3.0		T2-101		24.91	+		
27			100	100	74	8.1		T2-101		25.10	+		
28	NX 27.66m		100	100	54	7.3		T2-101		25.76	+		
29			100	100	100	4.8		T-74		26.28	+		
30			100	100	69	9.4		T-74		27.25	+		
										27.66	+		
										28.91	+		

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- ▨ SPT LINER SAMPLE
- ▨ U76 UNDISTURBED SAMPLE
- ▨ U100 UNDISTURBED SAMPLE
- ▨ MAZIER SAMPLE (70mm)
- ▨ PISTON SAMPLE
- △ WATER SAMPLE
- ▲ PIEZOMETER TIP
- △ STANDPIPE
- ┆ STANDARD PENETRATION TEST
- ┆ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 10/02/96

APPROVED C.LUN

DATE 12/02/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

CONTRACT

HOLE NO. DH38

SHEET 4 of 4

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. ACKER-35

E 839920.84
N 816562.25

DATE from 7/2/96 to 9/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 3.68 mPD

Drilling Progress	Casing size	Water level (m) Shift start/ end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
31									26.37	30.05			AS SHEET 3 OF 4. End of hole at 30.05m.
32													
33													
34													
35													
36													
37													
38													
39													
40													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- PIEZOMETER TIP
- Δ STANDPIPE
- ▮ STANDARD PENETRATION TEST
- ▮ PERMEABILITY TEST
- ▮ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 10/02/96

APPROVED C.LUN

DATE 12/02/96

REMARKS