



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH16

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM 37

E 839894.90
N 816533.57

DATE from 25/3/96 to 28/3/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.46 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX		100					PX		0.00			Angular COBBLES and GRAVELS of moderately decomposed granite and tuff with some grey, silty SAND and some red brick and concrete fragments and some domestic rubbish. (FILL)
2			100					PX	2.46	2.00			
3	PX 3.00m HX												Wash Boring. (No Recovery)
4													
5													
6													
7													
8													
9													
10													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ⊥ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED F.CHAN
DATE 29/03/96
APPROVED C.LUN
DATE 30/03/96

REMARKS
Hole termination depth at 27.45m

		BACHY SOLETANCHE GROUP SOIL & FOUNDATIONS SPECIALISTS		DRILLHOLE RECORD				HOLE NO. DH16						
		CONTRACT				SHEET 2 of 3								
PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY														
METHOD ROTARY				CO-ORDINATES				W.O. W-518						
MACHINE & No. YBM 37				E 839894.90 N 816533.57				DATE from 25/3/96 to 28/3/96						
FLUSHING MEDIUM WATER				ORIENTATION Vertical				GROUND-LEVEL 4.46 mPD						
Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description	
11 25/03/96													Wash Boring. (No Recovery)	
12	HX 12.00m NX													
13														
14														
15														
16 26/03/96														
17														
18														
19			40					↑ 1-76	-14.04	18.50	○			Sub-rounded to rounded BOULDERS, COBBLES and GRAVELS of moderately decomposed granite and tuff with some brown, silty SAND. (ALLUVIUM) Boulder at 19.50m-19.70m.
20			40					↓ 1-76		19.50	○			
• SMALL DISTURBED SAMPLE ▲ WATER SAMPLE ▬ LARGE DISTURBED SAMPLE ▲ PIEZOMETER TIP ▨ SPT LINER SAMPLE □ STANDPIPE ▩ U76 UNDISTURBED SAMPLE STANDARD PENETRATION TEST ▩ U100 UNDISTURBED SAMPLE PERMEABILITY TEST ▩ MAZIER SAMPLE (70mm) V IN-SITU VANE SHEAR TEST ▩ PISTON SAMPLE LOGGED <u>F.CHAN</u> DATE <u>29/03/96</u> APPROVED <u>C.LUN</u> DATE <u>30/03/96</u>								REMARKS						



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH16

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM 37

E 839894.90
N 816533.57

DATE from 25/3/96 to 28/3/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.46 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21	NX 22.00M		40					T-74		20.50			Sub-rounded to rounded BOULDERS, COBBLES and GRAVELS of moderately decomposed granite and tuff with some brown, silty SAND. (ALLUVIUM) Boulder at 19.50m-19.70m.
			60					T-76		21.00			
			30					T-76					
22			100	100	100	1.6		T-74	-17.54	22.00		III/II	Moderately strong to strong, pinkish grey to grey spotted black and white, moderately to slightly decomposed medium to coarse grained GRANITE with widely to medium spaced and occasionally closely spaced, extremely narrow, rough planar, limonite and manganese stained joints, dipping 10°-20°, 70°-80°.
			100	100	100			T-76		22.39			
23			100	100	100			T-74		22.74			
24			100	100	100	1.4		T-74		23.73			
			100	100	89			T-76		24.45			
25			100	100	100			T-74					
26			100	100	100	7.2		T-74		25.95			
			100	100	100			T-76		26.33			
27			100	100	98			T-74	-22.99	27.45			
28													End of hole at 27.45m.
29													
30													

• SMALL DISTURBED SAMPLE	Δ WATER SAMPLE
▬ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	◻ STANDPIPE
▩ U76 UNDISTURBED SAMPLE	⊥ STANDARD PENETRATION TEST
▩ U100 UNDISTURBED SAMPLE	⊥ PERMEABILITY TEST
▩ MAZIER SAMPLE (70mm)	∨ IN-SITU VANE SHEAR TEST
▩ PISTON SAMPLE	

LOGGED F.CHAN
DATE 29/03/96
APPROVED C.LUN
DATE 30/03/96

REMARKS