



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH10

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839894.66
N 816517.40

DATE from 24/4/96 to 26/4/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.77 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX									1.00			Wash Boring. (No Recovery)
2										2.00			
3										2.50			
4			0					T2 -101		3.00			
5	PX 4.50m HX									4.00			
6										5.00			
7										6.00			
8	HX 7.50m NX									7.00			
9										8.00			
10										9.00			

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ⊥ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 27/04/96

APPROVED C.LUN

DATE 29/04/96

REMARKS

Hole termination depth at 27.43m



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH10

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839894.66
N 816517.40

DATE from 24/4/96 to 26/4/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.77 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
11										10.00			Wash Boring. (No Recovery)
12										11.00			
13										12.00			
14										13.00			
15										14.00			
16										15.00			
17										16.00			
18										17.00			
19			80						-14.23	19.00			
20									-14.73	19.50			
										20.00			Sub-rounded COBBLES and GRAVELS of moderately decomposed granite and tuff with some grey, silty SAND. (ALLUVIUM)

- SMALL DISTURBED SAMPLE
- LARGE DISTURBED SAMPLE
- SPT LINER SAMPLE
- U76 UNDISTURBED SAMPLE
- U100 UNDISTURBED SAMPLE
- MAZIER SAMPLE (70mm)
- PISTON SAMPLE
- WATER SAMPLE
- PIEZOMETER TIP
- STANDPIPE
- STANDARD PENETRATION TEST
- PERMEABILITY TEST
- IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 27/04/96

APPROVED C.LUN

DATE 29/04/96

REMARKS



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH10

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM36

E 839894.66
N 816517.40

DATE from 24/4/96 to 26/4/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.77 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21 25/04/96	NX 21.20m									20.00			Wash Boring. (No Recovery)
22			100	66	25	9.1		T-76	-16.43	21.20		III	Moderately weak to moderately strong, brownish pink spotted black and white, moderately decomposed medium to coarse grained GRANITE with medium to closely spaced, very narrow, rough planar, limonite and manganese stained and kaolin coated joints, dipping 10°-20° and 50°-60°. Moderately strong to strong, greyish pink spotted black and white, moderately to slightly decomposed medium to coarse grained GRANITE with widely to medium spaced, extremely narrow, rough planar, limonite and manganese stained joints, dipping 10°-20° and 50°-60°.
						NI							
23			100	100	71	4.8		T-76	-17.30	22.07		III/II	
						NI				22.70			
24			100	97	97			T-76					
25 26/04/96													
			100	100	92			T-76		24.25			
26			100	100	94	1.5		T-76		25.25			
27			100	100	100			T-76		26.34			
										26.81			
			100	100	100			T-76		27.43			
28									-22.66				End of hole at 27.43m.
29													
30													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- Δ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ┃ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 27/04/96

APPROVED C.LUN

DATE 29/04/96

REMARKS