

BACHY SOLETANCHE GROUP SOIL & FOUNDATIONS SPECIALISTS		DRILLHOLE RECORD		HOLE NO. DH16	
		CONTRACT		SHEET 2 of 3	
PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY					
METHOD ROTARY			CO-ORDINATES		W.O. W-518
MACHINE & No. YBM 37			E 839894.90 N 816533.57		DATE from 25/3/96 to 28/3/96
FLUSHING MEDIUM WATER			ORIENTATION Vertical		GROUND-LEVEL 4.46 mPD
Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.
					Fracture Index
					Tests
					Samples
					Reduced Level
					Depth (m)
					Legend
					Grade
Description					
11					
12	HX 12.00m NX				
13					
14					
15					
16					
17					
18					
19			40		
20			40		
11/03/96 25/03/96 26/03/96 14.04 18.50 19.50 Wash Boring. (No Recovery) Sub-rounded to rounded BOULDERS, COBBLES and GRAVELS of moderately decomposed granite and tuff with some brown, silty SAND. (ALLUVIUM) Boulder at 19.50m-19.70m.					
SMALL DISTURBED SAMPLE LARGE DISTURBED SAMPLE SPT LINER SAMPLE U76 UNDISTURBED SAMPLE U100 UNDISTURBED SAMPLE MAZIER SAMPLE (70mm) PISTON SAMPLE WATER SAMPLE PIEZOMETER TIP STANDPIPE STANDARD PENETRATION TEST PERMEABILITY TEST IN-SITU VANE SHEAR TEST			LOGGED <u>F.CHAN</u> DATE <u>29/03/96</u> APPROVED <u>C.LUN</u> DATE <u>30/03/96</u> REMARKS		



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. DH16

CONTRACT

SHEET 3 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. YBM 37

E 839894.90

DATE from 25/3/96 to 28/3/96

N 816533.57

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.46 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
21	NX 22.00M		40					T-74		20.50			Sub-rounded to rounded BOULDERS, COBBLES and GRAVELS of moderately decomposed granite and tuff with some brown, silty SAND. (ALLUVIUM) Boulder at 19.50m-19.70m.
			60					T-76		21.00			
			30					T-76					
22			100	100	100	1.6		T-74	-17.54	22.00		III/II	Moderately strong to strong, pinkish grey to grey spotted black and white, moderately to slightly decomposed medium to coarse grained GRANITE with widely to medium spaced and occasionally closely spaced, extremely narrow, rough planar, limonite and manganese stained joints, dipping 10°-20°, 70°-80°.
			100	100	100			T-76		22.39			
23			100	100	100			T-74		22.74			
24			100	100	100	1.4		T-74		23.73			
			100	100	89			T-76		24.45			
25			100	100	100			T-74					
26			100	100	100	7.2		T-74		25.95			
			100	100	100			T-76		26.33			
27			100	100	98			T-74	-22.99	27.45			
28													End of hole at 27.45m.
29													
30													

• SMALL DISTURBED SAMPLE	Δ WATER SAMPLE
▬ LARGE DISTURBED SAMPLE	▲ PIEZOMETER TIP
▨ SPT LINER SAMPLE	◻ STANDPIPE
▩ U76 UNDISTURBED SAMPLE	⊥ STANDARD PENETRATION TEST
▩ U100 UNDISTURBED SAMPLE	⊥ PERMEABILITY TEST
▩ MAZIER SAMPLE (70mm)	∨ IN-SITU VANE SHEAR TEST
▩ PISTON SAMPLE	

LOGGED F.CHAN
DATE 29/03/96
APPROVED C.LUN
DATE 30/03/96

REMARKS