



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. C5

CONTRACT

SHEET 1 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-57

E 839916.63
N 816512.00

DATE from 30/1/96 to 3/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
1	PX								4.24	0.00			Concrete Slab.
										0.20			
										0.30			
2	PX 1.50m NX		100					T2 -101		1.20			Concrete with Cobbles and Gravels of moderately decomposed granite with some steel bars and steel fragment. (FILL)
			100					T2 -101		2.00			
			100					T2 -101		2.24			
								T2 -101	1.94	2.50			
3													Wash boring. (No recovery)
4													
5													
6													
7													
8													
9													
10													

- SMALL DISTURBED SAMPLE
- ▬ LARGE DISTURBED SAMPLE
- ▬ SPT LINER SAMPLE
- ▬ U76 UNDISTURBED SAMPLE
- ▬ U100 UNDISTURBED SAMPLE
- ▬ MAZIER SAMPLE (70mm)
- ▬ PISTON SAMPLE
- △ WATER SAMPLE
- ▲ PIEZOMETER TIP
- STANDPIPE
- ↓ STANDARD PENETRATION TEST
- ├ PERMEABILITY TEST
- ∇ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 05/02/96

APPROVED C.LUN

DATE 06/02/96

REMARKS

Hole termination depth at 28.07m.
Inspection Pit from 0.00m to 0.30m.



BACHY SOLETANCHE GROUP
SOIL & FOUNDATIONS SPECIALISTS

DRILLHOLE RECORD

HOLE NO. C5

CONTRACT

SHEET 2 of 3

PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY

METHOD ROTARY

CO-ORDINATES

W.O. W-518

MACHINE & No. CMC-57

E 839916.63
N 816512.00

DATE from 30/1/96 to 3/2/96

FLUSHING MEDIUM WATER

ORIENTATION Vertical

GROUND-LEVEL 4.44 mPD

Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
31/01													AS SHEET 1 OF 3.
11													
12													
13													
14													
15													
01/02/96													
16													
	NX	16.45m							-12.01	16.45			
17			100	100	90	3.0		T-74		17.45		III/II	Strong, pinkish grey spotted black and white, slightly decomposed medium to coarse grained GRANITE with widely to medium spaced, extremely narrow, rough planar, limonite, manganese stained, kaolin coated joints, dipping 10°-20°.
18			100	100	100	1.7		T-74		17.81			16.45m-19.01m: moderately strong to strong, pinkish grey spotted black and white, moderately to slightly decomposed medium to coarse grained GRANITE.
19			100	100	96			T-74	-14.57	19.01		II	
20													

- SMALL DISTURBED SAMPLE
- ▮ LARGE DISTURBED SAMPLE
- ▮ SPT LINER SAMPLE
- ▮ U76 UNDISTURBED SAMPLE
- ▮ U100 UNDISTURBED SAMPLE
- ▮ MAZIER SAMPLE (70mm)
- ▮ PISTON SAMPLE
- △ WATER SAMPLE
- ▲ PIEZOMETER TIP
- ▮ STANDPIPE
- ┆ STANDARD PENETRATION TEST
- ┆ PERMEABILITY TEST
- ∨ IN-SITU VANE SHEAR TEST

LOGGED FRANK CHAN

DATE 05/02/96

APPROVED C.LUN

DATE 06/02/96

REMARKS

BACHY SOLETANCHE BACHY SOLETANCHE GROUP SOIL & FOUNDATIONS SPECIALISTS		DRILLHOLE RECORD		HOLE NO. C5									
		CONTRACT		SHEET 3 of 3									
PROJECT LINCOLN HOUSE DEVELOPMENT, QUARRY BAY													
METHOD ROTARY				CO-ORDINATES		W.O. W-518							
MACHINE & No. CMC-57				E 839916.63 N 816512.00		DATE from 30/1/96 to 3/2/96							
FLUSHING MEDIUM WATER				ORIENTATION Vertical		GROUND-LEVEL 4.44 mPD							
Drilling Progress	Casing size	Water level (m) Shift start/end	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description
01/02			100	100	96	1.7		T-76		20.35	+	II	AS SHEET 2 OF 3.
21			100	100	100	2.2		T-76		21.78	+		
22			100	100	100			T-76		22.45	+		
23			100	100	100			T-76		22.66	+		
24			100	100	100	0.9		T-76		23.07	+		
02/02/96			100	100	100			T-76		23.81	+		
25			100	100	100			T-76		24.81	+		
26			100	100	100	1.5		T-76		25.11	+		
27			100	100	95			T-76		26.41	+		
28			100	100	100	0.0		T-76		26.81	+		
03/02/96			100	100	100			T-76		27.44	+		
29									23.63	28.07	+		End of hole at 28.07m.
30													
SMALL DISTURBED SAMPLE LARGE DISTURBED SAMPLE SPT LINER SAMPLE U76 UNDISTURBED SAMPLE U100 UNDISTURBED SAMPLE MAZIER SAMPLE (70mm) PISTON SAMPLE WATER SAMPLE PIEZOMETER TIP STANDPIPE STANDARD PENETRATION TEST PERMEABILITY TEST IN-SITU VANE SHEAR TEST								LOGGED FRANK CHAN		REMARKS			
								DATE 05/02/96					
								APPROVED C.LUN					
								DATE 06/02/96					