

# Talking About Mathematics in a Programming Language

---

Donnacha Oisín Kidney

October 15, 2018

2018-10-15

## Talking About Mathematics in a Programming Language

Talking About Mathematics in a  
Programming Language

---

Donnacha Oisín Kidney  
October 15, 2018

What do Programming Languages Have to do with Mathematics?

Programming is Proving

A Polynomial Solver

The  $p$ -Adics

2018-10-15

## Talking About Mathematics in a Programming Language

Talking About Mathematics in a  
Programming Language

---

Donacha Oisin Kidney  
October 15, 2018

# What do Programming Languages Have to do with Mathematics?

---

2018-10-15

Talking About Mathematics in a Programming  
Language

└─What do Programming Languages Have to do with  
Mathematics?

What do Programming Languages  
Have to do with Mathematics?

---

Languages for proofs and languages for programs have a lot of the same requirements.

2018-10-15

## Talking About Mathematics in a Programming Language

└ What do Programming Languages Have to do with Mathematics?

Languages for proofs and languages for programs have a lot of the same requirements.

Languages for proofs and languages for programs have a lot of the same requirements.

### A *Syntax* that is

- Readable
- Precise
- Terse

2018-10-15

## Talking About Mathematics in a Programming Language

### └ What do Programming Languages Have to do with Mathematics?

Languages for proofs and languages for programs have a lot of the same requirements.

A *Syntax* that is

- Readable
- Precise
- Terse

2018-10-15

## Talking About Mathematics in a Programming Language

### └ What do Programming Languages Have to do with Mathematics?

Languages for proofs and languages for programs have a lot of the same requirements.

A Syntax that is

- Readable
- Precise
- Terse

Semantics that are

- Small
- Powerful
- Consistent

Languages for proofs and languages for programs have a lot of the same requirements.

#### A *Syntax* that is

- Readable
- Precise
- Terse

#### *Semantics* that are

- Small
- Powerful
- Consistent

Semantics/axiomatic core Some of these are conflicting!

2018-10-15

## Talking About Mathematics in a Programming Language

└ What do Programming Languages Have to do with Mathematics?

Why not use a programming language as our proof language?

Why not use a programming language as our proof language?

# Benefits For Programmers

2018-10-15

## Talking About Mathematics in a Programming Language

- └ What do Programming Languages Have to do with Mathematics?
  - └ Benefits For Programmers

Mathematics and formal language has existed for thousands of years; programming has existed for only 60!



- *Prove* things about code

```
assert(list(reversed([1,2,3]))) == [3,2,1])
```

VS

```
reverse-involution :  $\forall xs \rightarrow \text{reverse} (\text{reverse } xs) \equiv xs$ 
```

2018-10-15

## Talking About Mathematics in a Programming Language

└ What do Programming Languages Have to do with Mathematics?

└ Benefits For Programmers

Not just test! Mathematics and formal language has existed for thousands of years; programming has existed for only 60!

- *Prove* things about code

```
assert(list(reversed([1,2,3]))) == [3,2,1])
```

VS

```
reverse-involution :  $\forall xs \rightarrow \text{reverse} (\text{reverse } xs) \equiv xs$ 
```

- *Prove* things about code
- Use ideas and concepts from maths—why reinvent them?

2018-10-15

## Talking About Mathematics in a Programming Language

- └ What do Programming Languages Have to do with Mathematics?
  - └ Benefits For Programmers

Mathematics and formal language has existed for thousands of years; programming has existed for only 60!

- *Prove* things about code
- Use ideas and concepts from maths—why reinvent them?

- *Prove* things about code
- Use ideas and concepts from maths—why reinvent them?
- Provide coherent *justification* for language features

2018-10-15

## Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─Benefits For Programmers

Mathematics and formal language has existed for thousands of years; programming has existed for only 60!

- *Prove* things about code
- Use ideas and concepts from maths—why reinvent them?
- Provide coherent *justification* for language features

# Benefits For Mathematicians

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─Benefits For Mathematicians

- Have a machine check your proofs

Currently, though, this is *tedious*

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─Benefits For Mathematicians

- Have a machine check your proofs

Currently, though, this is *tedious*

- Have a machine check your proofs
- Run your proofs

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─Benefits For Mathematicians

- Have a machine check your proofs
- Run your proofs

- Have a machine check your proofs
- Run your proofs
- Develop a consistent foundation for maths

2018-10-15

## Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─Benefits For Mathematicians

- Have a machine check your proofs
- Run your proofs
- Develop a consistent foundation for maths

- Have a machine check your proofs
- Run your proofs
- Develop a consistent foundation for maths

Wait— isn't this impossible?

2018-10-15

Talking About Mathematics in a Programming Language

└ What do Programming Languages Have to do with Mathematics?

└ Benefits For Mathematicians

- Have a machine check your proofs
  - Run your proofs
  - Develop a consistent foundation for maths
- Wait— isn't this impossible?



2018-10-15

Talking About Mathematics in a Programming  
Language

└─What do Programming Languages Have to do with  
Mathematics?

└─Formalizing Mathematics

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

Whitehead and Russell took  
*hundreds* of pages to prove  
 $1 + 1 = 2$

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

2018-10-15

Talking About Mathematics in a Programming  
Language

- └ What do Programming Languages Have to do with Mathematics?
- └ Formalizing Mathematics

Whitehead and Russell took  
*hundreds* of pages to prove  
 $1 + 1 = 2$

Gödel showed that universal  
formal systems are incomplete

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

2018-10-15

Talking About Mathematics in a Programming  
Language

└─What do Programming Languages Have to do with  
Mathematics?

└─Formalizing Mathematics

Whitehead and Russell took  
*hundreds* of pages to prove  
 $1 + 1 = 2$

Gödel showed that universal  
formal systems are incomplete

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

Whitehead and Russell took  
*hundreds* of pages to prove  
 $1 + 1 = 2$

Formal systems have improved

Gödel showed that universal  
formal systems are incomplete

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

2018-10-15

Talking About Mathematics in a Programming  
Language

└─What do Programming Languages Have to do with  
Mathematics?

└─Formalizing Mathematics

Whitehead and Russell took  
hundreds of pages to prove  
 $1 + 1 = 2$

Formal systems have improved

Gödel showed that universal  
formal systems are incomplete

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

Whitehead and Russell took  
*hundreds* of pages to prove  
 $1 + 1 = 2$

Formal systems have improved

Gödel showed that universal  
formal systems are incomplete

We don't need universal systems

Lawrence C Paulson. The Future of Formalised Mathematics, 2016

2018-10-15

Talking About Mathematics in a Programming  
Language

└ What do Programming Languages Have to do with  
Mathematics?

└ Formalizing Mathematics

Whitehead and Russell took  
*hundreds* of pages to prove  
 $1 + 1 = 2$

Formal systems have improved

Gödel showed that universal  
formal systems are incomplete

We don't need universal systems

# What About Automated Theorem Provers?

2018-10-15

Talking About Mathematics in a Programming Language

- └ What do Programming Languages Have to do with Mathematics?

- └ What About Automated Theorem Provers?

Use a combination of heuristics and exhaustive search to check some proposition.

*We have to trust the implementation.*

# What About Automated Theorem Provers?

Generally regarded as:

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─What About Automated Theorem Provers?

Generally regarded as:

# What About Automated Theorem Provers?

Generally regarded as:

- Inelegant

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─What About Automated Theorem Provers?

Generally regarded as:

- Inelegant



# What About Automated Theorem Provers?

Generally regarded as:

- Inelegant
- Lacking Rigour

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─What About Automated Theorem Provers?

Generally regarded as:

- Inelegant
- Lacking Rigour

# What About Automated Theorem Provers?

Generally regarded as:

- Inelegant
- Lacking Rigour
- Not Insightful

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─What About Automated Theorem Provers?

Generally regarded as:

- Inelegant
- Lacking Rigour
- Not Insightful

# What About Automated Theorem Provers?

Generally regarded as:

- Inelegant
- Lacking Rigour
- Not Insightful

Require trust

Non Surveyable

2018-10-15

Talking About Mathematics in a Programming Language

└ What do Programming Languages Have to do with Mathematics?

└ What About Automated Theorem Provers?

Generally regarded as:

- Inelegant
- Lacking Rigour
- Not Insightful

Require trust

Non Surveyable

# The Four-Colour Theorem

Kenneth Appel and Wolfgang Haken. The Solution of the Four-Color-Map Problem.

*Scientific American*, 237(4):108–121, 1977

Did contain bugs!

2018-10-15

Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

└─The Four-Colour Theorem

The Four-Colour Theorem

Kenneth Appel and Wolfgang Haken. The Solution of the Four-Color-Map Problem.

*Scientific American*, 237(4):108–121, 1977

Did contain bugs!

2018-10-15

## Talking About Mathematics in a Programming Language

└─What do Programming Languages Have to do with Mathematics?

But what if our formal language is executable?

But what if our formal language is executable?

2018-10-15

## Talking About Mathematics in a Programming Language

└ What do Programming Languages Have to do with Mathematics?

But what if our formal language is executable?  
Can we write *verified* automated theorem provers?

But what if our formal language is executable?

Can we write *verified* automated theorem provers?

Prove things about programs, and prove things about maths

2018-10-15

## Talking About Mathematics in a Programming Language

### └ What do Programming Languages Have to do with Mathematics?

But what if our formal language is executable?  
Can we write *verified* automated theorem provers?  
Georges Gonthier. Formal Proof—The Four-Color Theorem.  
*Notices of the AMS*, 55(11):12, 2008

But what if our formal language is executable?

Can we write *verified* automated theorem provers?

Georges Gonthier. Formal Proof—The Four-Color Theorem.

*Notices of the AMS*, 55(11):12, 2008

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving


Programming is Proving

# Programming is Proving

---



# The Curry-Howard Correspondence



Philip Wadler. Propositions As Types.

*Commun. ACM*, 58(12):75–84, November 2015

2018-10-15

Talking About Mathematics in a Programming  
Language

└ Programming is Proving

└ The Curry-Howard Correspondence

The Curry-Howard Correspondence



Philip Wadler. Propositions As Types.

*Commun. ACM*, 58(12):75–84, November 2015

# Types are Propositions

Types are (usually):

- `Int`
- `String`
- ...

How are these propositions?

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Types are Propositions

Propositions are things like “there are infinite primes”, etc. `Int` certainly doesn’t *look* like a proposition.

Types are Propositions

Types are (usually):

- `Int`
- `String`
- ...

How are these propositions?

# Existential Proofs

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Existential Proofs

We use a trick to translate: put a “there exists” before the type.

So when you see:

$x : \mathbb{N}$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Existential Proofs

So when you see:

$x : \mathbb{N}$

So when you see:

$x : \mathbb{N}$

Think:

$\exists. \mathbb{N}$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Existential Proofs

So when you see:

$x : \mathbb{N}$

Think:

$\exists. \mathbb{N}$

So when you see:

$x : \mathbb{N}$

Think:

$\exists . \mathbb{N}$

**NB**

We'll see a more powerful and precise version of  $\exists$  later.

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Existential Proofs

So when you see:

$x : \mathbb{N}$

Think:

$\exists . \mathbb{N}$

**NB**

We'll see a more powerful and precise version of  $\exists$  later.

So when you see:

$x : \mathbb{N}$

Think:

$\exists.\mathbb{N}$

**NB**

We'll see a more powerful and precise version of  $\exists$  later.

Proof is “by example”:

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Existential Proofs

So when you see:

$x : \mathbb{N}$

Think:

$\exists.\mathbb{N}$

**NB**

We'll see a more powerful and precise version of  $\exists$  later.

Proof is “by example”.

So when you see:

$x : \mathbb{N}$

Think:

$\exists . \mathbb{N}$

**NB**

We'll see a more powerful and precise version of  $\exists$  later.

Proof is “by example”:

$x = 1$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Existential Proofs

So when you see:

$x : \mathbb{N}$

Think:

$\exists . \mathbb{N}$

**NB**

We'll see a more powerful and precise version of  $\exists$  later.

Proof is “by example”:

$x = 1$



2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Programs are Proofs

Let's start working with a function as if it were a proof. The function we'll choose gets the first element from a list. It's commonly called "head" in functional programming.

```
>>> head [1,2,3]
1
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Programs are Proofs

Programs are Proofs

```
>>> head [1,2,3]
1
```

```
>>> head [1,2,3]
```

```
1
```

Here's the type:

```
head : {A : Set} → List A → A
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Programs are Proofs

```
>>> head [1,2,3]  
1
```

Here's the type:

```
head : {A : Set} → List A → A
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Basic Agda Syntax

`head` is what would be called a “generic” function in languages like Java.  
In other words, the type  $A$  is not specified in the implementation of the  
function.

Equivalent in other languages:

**Haskell**

```
head :: [a] -> a
```

**Swift**

```
func head<A>(xs : [A]) -> A {
```

Equivalent in other languages:

**Haskell**          `head :: [a] -> a`

**Swift**            `func head<A>(xs : [A]) -> A {`

`head : {A : Set} → List A → A`

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Basic Agda Syntax

In Agda, you must supply the type to the function: the curly brackets mean the argument is implicit.

Equivalent in other languages:

**Haskell**          `head :: [a] -> a`  
**Swift**            `func head<A>(xs : [A]) -> A {`  
`head : {A : Set} → List A → A`

Equivalent in other languages:

**Haskell**      `head :: [a] -> a`

**Swift**      `func head<A>(xs : [A]) -> A {`

`head : {A : Set} → List A → A` “Takes a list of things, and  
returns one of those things”.

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Basic Agda Syntax

Equivalent in other languages:

**Haskell**      `head :: [a] -> a`  
**Swift**      `func head<A>(xs : [A]) -> A {`  
`head : {A : Set} → List A → A` “Takes a list of things, and  
returns one of those things”.

# The Proposition is False!

```
>>> head []  
error "head: empty list"
```

2018-10-15

Talking About Mathematics in a Programming  
Language

└ Programming is Proving

└ The Proposition is False!

head isn't defined on the empty list, so the function *doesn't* exist. In other words, its type is a false proposition.

The Proposition is False!

```
>>> head []  
error "head: empty list"
```



# The Proposition is False!

```
>>> head []  
error "head: empty list"
```

```
head : {A : Set} → List A → A
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ The Proposition is False!

The Proposition is False!

```
>>> head []  
error "head: empty list"  
  
head : {A : Set} → List A → A
```

# The Proposition is False!

```
>>> head []  
error "head: empty list"
```

$\text{head} : \{A : \text{Set}\} \rightarrow \text{List } A \rightarrow A$

False

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ The Proposition is False!

The Proposition is False!

```
>>> head []  
error "head: empty list"  
  
head : {A : Set} → List A → A  
False
```

2018-10-15

# Talking About Mathematics in a Programming Language

## └ Programming is Proving

If Agda is correct (as a formal logic):

If Agda is correct (as a formal logic):

If Agda is correct (as a formal logic):

We shouldn't be able to prove this using Agda

If Agda is correct (as a formal logic):

We shouldn't be able write this function in Agda

# But Let's Try Anyway!

## Function definition syntax

```
fib :  $\mathbb{N} \rightarrow \mathbb{N}$   
fib 0 = 0  
fib (1+ 0) = 1+ 0  
fib (1+ (1+ n)) = fib (1+ n) + fib n
```

2018-10-15

## Talking About Mathematics in a Programming Language

└ Programming is Proving

└ But Let's Try Anyway!

Agda functions are defined (usually) with *pattern-matching*. For the natural numbers, we use the Peano numbers, which gives us 2 patterns: zero, and successor.

Function definition syntax

```
fib :  $\mathbb{N} \rightarrow \mathbb{N}$   
fib 0 = 0  
fib (1+ 0) = 1+ 0  
fib (1+ (1+ n)) = fib (1+ n) + fib n
```

# But Let's Try Anyway!

```
length : {A : Set} → List A → ℕ
length [] = 0
length (x :: xs) = 1 + length xs
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ But Let's Try Anyway!

For lists, we also have two patterns: the empty list, and the head element followed by the rest of the list.

length : {A : Set} → List A → ℕ  
length [] = 0  
length (x :: xs) = 1 + length xs

# But Let's Try Anyway!

Here's a definition for `head`:

`head (x :: xs) = x`

**No!**

For correct proofs, partial functions aren't allowed

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ But Let's Try Anyway!

We need to disallow functions which don't match all patterns. Array access out-of-bounds, etc., also not allowed.

But Let's Try Anyway!

Here's a definition for `head`:

`head (x :: xs) = x`

**No!**

For correct proofs, partial functions aren't allowed



# But Let's Try Anyway!

We're not out of the woods yet:

`head [] = head []`

**No!**

For correct proofs, all functions must be total

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ But Let's Try Anyway!

To disallow *this* kind of thing, we must ensure all functions are *total*. For now, assume this means “terminating”.

But Let's Try Anyway!

We're not out of the woods yet:

`head [] = head []`

**No!**

For correct proofs, all functions must be total

For the proofs to be correct, we have two extra conditions that you usually don't have in programming:

- No partial programs
- Only total programs

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Correctness

Without these conditions, your proofs are still correct *if they run*.

For the proofs to be correct, we have two extra conditions that you usually don't have in programming:

- No partial programs
- Only total programs

2018-10-15

## Talking About Mathematics in a Programming Language

- └ Programming is Proving

Enough Restrictions!

That's a lot of things we *can't* prove.

How about something that we can?

How about the converse?

2018-10-15

## Talking About Mathematics in a Programming Language

- └ Programming is Proving

Can we prove that `head` doesn't exist?

Can we *prove* that `head` doesn't exist?

After all, all we have so far is “proof by trying really hard”.

First we'll need a notion of "False". Often it's said that you can't prove negatives in dependently typed programming: not true! We'll use the principle of explosion: "A false thing is one that can be used to prove anything".

## Principle of Explosion

*“Ex falso quodlibet”*

If you stand for nothing, you'll  
fall for anything.

2018-10-15

Talking About Mathematics in a Programming

Language

└ Programming is Proving

└ Falsehood

Falsehood

Principle of Explosion  
“Ex falso quodlibet”  
If you stand for nothing, you'll  
fall for anything.

$\neg : \forall \{l\} \rightarrow \text{Set } l \rightarrow \text{Set } \_$   
 $\neg A = A \rightarrow \{B : \text{Set}\} \rightarrow B$

## Principle of Explosion

*"Ex falso quodlibet"*

If you stand for nothing, you'll  
fall for anything.

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Falsehood

Falsehood

$\neg : \forall \{l\} \rightarrow \text{Set } l \rightarrow \text{Set } \_$   
 $\neg A = A \rightarrow \{B : \text{Set}\} \rightarrow B$

Principle of Explosion  
"Ex falso quodlibet"  
If you stand for nothing, you'll  
fall for anything.

```
head-doesn't-exist : ¬ ({A : Set} → List A → A)  
head-doesn't-exist head = head []
```

Here's how the proof works: for falsehood, we need to prove the supplied proposition, no matter what it is. If `head` exists, this is no problem! Just get the head of a list of proofs of the proposition, which can be empty.



2018-10-15

- Talking About Mathematics in a Programming Language
  - └ Programming is Proving
    - └ Proofs are Programs

Types/Propositions are *sets*

```
data Bool : Set where
  true  : Bool
  false : Bool
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Proofs are Programs

Types/Propositions are sets

```
data Bool : Set where
  true  : Bool
  false : Bool
```

Types/Propositions are *sets*

```
data Bool : Set where
  true  : Bool
  false : Bool
```

Inhabited by *proofs*

Bool	Proposition
true, false	Proof

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Proofs are Programs

Proofs are Programs

Types/Propositions are sets

```
data Bool : Set where
  true  : Bool
  false : Bool
```

Inhabited by *proofs*

Bool	Proposition
true, false	Proof

# Implication

2018-10-15

Talking About Mathematics in a Programming

Language

└ Programming is Proving

└ Implication

Just a function arrow

$$A \rightarrow B$$

2018-10-15	Talking About Mathematics in a Programming Language
	└ Programming is Proving
	└ Implication

Implication

A → B

$A \rightarrow B$

A implies B

2018-10-15

Talking About Mathematics in a Programming Language
└ Programming is Proving
└ Implication

Implication
└ $A \rightarrow B$
└ A implies B

# Implication

$A \rightarrow B$

$A$  implies  $B$

Constructivist/Intuitionistic

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Implication

Give me a proof of  $a$ , I'll give you a proof of  $b$

Implication

$A \rightarrow B$

$A$  implies  $B$

Constructivist/Intuitionistic

# Booleans?

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Booleans?

We *don't* use bools to express truth and falsehood.

Bool is just a set with two values: nothing “true” or “false” about either of them!

This is the difference between using a computer to do maths and *doing maths in a programming language*



# Booleans?

`data ⊥ : Set where`

Contradiction

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Booleans?

Falsehood (contradiction) is the proposition with no proofs.  
It's equivalent to what we had previously.

Booleans?

`data ⊥ : Set where`

Contradiction

# Booleans?

`data ⊥ : Set where`

Contradiction

`ptb : ∀ {a} {A : Set a} → ¬ A → A → ⊥`

`ptb f x = f x`

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Booleans?

In fact, we can convert from what we had previously

Booleans?

`data ⊥ : Set where`

Contradiction

`ptb : ∀ {a} {A : Set a} → ¬ A → A → ⊥`  
`ptb f x = f x`

# Booleans?

data  $\perp$  : Set where

Contradiction

ptb :  $\forall \{a\} \{A : \text{Set } a\} \rightarrow \neg A \rightarrow A \rightarrow \perp$

ptb  $f\ x = f\ x$

inc :  $\neg \perp$

inc ()

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Booleans?

And *to* what we had previously.

Here, we use an impossible pattern.

Booleans?

data  $\perp$  : Set where

Contradiction

ptb :  $\forall \{a\} \{A : \text{Set } a\} \rightarrow \neg A \rightarrow A \rightarrow \perp$   
ptb  $f\ x = f\ x$

inc :  $\neg \perp$   
inc ()

# Booleans?

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Booleans?

Booleans?

`data ⊥ : Set where`

Contradiction

`data ⊤ : Set where`

Tautology

`tt : ⊤`

`data ⊥ : Set where`

Contradiction

`data ⊤ : Set where`

`tt : ⊤`

Tautology

Tautology is kind of the “boring” type.

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Conjunction

Conjunction (“and”) is represented as a data type.

# Conjunction

```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Conjunction

It has two type parameters, and two fields.

Conjunction

```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

# Conjunction

```
record __×__ (A B : Set) : Set where
  constructor __,__
  field
    fst : A
    snd : B
```

## Swift

```
struct Pair<A,B>{
  let fst: A
  let snd: B
}
```

## Python

```
class Pair:
    def __init__(self, x, y):
        self.fst = x
        self.snd = y
```

2018-10-15

## Talking About Mathematics in a Programming Language

- └ Programming is Proving

- └ Conjunction

Syntax-wise, it's equivalent to a *class* in other languages.

Conjunction

```
record __×__ (A B : Set) : Set where
  constructor __,__
  field
    fst : A
    snd : B
```

Swift

```
struct Pair<A,B>{
  let fst: A
  let snd: B
}
```

Python

```
class Pair:
    def __init__(self, x, y):
        self.fst = x
        self.snd = y
```

# Conjunction


```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

```
data _×_ (A B : Set) : Set where
  _,_ : A → B → A × B
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Conjunction



We could also have written it like this. (Haskell-style)

The definition is basically equivalent, but we don't get two field accessors (we'd have to define them manually) and some of the syntax is better suited to the record form.

It does show the type of the constructor, though (which is the same in both).

It's curried, which you don't need to understand: just think of it as taking two arguments.

"If you have a proof of A, and a proof of B, you have a proof of A *and* B"



# Conjunction

```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

Type Theory  
2-Tuple

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Conjunction

Conjunction

```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

Type Theory  
2-Tuple

# Conjunction

```
record __×__ (A B : Set) : Set where
  constructor __,__
  field
    fst : A
    snd : B
```

Set Theory  
Cartesian Product

$$\{t, f\} \times \{1, 2, 3\} = \{(t, 1), (f, 1), (t, 2), (f, 2), (t, 3), (f, 3)\}$$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Conjunction

Conjunction

```
record __×__ (A B : Set) : Set where
  constructor __,__
  field
    fst : A
    snd : B
```

Set Theory  
Cartesian Product

$\{t, f\} \times \{1, 2, 3\} = \{(t, 1), (f, 1), (t, 2), (f, 2), (t, 3), (f, 3)\}$

# Conjunction

```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

Familiar identities: conjunction-elimination

```
cnj-elim : ∀ {A B} → A × B → A
cnj-elim = fst
```

$$A \wedge B \implies A$$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Conjunction

Conjunction

```
record _×_ (A B : Set) : Set where
  constructor _,_
  field
    fst : A
    snd : B
```

Familiar identities: conjunction-elimination

```
cnj-elim : ∀ {A B} → A × B → A
cnj-elim = fst
```

$A \wedge B \implies A$

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Currying

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

$\text{curry} : \{A\ B\ C : \text{Set}\} \rightarrow (A \times B \rightarrow C) \rightarrow A \rightarrow (B \rightarrow C)$   
 $\text{curry } f\ x\ y = f(x, y)$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Currying

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

$\text{curry} : \{A\ B\ C : \text{Set}\} \rightarrow (A \times B \rightarrow C) \rightarrow A \rightarrow (B \rightarrow C)$   
 $\text{curry } f\ x\ y = f(x, y)$

The type:  
 $A, B \rightarrow C$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Currying

Currying  
The type:  
 $A, B \rightarrow C$

Just a short note on currying.  
People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

The type:  
 $A, B \rightarrow C$

Is isomorphic to:  
 $A \rightarrow (B \rightarrow C)$

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Currying

Currying

The type:  
 $A, B \rightarrow C$

Is isomorphic to:  
 $A \rightarrow (B \rightarrow C)$

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

The type:

$A, B \rightarrow C$

Is isomorphic to:

$A \rightarrow (B \rightarrow C)$

Because the statement:

“A and B implies C”

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Currying

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

The type:  
 $A, B \rightarrow C$

Is isomorphic to:  
 $A \rightarrow (B \rightarrow C)$

Because the statement:  
“A and B implies C”



The type:

$A, B \rightarrow C$

Is isomorphic to:

$A \rightarrow (B \rightarrow C)$

Because the statement:

"A and B implies C"

Is the same as saying:

"A implies B implies C"

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

“If I’m outside and it’s raining, I’m going to get wet”

$Outside \wedge Raining \implies Wet$

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Currying

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

"If I'm outside and it's raining, I'm going to get wet"

$Outside \wedge Raining \implies Wet$

“If I’m outside and it’s raining, I’m going to get wet”

$$Outside \wedge Raining \implies Wet$$

“When I’m outside, if it’s raining I’m going to get wet”

$$Outside \implies Raining \implies Wet$$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Currying

Just a short note on currying.

People familiar with Haskell will know what it is, I won't explain it in its entirety here, though. Just a little interesting thing on how it translates into logic.

“If I’m outside and it’s raining, I’m going to get wet”

$Outside \wedge Raining \implies Wet$

“When I’m outside, if it’s raining I’m going to get wet”

$Outside \implies Raining \implies Wet$

```
data _∪_ (A B : Set) : Set where
  inl : A → A ∪ B
  inr : B → A ∪ B
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ Disjunction

Disjunction

```
data _∪_ (A B : Set) : Set where
  inl : A → A ∪ B
  inr : B → A ∪ B
```

2018-10-15

- Talking About Mathematics in a Programming Language
  - └ Programming is Proving
    - └ Dependent Types

Everything so far has been non-dependent

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Dependent Types

In other words, lots of modern languages support it. (Haskell)

Everything so far has been non-dependent

Proving things using this bare-bones toolbox is difficult (though possible)

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Dependent Types

Dependent Types

Everything so far has been non-dependent  
Proving things using this bare-bones toolbox is difficult (though possible)

The proof that head doesn't exist, for instance, could be written in vanilla Haskell.

It's difficult to prove more complex statements using this pretty bare-bones toolbox, though, so we're going to introduce some extra handy features.

NOTE: when you prove things in non-total languages, the proofs only hold *if they terminate*. That doesn't *really* mean that they're "invalid", it just means that you have to run it for every case you want to check.

Everything so far has been non-dependent

Proving things using this bare-bones toolbox is difficult (though possible)

To make things easier, we're going to add some things to our types

Per Martin-Löf. *Intuitionistic Type Theory*.

**Padua, June 1980**

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Dependent Types

Everything so far has been non-dependent

Proving things using this bare-bones toolbox is difficult (though possible)

To make things easier, we're going to add some things to our types

Per Martin-Löf. *Intuitionistic Type Theory*.

**Padua, June 1980**



2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ The  $\Pi$  Type

The  $\Pi$  Type

2018-10-15

Upgrade the *function arrow*

2018-10-15

Talking About Mathematics in a Programming Language

└ Programming is Proving

└ The  $\Pi$  Type

First, we upgrade the function arrow, so the right-hand-side can talk about the value on the left.

Upgrade the *function arrow*

`prop` :  $(x : \mathbb{N}) \rightarrow 0 \leq x$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ The  $\Pi$  Type

This lets us easily express *properties*

Upgrade the *function arrow*

`prop` :  $(x : \mathbb{N}) \rightarrow 0 \leq x$

Upgrade the *function arrow*

`prop` :  $(x : \mathbb{N}) \rightarrow 0 \leq x$

Now we have a proper  $\forall$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ The  $\Pi$  Type

The  $\Pi$  Type

Upgrade the *function arrow*

`prop` :  $(x : \mathbb{N}) \rightarrow 0 \leq x$

Now we have a proper  $\forall$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ The  $\Sigma$  Type

The  $\Sigma$  Type

Upgrade *product types*

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving  
└ The  $\Sigma$  Type

The  $\Sigma$  Type

Upgrade *product types*

Upgrade *product types*

```
record NonZero : Set where
  field
    n      :  $\mathbb{N}$ 
    proof :  $0 < n$ 
```

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ The  $\Sigma$  Type

Later fields can refer to earlier ones.

Upgrade *product types*

```
record NonZero : Set where
  field
    n      :  $\mathbb{N}$ 
    proof :  $0 < n$ 
```

Upgrade *product types*

```
record NonZero : Set where
  field
    n      :  $\mathbb{N}$ 
    proof :  $0 < n$ 
```

Now we have a proper  $\exists$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ The  $\Sigma$  Type

The  $\Sigma$  Type

Upgrade *product types*

```
record NonZero : Set where
  field
    n      :  $\mathbb{N}$ 
    proof :  $0 < n$ 
```

Now we have a proper  $\exists$



# The Equality Type

```
infix 4 _≡_  
data _≡_ {A : Set} (x : A) : A → Set where  
  refl : x ≡ x
```

2018-10-15

Talking About Mathematics in a Programming  
Language

└ Programming is Proving

└ The Equality Type

The Equality Type

```
infix 4 _≡_  
data _≡_ {A : Set} (x : A) : A → Set where  
  refl : x ≡ x
```

Final piece of the puzzle.

The type of this type has 2 parameters.

But the only way to construct the type is if the two parameters are the same.

You then get evidence of their sameness when you pattern-match on that constructor.

# Equality

$\_ + \_ : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N}$

$0 + y = y$

$\text{suc } x + y = \text{suc } (x + y)$

$\text{obvious} : \forall x \rightarrow 0 + x \equiv x$

$\text{obvious } \_ = \text{refl}$

2018-10-15

Talking About Mathematics in a Programming  
Language  
└ Programming is Proving

└ Equality

Agda uses propositional equality

You can construct the equality proof when it's obvious.

Equality

```
 $\_ + \_ : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N}$   
 $0 + y = y$   
 $\text{suc } x + y = \text{suc } (x + y)$   
 $\text{obvious} : \forall x \rightarrow 0 + x \equiv x$   
 $\text{obvious } \_ = \text{refl}$ 
```

# Equality

$\_ + \_ : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N}$

$0 + y = y$

$\text{suc } x + y = \text{suc } (x + y)$

$\text{obvious} : \forall x \rightarrow 0 + x \equiv x$

$\text{obvious } \_ = \text{refl}$

$\text{cong} : \forall \{A B\} \rightarrow (f : A \rightarrow B) \rightarrow \forall \{x y\} \rightarrow x \equiv y \rightarrow f x \equiv f y$

$\text{cong } \_ \text{refl} = \text{refl}$

$\text{not-obvious} : \forall x \rightarrow x + 0 \equiv x$

$\text{not-obvious } \text{zero} = \text{refl}$

$\text{not-obvious } (\text{suc } x) = \text{cong } \text{suc } (\text{not-obvious } x)$

2018-10-15

## Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Equality

you need to supply the proof yourself when it's not obvious.

Equality

```
_+_ : ℕ → ℕ → ℕ
0 + y = y
suc x + y = suc (x + y)
obvious : ∀ x → 0 + x ≡ x
obvious _ = refl

cong : ∀ {A B} → (f : A → B) → ∀ {x y} → x ≡ y → f x ≡ f y
cong _ refl = refl

not-obvious : ∀ x → x + 0 ≡ x
not-obvious zero = refl
not-obvious (suc x) = cong suc (not-obvious x)
```

- Law of Excluded Middle?
- Russell's Paradox
- Function Extensionality
- Data Constructor Injectivity
- Observational Equality
- Homotopy Type Theory

2018-10-15

## Talking About Mathematics in a Programming Language

└ Programming is Proving

└ Open Areas and Weirdness

- Law of Excluded Middle?
- Russell's Paradox
- Function Extensionality
- Data Constructor Injectivity
- Observational Equality
- Homotopy Type Theory

2018-10-15

Talking About Mathematics in a Programming  
Language  
└─ A Polynomial Solver

A Polynomial Solver

---

# A Polynomial Solver

---

2018-10-15

Talking About Mathematics in a Programming  
Language  
└─ The  $p$ -Adics

The  $p$ -Adics

---

# The $p$ -Adics

---