HELP NIVO

Complete Manual End-to-End Testing Guide

Version 4.5.1 | AWS Ubuntu + Docker + PostgreSQL 17 | Browser-based functional acceptance

188 detailed test cases

13 functional areas • Step-by-step navigation • Fictional example entries • Expected results • Pass / Fail / Blocked checkboxes

Testing environment

Application URL	https://3-228-147-200.sslip.io (temporary evaluation hostname)
Version	Help Nivo 4.5.1
Tested by / date	_____
Environment	QA staging: _____

Safety first

Do not run disruptive cases against real customer data. Use two dedicated test organizations and non-sensitive records. A passing readiness endpoint is not proof that every workflow, backup, integration, or security control passes.

Based on the packaged 4.5.1 user and operations guides, notification and launch documentation, and the supplied 188-case end-to-end workbook. No case is marked as executed.

1 How to run this guide

This is a manual walkthrough for a person operating the Help Nivo interface. Follow the numbered instructions for each case, compare with its expected result, then mark exactly one result box. Keep evidence of failures in a secure test folder.

PASS The actual behavior matches the expected result and the test data can be verified.

FAIL The feature behaved incorrectly. Record the difference, steps, screenshot and defect ID.

BLOCKED A prerequisite is missing (for example SMTP, Google OAuth, role permissions, or a required test environment).

N/A The feature is intentionally disabled or outside the current accepted deployment scope. Record why.

Before you begin: safety checklist

- [ ] Use a dedicated QA/staging workspace and entirely fictional tickets, assets, contacts and vendor data.
- [ ] Confirm the HTTPS site opens from your test workstation; do not bypass browser TLS warnings.
- [ ] Confirm your platform administrator has MFA and recovery codes stored privately.
- [ ] Create two separate organizations (Org A and Org B) and several distinct user accounts.
- [ ] Record the current Help Nivo release, date, browser, tester name and AWS environment.
- [ ] Before reboot, restore, quota exhaustion, suspension or destructive tests, take a verified backup and use disposable staging.
- [ ] Do not paste passwords, MFA codes, recovery links, OAuth secrets, keyrings or real customer records into the evidence log.
- [ ] Keep AWS port 443 restricted to approved testers until security acceptance is complete; never expose PostgreSQL publicly.

Suggested test sequence

1. **Environment and admin -** Deployment -> Authentication -> first two organizations.
2. **Service desk configuration -** Starter values, people, groups, templates, SLAs and routing.
3. **Ticket life cycle -** Submit, assign, reply, hold, resolve, close, reopen, worklogs and files.
4. **Approvals and ITIL -** Service catalog, change, release, problems and knowledge.
5. **Operations and reporting -** Assets, CMDB, procurement, projects, dashboards and exports.
6. **Communications -** Notifications, SMTP, optional Google identity, AI and voice.
7. **Negative and recovery -** Tenant isolation, security checks, backups, restore and load: staging only.

2 Sample accounts and records

Use these examples consistently across all tests. Replace YOUR_TEST_DOMAIN only with a domain and mailbox you control for email-delivery tests. For other scenarios the example values are fictional; do not create real customer data.

Item	Example	Use

Platform operator	Existing platform admin	Provider configuration, plans, SMTP; no automatic tenant ticket visibility
Org A	Nivo QA Alpha / nivo-qa-alpha	Primary test company; timezone Asia/Dubai
Org B	Nivo QA Beta / nivo-qa-beta	Isolation checks; should not access Org A records
Owner A	qa-owner-alpha@YOUR_TEST_DOMAIN	Company A owner; setup and invitations
Technician A	qa-tech-alpha@YOUR_TEST_DOMAIN	Works tickets, changes, tasks and worklogs
Approver A	qa-approver-alpha@YOUR_TEST_DOMAIN	Independent approvals
Requester A	qa-requester-alpha@YOUR_TEST_DOMAIN	Submits service requests and feedback
Owner/Requester B	qa-owner-beta / qa-requester-beta@YOUR_TEST_DOMAIN	Negative cross-company cases
Request	QA-A-INC-01 VPN disconnect	Ticket end-to-end flow
Service	QA New Laptop	Two approval stages and fulfillment
Change / release	QA-CHG-VPN-01 / QA-REL-VPN-01	Independent workflow approval and prerequisites
Asset / CI	QA-LAP-001 / QA-CI-VPN-01	Asset register, loans, licenses, CMDB links
Supplier / purchase	QA Vendor / QA-PO-001	Supplier, purchase approval and receiving
SMTP / AI / Google	Configured only when available	Mark BLOCKED when integrations are unavailable

3 Functional coverage by module

No.	Module	Cases
01	Deployment	5
02	Authentication	10
03	Tenancy & membership	12

04	Provider console	12
05	Requests & incidents	26
06	Catalog SLA & routing	17
07	Change release & knowledge	18
08	Assets CMDB & operations	18
09	Notifications & email	14
10	Dashboard & reports	10
11	AI & voice	11
12	Setup UI & branding	15
13	Security & launch gates	20
	TOTAL	188

The full guide follows the same 188 scenario IDs as the separate E2E Excel workbook. You can use either file to track the run; do not mark a test PASS until executed on your target environment.

4 Detailed step-by-step test cases

For every scenario: follow the numbered steps, use the listed example, verify the expected result, and mark exactly one result box. Entries are editable in Word and printable from PDF. When a specific control label differs slightly, use the named module or page finder (Cmd/Ctrl+K).

01 Deployment

5 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

Operator-sensitive checks: Reboot, backups/restores, port/security testing and scans should be performed in an approved maintenance window or disposable staging environment.

HNV-E2E-001 Public hostname serves login P0

Role Visitor | **Dependency** AWS HTTPS

Navigate: Mac/Safari or Chrome > https://3-228-147-200.sslip.io/ ; /readyz

Example entry: URL: https://3-228-147-200.sslip.io/ ; check /readyz.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Mac/Safari or Chrome > https://3-228-147-200.sslip.io/ ; /readyz.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.

3. From a permitted external network open https://3-228-147-200.sslip.io/.
4. Inspect the certificate and login page.
5. Open /readyz.

EXPECTED Login page loads; valid hostname certificate; /readyz returns HTTP 200 and ready.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-002 Internal ports are not public P0

Role Operator | **Dependency** AWS

Navigate: AWS Console > EC2 > Security groups > Inbound rules

Example entry: Check inbound 22 (admin IP), 80/443 (approved); verify 8010/5433 are NOT public.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: AWS Console > EC2 > Security groups > Inbound rules.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. From an authorized external host attempt TCP connections to 8010, 5432, 5433, 8001, 8002.
4. Check EC2 inbound rules.

EXPECTED Internal services cannot be reached publicly; only authorized 22 and web 80/443 rules exist.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-003 Services recover after EC2 reboot P0

Role Operator | **Dependency** AWS / Docker | **STAGING ONLY**

Navigate: AWS Console > EC2 > Instances > Reboot (staging only)

Example entry: Use a planned 10-minute maintenance window; test ticket QA-HNV-PERSIST-01.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: AWS Console > EC2 > Instances > Reboot (staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Take backup and arrange maintenance window.
4. Reboot EC2.
5. Wait and check docker compose ps; test HTTPS /readyz and login.

EXPECTED API, DB, workers and Caddy recover; no loss of saved records.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-004 Database survives container recreation P0

Role Operator | **Dependency** Docker | **STAGING ONLY**

Navigate: Ubuntu SSH > Help Nivo project > Docker Compose

Example entry: Create request QA-HNV-PERSIST-02 before API-only recreation.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Ubuntu SSH > Help Nivo project > Docker Compose.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create a unique test ticket.
4. Recreate only API container with docker compose up -d --no-deps --force-recreate api.
5. Log in and locate ticket.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Ticket persists; no volume loss. Never use down -v.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-005 APP_PORT uses 8010 P1

Role Operator | **Dependency** AWS / Docker

Navigate: Ubuntu SSH > Help Nivo .env / Docker Compose

Example entry: APP_PORT=8010; PUBLIC_ORIGIN=https://3-228-147-200.sslip.io.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Ubuntu SSH > Help Nivo .env / Docker Compose.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Inspect APP_PORT and PUBLIC_ORIGIN without exposing secrets.
4. Verify API binds only to 127.0.0.1:8010.
5. Test HTTPS through Caddy.

EXPECTED Private port 8010 works; public HTTPS 443 works; internal DB remains private.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

02 Authentication

10 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-006 First administrator initialization P0

Role Platform admin / Visitor | **Dependency** Core | **STAGING ONLY**

Navigate: Ubuntu SSH > bootstrap_admin.py; browser > /#/initialize

Example entry: Administrator name: QA Platform Operator; email: an address you control; use a unique strong password and TOTP.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Ubuntu SSH > bootstrap_admin.py; browser > /#/initialize.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Generate a fresh one-time bootstrap link on host, open privately and complete name/password/MFA enrollment.
4. Verify access/session state in a fresh tab.

EXPECTED Admin is created once; login redirects to Platform Administration; link cannot be reused.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-007 Bootstrap expiry P0

Role Platform admin / Visitor | **Dependency** Core | **STAGING ONLY**

Navigate: Browser > private /#/initialize link (uninitialized staging only)

Example entry: Use an expired single-use initialization link on a disposable, uninitialized staging instance.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > private /#/initialize link (uninitialized staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Generate an initialization link; attempt use after its configured 30-minute expiry in controlled test.
4. Verify access/session state in a fresh tab.

EXPECTED Expired link is rejected; no administrator created.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-008 Password and MFA login P0

Role Platform admin / Visitor | **Dependency** Core

Navigate: Browser > Login; Platform administration

Example entry: Sign in with your own platform-admin email, unique password and current 6-digit authenticator code.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > Login; Platform administration.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter correct administrator email, password, and current authenticator code.
4. Verify access/session state in a fresh tab.

EXPECTED Authenticated provider session is created.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-009 Incorrect password P0

Role Platform admin / Visitor | **Dependency** Core

Navigate: Browser > Login

Example entry: Use one intentionally wrong password; do not perform large-scale guessing.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > Login.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter correct email with an incorrect password.
4. Verify access/session state in a fresh tab.

EXPECTED Login rejected without revealing whether an account exists.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-010 Incorrect MFA P0

Role Platform admin / Visitor | **Dependency** Core

Navigate: Browser > Login > MFA verification

Example entry: Enter a wrong or expired 6-digit MFA code once.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > Login > MFA verification.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter valid password and invalid/expired authenticator code.
4. Verify access/session state in a fresh tab.

EXPECTED Login rejected; provider session not created.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-011 Recovery code single use P0

Role Platform admin / Visitor | **Dependency** Core

Navigate: Browser > Login > recovery code field

Example entry: Use one unused recovery code, then try that same code a second time.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > Login > recovery code field.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in using an unused recovery code, then try same code again.
4. Verify access/session state in a fresh tab.

EXPECTED First use succeeds; reuse fails.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-012 Password reset P0

Role Platform admin / Visitor | **Dependency** SMTP

Navigate: Browser > Forgot password; Account security

Example entry: Request reset for a verified QA mailbox; use MFA/recovery code for protected administrator.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > Forgot password; Account security.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Request reset using configured SMTP; complete link and second-factor requirements.
4. Verify access/session state in a fresh tab.

EXPECTED Password changes; old password/sessions invalidated; MFA retained.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-013 Logout P0

Role Platform admin / Visitor | **Dependency** Core

Navigate: Header account menu > Sign out

Example entry: Sign out after opening the Overview; revisit a protected page.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Header account menu > Sign out.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in then use account menu > Sign out; try previously open protected URL.
4. Verify access/session state in a fresh tab.

EXPECTED Session invalidated; protected content requires login.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-014 Account security P1

Role Platform admin / Visitor | **Dependency** Core

Navigate: Account menu > Account security

Example entry: Generate replacement recovery codes; store in a password manager (never in screenshots).

FOLLOW THESE STEPS

1. Use the designated test identity and open: Account menu > Account security.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open Account menu > Account security and rotate recovery codes with reauthentication.
4. Verify access/session state in a fresh tab.

EXPECTED New codes work and old codes are invalidated.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-015 Unauthenticated API P0

Role Platform admin / Visitor | **Dependency** Core

Navigate: Private browser > protected API/record URL

Example entry: In a private browser window, request a member-only /api endpoint without a session.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Private browser > protected API/record URL.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign out and open a protected API URL or protected application view.
4. Verify access/session state in a fresh tab.

EXPECTED No customer data is returned.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

03 Tenancy & membership

12 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-016 Create organization P1

Role Owner / invited member | **Dependency** Core

Navigate: Login > Create organization or Workspace selector

Example entry: Name: Nivo QA Alpha; slug: nivo-qa-alpha; timezone: Asia/Dubai.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Login > Create organization or Workspace selector.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in as permitted user; choose Create organization; enter unique company name and workspace ID.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Only one organization created; current user is its owner.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-017 Duplicate workspace ID P1

Role Owner / invited member | **Dependency** Core | **STAGING ONLY**

Navigate: Workspace selector > Create organization

Example entry: Try creating Nivo QA Alpha again with the same slug; use a different organization name.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Workspace selector > Create organization.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt to create a second company with an existing workspace ID.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Duplicate rejected with understandable validation.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-018 Switch organizations P1

Role Owner / invited member | **Dependency** Core

Navigate: Header Workspace selector

Example entry: Switch between Nivo QA Alpha and Nivo QA Beta; keep a separate request in each.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Header Workspace selector.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Join Org A and Org B; use workspace selector to switch A -> B -> A.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Visible records, branding and dropdowns match selected organization.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-019 Invite technician P1

Role Owner / invited member | **Dependency** SMTP

Navigate: Setup Center > People & invitations > Invite

Example entry: Invite qa-tech-alpha@YOUR_TEST_DOMAIN; role: Technician (use a real controlled QA mailbox).

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Setup Center > People & invitations > Invite.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. From Org A member setup invite Technician A using email and role; accept invitation.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Technician gains Org A membership only.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-020 Invite requester P1

Role Owner / invited member | **Dependency** SMTP

Navigate: Setup Center > People & invitations > Invite

Example entry: Invite qa-requester-alpha@YOUR_TEST_DOMAIN; role: Requester.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Setup Center > People & invitations > Invite.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Invite Requester A, accept invitation, sign in.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Requester has only requester-permitted features.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-021 Wrong email invitation P0

Role Owner / invited member | **Dependency** SMTP

Navigate: Invitation link > Login

Example entry: Open the invitation in a different test account with a nonmatching email.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Invitation link > Login.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Invite email A; try accepting with authenticated email B.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Acceptance denied; no membership granted.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-022 Revoke membership P0

Role Owner / invited member | **Dependency** Core | **STAGING ONLY**

Navigate: Setup Center > People & invitations > Active members

Example entry: Revoke Technician A only AFTER recording their access and notices; re-invite if necessary.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Setup Center > People & invitations > Active members.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Revoke an active user in Org A while their session is open.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED User loses Org A access; no stale protected data remains.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-023 Cross-tenant ticket URL P0

Role Owner / invited member | **Dependency** Core

Navigate: Org A ticket URL copied into Org B user session

Example entry: Ticket QA-A-INC-01 belongs to Org Alpha; copy its URL into Org Beta user session.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org B unless the scenario specifies otherwise. Open: Org A ticket URL copied into Org B user session.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Copy an Org A ticket URL/ID; open while signed in as Org B-only user.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED No Org A ticket content is returned.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-024 Cross-tenant API write P0

Role Owner / invited member | **Dependency** Core | **STAGING ONLY**

Navigate: Staging tenant-isolation API test (technical operator)

Example entry: Attempt a cross-org update only in authorized staging using supported tests; no production data.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Staging tenant-isolation API test (technical operator).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt to edit Org A record using Org B membership/API session.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Request rejected; Org A record unchanged.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-025 Organization limit P1

Role Owner / invited member | **Dependency** Core | **STAGING ONLY**

Navigate: Platform administration > Plans & limits; Workspace selector > Create

Example entry: Use a staging plan allowing one additional organization, then try to exceed its cap.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Platform administration > Plans & limits; Workspace selector > Create.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Reach configured per-account organization creation limit; attempt another.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED New organization creation blocked by server entitlement.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-026 Brand prefix P1

Role Owner / invited member | **Dependency** Core

Navigate: Setup Center > Brand & app icon

Example entry: Brand prefix: Alpha IT; app title should show organization-specific prefix.

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Setup Center > Brand & app icon.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Set organization prefix DevOps in Brand & app icon.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Workspace displays DevOps | Help Nivo; base brand preserved.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-027 Custom hostname request P1

Role Owner / invited member | **Dependency** Core

Navigate: Platform administration > Customer domains; Setup Center > Brand & app icon

Example entry: Hostname request: qa-alpha.example.test (illustrative; only real owned domains can activate).

FOLLOW THESE STEPS

1. Sign in as Owner / invited member; select Org A unless the scenario specifies otherwise. Open: Platform administration > Customer domains; Setup Center > Brand & app icon.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter a permitted fully qualified hostname in Brand & URL; follow ownership request.
4. Refresh, switch organization and inspect resulting permissions.

EXPECTED Hostname remains pending until verification/provider activation.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

04 Provider console

12 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-028 View all organizations P1

Role Platform admin | **Dependency** Core

Navigate: Platform administration > Organizations

Example entry: Org A: Nivo QA Alpha; Org B: Nivo QA Beta. Confirm both listed in provider console.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Organizations.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.

4. Open Platform Administration > Organizations; inspect two test tenants.
5. Save and validate using an affected organization account.

EXPECTED Both tenants listed with correct plan and status; no unauthorized content exposure.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-029 Create plan P1

Role Platform admin | **Dependency** Core

Navigate: Platform administration > Plans & limits

Example entry: Plan: QA Pilot Limited; 5 members, 3 tickets/day, 20 tickets/month.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Plans & limits.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Create a test plan with daily/monthly ticket quotas and member/AI limits.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Plan persists with specified limits.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-030 Assign plan P1

Role Platform admin | **Dependency** Core

Navigate: Platform administration > Organizations > Plan assignment

Example entry: Assign QA Pilot Limited to Nivo QA Alpha; leave Org Beta on another plan.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Organizations > Plan assignment.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Assign plan to Org A, leave Org B unchanged.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Org A entitlements update; Org B unaffected.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-031 Daily ticket quota P0

Role Platform admin | **Dependency** Core | **STAGING ONLY**

Navigate: Platform administration > Plans & limits / Organizations

Example entry: Limit: 3 tickets/day; attempt the 4th new request in Org Alpha.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Plans & limits / Organizations.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Set small daily quota for Org A; create up to limit and one additional ticket.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Extra ticket rejected server-side; no partial record created.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-032 Monthly ticket quota P1

Role Platform admin | **Dependency** Core | **STAGING ONLY**

Navigate: Platform administration > Plans & limits / Organizations

Example entry: Limit: 5 tickets/month; create controlled test requests, then exceed limit.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Plans & limits / Organizations.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Set small monthly quota; attempt ticket beyond quota.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Extra ticket rejected with plan/usage explanation.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-033 Feature gate P1

Role Platform admin | **Dependency** Core | **STAGING ONLY**

Navigate: Platform administration > Plans & limits / Organizations

Example entry: Disable a nonessential module in a QA plan; confirm unavailable to Org Alpha.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Plans & limits / Organizations.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Disable a supported module for Org A; attempt direct API and UI access.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED UI access removed and backend denies unauthorized action.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-034 Suspension P0

Role Platform admin | **Dependency** Core | **STAGING ONLY**

Navigate: Platform administration > Organizations > State

Example entry: Suspend only Nivo QA Beta; confirm Org Alpha still works.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Organizations > State.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Suspend Org A, attempt user write, then restore.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Writes blocked during suspension; restored according to policy.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-035 Provider isolation P0

Role Platform admin | **Dependency** Core

Navigate: Platform administration > Organizations; workspace selector

Example entry: Provider-only account should not see Org Alpha ticket details without membership.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Organizations; workspace selector.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.

3. Sign in with provider MFA.
4. Use provider account without Org A membership to open Org A ticket URL.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Provider privilege alone does not grant customer ticket visibility.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-036 SMTP provider settings P1

Role Platform admin | **Dependency** SMTP

Navigate: Platform administration > Email delivery

Example entry: Sender: notifications@YOUR_TEST_DOMAIN; Reply-To: support@YOUR_TEST_DOMAIN; test mailbox required.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Email delivery.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Open Email delivery; configure test SMTP and send a test message.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Test delivery queued; accepted/failed status visible without exposing password.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-037 Shared AI policy P1

Role Platform admin | **Dependency** Ollama

Navigate: Platform administration > AI & voice services

Example entry: AI provider: private Ollama URL (only if configured), allowance 2 jobs/day.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > AI & voice services.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Configure shared Ollama URL/model and org entitlement.
5. Save and validate using an affected organization account.

6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Only authorized organizations can use configured gateway.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-038 Brand default P1

Role Platform admin | **Dependency** Core

Navigate: Platform administration > Signup & branding

Example entry: Default application name: Help Nivo; provider icon: a safe 256x256 PNG.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Signup & branding.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Change provider application icon/default branding.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Shared sign-in uses provider icon; org overrides preserved.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-039 Google identity config P1

Role Platform admin | **Dependency** Google OAuth

Navigate: Platform administration > Identity & sign-in

Example entry: Google OIDC: use dedicated QA client ID, exact HTTPS callback URI; no real secret in evidence.

FOLLOW THESE STEPS

1. Sign in as Platform admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Identity & sign-in.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in with provider MFA.
4. Configure Google OAuth client/callback on provider identity page.
5. Save and validate using an affected organization account.
6. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Adapter activates only after valid provider configuration.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

05 Requests & incidents

26 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-040 Create incident P0

Role Technician / Requester | **Dependency** Core

Navigate: Requests > New request

Example entry: Type Incident; subject QA-A-INC-01 VPN disconnect; description VPN drops every 10 minutes; priority Normal.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > New request.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Choose Requests > New; select Incident, enter unique subject/description, priority, category and submit.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Ticket ID created; requester and permitted assignee see record.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-041 Create service request P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > New request

Example entry: Type Service request; subject QA-A-SR-01 New mouse; description USB mouse required for QA desk.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > New request.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Choose Requests > New > Service request; complete mandatory fields.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Request saved with correct type and organization.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-042 Mandatory field validation P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > New request

Example entry: Open New request with Subject blank; then enter QA-A-INC-INVALID only after checking validation.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > New request.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Submit new ticket without subject or required configured fields.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Inline validation; no incomplete ticket saved.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-043 Invalid dropdown value P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > New request; Setup Center > Reference settings

Example entry: Attempt a value not in the configured category list through approved UI/API staging test.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > New request; Setup Center > Reference settings.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt an unsupported category or inactive option through UI/API.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Selection rejected; only organization-active choices accepted.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-044 Assign technician P0

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Open a ticket > Assignment

Example entry: Assign QA-A-INC-01 to Technician A.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Open a ticket > Assignment.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open unassigned request and assign to active technician.

4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Assignee updates; assignment event recorded and recipient notified.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-045 Assign to me P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Open unassigned ticket > Assign to me

Example entry: Technician A chooses Assign to me on an unassigned ticket QA-A-INC-02.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Open unassigned ticket > Assign to me.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open eligible unassigned request and select Assign to me.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Current technician becomes assignee.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-046 Start work P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Start

Example entry: Set ticket QA-A-INC-01 from Open to In progress/Start.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Start.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open assigned request; choose Start.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Request transitions to in-progress state with history entry.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-047 Put on hold P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Hold

Example entry: Put QA-A-INC-01 On hold; note: Awaiting user VPN logs.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Hold.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Choose Hold, enter required reason.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Request on hold; reason recorded; SLA pause applied if configured.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-048 Resume from hold P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Resume

Example entry: Resume QA-A-INC-01 after recording hold.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Resume.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open on-hold request and choose Resume.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Request returns to active state; SLA resumes.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-049 Resolve request P0

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Resolve

Example entry: Resolution note: Cleared cached VPN profile and reauthenticated.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Resolve.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter resolution notes and choose Resolve.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Resolved state and history recorded; requester notification generated.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-050 Close request P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Close

Example entry: Close resolved QA-A-INC-01; requester verifies final status.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Close.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Close eligible resolved request.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Closed state recorded; duplicate closure events avoided.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-051 Reopen request P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Reopen

Example entry: Requester A reopens QA-A-INC-01; reason: VPN issue returned.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Reopen.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. As eligible requester reopen resolved/closed request.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Reopened state recorded; eligible technician/owner notified.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-052 Auto closure P1

Role Technician / Requester | **Dependency** Background worker

Navigate: Setup Center > SLA & policies > Automatic closure; Requests

Example entry: Configure a short QA auto-close window; resolve QA-A-AUTOCLOSE-01.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Setup Center > SLA & policies > Automatic closure; Requests.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Configure short closure interval in test org; resolve and run worker after elapsed test interval.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Eligible request auto-closes once; no duplicate notifications.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-053 Public reply P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Conversation > Public reply

Example entry: Public reply: Please confirm your VPN is stable after reconnecting.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Conversation > Public reply.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Add public response as technician.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Requester can see reply; public-reply notification generated.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-054 Private note P0

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Conversation > Internal/private note

Example entry: Internal note: Recheck VPN gateway policy; must remain invisible to requester.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Conversation > Internal/private note.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Add private technician note.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Only authorized internal users see note; requester cannot.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-055 Request template P1

Role Technician / Requester | **Dependency** Core

Navigate: Setup Center > Request templates; Requests > New

Example entry: Template QA Password Reset: title + standard category, requester-visible.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Setup Center > Request templates; Requests > New.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create template in Setup Center; apply to new request.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Configured fields prepopulate correctly.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-056 Reply template P1

Role Technician / Requester | **Dependency** Core

Navigate: Setup Center > Reply templates; Requests > Conversation

Example entry: Reply template: Hello {requester}, we are investigating request {ticket}.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Setup Center > Reply templates; Requests > Conversation.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create reusable reply; insert into ticket reply editor.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Placeholder substitution renders expected values and is editable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-057 Worklog P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Worklogs

Example entry: Worklog: 25 minutes, billable No, note Reviewed VPN logs.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Worklogs.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Add a 30-minute billable worklog entry.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Worklog saved with user/time and report totals updated.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-058 Upload attachment P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Attachments

Example entry: Create qa-test.txt containing fictional text; upload as permitted public attachment.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Attachments.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attach a small allowed-format file to ticket.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Upload succeeds; authorized download returns same content.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-059 Reject oversized attachment P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Attachments

Example entry: Upload an intentionally oversized synthetic text file in disposable test environment.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Attachments.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Upload file exceeding documented 2 MiB per-file limit.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Upload rejected; no attachment persisted.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-060 Unauthorized attachment P0

Role Technician / Requester | **Dependency** Core | **STAGING ONLY**

Navigate: Requests > Ticket details > Attachments (separate requester session)

Example entry: Requester B attempts access to private attachment of QA-A-INC-01 (should be denied).

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org B unless the scenario specifies otherwise. Open: Requests > Ticket details > Attachments (separate requester session).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Copy attachment URL; open with another organization account.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED No access to attachment bytes or metadata.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-061 Merge duplicate P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Merge

Example entry: Merge duplicates QA-A-DUP-01 into QA-A-DUP-02 created by same Requester A.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Merge.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create two eligible requests; merge one into the other.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Single target retains allowed history; source marked merged.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-062 Related CI P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Ticket details > Related CI

Example entry: Link CI QA-A-CI-VPN-01 to request QA-A-INC-01.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Related CI.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Link an existing Org A configuration item to ticket.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Link saved; visible only within Org A.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-063 Satisfaction survey P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > Resolved ticket > Satisfaction

Example entry: Requester A enters satisfaction 5/5; comment Fast response and clear fix.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > Resolved ticket > Satisfaction.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. After resolution, submit requester rating and comment.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Rating saved once and appears in relevant reports.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-064 Search and filter P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > All / Closed > Search and filters

Example entry: Search term QA-A-INC; filter Incident and relevant status.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > All / Closed > Search and filters.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Filter Requests by status, priority, assignee and subject.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Only matching current-organization requests displayed.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-065 Bulk update P1

Role Technician / Requester | **Dependency** Core

Navigate: Requests > List > multi-select > Bulk actions

Example entry: Select two disposable QA tickets; bulk assign to Technician A.

FOLLOW THESE STEPS

1. Sign in as Technician / Requester; select Org A unless the scenario specifies otherwise. Open: Requests > List > multi-select > Bulk actions.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Select multiple eligible tickets and perform supported bulk action.
4. Reopen ticket, verify history and compare requester/technician views.

EXPECTED Selected records update; unauthorized records unchanged.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

06 Catalog SLA & routing

17 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-066 Create catalog service P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > Service catalog; Sidebar > Service catalog

Example entry: Catalog: QA New Laptop; category Hardware; default priority Normal; active Yes.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > Service catalog; Sidebar > Service catalog.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open Setup Center > Service catalog; create New laptop request with title, category and group.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Service appears in the same organization only.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-067 Required catalog question P1

Role Org admin / Approver | **Dependency** Core

Navigate: Service catalog > New laptop request > Questions

Example entry: Required question: Cost center; leave it empty once, then enter CC-100.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Service catalog > New laptop request > Questions.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Add required text/dropdown question; submit request without response.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Validation prevents incomplete submission.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-068 Catalog option isolation P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > Service catalog > Dropdown question

Example entry: Dropdown question Laptop size: 13-inch / 15-inch; ensure Org Beta has its own options.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > Service catalog > Dropdown question.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Configure different dropdown choices in Org A and Org B; open forms.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Each organization sees only its own choices.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-069 Submit catalog request P1

Role Org admin / Approver | **Dependency** Core

Navigate: Service catalog > New laptop request > Request

Example entry: Requester A submits QA New Laptop; answer Cost center CC-100, Size 13-inch.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Service catalog > New laptop request > Request.

2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. As requester select catalog service, answer required questions and submit.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Service request created with captured answers.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-070 Sequential approval P0

Role Org admin / Approver | **Dependency** Core

Navigate: Sidebar > Service approvals > Pending

Example entry: Approval stage 1: Technician A; stage 2: Approver A (different account).

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Sidebar > Service approvals > Pending.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Configure two independent approval stages and submit service request.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Stage 2 remains pending until stage 1 approved.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-071 Reject service approval P0

Role Org admin / Approver | **Dependency** Core

Navigate: Service approvals > Pending > Reject

Example entry: Reject request QA-A-SVC-REJECT-01; reason Not budgeted.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Service approvals > Pending > Reject.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. As designated approver reject stage with reason.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Fulfillment blocked and reason recorded.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-072 Approve service request P1

Role Org admin / Approver | **Dependency** Core

Navigate: Service approvals > Pending > Approve; Tasks

Example entry: Approve request QA-A-SVC-APPROVE-01; task Prepare device should appear once.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Service approvals > Pending > Approve; Tasks.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Approve all configured stages using distinct eligible approvers.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Fulfillment tasks created exactly once.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-073 Prevent self-approval P0

Role Org admin / Approver | **Dependency** Core | **STAGING ONLY**

Navigate: Service approvals > Pending > Approve as requester

Example entry: Requester A must not approve their own laptop request.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Service approvals > Pending > Approve as requester.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt to approve request created/owned by same user.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Self-approval blocked.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-074 Duplicate approval P0

Role Org admin / Approver | **Dependency** Core | **STAGING ONLY**

Navigate: Service approvals > Pending > Approve from two tabs

Example entry: Click Approve twice/replay request from two tabs; only one decision should persist.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Service approvals > Pending > Approve from two tabs.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Submit same approval action twice.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED No duplicate tasks or duplicate decisions.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-075 Business calendar P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > SLA & policies > Business hours

Example entry: Timezone Asia/Dubai, Mon-Fri 09:00-17:00; holiday: one test date.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > SLA & policies > Business hours.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Set working days, timezone, hours and holiday.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED SLA due calculation excludes configured non-working time.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-076 SLA breach P0

Role Org admin / Approver | **Dependency** Background worker | **STAGING ONLY**

Navigate: Setup Center > SLA & policies; Requests > SLA

Example entry: SLA resolution target 30 business minutes; create QA-A-SLA-01 for controlled breach.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > SLA & policies; Requests > SLA.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create overdue test request with short SLA; run worker.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Breach recorded; authorized recipient notified once.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-077 SLA hold pause P1

Role Org admin / Approver | **Dependency** Core

Navigate: Requests > Ticket details > SLA; Hold/Resume

Example entry: Hold QA-A-SLA-02 for 15 minutes, then resume; compare remaining time.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > SLA; Hold/Resume.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Put ticket on hold with pause-on-hold enabled.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Paused interval not counted toward configured SLA.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-078 SLA escalation P1

Role Org admin / Approver | **Dependency** Background worker | **STAGING ONLY**

Navigate: Setup Center > SLA & policies > Escalation

Example entry: Configured escalation group: QA Service Desk; test breach after safe time interval.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > SLA & policies > Escalation.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Configure escalation support group and breach target.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Escalation follows configured rule and audit trail.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-079 First-match assignment P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > Assignment rules

Example entry: Rules: subject contains VPN -> group QA Service Desk, priority Normal.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > Assignment rules.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create two matching ordered assignment rules; submit matching ticket.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED First matching rule determines routing.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-080 Round-robin P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > Assignment rules > Round-robin pool

Example entry: Pool: Technician A and Approver A; create QA-A-ROUND-01 and QA-A-ROUND-02.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > Assignment rules > Round-robin pool.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Configure eligible technicians and submit successive requests.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Assignments rotate among eligible configured technicians.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-081 Impact urgency priority P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > SLA & policies > Impact/urgency matrix

Example entry: Impact High + Urgency High -> mapped High priority; compare calculated result.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > SLA & policies > Impact/urgency matrix.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Set impact and urgency in a request.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Priority resolves using organization matrix.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-082 Disabled catalog value P1

Role Org admin / Approver | **Dependency** Core

Navigate: Setup Center > Reference settings > Category

Example entry: Disable temporary category QA Legacy Access; it should not be selectable for new tickets.

FOLLOW THESE STEPS

1. Sign in as Org admin / Approver; select Org A unless the scenario specifies otherwise. Open: Setup Center > Reference settings > Category.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Disable category used by historical ticket.
4. Validate via a newly created request and its audit/history.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Existing history retained; new forms do not offer disabled option.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

07 Change release & knowledge

18 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-083 Create change P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Sidebar > Changes > New

Example entry: Change title QA-CHG-VPN-01; type Normal; risk Medium; rollback Restore old VPN policy.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Sidebar > Changes > New.

2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open Changes; create a change with owner, type, priority, risk and plan.
4. Reopen record and review process history/permissions.

EXPECTED Change created in current organization.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-084 Change schedule P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Sidebar > Changes > Schedule / Calendar

Example entry: Scheduled start: next business day at 11:00; end 12:00 (Asia/Dubai).

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Sidebar > Changes > Schedule / Calendar.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Set planned start/end dates on a change.
4. Reopen record and review process history/permissions.

EXPECTED Dates persist and appear in supported scheduler.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-085 Create workflow draft P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Setup Center > Workflow designer > New workflow

Example entry: Workflow QA Change Standard: Submit -> Assess -> Independent approval -> Implement -> Validate -> Done.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Setup Center > Workflow designer > New workflow.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open Setup Center > Workflow designer; create change workflow draft.
4. Reopen record and review process history/permissions.

EXPECTED Draft saves without affecting active records.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-086 Validate connections P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Setup Center > Workflow designer > Draft > Connections

Example entry: Temporarily disconnect Assess -> Approval in QA draft; click Validate.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Setup Center > Workflow designer > Draft > Connections.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Make a workflow node point to missing/invalid destination and attempt publish.
4. Reopen record and review process history/permissions.

EXPECTED Publish blocked with useful validation.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-087 Publish revision P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Setup Center > Workflow designer > Publish revision

Example entry: Publish QA Change Standard revision 1; edit draft and publish revision 2.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Setup Center > Workflow designer > Publish revision.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Publish valid workflow; then edit draft and publish again.
4. Reopen record and review process history/permissions.

EXPECTED Revision numbers differ; published prior revision remains immutable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-088 Attach workflow P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Changes > QA change detail > Workflow panel

Example entry: Attach published QA Change Standard to QA-CHG-VPN-01; owner Technician A.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Changes > QA change detail > Workflow panel.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Apply published workflow to prepared change.

4. Reopen record and review process history/permissions.

EXPECTED Record begins at configured start node.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-089 Approval progression P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Changes > Workflow panel > Approve / Complete

Example entry: Approver A approves, Technician A completes implementation notes.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Changes > Workflow panel > Approve / Complete.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Complete assessment then approve with designated reviewer.
4. Reopen record and review process history/permissions.

EXPECTED Workflow moves to approved successor and records decision.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-090 Workflow rejection P1

Role Change owner / Reviewer | **Dependency** Core | **STAGING ONLY**

Navigate: Changes > Workflow panel > Reject

Example entry: Approver A rejects QA-CHG-REJECT-01; reason Incomplete rollback plan.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Changes > Workflow panel > Reject.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Reject approval as designated reviewer.
4. Reopen record and review process history/permissions.

EXPECTED Workflow follows rejected path; implementation not allowed.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-091 Workflow self-approval P0

Role Change owner / Reviewer | **Dependency** Core | **STAGING ONLY**

Navigate: Changes > Workflow panel > Approve as owner

Example entry: Change owner Technician A attempts to approve their own change.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Changes > Workflow panel > Approve as owner.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt workflow approval as initiator/owner.
4. Reopen record and review process history/permissions.

EXPECTED Action denied.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-092 Skip workflow stage P0

Role Change owner / Reviewer | **Dependency** Core | **STAGING ONLY**

Navigate: Changes > Record Edit vs Workflow panel

Example entry: Try direct status edit to Completed while workflow waits for approval.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Changes > Record Edit vs Workflow panel.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Try direct edit/API status jump to implementation/completion.
4. Reopen record and review process history/permissions.

EXPECTED Workflow-controlled stage cannot be bypassed.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-093 Complete implementation P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Changes > Workflow panel > Implementation / Validation

Example entry: Implementation note: Updated QA VPN policy; validation: connected successfully.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Changes > Workflow panel > Implementation / Validation.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Complete approved implementation node and validation node.
4. Reopen record and review process history/permissions.

EXPECTED Workflow reaches terminal completed stage with history.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-094 Create release P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Operations > Releases > New release

Example entry: Release QA-REL-VPN-01; owner Technician A; link QA-CHG-VPN-01.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Operations > Releases > New release.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open Releases; create release linked to change and CI.
4. Reopen record and review process history/permissions.

EXPECTED Release persists with links.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-095 Release prerequisites P1

Role Change owner / Reviewer | **Dependency** Core | **STAGING ONLY**

Navigate: Operations > Releases > Linked change / Schedule

Example entry: Attempt release completion before linked change is completed.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Operations > Releases > Linked change / Schedule.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt release completion while linked change is not ready.
4. Reopen record and review process history/permissions.

EXPECTED Completion blocked until prerequisites satisfied.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-096 Release workflow P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Setup Center > Workflow designer > Release workflow

Example entry: Workflow QA Release Standard: Plan -> Approve -> Deploy -> Validate -> Done.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Setup Center > Workflow designer > Release workflow.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Publish release workflow and apply it to release.
4. Reopen record and review process history/permissions.

EXPECTED Release follows defined steps and approval path.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-097 Problem record P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Sidebar > Problems > New

Example entry: Problem QA-PRB-VPN-01: repeated VPN disconnects; root cause stale client policy.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Sidebar > Problems > New.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create problem linked to recurring incidents.
4. Reopen record and review process history/permissions.

EXPECTED Problem and incident relationships saved.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-098 Known error P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Problems > QA problem > Publish known error

Example entry: Known error: VPN cache corruption; workaround delete cached VPN profile.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Problems > QA problem > Publish known error.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Publish known-error information for a problem.
4. Reopen record and review process history/permissions.

EXPECTED Knowledge/known-error view reflects recorded workaround.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-099 Knowledge article P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Sidebar > Knowledge base > New article

Example entry: Knowledge article QA VPN Troubleshooting; body contains fictional steps.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Sidebar > Knowledge base > New article.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create and publish article, search as permitted requester.
4. Reopen record and review process history/permissions.

EXPECTED Published article searchable and viewable according to audience.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-100 Knowledge rating P1

Role Change owner / Reviewer | **Dependency** Core

Navigate: Knowledge base > Published article > Rating

Example entry: Rate published QA VPN Troubleshooting article 4/5.

FOLLOW THESE STEPS

1. Sign in as Change owner / Reviewer; select Org A unless the scenario specifies otherwise. Open: Knowledge base > Published article > Rating.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Rate a published knowledge article.
4. Reopen record and review process history/permissions.

EXPECTED Rating recorded and aggregated without duplicate misuse.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

08 Assets CMDB & operations

18 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-101 Create asset P1

Role Technician / Org admin | **Dependency** Core

Navigate: Sidebar > Assets > New asset

Example entry: Asset QA-LAP-001; serial QA-ONLY-001; location Dubai Office; state In store.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > Assets > New asset.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open Assets; create an asset with serial/category/location/status.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Asset appears in Org A inventory.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-102 Asset category setup P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Asset loans > New loan

Example entry: Loan QA-LAP-001 to Requester A; due in 7 days; then return.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Asset loans > New loan.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Add asset category in Setup Center > Reference settings.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED New category appears in Org A asset form only.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-103 Asset loan P1

Role Technician / Org admin | **Dependency** Core | **STAGING ONLY**

Navigate: Operations > Asset loans > New loan

Example entry: Try a second active loan for QA-LAP-001 while first is open.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Asset loans > New loan.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Assign asset loan to a person with return date.

4. Refresh, inspect history and verify Org B isolation.

EXPECTED Asset loan recorded; status/holder updated.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-104 Return asset P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Asset loans > Return

Example entry: Return QA-LAP-001; confirm inventory state restored.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Asset loans > Return.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Return loaned asset.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Loan closes and asset returns to appropriate state.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-105 Create CI P1

Role Technician / Org admin | **Dependency** Core

Navigate: Sidebar > CMDB > New CI

Example entry: CI QA-CI-VPN-01; type Network service; environment QA; status Operational.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > CMDB > New CI.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open CMDB; add a configuration item and owner.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED CI saved in Org A only.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-106 CI relationship P1

Role Technician / Org admin | **Dependency** Core

Navigate: Sidebar > CMDB > CI relationships

Example entry: Relation: QA-CI-VPN-01 depends on QA-CI-EDGE-01.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > CMDB > CI relationships.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Link application CI to database CI.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Relationship saved; impact view traverses relationship.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-107 Cross-org CI link P0

Role Technician / Org admin | **Dependency** Core | **STAGING ONLY**

Navigate: Sidebar > CMDB > New relationship (staging isolation)

Example entry: In Org A try to link CI belonging only to Org B; should be refused.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org B unless the scenario specifies otherwise. Open: Sidebar > CMDB > New relationship (staging isolation).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt to link Org A CI to Org B CI.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Cross-tenant relationship rejected.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-108 Software entitlement P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Software licenses > New entitlement

Example entry: Software QA Antivirus; vendor QA Vendor; purchased seats 2.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Software licenses > New entitlement.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Record software entitlement with purchased seat count.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Entitlement appears with correct total.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-109 Allocate software seat P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Software licenses > Allocations

Example entry: Allocate one QA Antivirus seat to QA-LAP-001.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Software licenses > Allocations.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Allocate an available seat to an eligible asset/user.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Allocation recorded; available seat count reduces.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-110 Over-allocate license P1

Role Technician / Org admin | **Dependency** Core | **STAGING ONLY**

Navigate: Operations > Software licenses > Allocations

Example entry: Attempt a third seat allocation after two seats are assigned.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Software licenses > Allocations.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt allocation beyond purchased seats.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED System enforces documented allocation controls or flags the discrepancy; record observed behavior.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-111 Supplier P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Suppliers > New

Example entry: Supplier QA Vendor; contact qa-vendor@YOUR_TEST_DOMAIN (use synthetic contact).

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Suppliers > New.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create supplier with contact details.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Supplier available for purchasing in Org A.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-112 Contract expiry P1

Role Technician / Org admin | **Dependency** Background worker

Navigate: Operations > Contracts > New

Example entry: Contract QA-SUPPORT-01; vendor QA Vendor; expiry in 20 days; value 5000 minor units.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Contracts > New.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create contract with approaching expiry and run scheduled worker.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Contract expiry appears in alerts/report when due.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-113 Purchase order P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Purchases > New

Example entry: Purchase QA-PO-001; item Laptop dock; quantity 2; unit price 15000 minor units.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Purchases > New.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create purchase with supplier, quantities and unit prices.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Total equals sum of line item amounts.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-114 Purchase approval P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Purchases > Approval

Example entry: Requester Technician A; independent approver Approver A.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Purchases > Approval.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Submit purchase for independent approval.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Eligible reviewer can approve/reject; initiator cannot self-approve.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-115 Purchase receiving P0

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Purchases > Receive

Example entry: Receive approved QA-PO-001 once; verify exactly two items are reflected.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Purchases > Receive.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Mark approved purchase received.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Received assets created exactly once; repeat receive does not duplicate.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-116 Create project P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Projects > New

Example entry: Project QA Office Upgrade; owner Technician A; due in 30 days.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Projects > New.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create project and milestone with dates.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Project and milestone visible in Org A.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-117 Task dependency P1

Role Technician / Org admin | **Dependency** Core

Navigate: Operations > Projects > Work items

Example entry: Project items: Buy docks -> Install docks; only one prerequisite.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Operations > Projects > Work items.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create task dependent on unfinished prerequisite; attempt complete.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Completion respects documented dependency rules.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-118 Task scheduler P1

Role Technician / Org admin | **Dependency** Core

Navigate: Sidebar > Tasks; Scheduler

Example entry: Task QA Configure VPN; assign Technician A; schedule tomorrow 10:00-11:00.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > Tasks; Scheduler.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Assign due date and owner to task; open scheduler.
4. Refresh, inspect history and verify Org B isolation.

EXPECTED Task appears on appropriate date for permitted user.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

09 Notifications & email

14 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-119 Ticket creation pop-up P0

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Requester A browser > Requests; Owner A browser > bell

Example entry: Unassigned new request QA-NOTIFY-UNASSIGNED-01 created by Requester A.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Requester A browser > Requests; Owner A browser > bell.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Create unassigned request as requester in browser A; keep owner session open in browser B.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Owner sees non-blocking pop-up and unread badge within next successful poll.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-120 Assigned ticket notification P1

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Technician A browser > bell / Notifications

Example entry: Request QA-NOTIFY-ASSIGNED-01 assigned to Technician A.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Technician A browser > bell / Notifications.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Create request assigned to technician; inspect requester and technician sessions.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Eligible recipients get one notification each.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-121 Notification inbox P1

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Header bell > Notifications > All

Example entry: Bell count contains QA-NOTIFY-UNASSIGNED-01; inbox shows its record.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Header bell > Notifications > All.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Open bell icon; inspect unread and history.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Current organization inbox lists authorized notifications.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-122 Mark read P1

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Notifications > Open item / Mark read

Example entry: Open first unread QA notification and mark it read.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Notifications > Open item / Mark read.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Open one notification and mark read.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Unread count decreases; record remains in history.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-123 Dismiss pop-up P1

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Header notification pop-up > Dismiss

Example entry: Dismiss popup for QA-NOTIFY-02 without opening it.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Header notification pop-up > Dismiss.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Dismiss pop-up without opening record.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Pop-up disappears but inbox entry remains.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-124 Mute category P1

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Header bell > Delivery settings

Example entry: Mute category New requests for a single Org A membership.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Header bell > Delivery settings.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Open Bell > Delivery settings; mute ticket-created pop-ups.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Muted event does not pop up; other categories behave as configured.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-125 Org switch notifications P0

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Header Workspace selector + bell

Example entry: Switch Org A -> Org B while unread Org A notice exists.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org B unless the scenario specifies otherwise. Open: Header Workspace selector + bell.

2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Switch Org A to Org B with unread notifications in A.
5. Verify inbox, unread count, recipient and timing.

EXPECTED No Org A ticket details exposed in Org B.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-126 Revoke then poll P0

Role Requester / Technician / Owner | **Dependency** Background worker | **STAGING ONLY**

Navigate: Setup Center > People & invitations + Notifications

Example entry: Revoke Technician A membership after making an assigned QA notification.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Setup Center > People & invitations + Notifications.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Revoke member in Org A while notification inbox open.
5. Verify inbox, unread count, recipient and timing.

EXPECTED No stale Org A notification details returned after next check.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-127 Scheduled reminder P1

Role Requester / Technician / Owner | **Dependency** Background worker

Navigate: Reminders > New; background worker > Notifications

Example entry: Personal reminder QA Follow up VPN due within 5 minutes; worker must run.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Reminders > New; background worker > Notifications.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Create due reminder; run background worker at test due time.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Correct recipient receives reminder once.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-128 Email invite P1

Role Requester / Technician / Owner | **Dependency** SMTP

Navigate: Setup Center > People & invitations; recipient inbox

Example entry: Invite qa-tech-alpha@YOUR_TEST_DOMAIN and verify invitation email is delivered.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Setup Center > People & invitations; recipient inbox.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Invite test user with working SMTP; check actual mailbox.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Email arrives with valid organization-bound invitation link.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-129 Welcome email P1

Role Requester / Technician / Owner | **Dependency** SMTP

Navigate: Signup / Activation; recipient inbox

Example entry: Activate Org QA Gamma with a controlled mailbox; verify welcome (staging only).

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Signup / Activation; recipient inbox.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Complete verified signup using real SMTP.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Welcome email delivered without plaintext password.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-130 Password reset email P1

Role Requester / Technician / Owner | **Dependency** SMTP

Navigate: Login > Forgot password; recipient inbox

Example entry: Request password reset for controlled QA account; verify email link.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Login > Forgot password; recipient inbox.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Request password reset for test user.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Single-use expiring reset link delivered; no plaintext password.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-131 Email retry P1

Role Requester / Technician / Owner | **Dependency** SMTP | **STAGING ONLY**

Navigate: Platform administration > Email delivery > Queue

Example entry: Pause SMTP test relay temporarily in isolated staging; watch queued->retry->sent.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Platform administration > Email delivery > Queue.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Simulate SMTP temporary failure and inspect mail queue.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Failure recorded; retry behavior follows policy without duplicate send.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-132 Desktop notification P1

Role Requester / Technician / Owner | **Dependency** Browser permission

Navigate: Header bell > Delivery settings > Desktop alerts

Example entry: Enable desktop alerts and browser permission; title preview remains off.

FOLLOW THESE STEPS

1. Sign in as Requester / Technician / Owner; select Org A unless the scenario specifies otherwise. Open: Header bell > Delivery settings > Desktop alerts.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Open two independent browser sessions for Org A.
4. Enable browser permission on secure origin with tab open; trigger event.
5. Verify inbox, unread count, recipient and timing.

EXPECTED Optional desktop notification displayed where supported; no closed-browser push expected.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

10 Dashboard & reports

10 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-133 Overview metrics P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Overview

Example entry: Before opening Overview create 2 open QA tickets and 1 resolved QA ticket.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Sidebar > Overview.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create and resolve a ticket; return to Overview.
4. Compare displayed totals with source records.

EXPECTED Counters reflect actual Org A records after refresh.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-134 Ticket trend chart P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Overview > Request trend

Example entry: Create 3 requests with distinct dates; compare 14-day trend bars.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Sidebar > Overview > Request trend.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create tickets on two dates in test environment and open Dashboard.
4. Compare displayed totals with source records.

EXPECTED Chart represents recorded activity, not sample data.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-135 Technician workload P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Overview / Reports > Technician activity

Example entry: Assign 2 tickets to Technician A and 1 to Approver A; inspect workload.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Sidebar > Overview / Reports > Technician activity.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Assign several tickets to two technicians; inspect dashboard.
4. Compare displayed totals with source records.

EXPECTED Per-technician counts reflect assignments.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-136 SLA report P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Reports / Operations > Operational reports

Example entry: Create QA SLA breach and one on-time resolution, then compare report.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Sidebar > Reports / Operations > Operational reports.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Generate supported SLA report after creating breached/non-breached cases.
4. Compare displayed totals with source records.

EXPECTED Correct statuses and totals.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-137 Worklog report P1

Role Owner / Technician | **Dependency** Core

Navigate: Requests > Worklogs; Operations > Operational reports

Example entry: Record 25 and 45 minutes in worklogs; total should be 70 minutes.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Requests > Worklogs; Operations > Operational reports.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Add worklogs and open supported effort report.
4. Compare displayed totals with source records.

EXPECTED Totals match entered time.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-138 Contract expiry report P1

Role Owner / Technician | **Dependency** Core

Navigate: Operations > Contracts; Operations > Operational reports

Example entry: Make QA contract expire in 20 days; inspect contract-expiry report.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Operations > Contracts; Operations > Operational reports.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create near-expiry contract and open report.
4. Compare displayed totals with source records.

EXPECTED Record included within report filters.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-139 CSV export P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Reports / Operations > Operational reports > Export CSV

Example entry: Export ticket report containing a cell starting with =1+1 to verify CSV neutralization.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Sidebar > Reports / Operations > Operational reports > Export CSV.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Apply report filters then export CSV.
4. Compare displayed totals with source records.

EXPECTED Downloaded file matches visible scoped results and columns.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-140 Cross-tenant report P0

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Reports (as Org B)

Example entry: Org B requester opens Reports; Org A ticket QA-A-INC-01 must not appear.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org B unless the scenario specifies otherwise. Open: Sidebar > Reports (as Org B).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. As Org B account request Org A report identifiers.
4. Compare displayed totals with source records.

EXPECTED No Org A data in report or CSV.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-141 Empty dashboard P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Overview (new empty org)

Example entry: Create new empty QA Org C and view empty dashboard (no fabricated data).

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org B unless the scenario specifies otherwise. Open: Sidebar > Overview (new empty org).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Create fresh empty organization and open Overview/Reports.
4. Compare displayed totals with source records.

EXPECTED Clear empty states; no fabricated records or errors.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-142 Date filter P1

Role Owner / Technician | **Dependency** Core

Navigate: Sidebar > Reports > Date filters

Example entry: Choose this week and last 30 days; compare report totals with test tickets.

FOLLOW THESE STEPS

1. Sign in as Owner / Technician; select Org A unless the scenario specifies otherwise. Open: Sidebar > Reports > Date filters.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Apply date range to request/report views.
4. Compare displayed totals with source records.

EXPECTED Only records in selected range included.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

11 AI & voice

11 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-143 Ollama provider connection P2

Role Technician / Org admin | **Dependency** Ollama

Navigate: Platform administration > AI & voice services

Example entry: Provider Ollama private endpoint; model qwen3:4b only if installed and reachable.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > AI & voice services.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Configure reachable private Ollama base URL and supported model.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Connection test succeeds; URL not exposed to end users.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-144 AI consent disabled P0

Role Technician / Org admin | **Dependency** Ollama

Navigate: Setup Center > AI & voice / consent

Example entry: Keep Org A AI processing consent disabled; attempt AI Workbench generation.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Setup Center > AI & voice / consent.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Disable organization AI consent; attempt AI request.
4. Review audit/usage and verify no unauthorized write.

EXPECTED AI operation blocked server-side.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-145 AI ticket proposal P2

Role Technician / Org admin | **Dependency** Ollama

Navigate: Sidebar > AI Workbench > Ticket proposal

Example entry: Input: Draft a request about intermittent VPN failures for the QA office.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Ticket proposal.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter text describing issue; request draft ticket.
4. Review audit/usage and verify no unauthorized write.

EXPECTED AI produces editable proposal; no ticket saved before explicit confirmation.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-146 AI task proposal P2

Role Technician / Org admin | **Dependency** Ollama

Navigate: Sidebar > AI Workbench > Task proposal

Example entry: Input: Draft a task to reconfigure QA VPN profile by Friday.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Task proposal.

2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Request task draft from text.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Reviewable task draft created; no silent execution.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-147 AI reply draft P2

Role Technician / Org admin | **Dependency** Ollama

Navigate: Sidebar > AI Workbench > Reply draft

Example entry: Input: Draft a polite response requesting VPN logs from requester.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Reply draft.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Ask for response suggestion from existing ticket.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Suggestion displayed for review, not auto-sent.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-148 AI report proposal P2

Role Technician / Org admin | **Dependency** Ollama

Navigate: Sidebar > AI Workbench > Report proposal

Example entry: Input: Report count of open QA tickets by priority (bounded report proposal).

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Report proposal.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Ask for ticket summary/report in permitted organization.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Only supported scoped aggregate query used; no arbitrary SQL.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-149 AI quota P2

Role Technician / Org admin | **Dependency** Ollama | **STAGING ONLY**

Navigate: Platform administration > Plans & limits > AI quota

Example entry: Set AI daily jobs to 1; attempt a second AI job.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Platform administration > Plans & limits > AI quota.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Set low AI allowance and exceed it.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Excess usage rejected according to plan.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-150 Voice transcript P2

Role Technician / Org admin | **Dependency** Speech service

Navigate: Sidebar > AI Workbench > Voice recording/transcription

Example entry: Use synthetic audio: I need access to the QA VPN today.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Voice recording/transcription.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enable speech service; record permitted short voice message.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Speech converted to editable transcript.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-151 Voice ticket P2

Role Technician / Org admin | **Dependency** Speech service

Navigate: Sidebar > AI Workbench > Voice to ticket

Example entry: Transcribe synthetic request and review proposed ticket before saving.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Voice to ticket.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Transcribe voice; generate ticket proposal and explicitly save.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Ticket created only after user review and Save.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-152 AI tenant isolation P0

Role Technician / Org admin | **Dependency** Ollama | **STAGING ONLY**

Navigate: Sidebar > AI Workbench > Record scoping (Org A)

Example entry: Attempt to reference Org B ticket in Org A AI prompt; must not leak record data.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Record scoping (Org A).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Ask AI to summarize a ticket from a different organization.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Unauthorized record content never sent to model or returned.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-153 Provider failure P2

Role Technician / Org admin | **Dependency** Ollama | **STAGING ONLY**

Navigate: Sidebar > AI Workbench > Generate / Retry

Example entry: Temporarily disable QA model endpoint; user should receive safe failure.

FOLLOW THESE STEPS

1. Sign in as Technician / Org admin; select Org A unless the scenario specifies otherwise. Open: Sidebar > AI Workbench > Generate / Retry.

2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Stop optional AI service; attempt draft.
4. Review audit/usage and verify no unauthorized write.

EXPECTED Clear failure/retry message; core ticketing still works.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

12 Setup UI & branding

15 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

HNV-E2E-154 Reference starter values P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Starter values

Example entry: Open Starter values; expect 141 starter reference values across supported categories.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Starter values.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Create empty organization and inspect Setup Center > Starter values.
5. Refresh and compare with another organization or viewport.

EXPECTED Documented 141 reference values available for supported categories.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-155 Add missing defaults P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Starter values > Add missing defaults

Example entry: In Org A disable category QA Old Hardware, then Add missing defaults.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Starter values > Add missing defaults.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.

4. Disable/customize an option then use Add missing defaults.
5. Refresh and compare with another organization or viewport.

EXPECTED Only missing defaults added; customized/inactive values preserved.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-156 Category creation P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Reference settings

Example entry: Create category QA Network Support in Org A, then inspect ticket dropdown.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Reference settings.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Add a request category in Setup Center > Reference settings.
5. Refresh and compare with another organization or viewport.

EXPECTED Category selectable only in current organization.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-157 Category deactivation P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Reference settings > Activate/Deactivate

Example entry: Deactivate QA Network Support and open new request; it must not be selectable.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Reference settings > Activate/Deactivate.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Deactivate category already used by ticket.
5. Refresh and compare with another organization or viewport.

EXPECTED Existing ticket history intact; new forms omit inactive choice.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-158 Support group setup P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Reference settings > Support groups; People

Example entry: Support group QA Service Desk; invite Technician A; select group for requests.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Reference settings > Support groups; People.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Create support group reference value.
5. Refresh and compare with another organization or viewport.

EXPECTED Group available in assignment setup; no staff auto-created.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-159 Custom field P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Custom fields

Example entry: Custom field Laptop Asset Tag, type text, required for relevant form.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Custom fields.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Add required custom field to request form.
5. Refresh and compare with another organization or viewport.

EXPECTED Field appears and is enforced on new request.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-160 Dropdown directory P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Dropdown directory

Example entry: Lookup dropdown directory: categories from Reference settings; assignees from People.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Dropdown directory.

2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Open Setup Center > Dropdown directory.
5. Refresh and compare with another organization or viewport.

EXPECTED Each documented selector identifies correct catalog or protected source.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-161 Appearance P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Appearance

Example entry: Appearance: Evergreen accent; large text; compact density.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Appearance.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Change organization accent, density and reading size.
5. Refresh and compare with another organization or viewport.

EXPECTED Appearance updates without altering another organization.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-162 App icon upload P1

Role Org admin / User | **Dependency** Core

Navigate: Setup Center > Brand & app icon

Example entry: Upload square 256x256 PNG test icon qa-app-icon.png (under 512 KiB).

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Brand & app icon.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Upload valid PNG/JPEG under 512 KiB in Brand & app icon.
5. Refresh and compare with another organization or viewport.

EXPECTED Icon saved; workspace/browser favicon updated where supported.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-163 Invalid app icon P1

Role Org admin / User | **Dependency** Core | **STAGING ONLY**

Navigate: Setup Center > Brand & app icon

Example entry: Attempt SVG or corrupted PNG icon; ensure error without changing current icon.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Setup Center > Brand & app icon.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Upload unsupported SVG or oversized image.
5. Refresh and compare with another organization or viewport.

EXPECTED Upload rejected; prior icon retained.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-164 Provider versus org icon P1

Role Org admin / User | **Dependency** Core

Navigate: Platform administration > Signup & branding; Org A/Org B Brand

Example entry: Set provider icon then different Org A icon; check Org B inherits provider default.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org B unless the scenario specifies otherwise. Open: Platform administration > Signup & branding; Org A/Org B Brand.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Set provider icon and Org A override.
5. Refresh and compare with another organization or viewport.

EXPECTED Shared login uses provider icon; Org A override does not affect Org B.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-165 Module configuration P1

Role Org admin / User | **Dependency** Core | **STAGING ONLY**

Navigate: Platform administration > Plans & limits; Setup Center > Modules

Example entry: Disable Reports for Org B through supported module entitlement.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org B unless the scenario specifies otherwise. Open: Platform administration > Plans & limits; Setup Center > Modules.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Disable supported optional module in Org A.
5. Refresh and compare with another organization or viewport.

EXPECTED Navigation and backend entitlement match configuration.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-166 Search page finder P1

Role Org admin / User | **Dependency** Core

Navigate: Header > Find a page (Cmd/Ctrl+K)

Example entry: Press Cmd+K / Ctrl+K; find Requests or Assets; press Enter.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Header > Find a page (Cmd/Ctrl+K).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Press Cmd+K (Mac) or Ctrl+K; search permitted page.
5. Refresh and compare with another organization or viewport.

EXPECTED Page finder navigates only to allowed destinations.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-167 Sidebar scrolling P1

Role Org admin / User | **Dependency** Core

Navigate: Sidebar > Navigation groups and scroll

Example entry: Collapse sidebar group; scroll to Setup Center; reopen and confirm position.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Sidebar > Navigation groups and scroll.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Open multiple menu sections on short viewport; scroll and collapse.
5. Refresh and compare with another organization or viewport.

EXPECTED All menus reachable; account footer does not cover links.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-168 Mobile navigation P1

Role Org admin / User | **Dependency** Core

Navigate: Mobile browser > Navigation drawer

Example entry: Use mobile viewport ~390px; open drawer, choose Requests, press Escape.

FOLLOW THESE STEPS

1. Sign in as Org admin / User; select Org A unless the scenario specifies otherwise. Open: Mobile browser > Navigation drawer.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Navigate to relevant setup or UI section.
4. Open narrow browser viewport; use drawer and keyboard.
5. Refresh and compare with another organization or viewport.

EXPECTED Menus and actions remain reachable; drawer closes correctly.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

13 Security & launch gates

20 test scenarios | Work with Org A and fictional sample data unless a test explicitly uses Org B, the provider console, or a staging operator.

Operator-sensitive checks: Reboot, backups/restores, port/security testing and scans should be performed in an approved maintenance window or disposable staging environment.

HNV-E2E-169 Google sign-in P0

Role Operator / Security tester | **Dependency** Google OAuth

Navigate: Platform administration > Identity & sign-in; Login > Continue with Google

Example entry: Google QA test client; exact callback https://3-228-147-200.sslip.io/api/auth/google/callback.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Platform administration > Identity & sign-in; Login > Continue with Google.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enable Google OIDC and use Continue with Google with approved account.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Verified identity signs in to linked Help Nivo account.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-170 Google explicit linking P0

Role Operator / Security tester | **Dependency** Google OAuth

Navigate: Account menu > Account security > Link Google

Example entry: Existing QA email links Google only after password login + Account security linking.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Account menu > Account security > Link Google.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Try Google sign-in with email matching an existing password account but not linked.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED No silent account takeover; explicit linking required.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-171 Google org membership P0

Role Operator / Security tester | **Dependency** Google OAuth

Navigate: Login with Google > Workspace selector

Example entry: Google email with @somecompany domain does not automatically join another organization.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Login with Google > Workspace selector.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Use Google account from same email domain without invitation.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED No automatic organization membership.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-172 Activation expiry P0

Role Operator / Security tester | **Dependency** SMTP | **STAGING ONLY**

Navigate: Signup > Activation email (expired token)

Example entry: Use an expired account activation link (one hour) in a test mailbox.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Signup > Activation email (expired token).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Start email-first signup; attempt expired activation token.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Expired link rejected; no workspace created.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-173 Activation single-use P0

Role Operator / Security tester | **Dependency** SMTP | **STAGING ONLY**

Navigate: Signup > Activation email (replayed token)

Example entry: Click the same activation link twice; second use should fail.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Signup > Activation email (replayed token).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Complete valid activation then replay same link.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Second use rejected.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-174 Signup welcome P0

Role Operator / Security tester | **Dependency** SMTP

Navigate: Public signup > Email activation > Welcome

Example entry: Register Org QA Gamma through verified signup; confirm owner/welcome email.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Public signup > Email activation > Welcome.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Complete verified registration and inspect mail inbox.
4. Capture logs/evidence without passwords, tokens or PII.

EXPECTED Organization created once and welcome email contains no password.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-175 SMTP unavailable P0

Role Operator / Security tester | **Dependency** SMTP | **STAGING ONLY**

Navigate: Platform administration > Email delivery > Queue/Failed

Example entry: Temporarily disable SMTP in staging; verify no plain-text password is sent and queue failure is observable.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Platform administration > Email delivery > Queue/Failed.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt public signup while SMTP is unavailable.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED No unsafe bypass of production email verification.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-176 Login CSRF P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Authenticated browser > Request with invalid CSRF (staging only)

Example entry: In a disposable staging session attempt a protected action without correct CSRF/origin.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Authenticated browser > Request with invalid CSRF (staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Send cross-origin write request to login/API from disallowed origin.

4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Rejected with appropriate origin/CSRF response.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-177 Session cookie flags P0

Role Operator / Security tester | **Dependency** Core

Navigate: Browser > Developer tools > Storage > Cookies

Example entry: Inspect session cookie in browser devtools; expect Secure, HttpOnly, SameSite.

FOLLOW THESE STEPS

1. Use the designated test identity and open: Browser > Developer tools > Storage > Cookies.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Sign in via HTTPS and inspect cookie properties in browser developer tools.
4. Capture logs/evidence without passwords, tokens or PII.

EXPECTED Session cookie Secure, HttpOnly and appropriate SameSite policy.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-178 Stored XSS P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Requests > New > Subject; Request list

Example entry: Create ticket subject containing harmless literal <script>alert(1)</script>; UI must display as text.

FOLLOW THESE STEPS

1. Sign in as Operator / Security tester; select Org A unless the scenario specifies otherwise. Open: Requests > New > Subject; Request list.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Enter harmless script-like payload in ticket title/comment and render in another user session.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Content escaped; no script execution.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-179 File content type P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Requests > Ticket details > Attachments

Example entry: Rename a harmless text file to .png; upload should fail signature/content checks.

FOLLOW THESE STEPS

1. Sign in as Operator / Security tester; select Org A unless the scenario specifies otherwise. Open: Requests > Ticket details > Attachments.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Upload disguised executable as allowed extension.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Unsupported/invalid content rejected according to documented validation.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-180 Audit trail P0

Role Operator / Security tester | **Dependency** Core

Navigate: Changes > History / Audit; Provider audit

Example entry: Update status of QA-CHG-VPN-01; verify audit actor, time and transition.

FOLLOW THESE STEPS

1. Sign in as Operator / Security tester; select Org A unless the scenario specifies otherwise. Open: Changes > History / Audit; Provider audit.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Change privileged organization setting and review audit/history.
4. Capture logs/evidence without passwords, tokens or PII.

EXPECTED Actor/time/action recorded for supported operation.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-181 Backup creation P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Ubuntu SSH > Help Nivo backup command (staging)

Example entry: Create encrypted logical QA backup, store off VM; verify archive exists.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Ubuntu SSH > Help Nivo backup command (staging).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.

3. Run documented encrypted logical backup tool on isolated staging data.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Encrypted archive created; no plaintext secrets embedded.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-182 Backup restore P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Isolated restore VM / database (staging only)

Example entry: Restore backup ONLY to isolated staging, with matching historical keyring.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Isolated restore VM / database (staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Restore staging backup to a separate empty test database with matching keyring.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Restored records readable; original database unaffected.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-183 Key loss drill P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Isolated restore VM / keyring (staging only)

Example entry: Use isolated restore test with missing keyring; decrypt must fail safely; restore keys afterward.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Isolated restore VM / keyring (staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Attempt decrypt with missing/wrong keyring in isolated recovery environment.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Protected fields cannot decrypt; clear recovery error.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-184 PostgreSQL tenant policy P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Ubuntu SSH > PostgreSQL test harness (staging only)

Example entry: Run supplied PostgreSQL tests only against a disposable _test database.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Ubuntu SSH > PostgreSQL test harness (staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Run documented PostgreSQL-specific acceptance tests with runtime role.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Tenant policy blocks cross-org queries and writes.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-185 Security scans P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Ubuntu SSH > security-scanning wrapper

Example entry: Run scanner wrapper (Bandit, pip-audit, Gitleaks, Trivy) in CI/staging.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Ubuntu SSH > security-scanning wrapper.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Run Bandit, pip-audit, Gitleaks and Trivy in CI/staging.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Reports generated; missing scanner or high-severity issue fails gate.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-186 Load test P0

Role Operator / Security tester | **Dependency** Core | **STAGING ONLY**

Navigate: Performance test runner on isolated staging only

Example entry: Run load test against isolated staging with agreed user/volume targets.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Performance test runner on isolated staging only.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Run authorized concurrent ticket/list/poll workload with monitoring.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED Latency/error/resource thresholds meet agreed pilot SLO; no tenant leakage.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-187 SMTP deliverability P0

Role Operator / Security tester | **Dependency** SMTP | **STAGING ONLY**

Navigate: Provider Email delivery / mailbox header inspection

Example entry: Send staging email to Gmail + other controlled mailbox; check SPF/DKIM/DMARC.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: Provider Email delivery / mailbox header inspection.
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Verify SPF/DKIM/DMARC and delivery to major mail providers.
4. Capture logs/evidence without passwords, tokens or PII.

EXPECTED Authentication passes and test messages reach expected inboxes.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

HNV-E2E-188 Reboot recovery P0

Role Operator / Security tester | **Dependency** AWS / Docker | **STAGING ONLY**

Navigate: AWS Console > EC2 reboot; Ubuntu Docker Compose (staging only)

Example entry: Reboot staging VM in maintenance window; confirm API, DB, Caddy and workers recover.

FOLLOW THESE STEPS

1. From the authorized operator workstation or Ubuntu shell, open: AWS Console > EC2 reboot; Ubuntu Docker Compose (staging only).
2. Prepare the example data or test condition shown above; use only fictional records and controlled QA accounts.
3. Perform planned EC2 reboot with production-like compose profile.
4. Capture logs/evidence without passwords, tokens or PII.
5. Refresh the page and compare the saved record, state, permissions and history with the expected result below.

EXPECTED App/DB/proxy recover; saved data and TLS cert retained.

Prerequisite: External service, worker, approved operator action or isolated staging setup may be required. Mark BLOCKED if unavailable.

RESULT [ ] PASS [ ] FAIL [ ] BLOCKED [ ] N/A

Actual result / discrepancy: _____

Evidence / defect ID / tester / date: _____

5 Test execution summary

After executing the guide, fill one row per module. Count PASS, FAIL, BLOCKED and N/A outcomes. A failed or blocked critical case should be documented before approving a release.

Module	Total	Pass	Fail	Blocked	N/A
Deployment	5	____	____	____	____
Authentication	10	____	____	____	____
Tenancy & membership	12	____	____	____	____
Provider console	12	____	____	____	____
Requests & incidents	26	____	____	____	____
Catalog SLA & routing	17	____	____	____	____
Change release & knowledge	18	____	____	____	____
Assets CMDB & operations	18	____	____	____	____
Notifications & email	14	____	____	____	____
Dashboard & reports	10	____	____	____	____
AI & voice	11	____	____	____	____
Setup UI & branding	15	____	____	____	____
Security & launch gates	20	____	____	____	____

Defect log (copy this entry as needed)

Defect ID / test case ID: _____

Short description: _____

Observed behavior vs expected: _____

Steps to reproduce: _____

Screenshot/log reference (redacted): _____

Severity / owner / retest date: _____

Release decision checklist

- [ ] All critical (P0) scenarios completed and passed, or exceptions formally accepted.
- [ ] Cross-organization authorization and PostgreSQL row-security tests passed on actual PostgreSQL.
- [ ] Real SMTP, account activation, login and MFA checks passed before public registration.
- [ ] Backup and off-VM restore demonstration completed, including encryption keyring.
- [ ] Browser, certificate, CSRF/cookie and API security checks passed.
- [ ] No unresolved critical/high vulnerabilities from approved scans and independent review.
- [ ] Measured resources, scaling, worker health and performance meet pilot usage targets.
- [ ] Operations owner approves the release and records the test evidence archive.

Release verdict: [ ] GO [ ] NO-GO [ ] CONDITIONAL

Approved by: _____ Date: _____ Evidence folder: _____

Source notes and important limitations

Test baseline: Help Nivo 4.5.1 full source archive (docs/OPERATIONS_GUIDE.md, docs/LAUNCH_GUIDE.html, docs/NOTIFICATIONS.md, docs/DROPDOWNS.md, docs/FEATURE_COVERAGE.md) and Help_Nivo_4.5.1_End_to_End_Test_Cases.xlsx.

Not all cases are executable without separately configured services: SMTP, Google OpenID Connect, Ollama, voice transcription, public customer DNS, or a separate restore environment.

The application release remains evaluation beta until native browser, PostgreSQL, host, integration, recovery, load and independent security acceptance are completed. This document is a test plan, not test evidence.

Some labels may differ by user role, feature entitlement or configuration. Do not force access or bypass permissions; record BLOCKED or N/A when the prerequisite is intentionally absent.

Never test backup deletion, cross-tenant authorization bypass, raw scanner exploitation, account-lockout scenarios or recovery on a system containing customer production data.