

# Lab: ksqlDB Quickstart

The guide below demonstrates how to get a minimal environment up and running.

## Prerequisites

This lab installs Confluent Platform using Docker. Before proceeding:

- Connect with lab environment VM using SSH:

```
ssh USERNAME@YOUR_VM_DNS.courseware.io
```

- **Username:** Will be provided by Instructor.
- **Password:** Will be provided by Instructor.
- Verify that Docker is set up properly by ensuring no errors are output when you run `docker info` and `docker compose version` on the command line.

## 1. Get standalone ksqlDB

Since ksqlDB runs natively on Apache Kafka®, you'll need to have a Kafka installation running that ksqlDB is configured to use. The docker-compose files to the right will run everything for you via Docker, including ksqlDB itself.

Select the docker-compose file that you'd like to use, depending on whether or not you're already running Kafka. Next, copy and paste it into a file named docker-compose.yml on your local filesystem.

```
---
version: '2'

services:
  zookeeper:
    image: confluentinc/cp-zookeeper:6.1.0
    hostname: zookeeper
    container_name: zookeeper
    ports:
      - "2181:2181"
    environment:
      ZOOKEEPER_CLIENT_PORT: 2181
      ZOOKEEPER_TICK_TIME: 2000

  broker:
    image: confluentinc/cp-kafka:6.1.0
    hostname: broker
    container_name: broker
    depends_on:
      - zookeeper
    ports:
      - "29092:29092"
    environment:
      KAFKA_BROKER_ID: 1
      KAFKA_ZOOKEEPER_CONNECT: 'zookeeper:2181'
```

```

    KAFKA_LISTENER_SECURITY_PROTOCOL_MAP:
PLAINTEXT:PLAINTEXT,PLAINTEXT_HOST:PLAINTEXT
    KAFKA_ADVERTISED_LISTENERS:
PLAINTEXT://broker:9092,PLAINTEXT_HOST://localhost:29092
    KAFKA_OFFSETS_TOPIC_REPLICATION_FACTOR: 1
    KAFKA_GROUP_INITIAL_REBALANCE_DELAY_MS: 0
    KAFKA_TRANSACTION_STATE_LOG_MIN_ISR: 1
    KAFKA_TRANSACTION_STATE_LOG_REPLICATION_FACTOR: 1

ksqldb-server:
  image: confluentinc/ksqldb-server:0.15.0
  hostname: ksqldb-server
  container_name: ksqldb-server
  depends_on:
    - broker
  ports:
    - "8088:8088"
  environment:
    KSQL_LISTENERS: http://0.0.0.0:8088
    KSQL_BOOTSTRAP_SERVERS: broker:9092
    KSQL_KSQL_LOGGING_PROCESSING_STREAM_AUTO_CREATE: "true"
    KSQL_KSQL_LOGGING_PROCESSING_TOPIC_AUTO_CREATE: "true"

ksqldb-cli:
  image: confluentinc/ksqldb-cli:0.15.0
  container_name: ksqldb-cli
  depends_on:
    - broker
    - ksqldb-server
  entrypoint: /bin/sh
  tty: true

```

## 2. Start ksqldb's server

From a directory containing the docker-compose.yml file created in the previous step, run this command in order to start all services in the correct order.

Once all services have successfully launched, you will have a ksqldb server running and ready to use.

```
docker-compose up
```

## 3. Start ksqldb's interactive CLI

ksqldb runs as a server which clients connect to in order to issue queries.

Run this command to connect to the ksqldb server and enter an interactive command-line interface (CLI) session.

```
docker exec -it ksqldb-cli ksql http://ksqldb-server:8088
```

## 4. Create a stream

The first thing we're going to do is create a `stream`. A stream essentially associates a schema with an underlying Kafka topic. Here's what each parameter in the CREATE STREAM statement does:

- **kafka\_topic** - Name of the Kafka topic underlying the stream. In this case it will be automatically created because it doesn't exist yet, but streams may also be created over topics that already exist.
- **value\_format** - Encoding of the messages stored in the Kafka topic. For JSON encoding, each row will be stored as a JSON object whose keys/values are column names/values. For example: {"profileId": "c2309eec", "latitude": 37.7877, "longitude": -122.4205}
- **partitions** - Number of partitions to create for the locations topic. Note that this parameter is not needed for topics that already exist.

Copy and paste this statement into your interactive CLI session, and press enter to execute the statement.

```
CREATE STREAM riderLocations (profileId VARCHAR, latitude DOUBLE, longitude DOUBLE)
  WITH (kafka_topic='locations', value_format='json', partitions=1);
```

## 5. Run a persistent query over the stream

Run the given query using your interactive CLI session.

This query will output all rows from the riderLocations stream whose coordinates are within 5 miles of Mountain View.

This is the first thing that may feel a bit unfamiliar to you, because the query will never return until it's terminated. It will perpetually push output rows to the client as events are written to the riderLocations stream.

Leave this query running in the CLI session for now. Next, we're going to write some data into the riderLocations stream so that the query begins producing output.

```
-- Mountain View lat, long: 37.4133, -122.1162
SELECT * FROM riderLocations
  WHERE GEO_DISTANCE(latitude, longitude, 37.4133, -122.1162) <= 5 EMIT CHANGES;
```

## 6. Start another CLI session

Since the CLI session from (5) is busy waiting for output from the persistent query, let's start another session that we can use to write some data into ksqldb.

```
docker exec -it ksqldb-cli ksql http://ksqldb-server:8088
```

## 7. Populate the stream with events

Run each of the given INSERT statements within the new CLI session, and keep an eye on the CLI session from (5) as you do.

The persistent query will output matching rows in real time as soon as they're written to the riderLocations stream.

```
INSERT INTO riderLocations (profileId, latitude, longitude) VALUES ('c2309eec',
37.7877, -122.4205);
INSERT INTO riderLocations (profileId, latitude, longitude) VALUES ('18f4ea86',
37.3903, -122.0643);
INSERT INTO riderLocations (profileId, latitude, longitude) VALUES ('4ab5cbad',
37.3952, -122.0813);
INSERT INTO riderLocations (profileId, latitude, longitude) VALUES ('8b6eae59',
37.3944, -122.0813);
INSERT INTO riderLocations (profileId, latitude, longitude) VALUES ('4a7c7b41',
37.4049, -122.0822);
```

```
INSERT INTO riderLocations (profileId, latitude, longitude) VALUES ('4ddad000',
37.7857, -122.4011);
```

## Cleanup Resources

Delete all the resources by running following command in the `docker-compose.yml` file directory from the terminal:

```
docker compose down
```

```
ubuntu@ip-172-31-28-38:~/split-stream$ docker compose down
[+] Running 4/3
  ✓ Container schema-registry   Removed          10.4s
  ✓ Container broker            Removed          0.9s
  ✓ Container zookeeper         Removed          0.5s
  ✓ Network split-stream_default Error            0.0s
failed to remove network split-stream_default: Error response from daemon: error while removing network: network split-stream_default id 947bab6e7c6b74176aec928edf3567db72c046f65f397bd1e7fee36cc30b3b has active endpoints
```

**Note:** If you get above error while running above command. Manually stop the containers and run `docker compose down` again. **Do not delete kafka new container.**

```
no container to killubuntu@ip-172-31-28-38:~/split-stream$ docker ps
CONTAINER ID   IMAGE                                COMMAND                  CREATED        STATUS        PORTS
9465d6b4aa89   confluentinc/ksqldb-cli:0.28.2     "/bin/sh"               About an hour ago Up About an hour
b6887b23c1ca   confluentinc/ksqldb-server:0.28.2  "/usr/bin/docker/run"   About an hour ago Up About an hour  0.0.0.0:8088->8088/tcp, :::8088->8088/tcp
22652a43d640   fenago/kafka-intellij-new-2.8      "/dockerstartup/vnc_..." 8 weeks ago    Up 12 hours   0.0.0.0:80->80/tcp, :::80->80/tcp, 5900/tcp, 0.0.0.0:80->80/tcp, :::80->80/tcp
ubuntu@ip-172-31-28-38:~/split-stream$ docker stop 9465d6b4aa89 b6887b23c1ca
9465d6b4aa89
b6887b23c1ca
ubuntu@ip-172-31-28-38:~/split-stream$
ubuntu@ip-172-31-28-38:~/split-stream$ docker compose down
[+] Running 1/1
  ✓ Network split-stream_default Removed
```