

## Lab 5.3: Configuring Producer Durability

Welcome to the session 5 lab 3. The work for this lab is done in `~/kafka-training/labs/lab5.3`. In this lab, you are going to set up producer durability for our advanced producer.

Find the latest version of this lab [here](#).

### Lab Configuring Producer Durability

In this lab we will configure producer durability.

#### Set default acks to all

**ACTION** EDIT `StockPriceKafkaProducer` and set Producer config acks to all (this is the default). This means that all ISRs in-sync replicas have to respond for producer write to go through.

**StockPriceKafkaProducer.java**

```
public class StockPriceKafkaProducer {

    private static Producer<String, StockPrice>
        createProducer() {

        final Properties props = new Properties();
        ...

        //Set number of acknowledgments - acks - default is all
        props.put(ProducerConfig.ACKS_CONFIG, "all");
        return new KafkaProducer<>(props);
    }
}
```

Notice we set the Producer config property "acks" (`ProducerConfig.ACKS_CONFIG`) to all.

#### Kafka Broker Config for Min.Insync.Replicas

Next let's set the `min.insync.replicas` to three. This will force at least three in-sync replicas (ISRs) have to respond for our producer to get an ack from the Kafka Broker. NOTE: We have three brokers in this lab, thus all three have to be up for the Producer to work.

Ensure `min.insync.replicas` is set to three in all of the broker config files (`server-0.properties`, `server-1.properties` and `server-2.properties`).

**ACTION** EDIT `config/server-0.properties` and `min.insync.replicas=3`

**ACTION** EDIT `config/server-1.properties` and `min.insync.replicas=3`

**ACTION** EDIT `config/server-2.properties` and `min.insync.replicas=3`

#### Run this lab. Run it. Run Servers. Run Producer. Kill 1 Broker.

If not already, startup ZooKeeper. Now startup three Kafka brokers (or ensure they are running) using scripts described earlier. From the IDE run `StockPriceKafkaProducer` class. From the terminal kill one of the Kafka Brokers. Now look at the logs for the `StockPriceKafkaProducer`, you should see Caused by: `org.apache.kafka.common.errors.NotEnoughReplicasException`. Note that the Messages are rejected since there are

fewer in-sync replicas than required. Repeat this with only 2 min.insync.replicas set. (Change config and restart brokers and restart producer). Observe the behavior of using 2 for min.insync.replicas vs. three.

**ACTION** RUN brokers and zookeeper if needed.

**ACTION** RUN StockPriceKafkaProducer from the IDE

**ACTION** KILL 1 of the Kafka Brokers

**ACTION** OBSERVE Producer terminal messages

**ACTION** EDIT config/server-0.properties and min.insync.replicas=2

**ACTION** EDIT config/server-1.properties and min.insync.replicas=2

**ACTION** EDIT config/server-2.properties and min.insync.replicas=2

**ACTION** RESTART brokers

**ACTION** KILL 1 of the Kafka Brokers

**ACTION** OBSERVE Producer terminal messages

### Why did the send fail?

The producer config `ProducerConfig.ACKS_CONFIG` (acks config for producer) was set to "all". This settings expects leader to only give successful ack after all followers ack the send was written to their log. The Broker config `min.insync.replicas` set to 3. At least three in-sync replicas must respond before send is considered successful. Since we took one broker out and only had three to begin with, it forces the send to fail since the send can not get three acks from ISRs.

### Modify durability to leader only

Change `StockPriceKafkaProducer` acks config to 1 `props.put(ProducerConfig.ACKS_CONFIG, "1", i.e.,` leader sends ack after write to log. From the IDE run `StockPriceKafkaProducer` again. From the terminal kill one of the Kafka Brokers. Notice that the `StockPriceKafkaProducer` now runs normally.

**ACTION** EDIT `StockPriceKafkaProducer` and set Producer config acks to "1".

**ACTION** RUN all brokers and zookeeper if needed.

**ACTION** RUN `StockPriceKafkaProducer` from the IDE

**ACTION** KILL 1 of the Kafka Brokers

**ACTION** OBSERVE Producer terminal messages or lack thereof

### Why did the send not fail for acks 1?

Setting the Producer config `ProducerConfig.ACKS_CONFIG` (acks config for producer) to "1". This setting expects leader to only give successful ack after it writes to its log. Replicas still get replication but leader does not wait for replication to send ack. Broker Config `min.insync.replicas` is still set to 3, but this config only gets looked at if `acks="all"`.

### Running describe topics before and after stopping broker

Try the last steps again. Stop a server while producer is running. Then run `describe-topics.sh`. Then Rerun server you stopped and run `describe-topics.sh` again. Observe the changes to ISRs and partition to broker ownership.

## bin/describe-topics.sh

```
#!/usr/bin/env bash

cd ~/kafka-training

# List existing topics
kafka/bin/kafka-topics.sh --describe \
    --topic stock-prices \
    --zookeeper localhost:2181
```

The script bin/describe-topics.sh calls kafka-topics.sh to describe the topic layout with regards to brokers and partitions.

**ACTION** REPEAT Last experiment, but this time run bin/describe-topics.sh and observe.

### Retry with acks = 0

Run the last example again (servers, and producer), but this time set acks to 0. Run all three brokers then take one away. Then take another broker away. Try Run describe-topics. Take all of the brokers down and continue to run the producer. What do you think happens? When you are done, change acks back to acks=all.

**ACTION** EDIT StockPriceKafkaProducer and set Producer config acks to "0".

**ACTION** RUN all brokers and zookeeper if needed.

**ACTION** RUN StockPriceKafkaProducer from the IDE

**ACTION** REPEAT Last experiment, but this time run bin/describe-topics.sh and observe.

## Lab Review

Look at the following listing.

### Describe topic listing

```
$ bin/describe-topics.sh
Topic:stock-prices    PartitionCount:3    ReplicationFactor:3
Configs:min.insync.replicas=2
  Topic: stock-prices    Partition: 0    Leader: 2    Replicas: 1,2,0    Isr: 2
  Topic: stock-prices    Partition: 1    Leader: 2    Replicas: 2,0,1    Isr: 2
  Topic: stock-prices    Partition: 2    Leader: 2    Replicas: 0,1,2    Isr: 2
```

- How would you describe the above?
- How many servers are likely running out of the three?
- Would the producer still run with acks=all? Why or Why not?
- Would the producer still run with acks=1? Why or Why not?
- Would the producer still run with acks=0? Why or Why not?
- Which broker is the leader of partition 1?
- How would you describe the above? Two servers are down. Broker 0 and Broker 1.
- How many servers are likely running out of the three? Just the third broker.
- Would the producer still run with acks=all? Why or Why not? No. Only one server is running.
- Would the producer still run with acks=1? Why or Why not? No. Yes. The 3rd server owns the partitions.
- Would the producer still run with acks=0? Why or Why not? Yes.
- Which broker is the leader of partition 1? The third server one with broker id 2.