


Security

Objectives


After completing this lesson, you should be able to:

- Manage common and local users, roles, privileges, and profiles in PDBs
- Manage common and local objects in application containers
- Enable common users to access data in PDBs
- Manage PDB lockdown profiles
- Audit users in CDB and PDBs
- Manage other types of policies in application containers
- Protect data with Database Vault policies in CDB and PDBs
- Encrypt data in PDBs
- Configure isolated PDB keystores
- Unplug and plug an encrypted PDB in a one-step operation
- Allow per-PDB wallets for certificates

Creating Common Users in the CDB and PDBs



Creating Common Roles in the CDB and PDBs




Granting Privileges Commonly in the CDB and PDBs

CDB

In a CDB, a **common** privilege is granted to a grantee in **all** containers of the CDB.



CDB root



```
SQL> CONNECT / AS SYSDBA
SQL> GRANT create session TO c##u1 CONTAINER=ALL;
```

Application Container PDB_APP



Application root






In an application container, a **common** privilege is a privilege granted commonly to grantees in the application root and application PDBs.

```
SQL> CONN sys@PDB_APP AS SYSDBA
SQL> GRANT sysdba TO app_u1 CONTAINER=ALL;
```

A **local** privilege is granted to grantees in **one** single PDB.




```
SQL> GRANT logmining TO l_user1;
```




Note: All commands related to common entities created, altered, or dropped in application containers must be performed within an *INSTALL/UPGRADE/PATCH BEGIN/END* block and be replicated in application PDBs after sync.

Creating Common Profiles in the CDB and PDBs




Common Objects in Application Containers



Operations on Data-Linked Objects

Apply **recorded DDL or DML** statements at synchronization:

- To **new** application PDBs
- To PDBs that were **closed** when the DDL or DML statements were issued



Enabling Common Users to Access Data in PDBs

CDB1

CDB root

Application Container PDB_APP

Application root



select on
APP.T1



select on
APP.T1

PDB_APP1



select on
APP.T1



select on
APP.T1

PDB_APP2



select on
APP.T1



select on
APP.T1

PDB_APP3



select on
APP.T1



select on
APP.T1

1.Enable data access to application metadata-linked tables:

```
SQL> CONNECT sys@pdb_app AS SYSDBA
SQL> ALTER TABLE app.t1 ENABLE CONTAINER_DATA;
```

2.Enable common users to access data related to specific PDBs:

```
SQL> ALTER USER u1 SET CONTAINER_DATA =
(PDB_APP, PDB_APP1, PDB_APP2, PDB_APP3)
FOR app.t1 CONTAINER=CURRENT;
```

```
SQL> ALTER USER u2 SET
CONTAINER_DATA=(PDB_APP, PDB_APP1)
FOR app.t1 CONTAINER=CURRENT;
```

3.U1 views all rows in APP.T1:

C1	CON_ID
VAL1	3
VAL2	4
VAL3	5
VAL4	6

U2 views some rows:

C1	CON_ID
VAL1	3
VAL2	4

Finding Information About CONTAINER_DATA Attributes

Find information about the default (user-level) and object-specific CONTAINER_DATA attributes that are explicitly set to a value other than DEFAULT.

```
SQL> SELECT username, default_attr, object_name, all_containers, container_name,
           con_id
        FROM cdb_container_data ORDER BY object_name;
```


USERNAME	DEFAULT	OBJECT_NAME	ALL	CONTAINER_	CON_ID
-----	-----	-----	---	-----	-----
C##JIM	N	V\$SESSION	N	PDB_HR	1
C##JIM	N	V\$SESSION	N	CDB\$ROOT	1
C##JIM	N	V\$SESSION	N	PDB2_2	1
SYSTEM	Y		Y		1
DBSNMP	Y		Y		1
SYSBACKUP	Y		Y		1
SYS	Y		Y		1

Restricting Operations with PDB Lockdown Profiles

- A potential for elevation of privileges exists where identity is shared between PDBs.
- You can restrict operations, features, and options used by users connected to a given PDB by using three `ALTER SYSTEM` clauses.


STATEMENT	FEATURE	OPTION
ALTER SYSTEM FLUSH SHARED_POOL, CHECKPOINT, SWITCH LOGFILE, SET	NETWORK_ACCESS UTL_TCP, UTL_SMTP, UTL_HTTP, UTL_INADDR, XDB_PROTOCOLS, DBMS_DEBUG_JDWP	Partitioning
	COMMON_SCHEMA_ACCESS	Advanced Queuing
	OS_ACCESS UTL_FILE, JAVA_OS_ACCESS, EXTERNAL_PROCEdures	Real Application Clusters
	XDB_PROTOCOLS	Oracle Data Guard
	JAVA, JAVA_RUNTIME	

Restricting Operations in a PDB Lockdown Profile




1. Create PDB lockdown profiles.
2. Define enabled and disabled:
 - Statement and clauses
 - Feature
 - Option
3. Set the `PDB_LOCKDOWN` parameter to a PDB lockdown profile for all PDBs.
4. Optionally set the `PDB_LOCKDOWN` parameter to another PDB lockdown profile for a PDB.

PDB Lockdown Profiles Inheritance



Static and Dynamic PDB Lockdown Profiles



There are two ways to create lockdown profiles by using an existing profile:


- Static lockdown profiles:

```
SQL> CREATE LOCKDOWN PROFILE prof3  
      FROM base_lock_prof1;
```

- Dynamic lockdown profiles:

```
SQL> CREATE LOCKDOWN PROFILE prof4  
      INCLUDING base_lock_prof2;
```

Auditing Actions in the CDB and PDBs



1. Connect to the CDB root or to an application root or to a regular PDB.
2. Create common or local unified audit policies:
 - For all PDBs (*connect to CDB root*)
 - For all application PDBs of an application container (*connect to the application root*)
 - For a regular PDB or a specific application PDB (*connect to the PDB*)
3. Enable/disable audit policies:
 - Define users or users being granted roles to be audited (*DBA role*)
 - Use `AUDIT POLICY` and `NOAUDIT POLICY` commands

Managing Other Types of Security Policies in Application Containers


Policy Type	Compatible in Application Containers	Created in Install / Upgrade / Patch BEGIN-END block	Automatic synchronization in application PDBs
Unified Audit	Y	Y (explicit or implicit)	Y (explicit or implicit)
FGA	Y	Y	N
Application Context & VPD	Y	Y	N
TSDP	Y	N	n/a
OLS	N	n/a	n/a

Securing Data with Oracle Database Vault

- Each PDB has its own Database Vault metadata.
- Database Vault common protection can protect the common objects of an application container:
 - Database Vault common realm
 - Database Vault common command rule

DVSYS.DBA_DV_POLICY
DVSYS.DBA_DV_POLICY_OBJECT

DV policy



Oracle Database Vault-Enabled Strict Mode

- Mixed mode:


- Both Database Vault enabled and disabled PDBs can work together in the same application container.
→
- Database Vault common protection does not protect the common objects in the Database Vault disabled PDBs.

- Strict mode:

- The common protection must cover the common objects in every PDB in the same application container.
→
- The Database Vault disabled PDBs are opened in restricted mode.

Managing Keystore in the CDB and PDBs

- There is one TDE master encryption key per PDB to encrypt PDB data.
- The TDE master encryption key must be transported from the source database keystore to the target database keystore when a PDB is moved from one host to another.




Creating and Opening a Keystore

- Create the unique keystore in the CDB root.

```
SQL> ADMINISTER KEY MANAGEMENT CREATE KEYSTORE  
      'u01/app/oracle/product/19.1.0/dbhome_1/wallet'  
      IDENTIFIED BY k_password;
```

- Open the keystore in the CDB root and then for a specific PDB.

```
SQL> CONNECT john@PDBA AS SYSKM  
SQL> ADMINISTER KEY MANAGEMENT SET KEYSTORE OPEN IDENTIFIED BY k_password  
      CONTAINER = CURRENT;
```




Setting TDE Master Encryption Keys

3. Set the TDE master encryption key for a PDB.

```
SQL> CONNECT john@PDBA AS SYSKM  
SQL> ADMINISTER KEY MANAGEMENT SET KEY IDENTIFIED BY k_password WITH BACKUP  
CONTAINER = CURRENT;
```


```
SQL> CREATE TABLE hr.tab_sec  
(C1 NUMBER ENCRYPT);
```



You can now encrypt data in tablespaces and tables.

Managing Keystore in the CDB and PDBs

- There is still one single keystore for the CDB and optionally one keystore per PDB.
- There is still one TDE master encryption key per PDB to encrypt PDB data, stored in the PDB keystore.
- Modes of operation
 - United mode: PDB keys are stored in the unique CDB root keystore.
 - Isolated mode: PDBs keys are stored in their own keystore.
 - Mixed mode: Some PDBs use united mode; some use isolated mode.



Keystore Management Changes for PDBs

```
V$ENCRYPTION_WALLET  
ENCRIPTION_MODE = NONE
```

- PDBs can optionally have their own keystore, allowing tenants to manage their own keys.
- Define the shared location for the CDB root and PDB keystores:

```
SQL> ALTER SYSTEM SET wallet_root = /u01/app/oracle/admin/ORCL/tde_wallet;
```

- Define the default PDB keystore type for each future isolated PDB and then define a different file type in each isolated PDB if necessary:

```
SQL> ALTER SYSTEM SET tde_configuration = 'KEystore_CONFIGURATION=FILE';
```

- United: ➔ WALLET_ROOT/component/ewallet.p12

CDB root
and **PDBA**  /u01/app/oracle/admin/ORCL/tde_wallet/tde/ewallet.p12

- Isolated: ➔ WALLET_ROOT/pdb_guid/component/ewallet.p12

PDBB  /u01/app/oracle/admin/ORCL/tde_wallet/51FE2A4899472AE6/tde/ewallet.p12

PDBC  /u01/app/oracle/admin/ORCL/tde_wallet/7893AB8994724ZC8/tde/ewallet.p12

Defining the Keystore Type

Values of keystore types allowed:

- FILE
- OKV (Oracle Key Vault)
- HSM (Hardware Security Module)
- FILE|OKV: Reverse-migration from OKV to FILE has occurred.
- FILE|HSM: Reverse-migration from HSM to FILE has occurred.
- OKV|FILE: Migration from FILE to OKV has occurred.
- HSM|FILE: Migration from FILE to HSM has occurred.

In isolated mode, when the CDB is in mounted state:


```
SQL> STARTUP MOUNT  
SQL> ALTER SYSTEM SET tde_configuration='CONTAINER=pdb1; KEYSTORE_CONFIGURATION=FILE';
```

Isolating a PDB Keystore

- Create / open the CDB root keystore:
- Connect as the PDB security admin to the newly created PDB to:
 - Create the PDB keystore.

```
V$ENCRYPTION_WALLET  
ENCRYPTION_MODE = ISOLATED
```

```
SQL> ADMINISTER KEY MANAGEMENT CREATE KEYSTORE  
IDENTIFIED BY <united_keystore_pass> ;
```



```
SQL> ADMINISTER KEY MANAGEMENT CREATE KEYSTORE  
IDENTIFIED BY isolated_keystore_pass;
```




- Open the PDB keystore.

```
SQL> ADMINISTER KEY MANAGEMENT SET KEYSTORE OPEN  
IDENTIFIED BY isolated_keystore_pass;
```

- Create the TDE PDB key in the PDB keystore.


```
SQL> ADMINISTER KEY MANAGEMENT SET KEY IDENTIFIED BY isolated_keystore_pass  
WITH BACKUP;
```

Converting a PDB to Run in Isolated Mode

- In the CDB root:
 - Create a common user to act as the security officer 
 - Grant the ADMINISTER KEY MANAGEMENT privilege commonly 
- Connect as the security officer  the PDB and create the keystore in the PDB.

```
V$ENCRYPTION_WALLET  
ENCRYPTION_MODE = ISOLATED
```

```
SQL> ADMINISTER KEY MANAGEMENT ISOLATE KEYSTORE  
      IDENTIFIED BY isolated_keystore_password  
      FROM ROOT KEYSTORE IDENTIFIED BY [EXTERNAL STORE | <united_keystore_password>]  
      WITH BACKUP;
```



Converting a PDB to Run in United Mode

1. In the CDB root:


a. The security officer of the CDB  exists.

b. The security officer of the CDB  is granted the ADMINISTER KEY MANAGEMENT privilege commonly.

2. Connect as the security officer  to the PDB and unite the TDE PDB key with those of the CDB root.

```
V$ENCRYPTION_WALLET  
ENCRYPTION_MODE = UNITED
```

```
SQL> ADMINISTER KEY MANAGEMENT UNITE KEYSTORE  
      IDENTIFIED BY isolated_keystore_password  
      WITH ROOT KEYSTORE IDENTIFIED BY [EXTERNAL STORE | united_keystore_password]  
      [WITH BACKUP [USING backup_id]];
```



Migrating a PDB Between Keystore Types

To migrate a PDB from using wallet as the keystore to using Oracle Key Vault if the PDB is running in isolated mode:

1. Upload the TDE encryption keys from the isolated keystore to Oracle Key Vault by using a utility.
2. Set the `TDE_CONFIGURATION` parameter of the PDB to the appropriate value:


```
SQL> ALTER SYSTEM SET tde_configuration = 'KEystore_CONFIGURATION=OKV';
```

Unplugging and Plugging a PDB with Encrypted Data

- Unplugging an encrypted PDB exports the master encryption key of the PDB.

```
SQL> ALTER PLUGGABLE DATABASE pdb1  
      UNPLUG INTO '/tmp/pdb1.xml'  
      ENCRYPT USING "tpwd1";
```


PDB wallet opened



- Plugging the encrypted PDB imports the master encryption key of the PDB into the CDB keystore.


```
SQL> CREATE PLUGGABLE DATABASE pdb1  
      USING '/tmp/pdb1.xml'  
      KEYSTORE IDENTIFIED BY keystore_pwd1  
      DECRYPT USING "tpwd1";
```

Target CDB wallet
opened




Per-PDB Wallet for PDB Certificates

- There is only one `sqlnet.ora` file and one `WALLET_LOCATION` parameter per CDB.
- Each PDB has its own keystore to store the TLS credentials and identity to communicate with other PDBs.



```
WALLET_LOCATION = /home/oracle/wallet  
  
/home/oracle/wallet/20DCA332 contains certificate for PDBA  
  
/home/oracle/wallet/20DCA331 contains certificate for PDBB  
  
/home/oracle/wallet/20DCA334 contains certificate for PDBC
```



Summary

In this lesson, you should have learned how to:

- Manage common and local users, roles, privileges, and profiles in PDBs
- Manage common and local objects in application containers
- Enable common users to access data in PDBs
- Manage PDB lockdown profiles
- Audit users in CDB and PDBs
- Manage other types of policies in application containers
- Protect data with Database Vault policies in CDB and PDBs
- Encrypt data in PDBs
- Configure isolated PDB keystores
- Unplug and plug an encrypted PDB in a one-step operation
- Allow per-PDB wallets for certificates