

Practice 5-1: Shutting Down and Starting Up the Oracle Database

Objective:

To stop all running databases and listeners, create a new CDB named `CDBLAB` with three PDBs using DBCA, and ensure that all databases are running at the end of the practice.

Steps:

1. Identify and Stop All Running Databases and Listeners

First, identify all running databases and listeners:

```
xhost +  
su - oracle  
pgrep -lf smon  
pgrep -lf tns
```

Stop all running databases:

```
sqlplus / as sysdba  
SHUTDOWN IMMEDIATE;
```

Make sure listener is stopped:

```
lsnrctl status  
lsnrctl stop
```

Important: Open new terminal and run these commands as **root** user:

Make sure the `listener.ora` is created. If not, create it:

```
cd ~/Desktop  
git clone https://github.com/fenago/oracle19c-administration.git  
cd ~/Desktop/oracle19c-administration  
  
cp listener.ora /u01/app/oracle/product/19.3.0/dbhome_1/network/admin/  
  
sudo chown -R oracle  
/u01/app/oracle/product/19.3.0/dbhome_1/network/admin/listener.ora
```

Make sure listener is running:

```
su - oracle  
lsnrctl start
```

2. Set Oracle Environment Variables

Set the Oracle environment variables using the `oraenv` script:

```
. oraenv  
ORACLE_SID = [oracle] ? CDBLAB
```

Then

```
export ORACLE_BASE=/u01/app/oracle
export ORACLE_HOME=/u01/app/oracle/product/19.3.0/dbhome_1
export ORACLE_SID=CDBLAB
export PATH=$ORACLE_HOME/bin:$PATH
```


3. Create a New CDB with Three PDBs Using DBCA

Use the following command to create a new CDB named `CDBLAB` with three PDBs (`PDBLAB1` , `PDBLAB2` , and `PDBLAB3`):


```
dbca -silent -createDatabase \
-templateName General_Purpose.dbc \
-gdbName CDBLAB -sid CDBLAB -responseFile NO_VALUE \
-characterSet AL32UTF8 \
-sysPassword fenago \
-systemPassword fenago \
-createAsContainerDatabase true \
-numberOfPDBs 1 \
-pdbName PDBLAB1 \
-pdbAdminPassword fenago \
-databaseType MULTIPURPOSE \
-memoryMgmtType auto_sga \
-totalMemory 1536 \
-storageType FS \
-datafileDestination "/u01/app/oracle/oradata/" \
-redoLogFileSize 50 \
-listeners LISTENER \
-emConfiguration DBEXPRESS \
-emExpressPort 5501 \
-ignorePreReqs
```

Run the command `dbca` to launch the Oracle Database Configuration Assistant.

In the DBCA welcome screen or main menu, select the "Manage Pluggable Databases" option.



select the "Create a Pluggable Database" option.



DBCA will prompt you to connect to the CDB `CDBLAB` . Provide the necessary credentials.

User name: `sys`

Password: `fenago`

Database Configuration Assistant - Manage Pluggable databases - Step 3 of 8

19^c ORACLE Database

Select Source Database

Select a Container database within which Pluggable database needs to be created.

Database	Local instance	Type
<input type="radio"/> fenagodb	fenagodb	Single Instance
<input type="radio"/> CDBTEST	CDBTEST	Single Instance
<input type="radio"/> CDBTEST2	CDBTEST2	Single Instance
<input checked="" type="radio"/> CDBLAB	CDBLAB	Single Instance

DBCA will connect to the database using OS based authentication. Database credentials may be needed if OS based authentication is disabled. Specify the credentials, if needed.

User name:

Password:

Help < Back Next > Finish Cancel

Click **Create a new pluggable database from another PDB**, Choose `PDBLAB1` from dropdown and create `PDBLAB2` and `PDBLAB3` one by one.

Database Configuration Assistant - Manage Pluggable databases - Step 4 of 9

Create Pluggable Database

19c ORACLE Database

- Database Operation
- Manage Pluggable Databases
- Select Database
- Create Pluggable Database**
- PDB Identification
- Pluggable Database Options
- Summary
- Progress Page
- Finish

☒ Create a new Pluggable database from another PDB

Select Pluggable database:

☐ Create Pluggable database from an unplugged PDB

☐ Create as clone

☐ Create from PDB archive

Pluggable database archive:

☒ Create using PDB file set

Pluggable database metadata file:

Pluggable database datafile backup:

Database Configuration Assistant - Manage Pluggable databases - Step 5 of 9

Pluggable Database Identification Options

19c ORACLE Database

- Database Operation
- Manage Pluggable Databases
- Select Database
- Create Pluggable Database
- PDB Identification**
- Pluggable Database Options
- Summary
- Progress Page
- Finish

Pluggable database name:



☐ Create a new administrator



Administrator user name:

Administrator password:

Confirm administrator password:

☐ Lock all existing PDB users





Connecting to PDBs Using SQL Developer

1. **Launch SQL Developer:**

- Locate and double-click the SQL Developer launcher icon on your desktop.

2. **Create new connections for PDB2_CDBLAB and PDB3_CDBLAB:**

- **File -> New -> Database Connection...**
- **Connection Name:** PDB2_CDBLAB
- **Username:** sys
- **Password:** fenago
- **Connection Type:** Basic
- **Role:** SYSDBA
- **Hostname:** localhost
- **Port:** 1521
- **Service Name:** pdblab2

New / Select Database Connection

Name:

Database Type:

User Info Proxy User

Authentication Type:

Username: Role:

Password: ☐ Save Password

Connection Type:

Details Advanced

Hostname:

Port:

☐ SID

☒ Service name:

Repeat the same steps for PDB3_CDBLAB:

- **Connection Name:** PDB3_CDBLAB
- **Username:** sys
- **Password:** fenago
- **Connection Type:** Basic
- **Role:** SYSDBA
- **Hostname:** localhost
- **Port:** 1521
- **Service Name:** pdblab3

3. Test and Save the Connections:

- Click the **Test** button to verify the connection details.
- Click the **Save** button to save the connection.
- Click the **Connect** button to establish the connection to PDB1 and PDB2.

Manage PDBs in SQL Developer

- **Explore the PDBs:**

- In the **Connections** pane, expand `PDB1_CDBLAB` and `PDB2_CDBLAB` to explore tables, views, and other database objects.

4. Verify the CDB and PDBs Creation

Connect to the CDB and verify the creation of the PDBs:

```
sqlplus / as sysdba  
SELECT con_id, name, open_mode FROM v$pdb;
```

5. Start and Stop the CDB and PDBs

Shutdown the CDB:

```
SHUTDOWN IMMEDIATE;
```

Startup the CDB in NOMOUNT Mode:

```
STARTUP NOMOUNT;
```

Mount the CDB:

```
ALTER DATABASE MOUNT;
```

Open the CDB:

```
ALTER DATABASE OPEN;
```

Open All PDBs:

```
ALTER PLUGGABLE DATABASE ALL OPEN;
```

Verify the status of the PDBs:

```
SELECT con_id, name, open_mode FROM v$pdb;
```

6. Set the PDB Save States

Save the state of the PDBs so they open automatically on CDB startup:

```
ALTER PLUGGABLE DATABASE ALL SAVE STATE;
```

7. Check the PDB Save States

Verify the saved states:

```
SELECT con_id, con_name, state FROM DBA_PDB_SAVED_STATES;
```

8. Stop the CDB

Shut down the CDB:

```
SHUTDOWN IMMEDIATE;
```

9. Start the CDB and Verify PDB States

Start the CDB and verify the PDB states:

```
STARTUP;  
SELECT con_id, name, open_mode FROM v$pdb;
```

10. Ensure All PDBs Are Running

Ensure all PDBs are open:

```
ALTER PLUGGABLE DATABASE ALL OPEN;  
SELECT con_id, name, open_mode FROM v$pdb;
```

11. Exit SQL*Plus

Exit SQL*Plus:

```
EXIT;
```

12. Start the Listener

Start the Oracle listener:

```
lsnrctl start
```

Summary

By following these steps, you will successfully identify and stop all running databases and listeners, create a new CDB named `CDBLAB` with three PDBs, and ensure that all databases are running at the end of the practice. This practice helps in understanding the complete lifecycle management of Oracle databases using DBCA and SQL*Plus commands.

Addendum: Verifying Created Files and Running Processes

Objective:

To verify all the files created for the new CDB (`CDBLAB`) and its three PDBs (`PDBLAB1` , `PDBLAB2` , `PDBLAB3`), and to find the processes that are running for all of them.

Steps:

1. Open a New Terminal

Open a new terminal window.

2. Verify Files Created for CDB and PDBs

Navigate to the Oracle datafile destination directory:

```
cd /u01/app/oracle/oradata/CDBLAB
ls -l
```

Expected Files in CDBLAB Directory:

- **Control Files:** control01.ctl , control02.ctl
- **Redo Log Files:** redo01.log , redo02.log , redo03.log
- **System Data Files:** system01.dbf , sysaux01.dbf
- **Temporary Tablespace:** temp01.dbf
- **Undo Tablespace:** undotbs01.dbf
- **PDB Seed Files:** pdbseed/system01.dbf , pdbseed/sysaux01.dbf

Explanation:

- **Control Files:** Essential for database startup, containing metadata about the database structure.
- **Redo Log Files:** Used for recovery purposes, storing all changes made to the database.
- **System Data Files:** Contain the core data dictionary and system information.
- **Temporary Tablespace:** Used for temporary storage of data during SQL operations.
- **Undo Tablespace:** Stores undo information for transactions.
- **PDB Seed Files:** Template files for creating new PDBs.

3. Verify Files for Each PDB

Navigate to each PDB's directory and list the files:

For PDBLAB1 :

```
cd /u01/app/oracle/oradata/CDBLAB/PDBLAB1
ls -l
```

For PDBLAB2 :

```
cd /u01/app/oracle/oradata/CDBLAB/PDBLAB2
ls -l
```

For PDBLAB3 :

```
cd /u01/app/oracle/oradata/CDBLAB/PDBLAB3
ls -l
```

Expected Files in Each PDB Directory:

- **System Data File:** system01.dbf
- **Sysaux Data File:** sysaux01.dbf
- **Temporary Tablespace:** temp01.dbf
- **Users Tablespace:** users01.dbf

Explanation:

- **System Data File:** Contains the core data dictionary and system information for the PDB.
- **Sysaux Data File:** Auxiliary data for the PDB.
- **Temporary Tablespace:** Temporary storage for SQL operations within the PDB.
- **Users Tablespace:** Default tablespace for user data within the PDB.

4. Find Running Processes for the CDB and PDBs

Identify all running processes for the CDB and PDBs using the `pgrep` command:

```
pgrep -lf smon
```

Expected Output:

- You should see entries like `ora_smon_CDBLAB`, `ora_smon_PDB1`, `ora_smon_PDB2`, and `ora_smon_PDB3`.

Explanation:

- **SMON Process:** System Monitor process for each database, responsible for instance recovery, cleaning up temporary segments, and other tasks.

Check the listener process:

```
pgrep -lf tns
```

Expected Output:

- You should see an entry like `tnslsnr LISTENER`.

Explanation:

- **Listener Process:** Manages incoming client connections to the Oracle database.

5. Detailed Process Information

For more detailed information about each process, use the `ps` command:

```
ps -ef | grep smon
```

Explanation:

- This command provides detailed information about the `smon` processes, including the user running them, start time, and more.

6. Checking Database Status in SQL*Plus

Connect to SQL*Plus to check the status of the CDB and PDBs:

```
sqlplus / as sysdba
```

Check the Status of the PDBs:

```
SELECT con_id, name, open_mode FROM v$pdb;
```

Expected Output:

- You should see the following:

CON_ID	NAME	OPEN_MODE
-----	-----	-----
2	PDB\$SEED	READ ONLY
3	PDBLAB1	READ WRITE
4	PDBLAB2	READ WRITE
5	PDBLAB3	READ WRITE

Explanation:

- **PDB\$SEED**: Template for creating new PDBs, should be in READ ONLY mode.
- **PDBLAB1, PDBLAB2, PDBLAB3**: User-defined PDBs, should be in READ WRITE mode.

Summary

By following these detailed steps, you will verify the files created for the new CDB and its PDBs and identify the running processes associated with them. This addendum ensures a thorough understanding of the Oracle database's file structure and process management.

Summary: Important Files and Scripts for Managing CDBLAB and PDBs

Oracle Home Directory Structure

The Oracle Home directory structure is as follows:

```
/u01/app/oracle/product/19.3.0/
├─ dbhome_1/
│   ├── bin/
│   ├── config/
│   ├── dbs/
│   ├── include/
│   ├── inventory/
│   ├── javavm/
│   ├── jdbc/
│   ├── jlib/
│   ├── lib/
│   ├── network/
│   ├── OPatch/
│   ├── oracore/
│   ├── perl/
│   ├── plsql/
│   ├── precomp/
│   ├── racg/
│   ├── rdbms/
│   ├── relnotes/
│   ├── slax/
│   ├── sqlplus/
│   ├── srvn/
│   ├── suptools/
│   ├── uc4/
│   ├── ucp/
│   └─ xdk/
```

Important Directories and Files

1. bin/:

- **Location**: /u01/app/oracle/product/19.3.0/dbhome_1/bin/
- **Description**: Contains executable files for Oracle utilities and commands.
- **Important Files**:
 - **sqlplus**: Command-line tool to connect to the Oracle database.
 - **lsnrctl**: Listener control utility.

- `dbca` : Database Configuration Assistant.

2. `dbs/`:

- **Location:** `/u01/app/oracle/product/19.3.0/dbhome_1/dbs/`
- **Description:** Contains database initialization parameter files and password files.
- **Important Files:**
 - `initCDBLAB.ora` : Initialization parameter file for `CDBLAB` .
 - `spfileCDBLAB.ora` : Server parameter file for `CDBLAB` .

3. `network/admin/`:

- **Location:** `/u01/app/oracle/product/19.3.0/dbhome_1/network/admin/`
- **Description:** Contains network configuration files.
- **Important Files:**
 - `listener.ora` : Configuration file for Oracle Net Listener.
 - `tnsnames.ora` : Network service names configuration file.
 - `sqlnet.ora` : Oracle Net Services configuration file.

4. `rdbms/admin/`:

- **Location:** `/u01/app/oracle/product/19.3.0/dbhome_1/rdbms/admin/`
- **Description:** Contains SQL scripts for database creation, management, and maintenance.
- **Important Files:**
 - `catalog.sql` : Script to create the Data Dictionary.
 - `catproc.sql` : Script to compile and install the PL/SQL packages.

5. `OPatch/`:

- **Location:** `/u01/app/oracle/product/19.3.0/dbhome_1/OPatch/`
- **Description:** Contains the OPatch utility for applying patches to the Oracle software.
- **Important Files:**
 - `opatch` : OPatch executable file.

Datafile Locations

1. CDBLAB Datafiles:

- **Location:** `/u01/app/oracle/oradata/CDBLAB/`
- **Description:** Contains datafiles, control files, and redo log files for the `CDBLAB` .
- **Important Files:**
 - `control01.ctl` , `control02.ctl` : Control files.
 - `redo01.log` , `redo02.log` , `redo03.log` : Redo log files.
 - `system01.dbf` : System datafile.
 - `sysaux01.dbf` : SYSAUX tablespace datafile.
 - `temp01.dbf` : Temporary tablespace datafile.
 - `undotbs01.dbf` : Undo tablespace datafile.

2. PDB Datafiles:

- **Locations:**
 - `/u01/app/oracle/oradata/CDBLAB/PDBLAB1/`
 - `/u01/app/oracle/oradata/CDBLAB/PDBLAB2/`

- `/u01/app/oracle/oradata/CDBLAB/PDBLAB3/`
- **Description:** Contains datafiles for each PDB.
- **Important Files:**
 - `system01.dbf` : System datafile for each PDB.
 - `sysaux01.dbf` : SYSAUX tablespace datafile for each PDB.
 - `temp01.dbf` : Temporary tablespace datafile for each PDB.
 - `users01.dbf` : Users tablespace datafile for each PDB.

Verification and Management Scripts

1. Verify Database Status:

- **Command:** `SELECT con_id, name, open_mode FROM v$pdb;`
- **Description:** Checks the status of all PDBs within the CDB.

2. Shutdown and Startup Commands:

- **Shutdown:**

```
SHUTDOWN IMMEDIATE;
```

- **Startup:**

```
STARTUP;
```

3. Managing PDBs:

- **Open a PDB:**

```
ALTER PLUGGABLE DATABASE PDBLAB1 OPEN;
```

- **Close a PDB:**

```
ALTER PLUGGABLE DATABASE PDBLAB1 CLOSE IMMEDIATE;
```

Summary

This summary highlights the key directories and files necessary for managing the `CDBLAB` and its PDBs.

Understanding the location and purpose of these files and directories is crucial for effective database administration and maintenance.

Addendum: Shutting Down and Restarting a Single PDB

Objective:

To provide detailed steps for shutting down and restarting a single Pluggable Database (PDB) within a Container Database (CDB).

Steps:

1. Set Oracle Environment Variables

Set the Oracle environment variables using the `oraenv` script:

```
. oraenv
ORACLE_SID = [oracle] ? CDBLAB
```

2. Connect to SQL*Plus as SYSDBA

Start SQL*Plus and log in to the database as the SYS user with the SYSDBA privilege:

```
sqlplus / as sysdba
```

3. Check the Status of the PDBs

Before shutting down a PDB, check the current status of all PDBs:

```
SELECT con_id, name, open_mode FROM v$pdb;
```

Expected Output:

CON_ID	NAME	OPEN_MODE
-----	-----	-----
2	PDB\$SEED	READ ONLY
3	PDBLAB1	READ WRITE
4	PDBLAB2	READ WRITE
5	PDBLAB3	READ WRITE

4. Switch to the PDB

Switch to the PDB you want to shut down. For example, to switch to PDBLAB1 :

```
ALTER SESSION SET CONTAINER = PDBLAB1;
```

5. Shutdown the PDB

Shut down the PDB using the CLOSE command:

```
ALTER PLUGGABLE DATABASE CLOSE IMMEDIATE;
```

Verify the PDB Status:

```
SELECT name, open_mode FROM v$pdb WHERE name = 'PDBLAB1';
```

Expected Output:

NAME	OPEN_MODE
-----	-----
PDBLAB1	MOUNTED

Explanation:

- The PDB PDBLAB1 should now be in the MOUNTED state, indicating it is closed but not completely shut down.

6. Restart the PDB

To restart the PDB, open it:

```
ALTER PLUGGABLE DATABASE OPEN;
```


Verify the PDB Status:

```
SELECT name, open_mode FROM v$pdb$ WHERE name = 'PDBLAB1';
```

Expected Output:

NAME	OPEN_MODE
PDBLAB1	READ WRITE

Explanation:

- The PDB `PDBLAB1` should now be in the READ WRITE state, indicating it is fully operational.

7. Return to the Root Container

After managing the PDB, return to the root container (`CDB$ROOT`):

```
ALTER SESSION SET CONTAINER = CDB$ROOT;
```

8. Exit SQL*Plus

Exit SQL*Plus:

```
EXIT;
```

Summary

By following these steps, you can effectively shut down and restart a single PDB within a CDB. This procedure is essential for performing maintenance tasks or managing specific PDBs without affecting the entire CDB.

```
SID_LIST_LISTENER =
(
  (SID_LIST =
    (SID_DESC =
      (GLOBAL_DBNAME = pdblab2)
      (SID_NAME = PDBLAB2)
      (ORACLE_HOME = /u01/app/oracle/product/19.3.0/dbhome_1)
    )
  )
  (SID_DESC =
    (GLOBAL_DBNAME = pdblab3)
    (SID_NAME = PDBLAB3)
    (ORACLE_HOME = /u01/app/oracle/product/19.3.0/dbhome_1)
  )
)
```

this

```
PDBLAB2 =
(DESCRIPTION =
```

```
(ADDRESS = (PROTOCOL = TCP) (HOST = localhost) (PORT = 1521))
(CONNECT_DATA =
  (SERVER = DEDICATED)
  (SERVICE_NAME = pdblab2)
)
)

PDBLAB3 =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP) (HOST = localhost) (PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = pdblab3)
    )
  )
)
```