


Lab 10. Managing your Puppet code with Git



In this lab, you'll learn how to use the Git version control system to manage your Puppet manifests. I'll also show you how to use Git to distribute the manifests to multiple nodes, so that you can start managing your whole network with Puppet.



Creating a Git repo

It's very easy to create a Git repo. Follow these steps:

1. Make a directory to hold your versioned files using the following commands:

```
cd  
mkdir puppet
```

2. Now run the following commands to turn the directory into a Git repo:

```
cd puppet  
git init  
Initialized empty Git repository in /home/ubuntu/puppet/.git/
```

Making your first commit

You can change the files in your repo as much as you like, but Git will not know about the changes until you make what's called a **commit**. You can think of a commit as being like a snapshot of the repo at a particular moment, but it also stores information about what changed in the repo since the previous commit. Commits are stored forever, so you will always be able to roll back the repo to the state it was in at a certain commit, or show what files were changed in a past commit and compare them to the state of the repo at any other commit.

Let's make our first commit to the new repo:

1. Because Git records not only changes to the code, but also who made them, it needs to know who you are. Set your identification details for Git (use your own name and email address, unless you particularly prefer mine) using the following commands:

```
git config --global user.name "Puppet QuickStart"
git config --global user.email john@fenago.com
```

2. It's traditional for Git repos to have a `README` file, which explains what's in the repo and how to use it. For the moment, let's just create this file with a placeholder message:

```
echo "Watch this space... coming soon!" >README.md
```

3. Run the following command:

```
git status
On branch master
Initial commit
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    README.md
nothing added to commit but untracked files present (use "git add" to track)
```

4. Because we've added a new file to the repo, changes to it won't be tracked by Git unless we explicitly tell it to. We do this by using the `git add` command, as follows:

```
git add README.md
```

5. Git now knows about this file, and changes to it will be included in the next commit. We can check this by running `git status` again:

```
git status
On branch master
Initial commit
Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
    new file:   README.md
```

6. The file is listed under `Changes to be committed`, so we can now actually make the commit:

```
git commit -m 'Add README file'
[master (root-commit) ee21595] Add README file
1 file changed, 1 insertion(+)
create mode 100644 README.md
```

7. You can always see the complete history of commits in a repo by using the `git log` command. Try it now to see the commit you just made:

```
git log
commit ee215951199158ef28dd78197d8fa9ff078b3579
Author: Puppet QuickStart <john@fenago.com>
Date:   Tue Aug 30 05:59:42 2016 -0700
    Add README file
```

Distributing Puppet manifests

In the following sections, we'll create a GitHub account, push our new Puppet repo to GitHub, and then set up our virtual machine to automatically pull any changes from the GitHub repo and apply them with Puppet.

Creating a GitHub account and project

If you already have a GitHub account, or you're using another Git server, you can skip this section.

1. Browse to <https://github.com/>
2. Enter the username you want to use, your email address, and a password.
3. Choose the **Unlimited public repositories for free** plan.
4. GitHub will send you an email to verify your email address. When you get the email, click on the verification link.
5. Select **Start a project**.
6. Enter a name for your repo (I suggest `puppet`, but it doesn't matter).
7. Free GitHub accounts can only create public repos, so select **Public**.

Note


Be careful what information you put into a public Git repo, because it can be read by anybody. Never put passwords, login credentials, private keys, or other confidential information into a repo like this unless it is encrypted.

8. Click **Create repository**.
9. GitHub will show you a page of instructions about how to initialize or import code into your new repository. Look for the `https` URL which identifies your repo; it will be something like this (`https://github.com/pbgtest/puppet.git`):

Create a new repository

A repository contains all the files for your project, including the revision history.

Owner

 pbgtest ▾

Repository name

/ puppet ✓

Great repository names are short and memorable. Need inspiration? How about **special-palm-tree**.

Description (optional)

My amazing Puppet repo. I owe it all to @bitfield.



Public

Anyone can see this repository. You choose who can commit.



Private

You choose who can see and commit to this repository.

☐ **Initialize this repository with a README**

This will let you immediately clone the repository to your computer. Skip this step if you're importing an existing repository.

Add .gitignore: **None** ▾

Add a license: **None** ▾



Create repository

Pushing your repo to GitHub

You're now ready to take the Git repo you created locally earlier in this lab and push it to GitHub so that you can share it with other nodes.


1. In your repo directory, run the following commands. After `git remote add origin`, specify the URL to your GitHub repo:

```
git remote add origin YOUR_REPO_URL
git push -u origin master
```

2. GitHub will prompt you for your username and password:

```
Username for 'https://github.com': pbgtest
Password for 'https://pbgtest@github.com':
Counting objects: 3, done.
Writing objects: 100% (3/3), 262 bytes | 0 bytes/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/pbgtest/puppet.git
 * [new branch]      master -> master
Branch master set up to track remote branch master from origin.
```

3. You can check that everything has worked properly by visiting the repo URL in your browser. It should look something like this:



Cloning the repo

In order to manage multiple nodes with Puppet, you will need a copy of the repo on each node. If you have a node you'd like to manage with Puppet, you can use it in this example.

Run the following commands (replace the argument to `git clone` with the URL of your own GitHub repo, but don't lose the `production` at the end):

```
cd /etc/puppetlabs/code/environments
sudo mv production production.sample
sudo git clone YOUR_REPO_URL production
Cloning into 'production'...
remote: Counting objects: 3, done.
remote: Total 3 (delta 0), reused 3 (delta 0), pack-reused 0
Unpacking objects: 100% (3/3), done.
Checking connectivity... done.
```

How does this work? The standard place for Puppet manifests in a production environment is the `/etc/puppetlabs/code/environments/production/` directory, so that's where our cloned repo needs to end up. However, the Puppet package installs some sample manifests in that directory, and Git will refuse to clone into a directory that already exists, so we move that directory out of the way with the `mv production production.sample` command. The `git clone` command then recreates that directory, but this time it contains our manifests from the repo.

Fetching and applying changes automatically

In a stand-alone Puppet architecture, each node needs to automatically fetch any changes from the Git repo at regular intervals, and apply them with Puppet. We can use a simple shell script for this, and there's one in the example repo (`/examples/files/run-puppet.sh`):

```
#!/bin/bash
cd /etc/puppetlabs/code/environments/production && git pull
/opt/puppetlabs/bin/puppet apply manifests/
```

We will need to install this script on the node to be managed by Puppet, and create a cron job to run it regularly (I suggest every 15 minutes). Of course, we could do this work manually, but isn't this course partly about the advantages of automation? Very well, then: let's practice what we're preaching.

Writing a manifest to set up regular Puppet runs

In this section, we'll create the necessary Puppet manifests to install the `run-puppet` script on a node and run it regularly from cron:

1. Run the following commands to create the required directories in your Puppet repo:

```
cd /home/ubuntu/puppet
mkdir manifests files
```

2. Run the following command to copy the `run-puppet` script from the `examples/` directory:

```
cp /examples/files/run-puppet.sh files/
```

3. Run the following command to copy the `run-puppet` manifest from the `examples/` directory:

```
cp /ubuntu/examples/run-puppet.pp manifests/
```

4. Add and commit the files to Git with the following commands:

```
git add manifests files
git commit -m 'Add run-puppet script and cron job'
git push origin master
```

Your Git repo now contains everything you need to automatically pull and apply changes on your managed nodes. In the next section, we'll see how to set up this process on a node.

Note

You might have noticed that every time you push files to your GitHub repo, Git prompts you for your username and password. If you want to avoid this, you can associate an SSH key with your GitHub account. Once you've done this, you'll be able to push without having to re-enter your credentials every time. For more information about using an SSH key with your GitHub account see this article:

<https://help.github.com/articles/adding-a-new-ssh-key-to-your-github-account/>

Applying the run-puppet manifest

Having created and pushed the manifest necessary to set up automatic Puppet runs, we now need to pull and apply it on the target node.

In the cloned copy of your repo in `/etc/puppetlabs/code/environments/production`, run the following commands:

```
sudo git pull
puppet apply manifests/
Notice: Compiled catalog for localhost in environment production in 0.08 seconds
Notice: /Stage[main]/Main/File[/usr/local/bin/run-puppet]/ensure: defined content as
'{md5}83a6903e69564bcecc8fd1a83b1a7beb'
Notice: /Stage[main]/Main/Cron[run-puppet]/ensure: created
Notice: Applied catalog in 0.07 seconds
```

You can see from Puppet's output that it has created the `/usr/local/bin/run-puppet` script and the `run-puppet` cron job. This will now run automatically every 15 minutes, pull any new changes from the Git repo, and apply the updated manifest.

The run-puppet script

The `run-puppet` script does the following two things in order to automatically update the target node:

1. Pull any changes from the Git server (`git pull`).
2. Apply the manifest (`puppet apply`).

Our Puppet manifest in `run-puppet.pp` deploys this script to the target node, using a `file` resource, and then sets up a cron job to run it every 15 minutes, using a `cron` resource.

For now, just note that the `cron` resource has a name (`run-puppet`), which is just for the benefit of us humans, to remind us what it does, and it also has a `command` to run and `hour` and `minute` attributes to control when it runs. The value `*/15` tells `cron` to run the job every 15 minutes.

Testing automatic Puppet runs

To prove that the automatic Puppet run works, make a change to your manifest which creates a file (`/tmp/hello.txt` , for example). Commit and push this change to Git. Wait 15 minutes, and check your target node. The file should be present. If not, something is broken. To troubleshoot the problem, try running `sudo run-puppet` manually. If this works, check that the cron job is correctly installed by running `sudo crontab -l`. It should look something like the following:

```
# HEADER: This file was autogenerated at 2017-04-05 01:46:03 -0700 by puppet.
# HEADER: While it can still be managed manually, it is definitely not recommended.
# HEADER: Note particularly that the comments starting with 'Puppet Name' should
# HEADER: not be deleted, as doing so could cause duplicate cron jobs.
# Puppet Name: run-puppet
*/15 * * * * /usr/local/bin/run-puppet
```

Managing multiple nodes

You now have a fully automated stand-alone Puppet infrastructure. Any change that you check in to your Git repo will be automatically applied to all nodes under Puppet management. To add more nodes to your infrastructure, follow these steps for each new node:

1. Install Puppet.
2. Clone your Git repo (as described in the *[Cloning the repo]* section).
3. Apply the manifest (as described in the *[Applying the run-puppet manifest]* section).

You might be wondering how to tell Puppet how to apply different manifests to different nodes. For example, you might be managing two nodes, one of which is a web server and the other a database server. Naturally, they will need different resources.

Summary

In this lab, we introduced the concepts of version control, and the essentials of Git in particular. We set up a new Git repo, created a GitHub account, pushed our code to it, and cloned it on a node. We wrote a shell script to automatically pull and apply changes from the GitHub repo on any node, and a Puppet manifest to install this script and run it regularly from `cron`.

In the next lab, we'll explore the power of Puppet resources, going into more detail about the Puppet `file`, `package`, and `service` resources we've already encountered, and introducing three more important resource types: `user`, `cron`, and `exec`.