

PERFORMANCE METRICS

Prof. Ernesto Lee

HOW YOU MEASURE YOUR MODEL

- Classification Metrics
- Regression Metrics

CLASSIFICATION METRICS

● CLASSIFICATION METRICS

- ^ Classification Accuracy.
- ^ Logarithmic Loss.
- ^ Area Under ROC Curve.
- ^ Confusion Matrix.
- ^ Classification Report.

CLASSIFICATION ACCURACY

```
# Cross Validation Classification Accuracy
from pandas import read_csv
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LogisticRegression
filename = 'pima-indians-diabetes.data.csv'
names = ['preg', 'plas', 'pres', 'skin', 'test', 'mass', 'pedi', 'age', 'class']
dataframe = read_csv(filename, names=names)
array = dataframe.values
X = array[:,0:8]
Y = array[:,8]
kfold = KFold(n_splits=10, random_state=7)
model = LogisticRegression(solver='liblinear')
scoring = 'accuracy'
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
print("Accuracy: %.3f (%.3f)" % (results.mean(), results.std()))
```

LOGARITHMIC LOSS

```
# Cross Validation Classification LogLoss
from pandas import read_csv
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LogisticRegression
filename = 'pima-indians-diabetes.data.csv'
names = ['preg', 'plas', 'pres', 'skin', 'test', 'mass', 'pedi', 'age', 'class']
dataframe = read_csv(filename, names=names)
array = dataframe.values
X = array[:,0:8]
Y = array[:,8]
kfold = KFold(n_splits=10, random_state=7)
model = LogisticRegression(solver='liblinear')
scoring = 'neg_log_loss'
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
print("Logloss: %.3f (%.3f)" % (results.mean(), results.std()))
```

AUC: AREA UNDER ROC CURVE

```
# Cross Validation Classification ROC AUC
from pandas import read_csv
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LogisticRegression
filename = 'pima-indians-diabetes.data.csv'
names = ['preg', 'plas', 'pres', 'skin', 'test', 'mass', 'pedi', 'age', 'class']
dataframe = read_csv(filename, names=names)
array = dataframe.values
X = array[:,0:8]
Y = array[:,8]
kfold = KFold(n_splits=10, random_state=7)
model = LogisticRegression(solver='liblinear')
scoring = 'roc_auc'
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
print("AUC: %.3f (%.3f)" % (results.mean(), results.std()))
```



```
# Cross Validation Classification Confusion Matrix
from pandas import read_csv
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import confusion_matrix

filename = 'pima-indians-diabetes.data.csv'
names = ['preg', 'plas', 'pres', 'skin', 'test', 'mass', 'pedi', 'age', 'class']
dataframe = read_csv(filename, names=names)
array = dataframe.values
X = array[:,0:8]
Y = array[:,8]
test_size = 0.33
seed = 7
X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=test_size,
    random_state=seed)
model = LogisticRegression(solver='liblinear')
model.fit(X_train, Y_train)
predicted = model.predict(X_test)
matrix = confusion_matrix(Y_test, predicted)
print(matrix)
```


CLASSIFICATION REPORT

```
# Cross Validation Classification Report
from pandas import read_csv
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import classification_report
filename = 'pima-indians-diabetes.data.csv'
names = ['preg', 'plas', 'pres', 'skin', 'test', 'mass', 'pedi', 'age', 'class']
dataframe = read_csv(filename, names=names)
array = dataframe.values
X = array[:,0:8]
Y = array[:,8]
test_size = 0.33
seed = 7
X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=test_size,
                                                    random_state=seed)
model = LogisticRegression(solver='liblinear')
model.fit(X_train, Y_train)
predicted = model.predict(X_test)
report = classification_report(Y_test, predicted)
print(report)
```

REGRESSION METRICS

REGRESSION METRICS

- \hat{MAE} Mean Absolute Error.
- \hat{MSE} Mean Squared Error.
- $\hat{R^2}$.

MAE

```
# Cross Validation Regression MAE
from pandas import read_csv
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LinearRegression

filename = 'housing.csv'
names = ['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD', 'TAX', 'PTRATIO',
         'B', 'LSTAT', 'MEDV']
dataframe = read_csv(filename, delim_whitespace=True, names=names)
array = dataframe.values
X = array[:,0:13]
Y = array[:,13]
kfold = KFold(n_splits=10, random_state=7)
model = LinearRegression()
scoring = 'neg_mean_absolute_error'
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
print("MAE: %.3f (%.3f)" % (results.mean(), results.std()))
```

MEAN SQUARED ERROR

```
# Cross Validation Regression MSE
from pandas import read_csv
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LinearRegression
filename = 'housing.csv'
names = ['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD', 'TAX', 'PTRATIO',
        'B', 'LSTAT', 'MEDV']
dataframe = read_csv(filename, delim_whitespace=True, names=names)
array = dataframe.values
X = array[:,0:13]
Y = array[:,13]
kfold = KFold(n_splits=10, random_state=7)
model = LinearRegression()
scoring = 'neg_mean_squared_error'
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
print("MSE: %.3f (%.3f)" % (results.mean(), results.std()))
```

R SQUARED

```
# Cross Validation Regression R^2
from pandas import read_csv
from sklearn.model_selection import KFold
from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LinearRegression

filename = 'housing.csv'
names = ['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD', 'TAX', 'PTRATIO',
         'B', 'LSTAT', 'MEDV']

dataframe = read_csv(filename, delim_whitespace=True, names=names)
array = dataframe.values
X = array[:,0:13]
Y = array[:,13]
kfold = KFold(n_splits=10, random_state=7)
model = LinearRegression()
scoring = 'r2'
results = cross_val_score(model, X, Y, cv=kfold, scoring=scoring)
print("R^2: %.3f (%.3f)" % (results.mean(), results.std()))
```


SUMMARY



