

# Building a Real-Time Data Vault in Snowflake

## Overview

In this day and age, with the ever-increasing availability and volume of data from many types of sources such as IoT, mobile devices, and weblogs, there is a growing need, and yes, demand, to go from batch load processes to streaming or “real-time” (RT) loading of data. Businesses are changing at an alarming rate and are becoming more competitive all the time. Those that can harness the value of their data faster to drive better business outcomes will be the ones to prevail.

One of the benefits of using the Data Vault 2.0 architecture is that it was designed from inception not only to accept data loaded using traditional batch mode (which was the prevailing mode in the early 2000s when [Dan Linstedt](#) introduced Data Vault) but also to easily accept data loading in real or near-realtime (NRT). In the early 2000s, that was a nice-to-have aspect of the approach and meant the methodology was effectively future-proofed from that perspective. Still, few database systems had the capacity to support that kind of requirement. Today, RT or at least NRT loading is almost becoming a mandatory requirement for modern data platforms. Granted, not all loads or use cases need to be NRT, but most forward-thinking organizations need to onboard data for analytics in an NRT manner.

Those who have been using the Data Vault approach don’t need to change much other than figure out how to engineer their data pipeline to serve up data to the Data Vault in NRT. The data models don’t need to change; the reporting views don’t need to change; even the loading patterns don’t need to change. (NB: For those that aren’t using Data Vault already, if they have real-time loading requirements, this architecture and method might be worth considering.)

## Data Vault on Snowflake

Luckily, streaming data is one of the [use-cases] that Snowflake was built to support, so we have many features to help us achieve this goal. **This guide is an extended version of the [article](#) posted on Data Vault Alliance website, now including practical steps to build an example of real-time Data Vault feed on Snowflake. Join us on simple-to-follow steps to see it in action.**

## Prerequisites

- A Snowflake account. Existing or if you are not(yet) a Snowflake user, you can always get a [trial](#) account
- Familiarity with Snowflake and Snowflake objects
- Understanding of Data Vault concepts and modelling techniques

## What You’ll Learn


- how to use Data Vault on Snowflake
- how to build basic objects and write ELT code for it
- how to leverage [Snowpipe] and [Continuous Data Pipelines] to automate data processing
- how to apply data virtualization to accelerate data access

## What You’ll Build

- a Data Vault environment on Snowflake, based on sample dataset
- data pipelines, leveraging streams, tasks and Snowpipe

## Reference Architecture

Let's start with the overall architecture to put everything in context.



On the very left of figure above we have a list of **data providers** that typically include a mix of existing operational databases, old data warehouses, files, lakes as well as 3rd party apps. There is now also the possibility to leverage Snowflake Data Sharing/Marketplace as a way to tap into new 3rd party data assets to augment your data set.

On the very right we have our ultimate **data consumers**: business users, data scientists, IT systems or even other companies you decided to exchange your data with.


Architecturally, we will split the data lifecycle into following layers:

- **Data Acquisition:** extracting data from source systems and making it accessible for Snowflake.
- **Loading & Staging:** moving the source data into Snowflake. For this Snowflake has multiple options, including batch load, external tables and Snowpipe(our managed service for onboarding streaming data). Snowflake allows you to load and store structured and semi-structured in the original format whilst automatically optimizing the physical structure for efficient query access. The data is immutable and should be stored as it was received from source with no changes to the content. From a Data Vault perspective, functionally, this layer is also responsible for adding technical metadata (record source,, load date timestamp, etc.) as well as calculating business keys.
- **Raw Data Vault:** a data vault model with no soft business rules or transformations applied (only hard rules are allowed) loading all records received from source.
- **Business Data Vault:** data vault objects with soft business rules applied. The raw data vault data is getting augmented by the intelligence of the system. It is not a copy of the raw data vault, but rather a sparse addition with perhaps calculated satellites, mastered records,or maybe even commonly used aggregations. This could also optionally include PIT and Bridge tables helping to simplify access to bi-temporal view of the data. From a Snowflake perspective, raw and business data vaults could be separated by object naming convention or represented as different schemas or even different databases.
- **Information Delivery:** a layer of consumer-oriented models. This could be implemented as a set (or multiple sets) of views. It is common to see the use of dimensional models (star/snowflake) or denormalized flat tables (for example for data science or sharing) but it could be any other modeling stye (e.g., unified star


schema, supernova, key-value, document object mode, etc.) that fits best for your data consumer. Snowflake's scalability will support the required speed of access at any point of this data lifecycle. You should consider Business Vault and Information Delivery objects materialization as optional. This specific topic (virtualization) is going to be covered later in this article.

## Environment setup


1. Login to your Snowflake trial account.



2. First page you are going to see would likely be [Snowflake Classic UI]:



To keep things interesting, for the purpose of this lab let's use [Snowflake New Web Interface] also known as Snowsight. However, you absolutely can continue using Classic UI as all steps in this guide are expressed in SQL and will work regardless what interface is used. To switch into Snowsight, let's click the **Preview** button in the top-right corner:




Click Sign in to continue. You will need to use the same user and password that you used to login to your Snowflake account the first time.




[Sign in to continue](#)

You're now in the new UI - Snowsight. It's pretty cool - with charting, dashboards, autocompletion and new capabilities that our engineering team will continue to add on weekly. Now, let's click on Worksheets...

3. Let's click on the worksheets -> + **Worksheet**



And without going into too much details, this is a fairly intuitive SQL workbench. It has a section for code we are going to be copy-pasting, object tree on the left, the 'run' button and of course the result panel at the bottom with the simple charting functionality.



4. We are going to start by setting up basics for the lab environment. Creating a clean database and logically dividing it into four different schemas, representing each functional area mentioned in the reference architecture.

To keep things simple, we are going to use the ACCOUNTADMIN role. We also going to create two [Snowflake virtual warehouses] to manage compute - one for generic use during the course of this lab and the other one (dv\_rdv\_wh) that is going to be used by our data pipelines. You might notice that the code for two more virtual warehouses (dv\_bdv\_wh, dv\_id\_wh) is commented - again, this is just to keep things simple for the guide but we wanted to illustrate the fact you can have as many of virtual warehouses of any size and configuration as you needed. For example having separate ones to deal with different layers in our Data Vault architecture.

```
-- setting up the environment
```

```
USE ROLE accountadmin;
```

```
CREATE OR REPLACE DATABASE dv_lab;
```

```
USE DATABASE dv_lab;
```

```
CREATE OR REPLACE WAREHOUSE dv_lab_wh WITH WAREHOUSE_SIZE = 'XSMALL' MIN_CLUSTER_COUNT = 1 MAX_CLUSTER_COUNT = 1 AUTO_SUSPEND = 60 COMMENT = 'Generic WH';
```

```
CREATE OR REPLACE WAREHOUSE dv_rdv_wh WITH WAREHOUSE_SIZE = 'XSMALL' MIN_CLUSTER_COUNT = 1 MAX_CLUSTER_COUNT = 1 AUTO_SUSPEND = 60 COMMENT = 'WH for Raw Data Vault object pipelines';
```

```
--CREATE OR REPLACE WAREHOUSE dv_bdv_wh WITH WAREHOUSE_SIZE = 'XSMALL' MIN_CLUSTER_COUNT = 1 MAX_CLUSTER_COUNT = 1 AUTO_SUSPEND = 60 COMMENT = 'WH for Business Data Vault object pipelines';
```

```
--CREATE OR REPLACE WAREHOUSE dv_id_wh WITH WAREHOUSE_SIZE = 'XSMALL' MIN_CLUSTER_COUNT = 1 MAX_CLUSTER_COUNT = 1 AUTO_SUSPEND = 60 COMMENT = 'WH for information delivery object pipelines';
```

```
USE WAREHOUSE dv_lab_wh;
```

```
CREATE OR REPLACE SCHEMA 100_stg COMMENT = 'Schema for Staging Area objects';
```


```
CREATE OR REPLACE SCHEMA 110_rdv COMMENT = 'Schema for Raw Data Vault objects';
```

```
CREATE OR REPLACE SCHEMA 120_bdv COMMENT = 'Schema for Business Data Vault objects';
```

```
CREATE OR REPLACE SCHEMA 130_id COMMENT = 'Schema for Information Delivery objects';
```

## Data Pipelines: Design

# CONTINUOUS TRANSFORMATIONS



Snowflake supports multiple options for engineering data pipelines. In this post we are going to show one of the most efficient ways to implement incremental NRT integration leveraging Snowflake [Continuous Data Pipelines]. Let's take a look at the architecture diagram above to understand how it works.

Snowflake has a special [stream] object that tracks all data changes on a table (inserts, updates, and deletes). This process is 100% automatic and unlike traditional databases will never impact the speed of data loading. The change log from a stream is automatically 'consumed' once there is a successfully completed DML operation using the stream object as a source.

So, loading new data into a staging table, would immediately be reflected in a stream showing the ['delta'] that requires processing.

The second component we are going to use is [tasks]. It is a Snowflake managed data processing unit that will wake up on a defined interval (e.g., every 1-2 min), check if there is any data in the associated stream and if so, will run SQL to push it to the Raw Data Vault objects. Tasks could be arranged in a [tree-like dependency graph], executing child tasks the moment the predecessor finished its part.

Last but not least, following Data Vault 2.0 best practices for NRT data integration (to load data in parallel) we are going to use Snowflake's [multi-table insert (MTI)] inside tasks to populate multiple Raw Data Vault objects by a single DML command. (Alternatively you can create multiple streams & tasks from the same table in stage in order to populate each data vault object by its own asynchronous flow.)

Next step, you assign tasks to one or many virtual warehouses. This means you always have enough [compute power] (XS to 6XL) to deal with any size workload, whilst the [multi-cluster virtual warehouse] option will automatically scale-out and load balance all the tasks as you introduce more hubs, links and satellites to your vault.

Talking about tasks, Snowflake just introduced another fantastic capability - serverless tasks. This enables you to rely on compute resources managed by Snowflake instead of user-managed virtual warehouses. These compute resources are automatically resized and scaled up and down by Snowflake as required by each workload. This feature will be out of scope for this guide, but serverless compute model could reduce compute costs, in some cases significantly, allowing you to process more data, faster with even less management.

As your raw vault is updated, streams can then be used to propagate those changes to Business Vault objects (such as derived Sats, PITS, or Bridges, if needed) in the next layer. This setup can be repeated to move data through all the layers in small increments very quickly and efficiently. All the way until it is ready to be accessed by data consumers (if materialization of the data is required for performance).

Following this approach will result in a hands-off production data pipeline that feeds your Data Vault architecture.

## Sample data & staging area

Every Snowflake account provides access to [sample data sets]. You can find corresponding schemas in SNOWFLAKE\_SAMPLE\_DATA database in your object explorer. For this guide we are going to use a subset of objects from [TPC-H] set, representing **customers** and their **orders**. We also going to take some reference data about **nations** and **regions**.

Dataset	Description	Source	Load Scenario	Mechanism
Nation	Static ref data	snowflake.sample_data.tpch_sf10.nation	one-off CTAS	SQL
Region	Static ref data	snowflake.sample_data.tpch_sf10.region	one-off CTAS	SQL
Customer	Customer data	snowflake.sample_data.tpch_sf10.customer	incremental JSON files	Snowpipe

Orders	Orders data	snowflake.sample_data.tpch_sf10.orders	incremental CSV files	Snowpipe
--------	-------------	--	-----------------------	----------

1. Let's start with the static reference data:

```

-----
-- setting up staging area
-----

USE SCHEMA 100_stg;

CREATE OR REPLACE TABLE stg_nation
AS
SELECT src.*
      , CURRENT_TIMESTAMP()      ldts
      , 'Static Reference Data'  rscr
FROM snowflake_sample_data.tpch_sf10.nation src;

CREATE OR REPLACE TABLE stg_region
AS
SELECT src.*
      , CURRENT_TIMESTAMP()      ldts
      , 'Static Reference Data'  rscr
FROM snowflake_sample_data.tpch_sf10.region src;

```

2. Next, let's create staging tables for our data loading. This syntax should be very familiar with anyone working with databases before. It is ANSI SQL compliant DDL, with probably one key exception - for stg\_customer we are going to load the full payload of JSON into raw\_json column. For this, Snowflake has a special data type [VARIANT].

As we load data we also going to add some technical metadata, like load data timestamp, row number in a file.

```

CREATE OR REPLACE TABLE stg_customer
(
  raw_json          VARIANT
, filename          STRING    NOT NULL
, file_row_seq      NUMBER    NOT NULL
, ldts              STRING    NOT NULL
, rscr              STRING    NOT NULL
);

CREATE OR REPLACE TABLE stg_orders
(
  o_orderkey        NUMBER
, o_custkey         NUMBER
, o_orderstatus     STRING
, o_totalprice      NUMBER
, o_orderdate       DATE
, o_orderpriority   STRING
, o_clerk           STRING
, o_shippriority    NUMBER
, o_comment         STRING
, filename          STRING    NOT NULL

```



```
, file_row_seq          NUMBER    NOT NULL
, ldts                  STRING     NOT NULL
, rscr                  STRING     NOT NULL
);
```

3. Tables we just created are going to be used by Snowpipe to drip-feed the data as it is lands in the stage. In order to easily detect and incrementally process the new portion of data we are going to create [streams] on these staging tables:

```
CREATE OR REPLACE STREAM stg_customer_strm ON TABLE stg_customer;
CREATE OR REPLACE STREAM stg_orders_strm ON TABLE stg_orders;
```

4. Next we are going to produce some sample data. And for the sake of simplicity we are going to take a bit of a shortcut here. We are going to generate data by unloading subset of data from our TPCB sample dataset into files and then use Snowpipe to load it back into our Data Vault lab, simulating the streaming feed. Let's start by creating two stages for each data class type (orders, customers data). In real-life scenarios these could be internal or external stages as well as these feeds could be sourced via Kafka connector. The world is your oyster.

```
CREATE OR REPLACE STAGE customer_data FILE_FORMAT = (TYPE = JSON);
CREATE OR REPLACE STAGE orders_data FILE_FORMAT = (TYPE = CSV) ;
```

5. Generate and unload sample data. There are couple of things going on. First, we are using [object\_construct] as a quick way to create a object/document from all columns and subset of rows for customer data and offload it into customer\_data stage. Orders data would be extracted into compressed CSV files. There are many additional options in [COPY INTO stage] construct that would fit most requirements, but in this case we are using INCLUDE\_QUERY\_ID to make it easier to generate new incremental files as we are going to run these commands over and over again, without a need to deal with file overriding.

```
COPY INTO @customer_data
FROM
(SELECT object_construct(*)
 FROM snowflake_sample_data.tpch_sf10.customer limit 10
)
INCLUDE_QUERY_ID=TRUE;

COPY INTO @orders_data
FROM
(SELECT *
 FROM snowflake_sample_data.tpch_sf10.orders limit 1000
)
INCLUDE_QUERY_ID=TRUE;
```

You can now run the following to validate that the data is now stored in files:

```
list @customer_data;
SELECT METADATA$FILENAME,$1 FROM @customer_data;
```

+
ACCOUNTADMIN
→ DV\_LAB\_WH
Share
Updated 1 minute ago

```

1 COPY INTO @customer_data
2 FROM
3 (SELECT object_construct(*)
4  FROM snowflake_sample_data.tpch_sf10.customer Limit 10
5 )
6 INCLUDE_QUERY_ID=TRUE;
7
8 COPY INTO @orders_data
9 FROM
10 (SELECT *
11  FROM snowflake_sample_data.tpch_sf10.orders Limit 1000
12 )
13 INCLUDE_QUERY_ID=TRUE;
14
15 List @customer_data;
16 SELECT METADATA$FILENAME,$1 FROM @customer_data;
  
```

	METADATA\$FILENAME	\$1
1	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 3721.47, "C_ADDRESS": "k5jk4s9kvJ9PUzx3EFzrM4", "C_COMMENT": "lyly regular acco
2	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 9818.32, "C_ADDRESS": "pqu10,nyy34A6iCKaJY2r,2CuY6s2wC", "C_COMMENT": "apac
3	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 3596, "C_ADDRESS": "eJIEPg74BRuCb264YATBCJ3Sn", "C_COMMENT": "le furiously as
4	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 1909, "C_ADDRESS": "2hM3ZXslZf3J8iCeOK5Hh,Qb4RYD", "C_COMMENT": "slyly final i
5	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 6444.3, "C_ADDRESS": "FkxxXanVvhizhizvfu59 RTpM", "C_COMMENT": " requests. furic
6	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 1422.73, "C_ADDRESS": "dqNBzGhZ,uwKHWMEvgL5cdxW35fcd3l98YCss", "C_COMMEI
7	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 6753.74, "C_ADDRESS": "tn4flmwF35cQff5lBk6CBmYbHgQsviSMjeZN", "C_COMMENT
8	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": -822.31, "C_ADDRESS": "yIRFPvP44x8RKdQIHfIU803PgozFh", "C_COMMENT": "s thras
9	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 4356.55, "C_ADDRESS": "kYFa7jn7n3TZNeGeRqJvq8icPbhtISO", "C_COMMENT": "sl req
10	data_019e8775-0400-a098-0029-1b03002e8cae_0_0_0.json.gz	{ "C_ACCTBAL": 2486.05, "C_ADDRESS": "PHRO9AnJs,8MKkgM6ac", "C_COMMENT": "ts according to th

Clear selection

Cell in \$1
RECORD TEXT

**C\_ACCTBAL**  
3721.47  
**C\_ADDRESS**  
k5jk4s9kvJ9PUzx3EFzrM4  
**C\_COMMENT**  
lyly regular accounts.blithely final  
**C\_CUSTKEY**  
1320001  
**C\_MKTSEGMENT**  
MACHINERY  
**C\_NAME**  
Customer#001320001  
**C\_NATIONKEY**  
4  
**C\_PHONE**  
14-458-943-9790

6. Next, we are going to setup Snowpipe to load data from files in a stage into staging tables. In this guide, for better transparency we are going to trigger Snowpipe explicitly to scan for new files, but in real projects you will likely going to enable AUTO\_INGEST, connecting it with your cloud storage events (like AWS SNS) and process new files automatically.

```

CREATE OR REPLACE PIPE stg_orders_pp
AS
COPY INTO stg_orders
FROM
(
SELECT $1,$2,$3,$4,$5,$6,$7,$8,$9
      , metadata$filename
      , metadata$file_row_number
      , CURRENT_TIMESTAMP()
      , 'Orders System'
FROM @orders_data
);

CREATE OR REPLACE PIPE stg_customer_pp
--AUTO_INGEST = TRUE
--aws_sns_topic = 'arn:aws:sns:mybucketdetails'
AS
COPY INTO stg_customer
FROM
  
```

```
(
SELECT $1
      , metadata$filename
      , metadata$file_row_number
      , CURRENT_TIMESTAMP()
      , 'Customers System'
FROM @customer_data
);

ALTER PIPE stg_customer_pp REFRESH;

ALTER PIPE stg_orders_pp REFRESH;
```

Once this done, you should be able to see data appearing in the target tables and the stream on these tables. As you would notice, number of rows in a stream is exactly the same as in the base table. This is because we didn't process/consumed the delta of that stream yet. Stay tuned!

```
SELECT 'stg_customer', count(1) FROM stg_customer
UNION ALL
SELECT 'stg_orders', count(1) FROM stg_orders
UNION ALL
SELECT 'stg_orders_strm', count(1) FROM stg_orders_strm
UNION ALL
SELECT 'stg_customer_strm', count(1) FROM stg_customer_strm
;
```

+
ACCOUNTADMIN - DV\_LAB\_WH
Share
Updated 6 seconds ago

```

11         , CURRENT_TIMESTAMP()
12         , 'Orders System'
13     FROM @orders_data
14 );
15
16 CREATE OR REPLACE PIPE stg_customer_pp
17 --AUTO_INGEST = TRUE
18 --aws_sns_topic = 'arn:aws:sns:mybucketdetails'
19 AS
20 COPY INTO stg_customer
21 FROM
22 (
23     SELECT $1
24         , metadata$filename
25         , metadata$file_row_number
26         , CURRENT_TIMESTAMP()
27         , 'Customers System'
28     FROM @customer_data
29 );
30
31 ALTER PIPE stg_customer_pp REFRESH;
32
33 ALTER PIPE stg_orders_pp REFRESH;
34
35 SELECT 'stg_customer', count(1) FROM stg_customer
36 UNION ALL
37 SELECT 'stg_orders', count(1) FROM stg_orders
38 UNION ALL
39 SELECT 'stg_orders_strm', count(1) FROM stg_orders_strm
40 UNION ALL
41 SELECT 'stg_customer_strm', count(1) FROM stg_customer_strm
42 ;

```

Objects
Query
Results
Chart

	'STO_CUSTOMER'	COUNT(1)
1	stg_customer	10
2	stg_orders	1,000
3	stg_orders_strm	1,000
4	stg_customer_strm	10

**Query Details**

Query duration 320ms

Rows 4

'STO\_CUSTOMER' As

100% filled

**COUNT(1)** 123

10
1,000

7. Finally, now that we established the basics and new data is knocking at our door (stream), let's see how we can derive some of the business keys for the Data Vault entites we are going to model. In this example, we

will model it as a view on top of the stream that should allow us to perform data parsing (raw\_json -> columns) and business\_key, hash\_diff derivation on the fly. Another thing to notice here is the use of SHA1\_BINARY as hashing function. There are many articles on choosing between MD5/SHA1(2)/other hash functions, so we won't focus on this. For this lab, we are going to use fairly common SHA1 and its BINARY version from Snowflake arsenal of functions that use less bytes to encode value than STRING.

```
CREATE OR REPLACE VIEW stg_customer_strm_outbound AS
SELECT src.*
  , raw_json:C_CUSTKEY::NUMBER      c_custkey
  , raw_json:C_NAME::STRING         c_name
  , raw_json:C_ADDRESS::STRING      c_address
  , raw_json:C_NATIONKEY::NUMBER    C_nationcode
  , raw_json:C_PHONE::STRING        c_phone
  , raw_json:C_ACCTBAL::NUMBER      c_acctbal
  , raw_json:C_MKTSEGMENT::STRING   c_mktsegment
  , raw_json:C_COMMENT::STRING      c_comment

-----
-- derived business key
-----

  , SHA1_BINARY(UPPER(TRIM(c_custkey))) sha1_hub_customer
  , SHA1_BINARY(UPPER(ARRAY_TO_STRING(ARRAY_CONSTRUCT(
                                NVL(TRIM(c_name)      , '-1')
                                , NVL(TRIM(c_address)   , '-1')
                                , NVL(TRIM(c_nationcode), '-1')
                                , NVL(TRIM(c_phone)     , '-1')
                                , NVL(TRIM(c_acctbal)   , '-1')
                                , NVL(TRIM(c_mktsegment), '-1')
                                , NVL(TRIM(c_comment)   , '-1')
                                ), '^')))) AS customer_hash_diff

FROM stg_customer_strm src
;

CREATE OR REPLACE VIEW stg_order_strm_outbound AS
SELECT src.*
-----
-- derived business key
-----

  , SHA1_BINARY(UPPER(TRIM(o_orderkey)))          sha1_hub_order
  , SHA1_BINARY(UPPER(TRIM(o_custkey)))           sha1_hub_customer
  , SHA1_BINARY(UPPER(ARRAY_TO_STRING(ARRAY_CONSTRUCT( NVL(TRIM(o_orderkey)
, '-1')
                                , NVL(TRIM(o_custkey)
, '-1')
                                ), '^')))) AS
sha1_lnk_customer_order
  , SHA1_BINARY(UPPER(ARRAY_TO_STRING(ARRAY_CONSTRUCT( NVL(TRIM(o_orderstatus)
, '-1')
                                , NVL(TRIM(o_totalprice)
, '-1')
                                , NVL(TRIM(o_orderdate)
, '-1')
                                , NVL(TRIM(o_orderpriority)
, '-1')
                                )
```


Finally let's query these views to validate the results:

Well done! We build our staging/inbound pipeline, ready to accomodate streaming data and derived business keys that we are going to use in our Raw Data Vault. Let's move on to the next step!

## Build: Raw Data Vault

In this section, we will start building structures and pipelines for **Raw Data Vault** area.

Here is the ER model of the objects we are going to deploy using the script below:



1. We'll start by deploying DDL for the HUBs, LINKs and SATellite tables. As you can imagine, this guide has no chance to go in the detail on data vault modelling process. This is something we usually highly recommend to establish by working with experts & partners from Data Vault Alliance.

```

-----
-- setting up RDV
-----

USE SCHEMA l10_rdv;

-- hubs

CREATE OR REPLACE TABLE hub_customer
(
    sha1_hub_customer          BINARY    NOT NULL
,   c_custkey                 NUMBER    NOT NULL
,   ldts                      TIMESTAMP NOT NULL
,   rscr                      STRING    NOT NULL
,   CONSTRAINT pk_hub_customer PRIMARY KEY(sha1_hub_customer)
);

CREATE OR REPLACE TABLE hub_order
(
    sha1_hub_order            BINARY    NOT NULL
,   o_orderkey               NUMBER    NOT NULL
,   ldts                    TIMESTAMP NOT NULL
,   rscr                    STRING    NOT NULL
,   CONSTRAINT pk_hub_order  PRIMARY KEY(sha1_hub_order)

```

```

);

-- sats

CREATE OR REPLACE TABLE sat_customer
(
    sha1_hub_customer    BINARY    NOT NULL
,   ldts                TIMESTAMP NOT NULL
,   c_name              STRING
,   c_address           STRING
,   c_phone             STRING
,   c_acctbal           NUMBER
,   c_mktsegment        STRING
,   c_comment           STRING
,   nationcode          NUMBER
,   hash_diff           BINARY    NOT NULL
,   rscr                STRING    NOT NULL
,   CONSTRAINT pk_sat_customer PRIMARY KEY(sha1_hub_customer, ldts)
,   CONSTRAINT fk_sat_customer FOREIGN KEY(sha1_hub_customer) REFERENCES
hub_customer
);

CREATE OR REPLACE TABLE sat_order
(
    sha1_hub_order       BINARY    NOT NULL
,   ldts                TIMESTAMP NOT NULL
,   o_orderstatus       STRING
,   o_totalprice        NUMBER
,   o_orderdate         DATE
,   o_orderpriority    STRING
,   o_clerk             STRING
,   o_shippriority     NUMBER
,   o_comment           STRING
,   hash_diff           BINARY    NOT NULL
,   rscr                STRING    NOT NULL
,   CONSTRAINT pk_sat_order PRIMARY KEY(sha1_hub_order, ldts)
,   CONSTRAINT fk_sat_order FOREIGN KEY(sha1_hub_order) REFERENCES hub_order
);

-- links

CREATE OR REPLACE TABLE lnk_customer_order
(
    sha1_lnk_customer_order BINARY    NOT NULL
,   sha1_hub_customer      BINARY
,   sha1_hub_order         BINARY
,   ldts                  TIMESTAMP NOT NULL
,   rscr                  STRING    NOT NULL
,   CONSTRAINT pk_lnk_customer_order PRIMARY KEY(sha1_lnk_customer_order)
,   CONSTRAINT fk1_lnk_customer_order FOREIGN KEY(sha1_hub_customer) REFERENCES
hub_customer
,   CONSTRAINT fk2_lnk_customer_order FOREIGN KEY(sha1_hub_order) REFERENCES

```

```

hub_order
);

-- ref data

CREATE OR REPLACE TABLE ref_region
(
    regioncode          NUMBER
,   ldts                TIMESTAMP
,   rscr                STRING NOT NULL
,   r_name              STRING
,   r_comment           STRING
,   CONSTRAINT PK_REF_REGION PRIMARY KEY (REGIONCODE)
)
AS
SELECT r_regionkey
      , ldts
      , rscr
      , r_name
      , r_comment
FROM 100_stg.stg_region;

CREATE OR REPLACE TABLE ref_nation
(
    nationcode          NUMBER
,   regioncode          NUMBER
,   ldts                TIMESTAMP
,   rscr                STRING NOT NULL
,   n_name              STRING
,   n_comment           STRING
,   CONSTRAINT pk_ref_nation PRIMARY KEY (nationcode)
,   CONSTRAINT fk_ref_region FOREIGN KEY (regioncode) REFERENCES ref_region(regioncode)
)
AS
SELECT n_nationkey
      , n_regionkey
      , ldts
      , rscr
      , n_name
      , n_comment
FROM 100_stg.stg_nation;

```

- Now we have source data waiting in our staging streams & views, we have target RDV tables. Let's connect the dots. We are going to create tasks, one per each stream so whenever there is new records coming in a stream, that delta will be incrementally propagated to all dependent RDV models in one go. To achieve that, we are going to use multi-table insert functionality as described in design section before. As you can see, tasks can be set up to run on a pre-defined frequency (every 1 minute in our example) and use dedicated virtual warehouse as a compute power (in our guide we are going to use same warehouse for all tasks, though this could be as granular as needed). Also, before waking up a compute resource, tasks are going to check that there is data in a corresponding stream to process. Again, you are paying only for the compute when you actually use it.



```

CREATE OR REPLACE TASK customer_strm_tsk
  WAREHOUSE = dv_rdv_wh
  SCHEDULE = '1 minute'
WHEN
  SYSTEM$STREAM_HAS_DATA('L00_STG.STG_CUSTOMER_STRM')
AS
INSERT ALL
  WHEN (SELECT COUNT(1) FROM hub_customer tgt WHERE tgt.shal_hub_customer =
src_shal_hub_customer) = 0
  THEN INTO hub_customer
    ( shal_hub_customer
    , c_custkey
    , ldts
    , rscr
    )
VALUES
  ( src_shal_hub_customer
  , src_c_custkey
  , src_ldts
  , src_rscr
  )
  WHEN (SELECT COUNT(1) FROM sat_customer tgt WHERE tgt.shal_hub_customer =
src_shal_hub_customer AND tgt.hash_diff = src_customer_hash_diff) = 0
  THEN INTO sat_customer
    (
      shal_hub_customer
    , ldts
    , c_name
    , c_address
    , c_phone
    , c_acctbal
    , c_mktsegment
    , c_comment
    , nationcode
    , hash_diff
    , rscr
    )
VALUES
  (
    src_shal_hub_customer
  , src_ldts
  , src_c_name
  , src_c_address
  , src_c_phone
  , src_c_acctbal
  , src_c_mktsegment
  , src_c_comment
  , src_nationcode
  , src_customer_hash_diff
  , src_rscr
  )
SELECT shal_hub_customer    src_shal_hub_customer

```

```

    , c_custkey          src_c_custkey
    , c_name             src_c_name
    , c_address          src_c_address
    , c_nationcode       src_nationcode
    , c_phone            src_c_phone
    , c_acctbal          src_c_acctbal
    , c_mktsegment       src_c_mktsegment
    , c_comment          src_c_comment
    , customer_hash_diff src_customer_hash_diff
    , ldts               src_ldts
    , rscr               src_rscr
FROM 100_stg.stg_customer_strm_outbound src
;

CREATE OR REPLACE TASK order_strm_tsk
  WAREHOUSE = dv_rdv_wh
  SCHEDULE = '1 minute'
WHEN
  SYSTEM$STREAM_HAS_DATA('L00_STG.STG_ORDERS_STRM')
AS
INSERT ALL
WHEN (SELECT COUNT(1) FROM hub_order tgt WHERE tgt.shal_hub_order =
src_shal_hub_order) = 0
THEN INTO hub_order
( shal_hub_order
, o_orderkey
, ldts
, rscr
)
VALUES
( src_shal_hub_order
, src_o_orderkey
, src_ldts
, src_rscr
)
WHEN (SELECT COUNT(1) FROM sat_order tgt WHERE tgt.shal_hub_order = src_shal_hub_order
AND tgt.hash_diff = src_order_hash_diff) = 0
THEN INTO sat_order
(
  shal_hub_order
, ldts
, o_orderstatus
, o_totalprice
, o_orderdate
, o_orderpriority
, o_clerk
, o_shippriority
, o_comment
, hash_diff
, rscr
)

```

**VALUES**

```
(
    src_shal_hub_order
, src_ldts
, src_o_orderstatus
, src_o_totalprice
, src_o_orderdate
, src_o_orderpriority
, src_o_clerk
, src_o_shippriority
, src_o_comment
, src_order_hash_diff
, src_rscr
)
```

```
WHEN (SELECT COUNT(1) FROM lnk_customer_order tgt WHERE tgt.shal_lnk_customer_order =
src_shal_lnk_customer_order) = 0
```

```
THEN INTO lnk_customer_order
```

```
(
    shal_lnk_customer_order
, shal_hub_customer
, shal_hub_order
, ldts
, rscr
)
```

**VALUES**

```
(
    src_shal_lnk_customer_order
, src_shal_hub_customer
, src_shal_hub_order
, src_ldts
, src_rscr
)
```

```
SELECT shal_hub_order          src_shal_hub_order
      , shal_lnk_customer_order src_shal_lnk_customer_order
      , shal_hub_customer       src_shal_hub_customer
      , o_orderkey              src_o_orderkey
      , o_orderstatus           src_o_orderstatus
      , o_totalprice            src_o_totalprice
      , o_orderdate             src_o_orderdate
      , o_orderpriority         src_o_orderpriority
      , o_clerk                 src_o_clerk
      , o_shippriority          src_o_shippriority
      , o_comment               src_o_comment
      , order_hash_diff         src_order_hash_diff
      , ldts                    src_ldts
      , rscr                    src_rscr
FROM 100_stg.stg_order_strm_outbound src;
```

```
ALTER TASK customer_strm_tsk RESUME;
```

```
ALTER TASK order_strm_tsk    RESUME;
```

- Once tasks are created and RESUMED (by default, they are initially suspended) let's have a look on the task execution history to see how the process will start.

```
SELECT *  
FROM table(information_schema.task_history())  
ORDER BY scheduled_time DESC;
```

Notice how after successful execution, next two tasks run were automatically SKIPPED as there were nothing in the stream and there nothing to do.

1	SELECT *
2	FROM table(information_schema.task_history())
3	ORDER BY scheduled_time DESC;
4	
5	
6	
7	
8	
9	

		CONDITION_TEXT	STATE	ERROR_CODE	ERROR_MESSAGE
1	ha1_hub_c	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_ORDERS_STRM')	SCHEDULED		
2	gt.sha1_h	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_CUSTOMER_STRM')	SCHEDULED		
3	ha1_hub_c	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_ORDERS_STRM')	SKIPPED	0040003	Conditional expression for task evaluated to false.
4	gt.sha1_h	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_CUSTOMER_STRM')	SKIPPED	0040003	Conditional expression for task evaluated to false.
5	ha1_hub_c	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_ORDERS_STRM')	SUCCEEDED		
6	gt.sha1_h	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_CUSTOMER_STRM')	SUCCEEDED		
7	ha1_hub_c	SYSTEM\$\$STREAM_HAS_DATA('L00_STG.STG_ORDERS_STRM')	FAILED	002003	SQL compilation error: Object 'LNK_CUSTOMER_ORDER' does not exist or no

- We can also check content and stats of the objects involved. Please notice that views on streams in our staging area are no longer returning any rows. This is because that delta of changes was consumed by a successfully completed DML transaction (in our case, embedded in tasks). This way you don't need to spend any time implementing incremental detection/processing logic on the application side.

```
SELECT 'hub_customer', count(1) FROM hub_customer  
UNION ALL  
SELECT 'hub_order', count(1) FROM hub_order  
UNION ALL  
SELECT 'sat_customer', count(1) FROM sat_customer  
UNION ALL  
SELECT 'sat_order', count(1) FROM sat_order  
UNION ALL  
SELECT 'lnk_customer_order', count(1) FROM lnk_customer_order  
UNION ALL  
SELECT '100_stg.stg_customer_strm_outbound', count(1) FROM  
100_stg.stg_customer_strm_outbound  
UNION ALL  
SELECT '100_stg.stg_order_strm_outbound', count(1) FROM  
100_stg.stg_order_strm_outbound;
```

DV.LAB.L10.RDV

```

1 SELECT 'hub_customer', count(1) FROM hub_customer
2 UNION ALL
3 SELECT 'hub_order', count(1) FROM hub_order
4 UNION ALL
5 SELECT 'sat_customer', count(1) FROM sat_customer
6 UNION ALL
7 SELECT 'sat_order', count(1) FROM sat_order
8 UNION ALL
9 SELECT 'lnk_customer_order', count(1) FROM lnk_customer_order
10 UNION ALL
11 SELECT 'l00_stg.stg_customer_strm_outbound', count(1) FROM l00_stg.stg_customer_strm_outbound
12 UNION ALL
13 SELECT 'l00_stg.stg_order_strm_outbound', count(1) FROM l00_stg.stg_order_strm_outbound;
14

```

Objects

Query

Results

Chart

	'HUB_CUSTOMER'	COUNT(1)
1	hub_customer	10
2	hub_order	1,000
3	sat_customer	10
4	sat_order	1,000
5	lnk_customer_order	1,000
6	l00_stg.stg_customer_strm_outbound	0
7	l00_stg.stg_order_strm_outbound	0

Query Details

Query duration

1.7s

Rows

7

'HUB\_CUSTOMER'

100% filled

COUNT(1)

123

Great. We now have data in our **Raw Data Vault** core structures. Let's move on and talk about the concept of virtualization for building your near-real time Data Vault solution.


## Views for Agile Reporting

One of the great benefits of having the compute power from Snowflake is that now it is totally possible to have most of your business vault and information marts in a Data Vault architecture be built exclusively from views. There are numerous customers using this approach in production today. There is no longer a need to have the argument that there are “too many joins” or that the response won’t be fast enough. The elasticity of the Snowflake virtual warehouses combined with our dynamic optimization engine have solved that problem.

If you really want to deliver data to the business users and data scientists in NRT, in our opinion using views is the only option. Once you have the streaming loads built to feed your Data Vault, the fastest way to make that data visible downstream will be views. Using views allows you to deliver the data faster by eliminating any latency that would be incurred by having additional ELT processes between the Data Vault and the data consumers downstream.

All the business logic, alignment, and formatting of the data can be in the view code. That means fewer moving parts to debug, and reduces the storage needed as well.

# DATA VAULT VIRTUALIZATION



Looking at the diagram above you will see an example of how virtualization could fit in the architecture. Here, solid lines are representing physical tables and dotted lines - views. You incrementally ingest data into **Raw Data Vault** and all downstream transformations are applied as views. From a data consumer perspective when working with a virtualized information mart, the query always shows everything known by your data vault, right up to the point the query was submitted.

With Snowflake you have the ability to provide as much compute as required, on-demand, without a risk of causing performance impact on any surrounding processes and pay only for what you use. This makes materialization of transformations in layers like **Business Data Vault** and **Information delivery** an option rather than a must-have. Instead of “optimizing upfront” you can now make this decision based on the usage pattern characteristics, such as frequency of use, type of queries, latency requirements, readiness of the requirements etc.

Many modern data engineering automation frameworks are already actively supporting virtualization of logic. Several tools offer a low-code or configuration-like ability to switch between materializing an object as a view or a physical table, automatically generating all required DDL & DML. This could be applied on specific objects, layers or/and be environment specific. So even if you start with a view, you can easily refactor to use a table if user requirements evolve.

As said before, virtualization is not only a way to improve time-to-value and provide near real time access to the data, given the scalability and workload isolation of Snowflake, virtualization also is a design technique that could make your Data Vault excel: minimizing cost-of-change, accelerating the time-to-delivery and becoming an extremely agile, future proof solution for ever growing business needs.

## Build: Business Data Vault

As a quick example of using views for transformations we just discussed, here is how enrichment of customer descriptive data could happen in Business Data Vault, connecting data received from source with some reference data.

1. Let's create a view that will perform these additional derivations on the fly. Assuming non-functional capabilities are satisfying our requirements, deploying (and re-deploying a new version) transformations in this way is super easy.

```

USE SCHEMA l20_bdv;

CREATE OR REPLACE VIEW sat_customer_bv
AS
SELECT rsc.shal_hub_customer
      , rsc.ldts
      , rsc.c_name
      , rsc.c_address
      , rsc.c_phone
      , rsc.c_acctbal
      , rsc.c_mktsegment
      , rsc.c_comment
      , rsc.nationcode
      , rsc.rscr
      -- derived
      , rrn.n_name          nation_name
      , rrr.r_name          region_name
FROM l10_rdv.sat_customer      rsc
LEFT OUTER JOIN l10_rdv.ref_nation rrn
  ON (rsc.nationcode = rrn.nationcode)
LEFT OUTER JOIN l10_rdv.ref_region rrr
  ON (rrn.regioncode = rrr.regioncode)
;

```

- Now, let's imagine we have a heavier transformation to perform that it would make more sense to materialize it as a table. It could be more data volume, could be more complex logic, PITs, bridges or even an object that will be used frequently and by many users. For this case, let's first build a new business satellite that for illustration purposes will be deriving additional classification/tiering for orders based on the conditional logic.

```

CREATE OR REPLACE TABLE sat_order_bv
(
  sha1_hub_order      BINARY      NOT NULL
, ldts                TIMESTAMP NOT NULL
, o_orderstatus       STRING
, o_totalprice         NUMBER
, o_orderdate          DATE
, o_orderpriority     STRING
, o_clerk              STRING
, o_shippriority       NUMBER
, o_comment            STRING
, hash_diff            BINARY      NOT NULL
, rscr                 STRING      NOT NULL
-- additional attributes
, order_priority_bucket STRING
, CONSTRAINT pk_sat_order PRIMARY KEY(sha1_hub_order, ldts)
, CONSTRAINT fk_sat_order FOREIGN KEY(sha1_hub_order) REFERENCES l10_rdv.hub_order
)
AS
SELECT sha1_hub_order
      , ldts
      , o_orderstatus

```

```

    , o_totalprice
    , o_orderdate
    , o_orderpriority
    , o_clerk
    , o_shippriority
    , o_comment
    , hash_diff
    , rscr
    -- derived additional attributes
    , CASE WHEN o_orderpriority IN ('2-HIGH', '1-URGENT') AND
o_totalprice >= 200000 THEN 'Tier-1'
        WHEN o_orderpriority IN ('3-MEDIUM', '2-HIGH', '1-URGENT') AND
o_totalprice BETWEEN 150000 AND 200000 THEN 'Tier-2'
        ELSE 'Tier-3'
    END order_priority_bucket
FROM l10_rdv.sat_order;

```

3. What we are going to do from processing/orchestration perspective is extending our order processing pipeline so that when the task populates a **l10\_rdv.sat\_order** this will generate a new stream of changes and these changes are going to be propagated by a dependent task to **l20\_bdv.sat\_order\_bv**. This is super easy to do as tasks in Snowflake can be not only schedule-based but also start automatically once the parent task is completed.

```

CREATE OR REPLACE STREAM l10_rdv.sat_order_strm ON TABLE l10_rdv.sat_order;

ALTER TASK l10_rdv.order_strm_tsk SUSPEND;

CREATE OR REPLACE TASK l10_rdv.hub_order_strm_sat_order_bv_tsk
    WAREHOUSE = dv_rdv_wh
    AFTER l10_rdv.order_strm_tsk
AS
INSERT INTO l20_bdv.sat_order_bv
SELECT
    sha1_hub_order
    , ldts
    , o_orderstatus
    , o_totalprice
    , o_orderdate
    , o_orderpriority
    , o_clerk
    , o_shippriority
    , o_comment
    , hash_diff
    , rscr
    -- derived additional attributes
    , CASE WHEN o_orderpriority IN ('2-HIGH', '1-URGENT') AND o_totalprice >=
200000 THEN 'Tier-1'
        WHEN o_orderpriority IN ('3-MEDIUM', '2-HIGH', '1-URGENT') AND o_totalprice
BETWEEN 150000 AND 200000 THEN 'Tier-2'
        ELSE 'Tier-3'
    END order_priority_bucket
FROM sat_order_strm;

```



```
ALTER TASK l10_rdv.hub_order_strm_sat_order_bv_tsk RESUME;
ALTER TASK l10_rdv.order_strm_tsk RESUME;
```

4. Now, let's go back to our staging area to process another slice of data to test the task.

```
USE SCHEMA 100_stg;

COPY INTO @orders_data
FROM
(SELECT *
 FROM snowflake_sample_data.tpch_sf10.orders limit 1000
)
INCLUDE_QUERY_ID=TRUE;

ALTER PIPE stg_orders pp REFRESH;
```

5. Data is not automatically flowing through all the layers via asynchronous tasks. With the results you can validate:

```
SELECT '100_stg.stg_orders', count(1) FROM 100_stg.stg_orders
UNION ALL
SELECT '100_stg.stg_orders_strm', count(1) FROM 100_stg.stg_orders_strm
UNION ALL
SELECT '110_rdv.sat_order', count(1) FROM 110_rdv.sat_order
UNION ALL
SELECT '110_rdv.sat_order_strm', count(1) FROM 110_rdv.sat_order_strm
UNION ALL
SELECT '120_bdv.sat_order_bv', count(1) FROM 120_bdv.sat_order_bv;
```

```

1  USE SCHEMA l00_stg;
2
3  COPY INTO @orders_data
4  FROM
5  (SELECT *
6   FROM snowflake_sample_data.tpch_sf10.orders limit 1000
7  )
8  INCLUDE_QUERY_ID=TRUE;
9
10 ALTER PIPE stg_orders_pp REFRESH;
11
12 SELECT 'l00_stg.stg_orders', count(1) FROM l00_stg.stg_orders
13 UNION ALL
14 SELECT 'l00_stg.stg_orders_strm', count(1) FROM l00_stg.stg_orders_strm
15 UNION ALL
16 SELECT 'l10_rdv.sat_order', count(1) FROM l10_rdv.sat_order
17 UNION ALL
18 SELECT 'l10_rdv.sat_order_strm', count(1) FROM l10_rdv.sat_order_strm
19 UNION ALL
20 SELECT 'l20_bdv.sat_order_bv', count(1) FROM l20_bdv.sat_order_bv;

```

Great. Hope this example illustrated few ways of managing **Business Data Vault** objects in our pipeline. Let's finally move into the **Information Delivery** layer.

## Build: Information Delivery

When it comes to Information Delivery area we are not changing the meaning of data, but we may change format to simplify users to access and work with the data products/output interfaces. Different consumers may have different needs and preferences, some would prefer star/snowflake dimensional schemas, some would adhere to use flattened objects or even transform data into JSON/parquet objects.

1. First things we would like to add to simplify working with satellites is creating views that shows latest version for each key.

```
-----  
-- RDV curr views  
-----  
  
USE SCHEMA l10_rdv;  
  
CREATE VIEW sat_customer_curr_vw  
AS  
SELECT *  
FROM sat_customer  
QUALIFY LEAD(ldts) OVER (PARTITION BY sha1_hub_customer ORDER BY ldts) IS NULL;  
  
CREATE OR REPLACE VIEW sat_order_curr_vw  
AS  
SELECT *  
FROM sat_order  
QUALIFY LEAD(ldts) OVER (PARTITION BY sha1_hub_order ORDER BY ldts) IS NULL;  
  
-----  
-- BDV curr views  
-----  
  
USE SCHEMA l20_bdv;  
  
CREATE VIEW sat_order_bv_curr_vw  
AS  
SELECT *  
FROM sat_order_bv  
QUALIFY LEAD(ldts) OVER (PARTITION BY sha1_hub_order ORDER BY ldts) IS NULL;  
  
CREATE VIEW sat_customer_bv_curr_vw  
AS  
SELECT *  
FROM sat_customer_bv  
QUALIFY LEAD(ldts) OVER (PARTITION BY sha1_hub_customer ORDER BY ldts) IS NULL;
```

2. Let's create a simple dimensional structure. Again, we will keep it virtual(as views) to start with, but you already know that depending on access characteristics required any of these could be selectively materialized.

```
USE SCHEMA l30_id;  
  
-- DIM TYPE 1
```

```

CREATE OR REPLACE VIEW dim1_customer
AS
SELECT hub.shal_hub_customer          AS dim_customer_key
      , sat.ldts                      AS effective_dts
      , hub.c_custkey                 AS customer_id
      , sat.rscr                      AS record_source
      , sat.*
FROM   l10_rdv.hub_customer          hub
      , l20_bdv.sat_customer_bv_curr_vw sat
WHERE  hub.shal_hub_customer
      = sat.shal_hub_customer;

-- DIM TYPE 1
CREATE OR REPLACE VIEW dim1_order
AS
SELECT hub.shal_hub_order            AS dim_order_key
      , sat.ldts                      AS effective_dts
      , hub.o_orderkey                AS order_id
      , sat.rscr                      AS record_source
      , sat.*
FROM   l10_rdv.hub_order             hub
      , l20_bdv.sat_order_bv_curr_vw sat
WHERE  hub.shal_hub_order
      = sat.shal_hub_order;

-- FACT table

CREATE OR REPLACE VIEW fct_customer_order
AS
SELECT lnk.ldts                      AS effective_dts
      , lnk.rscr                      AS record_source
      , lnk.shal_hub_customer         AS dim_customer_key
      , lnk.shal_hub_order            AS dim_order_key
-- this is a factless fact, but here you can add any measures, calculated or derived
FROM   l10_rdv.lnk_customer_order    lnk;

```

3. All good so far? Now lets try to query **fct\_customer\_order** and at least in my case this view was not returning any rows. Why? If you remember, when we were unloading sample data, we took a subset of random orders and a subset of random customers. Which in my case didn't have any overlap, therefore doing the inner join with dim1\_order was resulting in all rows being eliminated from the resultset. Thankfully we are using Data Vault and all need to do is go and load full customer dataset. Just think about it, there is no need to reprocess any links or fact tables simply because customer/reference feed was incomplete. I am sure for those of you who were using different architectures for data engineering and warehousing have painful experience when such situations occur. So, lets go and fix it:

```

USE SCHEMA l00_stg;

COPY INTO @customer_data
FROM
(SELECT object_construct(*)
 FROM snowflake_sample_data.tpch_sf10.customer
  -- removed LIMIT 10
)
INCLUDE_QUERY_ID=TRUE;

```

```
ALTER PIPE stg_customer_pp REFRESH;
```

All you need to do now is just wait a few seconds whilst our continuous data pipeline will automatically propagate new customer data into Raw Data Vault. Quick check for the records count in customer dimension now shows that there are 1.5Mn records:


```
USE SCHEMA l30_id;
```

```
SELECT COUNT(1) FROM dim1_customer;
```

```
COUNT(1)
-----
1,500,000
```

4. Finally lets wear user's hat and run a query to break down orders by nation,region and order\_priority\_bucket (all attributes we derived in **Business Data Vault**). As we are using Snowsight, why not quickly creating a chart from this result set to better understand the data. For this simply click on the 'Chart' section on the bottom pane and put attributes/measures as it is shown on the screenshot below.

```
SELECT dc.nation_name
      , dc.region_name
      , do.order_priority_bucket
      , COUNT(1)                                cnt_orders
FROM   fct_customer_order                      fct
      , dim1_customer                          dc
      , dim1_order                            do
WHERE  fct.dim_customer_key                    = dc.dim_customer_key
      AND fct.dim_order_key                    = do.dim_order_key
GROUP BY 1,2,3;
```



Voila! This concludes our journey for this guide. Hope you enjoyed it and lets summarise key points in the next section.

## Conclusion

Simplicity of engineering, openness, scalable performance, enterprise-grade governance enabled by the core of the Snowflake platform are now allowing teams to focus on what matters most for the business and build truly agile, collaborative data environments. Teams can now connect data from all parts of the landscape, until there are no stones left unturned. They are even tapping into new datasets via live access to the Snowflake Data Marketplace. The Snowflake Data Cloud combined with a Data Vault 2.0 approach is allowing teams to democratize access to all their data assets at any scale. We can now easily derive more and more value through insights and intelligence, day after day, bringing businesses to the next level of being truly data-driven.

Delivering more usable data faster is no longer an option for today's business environment. Using the Snowflake platform, combined with the Data Vault 2.0 architecture it is now possible to build a world class analytics platform that delivers data for all users in near real-time.


## What we've covered

- unloading and loading back data using COPY and Snowpipe
- engineering data pipelines using virtualization, streams and tasks
- building multi-layer Data Vault environment on Snowflake:


## Staging



## RAW Data Vault



## Business Data Vault



## Information Delivery



## Call to action

- seeing is believing. Try it!
- we made examples limited in size, but feel free to scale the data volumes and virtual warehouse size to see scalability in action
- tap into numerous communities of practice for Data Engineering on Snowflake and Data Vault in particular
- talk to us about modernizing your data landscape! Whether it is Data Vault or not you have on your mind, we have the top expertise and product to meet your demand
- feedback is super welcome!
- Enjoy your journey!