Lab: Practice Basic Package Management Commands to Add, Update, and Remove Dependencies

Lab Overview

In this lab, you will practice adding, updating, and removing dependencies using package management tools in both Node.js (npm) and Python (pip).

Prerequisites

- 1. Node.js installed
 - Verify with node -v and npm -v
- 2. Python 3.8 installed
 - \circ Verify with python3 --version or python --version
- 3. A text editor or IDE (e.g., VS Code)
- 4. Command-line/terminal access

Part 1: Node.js Package Management with npm

Step 1: Initialize a Node.js Project

1. Open your terminal and create a new directory:

```
cd ~/Desktop
mkdir node-package-lab
cd node-package-lab
```

2. Initialize a new Node.js project:

```
npm init -y
```

- This creates a package.json file.
- 3. Print "Hello World":

```
echo "console.log('Hello World');" > index.js
node index.js
```

Step 2: Add Dependencies

1. Add a dependency (e.g., lodash):

```
npm install lodash
```

```
root@f4928a6101cf:~/Desktop/node-package-lab# echo "console.log('Hello World');" > index.js
root@f4928a6101cf:~/Desktop/node-package-lab# node index.js
Hello World
root@f4928a6101cf:~/Desktop/node-package-lab#
root@f4928a6101cf:~/Desktop/node-package-lab#
root@f4928a6101cf:~/Desktop/node-package-lab# npm install lodash
added 1 package, and audited 2 packages in 1s
found 0 vulnerabilities
```

- 2 Verify that lodash was added to your package.json under dependencies.
- 3. Check the node modules folder to confirm installation.

Step 3: Use and Run Installed Package

1. Modify index.js to use lodash:

```
const _ = require('lodash');
console.log(_.toUpper('hello world'));
```

Run the foolllowing command from the terminal:

```
node index.js
```

root@f4928a6101cf:~/Desktop/node-package-lab# node index.js HELLO WORLD

• This code uses lodash to to Upper the string "hello world".

Step 4: Update Dependencies

1. Update the lodash package to the latest version:

```
npm update lodash
```

2 Verify the updated version in package.json and package-lock.json.

Step 5: Remove Dependencies

1. Remove the lodash package:

```
npm uninstall lodash
```

2. Verify that lodash has been removed from package.json and the node modules folder.

Part 2: Python Package Management with pip

Step 1: Set Up a Python Virtual Environment

1. Create a new directory:

```
cd ~/Desktop
mkdir python-package-lab
```

```
cd python-package-lab
```

2. Create a virtual environment:

```
python3 -m venv venv
```

3. Activate the virtual environment in Linux:

```
source venv/bin/activate
```

4. Print "Hello World":

```
echo "print('Hello World')" > hello.py
python hello.py
```

```
root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab# python3 -m venv venv
root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab# source venv/bin/activate
(venv) root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab#
(venv) root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab#
(venv) root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab# echo "print('Hello World')" > hello.py
(venv) root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab# python hello.py
Hello World
```

Step 2: Add Dependencies

1. Install a package (e.g., requests):

```
pip install requests
```

2. Verify installation:

```
pip list
```

```
(venv) root@f4928a6101cf:~/Desktop/my-webpack-project/dist/python-package-lab# pip listPackageVersioncertifi2024.12.14charset-normalizer3.4.1idna3.10pip20.0.2pkg-resources0.0.0requests2.32.3setuptools44.0.0urllib32.2.3
```

3. Freeze dependencies to a requirements.txt file:

```
pip freeze > requirements.txt
```

Step 3: Use and Run Installed Package

1. Create a script.py file to use requests:

```
import requests

# Sending a GET request to the API endpoint
response = requests.get('https://jsonplaceholder.typicode.com/posts/1')
```

```
# Checking if the request was successful
if response.status_code == 200:
    # Printing the JSON response as a dictionary
    print(response.json())
else:
    # Printing an error message if the request failed
    print(f"Request failed with status code: {response.status_code}")
```

2. Run the script with following command:

```
python script.py
```

• This code fetches and prints a sample JSON response from a placeholder API.

```
(venv) roatgf4928a6101cf:=/Desktop/my-webpack-project/dist/python-package-lab# python script.py 
('userId': 1, 'id': 1, 'title': 'sunt aur facer repellat provident occaecati excepturi optio reprehenderit', 'body': 'quia et suscipit\nsuscipit recusandae consequuntur expedita et 
rehenderit nolestiae ut ut quas totam\nostrum rerum est autem sunt rem eveniet architecto'} 
(venv) roatgf4928a6101cf:-/posktop/my-webpack-project/dist/python-package-lab#
```

Step 4: Update Dependencies

1. Upgrade the requests package:

```
pip install --upgrade requests
```

2. Verify the updated version:

```
pip list
```

Step 5: Remove Dependencies

1. Uninstall the requests package:

```
pip uninstall requests
```

2. Verify removal:

```
pip list
```

Step 6: Deactivate Virtual Environment

1. Deactivate the virtual environment:

```
deactivate
```

Summary

In this lab, you learned how to:

- 1. Add, update, and remove dependencies using npm for Node.js.
- 2. Add, update, and remove dependencies using pip for Python in a virtual environment.
- 3. Run code using installed packages in both Node.js and Python.