

Migrate from Tabadmin to the TSM CLI

The Tableau Services Manager (TSM) command-line interface (CLI) replaces the tabadmin CLI in Tableau Server on Linux, and in Tableau Server on Windows version 2018.2. This page maps tabadmin commands to TSM commands to help you to migrate to the TSM CLI.

To learn more about the TSM CLI, see [tsm Command Line Reference](#).

Note: TSM is a batch file. To run tsm commands in another batch file, use the `call` command. For example "`call tsm maintenance ziplogs`". Doing this will return control to the batch file. You also need to authenticate to TSM before issuing any commands. For more information, see [Authenticating with tsm CLI](#).

To learn more about the differences between tabadmin and TSM, see [Comparing Functionality of tabadmin and TSM](#).

Looking for tabadmin commands for [Tableau Server] on Windows version 2018.1 and earlier? See [tabadmin Commands](#)[\(Link opens in a new window\)](#).

Tabadmin commands with a corresponding TSM CLI command

The following table shows which tabadmin commands correspond to commands available in the TSM CLI.

Comparable TSM CLI	Description	Command	Tabadmin Command(s)
Activate a	tabadmin activate --license license dmin activate --activate	tabadmin activate --license license dmin activate --activate	tabadmin activate --license license dmin activate --activate
Deactivate	tabadmin deactivate --license licenses	tabadmin deactivate --license licenses	tabadmin deactivate --license licenses
Create a	tabadmin backup tsm maintenance backup	tabadmin backup tsm maintenance backup	tabadmin backup tsm maintenance backup
Clear the	tabadmin clearcache ts server m	tabadmin clearcache ts server m	tabadmin clearcache ts server m
Clean up	tabadmin cleanup temporary tsm maintenance cleanup \ files and old log	tabadmin cleanup temporary tsm maintenance cleanup \ files and old log	tabadmin cleanup temporary tsm maintenance cleanup \ files and old log
Update the	tabadmin	tabadmin	tabadmin
Customize	tabadmin customize tsm customize the server name and logos	tabadmin customize tsm customize the server name and logos	tabadmin customize tsm customize the server name and logos
Enable	tabadmin dbpass tsm data-access access to	tabadmin dbpass tsm data-access access to	tabadmin dbpass tsm data-access access to
Disable	tabadmin dbpass --disable epository-access	tabadmin dbpass --disable epository-access	tabadmin dbpass --disable epository-access
Set a file	tabadmin decommission tsm topolog store y filestore decommission instance to	tabadmin decommission tsm topolog store y filestore decommission instance to	tabadmin decommission tsm topolog store y filestore decommission instance to
Delete one	tabadmin tsm data-access we or more Web delete_webdataconnector b-data-connectors delete	tabadmin tsm data-access we or more Web delete_webdataconnector b-data-connectors delete	tabadmin tsm data-access we or more Web delete_webdataconnector b-data-connectors delete
Add a Web	tabadmin tsm data-	tabadmin tsm data-	tabadmin tsm data-
Import a Web	tabadmin tsm data-	tabadmin tsm data-	tabadmin tsm data-

add | | | itelist_webdataconnector | WDCs to an allowlist. To | | | learn more, see [Web Data | | | Connectors in Tableau | | | Server | | |](<https://help.tableau.co> | | | m/current/server/en-us/da | | | tasource_wdc.htm){.MCXref | | | .xref}. | +-----+-----+-----+ | List Web | tabadmin | tsm data-access | Data | n list_webdataconnectors | web-data-connectors list | | Connectors | | | (WDCs) used | | To learn more, see [Web | | by Tableau | | Data Connectors in | | Server | | Tableau | | | Server | | |](<https://help.tableau.co> | | | m/current/server/en-us/da | | | tasource_wdc.htm){.MCXref | | | .xref}. | +-----+-----+-----+ | Export a | tabadmin exportsite | tsm sites export | | site from | | | Tableau | | | Server | | | +-----+-----+-----+ | Initiate a | tab | tsm topo | repository | admin failoverrepository | logy failover-repository | failover | | | +-----+-----+-----+ | Get a | tabadmin get | tsm configuration get | co | | | nfiguration | | | option | | | +-----+-----+-----+ | Get the | tabadmin | tsm authentication | | OpenID | get_openid_redirect_url | openid get-redirect-url | | redirect | | | URL | | | +-----+-----+-----+ | Import site | tabadmin importsite | tsm sites import | | .csv files | | | into | | | Tableau | | | Server | | | +-----+-----+-----+ | Import a | taba | t | site into | dmin importsite_verified | sm sites import-verified | | Tableau | | | Server | | | using .csv | | | files | | | +-----+-----+-----+ | Display | tabadmin licenses | tsm licenses list | | license | | | information | | **Note:** For more | | for Tableau | | information about the | | Server | | output of this command, | | | see [View Server | | | License | | | s](<https://help.tableau.c> | | | om/current/server/en-us/v | | | iew_licenses.htm){.MCXref | | | .xref}. | +-----+-----+-----+ | Move a file | tabadmin recommission | tsm topolog | | store from | | y filestore recommission | | read-only | | | mode to an | | | active | | | read/write | | | state | | | +-----+-----+-----+ | Regenerate | tabadmin re | tsm security re | | internal | generate_internal_tokens | generate-internal-tokens | | security | | | tokens | | | +-----+-----+-----+ | Register | tabadmin register | tsm register | | Tableau | | | Server | | | +-----+-----+-----+ | Rebuild the | tabadmin reindex | tsm ma | | search | | | intenance reindex-search | | index for | | | Tableau | | | Server | | | +-----+-----+-----+ | Reset the | tabadmin reset | tsm reset | | Tableau | | | Server | | | ad | | | ministrator | | | account | | | +-----+-----+-----+ | Stop and | tabadmin restart | tsm restart | | restart all | | | Tableau | | | Server | | | processes | | | +-----+-----+-----+ | Restore | tabadmin restore | tsm maintenance restore | | from a | | | Tableau | | The restore command does | | Server | | not restore any server | | backup file | | configuration data. This | | | is true whether you are | | | using a backup created | | | with TSM or a backup | | | created with tabadmin. | +-----+-----+-----+ | Set a | tabadmin set | tsm configuration set | co | | | nfiguration | | | option | | | +-----+-----+-----+ | Activate or | tabadmin sitestate | tsm sites unlock | | suspend a | | | site | | | +-----+-----+-----+ | Start all | tabadmin start | tsm start | | Tableau | | | Server | | | processes | | | +-----+-----+-----+ | Get the | tabadmin status | tsm status | | status of | | | Tableau | | | Server and | | | server | | | processes | | | +-----+-----+-----+ | Stop all | tabadmin stop | tsm stop | | Tableau | | | Server | | | processes | | | +-----+-----+-----+ | Create an | tabadmin ziplogs | tsm maintenance ziplogs | | archive | | | (.zip) file | | The default behavior of | | with | | the ziplogs command has | | Tableau | | changed: with tsm, the | | Server log | | command collects up to | | files | | the last two days of log | | | files by default. The | | | tabadmin ziplogs command | | | collected up to seven | | | days of log files. For | | | more information, see | | | [tsm maintenance | | | ziplogs](<https://help.ta> | | | bleau.com/current/server/ | | | en-us/cli_maintenance_tsm | | | .htm#tsm4ziplogs){.MCXref | | | .xref}. | +-----+-----+-----+ |