tsm email

Use the `tsm email` command to view and test your SMTP configuration.

For more information about configuring SMTP, see [Configure SMTP Setup](#).

tsm email test-smtp-connection

Run this command to test the STMP connection. When run, TSM will attempt to establish a connection with the SMTP server that you have configured for Tableau Server. TSM will also return a connection status and the details of the SMTP configuration.

In some cases, the command will return a false-positive status. For example, if your Postfix SMTP server is set to require TLS, but Tableau Server is not configured for TLS, the connection is established and TSM will report a succesful connection. However, in this scenario, Postfix actually rejects the email message after TSM has connected.

Synopsis

```
tsm email test-smtp-connection [global options]
```

Global options

-h, --help

Optional.

Show the command help.

-p, --password <password>

Required, along with `-u` or `--username` if no session is active.

Specify the password for the user specified in `-u` or `--username` .

If the password includes spaces or special characters, enclose it in quotes:

```
--password "my password"
```

-s, --server https://<hostname>:8850

Optional.

Use the specified address for Tableau Services Manager. The URL must start with `https` , include port 8850, and use the server name not the IP address. For example `https://<tsm_hostname>:8850` . If no server is specified, `https://<localhost | dnsname>:8850` is assumed.

--trust-admin-controller-cert

Optional.

Use this flag to trust the self-signed certificate on the TSM controller. For more information about certificate trust and CLI connections, see [Connecting TSM clients](#).

-u, --username <user>

Required if no session is active, along with `-p` or `--password` .

Specify a user account. If you do not include this option, the command is run using credentials you signed in with.