

Migrate from Tabadmin to the TSM CLI

The Tableau Services Manager (TSM) command-line interface (CLI) replaces the tabadmin CLI in Tableau Server on Linux, and in Tableau Server on Windows version 2018.2. This page maps tabadmin commands to TSM commands to help you to migrate to the TSM CLI.

To learn more about the TSM CLI, see [tsm Command Line Reference](#).

Note: TSM is a batch file. To run tsm commands in another batch file, use the `call` command. For example "`call tsm maintenance ziplogs`". Doing this will return control to the batch file. You also need to authenticate to TSM before issuing any commands. For more information, see [Authenticating with tsm CLI](#).

To learn more about the differences between tabadmin and TSM, see [Comparing Functionality of tabadmin and TSM](#).

Looking for tabadmin commands for [Tableau Server] on Windows version 2018.1 and earlier? See [tabadmin Commands](#)[\(Link opens in a new window\)](#)[\(sr-only\)](#).

[Tabadmin commands with a corresponding TSM CLI command](#)

The following table shows which tabadmin commands correspond to commands available in the TSM CLI.

Comparable TSM CLI	Description	Command
Activate a	taba tsm licenses activate license dmin activate --activate	Deactivate ta tsm licenses deactivate licenses
badmin activate --return	Activate a	t tsm trial abadmin activate --trial licenses activate --trial license
backup of the data A backup created using managed by TSM does not include any Tableau server configuration Server data. There is no option to include server configuration data.	Create a	tabadmin backup tsm maintenance backup
Clear the	tabadmin clearcache ts server m	
maintenance cleanup -r cache	Clean up	tabadmin cleanup temporary tsm maintenance cleanup \ files and old log files
Update the	tabadmin	configure t server sm pending-changes apply co nfiguration with any changes you've made
Customize	tabadmin customize tsm customize the server name and logos	Enable tabadmin dbpass tsm data-access access to
repository-access enable the repository	Disable t tsm data-access r access to abadmin dbpass --disable epository-access	Set a file
tabadmin decommission tsm topolog store y filestore decommission instance to	read-only mode	Delete one
tabadmin tsm data-access we or more Web delete_webdataconnector b-data-connectors delete	Data Connectors To learn more, see [Web (WDCs) from Data Connectors in Tableau Tableau Server Server](https://help.tableau.co m/current/server/en-us/da tasource_wdc.htm){MCXref	

.xref}. | +-----+-----+-----+ | Add a Web | tabadmin | tsm data-access || Data | import_webdataconnector | web-data-connectors add || Connector ||| (WDC) to | and |

Note: TSM does not || Tableau || support importing WDCs, || Server | tabadmin wh | instead it lets you add | | | itelist_webdataconnector | WDCs to an allowlist. To ||| learn more, see [Web Data ||| Connectors in Tableau ||| Server |||](https://help.tableau.com/current/server/en-us/data-source_wdc.htm){MCXref ||| .xref}. | +-----+-----+-----+ | List Web | tabadmin | tsm data-access || Data | n list_webdataconnectors | web-data-connectors list || Connectors ||| (WDCs) used || To learn more, see [Web || by Tableau || Data Connectors in || Server | Tableau ||| Server |||](https://help.tableau.com/current/server/en-us/data-source_wdc.htm){MCXref ||| .xref}. | +-----+-----+-----+ | Export a | tabadmin exportsite | tsm sites export || site from ||| Tableau ||| Server ||| +-----+-----+-----+ | Initiate a | tabadmin | tsm topo || repository | admin failoverrepository | logy failover-repository || failover ||| +-----+-----+-----+ | Get a | tabadmin get | tsm configuration get || co ||| nfiguration ||| option ||| +-----+-----+-----+ | Get the | tabadmin | tsm authentication || OpenID | get_openid_redirect_url | openid get-redirect-url || redirect ||| URL ||| +-----+-----+-----+ | Import site | tabadmin importsite | tsm sites import || .csv files ||| into ||| Tableau ||| Server ||| +-----+-----+-----+ | Import a | tabadmin | t | site into | dmin importsite_verified | tsm sites import-verified || Tableau ||| Server ||| using .csv ||| files ||| +-----+-----+-----+ | Display | tabadmin licenses | tsm licenses list || license ||| information || **Note:** For more || for Tableau || information about the || Server || output of this command, ||| see [View Server ||| License ||| s](https://help.tableau.com/current/server/en-us/view_licenses.htm){MCXref ||| .xref}. | +-----+-----+-----+ | Move a file | tabadmin recommission | tsm topolog | | store from | | y filestore recommission || read-only ||| mode to an ||| active ||| read/write ||| state ||| +-----+-----+-----+ | Regenerate | tabadmin re | tsm security re || internal | generate_internal_tokens | generate-internal-tokens || security ||| tokens ||| +-----+-----+-----+ | Register | tabadmin register | tsm register || Tableau ||| Server ||| +-----+-----+-----+ | Rebuild the | tabadmin reindex | tsm maintenance reindex-search || index for ||| Tableau ||| Server ||| +-----+-----+-----+ | Reset the | tabadmin reset | tsm reset || Tableau ||| Server ||| administrator ||| account ||| +-----+-----+-----+ | Stop and | tabadmin restart | tsm restart || restart all ||| Tableau ||| Server ||| processes ||| +-----+-----+-----+ | Restore | tabadmin restore | tsm maintenance restore || from a ||| Tableau || The restore command does || Server || not restore any server || backup file || configuration data. This ||| is true whether you are ||| using a backup created ||| with TSM or a backup ||| created with tabadmin. | +-----+-----+-----+ | Set a | tabadmin set | tsm configuration set || co ||| nfiguration ||| option ||| +-----+-----+-----+ | Activate or | tabadmin sitestate | tsm sites unlock || suspend a ||| site ||| +-----+-----+-----+ | Start all | tabadmin start | tsm start || Tableau ||| Server ||| processes ||| +-----+-----+-----+ | Get the | tabadmin status | tsm status || status of ||| Tableau ||| Server and ||| server ||| processes ||| +-----+-----+-----+ | Stop all | tabadmin stop | tsm stop || Tableau ||| Server ||| processes ||| +-----+-----+-----+ | Create an | tabadmin ziplogs | tsm maintenance ziplogs || archive ||| (.zip) file || The default behavior of || with || the ziplogs command has || Tableau || changed: with tsm, the || Server log || command collects up to || files || the last two days of log ||| files by default. The ||| tabadmin ziplogs command ||| collected up to seven ||| days of log files. For || more information, see ||| [tsm maintenance ||| ziplogs]([https://help.ta](https://help.tableau.com/current/server/en-us/) ||| bleau.com/current/server/ ||| en-

us/cli_maintenance_tsm |||.htm#tsm4ziplogs){MCXref |||.xref}. | +-----+-----+-----+-----
-----+