tsm register

You can use the tsm register command to register [Tableau Server]. This command lets you either display the registration file template (using the --template option) or provide the path to a completed registration file (using the --file option). You must use one of these two options when calling the tsm register command.

Synopsis

```
tsm register --template | --file <registration-filename> [global options]
```

Options

--file <registration-filename>

Required.

Path to the file that contains the registration data.

--template

Required.

Display registration filetemplate.

[]{.icon--med-lg_icon--arrow-up_heading-item_icon}{.heading-item_link .print-hidden} Global options

-h, --help

Optional.

Show the command help.

-p, --password <password>

Required, along with -u or --username if no session is active.

Specify the password for the user specified in $\, -u \,$ or $\, --u \,$ sername .

If the password includes spaces or special characters, enclose it in quotes:

```
--password "my password"
```

-s, --server https://<hostname>:8850

Optional.

Use the specified address for Tableau Services Manager. The URL must start with https://stam_hostname: 8850 . If no server is specified, https://stam_hostname: 8850 is assumed.

--trust-admin-controller-cert

Optional.

Use this flag to trust the self-signed certificate on the TSM controller. For more information about certificate trust and CLI connections, see <u>Connecting TSM clients</u>.

-u, --username <user>

Specify a user account. If you do not include this option, the command is run using credentials you signed in with.