

tabcmd Commands

Looking for Tableau Server on Linux? See [tabcmd Commands](#) (Link opens in a new window) (sr-only).

You can use the following commands with the tabcmd command line tool:

[addusers](#) (to group)
[createextracts](#)
[creategroup](#)
[createproject](#)
[createsite](#)
[createsiteusers](#)
[createusers](#)
[decryptextracts](#)
[delete *workbook-name* or *datasource-name*](#)
[deleteextracts](#)
[deletegroup](#)
[deleteproject](#)
[deletesite](#)
[deletesiteusers](#)
[deleteusers](#)
[editdomain](#)
[editsite](#)
[encryptextracts](#)
[export](#)
[get *url*](#)
[initialuser](#)
[listdomains](#)
[listsites](#)
[login](#)
[logout](#)
[publish](#)
[publishsamples](#)
[reencryptextracts](#)
[refreshextracts](#)
[removeusers](#)
[reset *openid sub*](#)
[runschedule](#)
[set](#)
[syncgroup](#)
[version](#) ...

[addusers](#) *group-name* {#addusers-groupname}

Adds users to the specified group.

Example

```
tabcmd addusers "Development" --users "users.csv"
```

Options

`--users`

Add the users in the given `.csv` file to the specified group. The file should be a simple list with one user name per line. User names are not case sensitive. The users should already be created on [Tableau Server].

If you use this command with large `.csv` files on Tableau Server, a server administrator can enable settings that help improve performance.

For more information, see [CSV Import File Guidelines](#).

`--[no-]complete`

When set to `complete` this option requires that all rows be valid for any change to succeed. If not specified, `--complete` is used.

[icon--xl .accordion__icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#) ::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p`, `--password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t`, `--site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or "") or use

Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

Creates extracts for a published workbook or data source.

Options

```
-d, --datasource
```

The name of the target data source for extract creation.

```
--embedded-datasources
```

A space-separated list of embedded data source names within the target workbook. Enclose data source names with double quotes if they contain spaces. Only available when creating extracts for a workbook.

```
--encrypt
```

Create encrypted extract.

```
--include-all
```

Include all embedded data sources within target workbook. Only available when creating extracts for workbook.

`--parent-project-path`

Path of the project that is the parent of the project that contains the target resource. Must specify the project name with `--project`.

`--project`

The name of the project that contains the target resource. Only necessary if `--workbook` or `--datasource` is specified. If unspecified, the default project 'Default' is used.

`-u , -url`

The canonical name for the resource as it appears in the URL.

`-w , -workbook`

The name of the target workbook for extract creation.

`{{.icon--xl.accordion__icon.icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}} Global options :::`

The following options are used by all `tabcmd` commands. The `--server` , `--user` , and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h , --help`

Displays the help for the command.

`-c , --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)`((Link opens in a new window)){sr-only}`.
- **Linux:** [Configure Mutual SSL](#)`((Link opens in a new window)){sr-only}` :::

`-s , --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u , --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p , --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t , --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use

Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::

[\[icon--med-lg icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#idbfa546df-2be7-444f-8bb8-07978b127783}creategroup *group-name* {#creategroup-groupname}](#)

Creates a group. Use `addusers` (for local groups) and `syncgroup` (for Active Directory groups) commands to add users after the group has been created.

Example

```
tabcmd creategroup "Development"
```

[icon--xl .accordion_icon icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand") Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

`-s, --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u, --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. ::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. ::

`--no-certcheck`

When specified, `tabcmd` (the client) does not validate the server's SSL certificate. ::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ::

[\[!{.icon--med-lg .icon--arrow-up .heading-item _icon\){.heading-item _link .print-hidden} \[!{#id5a3316ed-45bb-4da4-b557-58492b2d4ac8}createproject *project-name* {#createproject-projectname}](#)

Creates a project.

Example

```
tabcmd createproject -n "Quarterly_Reports" -d "Workbooks showing quarterly sales reports."
```

Options

```
-n, --name
```

Specifies the name of the project that you want to create.

```
--parent-project-path
```

Specifies the name of the parent project for the nested project as specified with the `-n` option. For example, to specify a project called "Nested" that exists in a "Main" project, use the following syntax: `--parent-project-path "Main" -n "Nested"`.

```
-d, --description
```

Specifies a description for the project.

[!{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand")} Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c , --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#) :::

```
-s , --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u , --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p , --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t , --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x , --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```


Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

--

Specifies the end of options on the command line. You can use -- to indicate to tabcmd that anything that follows -- should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use -- in a tabcmd command, where -430105/Sheet1 is a required value for the export command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...

[\[icon--med-lg icon--arrow-up heading-item icon\]{heading-item_link .print-hidden} \[{#id6f434e96-89d1-4aa2-a935-4c22fa1e2506}createsite *site-name* {#createsite}](#)

...

Creates a site.

Examples

Create a site named West Coast Sales. A site ID of WestCoastSales will be automatically created, the site will have no storage quota limit, and site administrators will be able to add and remove users:

```
tabcmd createsite "West Coast Sales"
```

Create a site named West Coast Sales with a site ID of wsales :

```
tabcmd createsite "West Coast Sales" -r "wsales"
```

Prevent site administrators from adding users to the site:

```
tabcmd createsite "West Coast Sales" --no-site-mode
```

Set a storage quota, in MB:

```
tabcmd createsite "West Coast Sales" --storage-quota 100
```

Options

-r, --url

Used in URLs to specify the site. Different from the site name.

--user-quota

Maximum number of users that can be added to the site.

--[no-]site-mode

Allows or denies site administrators the ability to add users to or remove users from the site.

--storage-quota

In MB, the amount of workbooks, extracts, and data sources that can be stored on the site.

`--extract-encryption-mode`

The extract encryption mode for the site can be **enforced**, **enabled** or **disabled**. For more information, see [Extract Encryption at Rest](#).

`--run-now-enabled`

Allow or deny users from running extract refreshes, flows, or schedules manually. **true** to allow users to run tasks manually or **false** to prevent users from running tasks manually. For more information, see [Server Settings \(General and Customization\)](#).

[{icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand")} Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) ::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p`, `--password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t`, `--site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x`, `--proxy`

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: ::: :::

[\[--med-lg --arrow-up .heading-item \]{.heading-item_link .print-hidden} \[#{#idd1b7729f-dd20-475a-96f6-17fcd2577894}createsiteusers filename.csv {#createsiteusers}\]](#)

Adds users to a site, based on information supplied in a comma-separated values (CSV) file. If the user is not already created on the server, the command creates the user before adding that user to the site.

The CSV file must contain one or more user names and can also include (for each user) a password, full name, license type, administrator level, publisher (yes/no), and email address. For information about the format of the CSV file, see [CSV Import File Guidelines](#).

As an alternative to including administrator level and publisher permissions in the CSV file, you can pass access level information by including the `--role` option and specifying the site role you want to assign users listed in the CSV file.

By default, users are added to the site that you are logged in to. To add users to a different site, include the global `-site` option and specify that site. (You must have permissions to create users on the site you specify.)

If the server contains multiple sites, you cannot add server (system) administrators through the `createsiteusers` command. Use `createusers` instead. If you specify the `ServerAdministrator` site role for the `--role`

option, the command returns an error. If the CSV file includes `System` as value for administrator, the value is ignored and the user is assigned the `Unlicensed` license type.

If the server contains only one site (the default site), you can specify `system` for the administrator value for a user, or even assign the `ServerAdministrator` site role using the `--role` option, if you want all users in the CSV file to be server administrators.

By default, this command creates users using a synchronous operation (it waits for all operations to complete before proceeding). You can use the `--no-wait` option to specify an asynchronous operation.

Improving performance for large CSV files

A server administrator can use the `tabadmin set` command to enable settings that help to improve performance for large CSV files. For more information, see [Improve performance for large CSV files passed through tabcmd](#) in the CSV Import File Guidelines topic.

Local authentication

If the server is configured to use local authentication, the information in the CSV file is used to create users.

Active Directory authentication

If the server is configured to use Active Directory authentication, user information is imported from Active Directory, and password and friendly name information in the CSV file is ignored. Further, if a user is specified in the CSV file but no corresponding user exists in Active Directory, the user is not added to Tableau Server. For Active Directory users, because the user name is not guaranteed to be unique across domains, you must include the domain as part of the user name. You can specify this as either `domain/username` or `username@domain.com`; however, we recommend using the `domain/username` format. For more information, see [User Management in Deployments with External Identity Stores](#).

Example

```
tabcmd createsiteusers "users.csv" --role "Explorer"
```

Options

```
--admin-type
```

Deprecated. Use the `--role` option instead.

```
--complete
```

Requires that all rows be valid for any change to succeed. This is the default setting.

```
--no-complete
```

Specifies that the command should make changes on the server even if not all rows contain valid information. Rows that contain invalid information are skipped.

```
--no-publisher
```

Deprecated. Use the `--role` option instead.

```
--nowait
```

Do not wait for asynchronous jobs to complete.

```
--publisher
```

Deprecated. Use the `--role` option instead.

`--role`

Specifies a site role for all users in the `.csv` file. When you want to assign site roles using the `--role` option, create a separate CSV file for each site role.

Valid values are `ServerAdministrator`, `SiteAdministratorCreator`, `SiteAdministratorExplorer`, `Creator`, `ExplorerCanPublish`, `Explorer`, `Viewer`, `ReadOnly`, and `Unlicensed`.

The default is `Unlicensed` for new users and unchanged for existing users. Users are added as unlicensed also if you have a user-based server installation, and if the `createsiteusers` command creates a new user, but you have already reached the limit on the number of licenses for your users.

Note: On a multi-site Tableau Server, if you want to assign the `ServerAdministrator` site role using the `--role` option, use the [createusers](#) command instead of `createsiteusers`.

`--silent-progress`

Do not display progress messages for the command.

`[{.icon--xl.accordion_icon.icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options ::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

`-s, --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u, --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::

[\[icon--med-lg .icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#ide42a948a-cd9c-4b73-9ef2-3a58eda2d095}createusers *filename.csv* {#createusers}](#)

...

Create users in Tableau Server, based on information supplied in a comma-separated values (CSV) file.

The CSV file must contain one or more user names and can also include (for each user) a password, full name, license type, administrator level, publisher (yes/no), and email address. For information about the format of the CSV file, see [CSV Import File Guidelines](#).

As an alternative to including administrator level and publisher permissions in the CSV file, you can pass access level information by including the `--role` option and specifying the site role you want to assign users listed in the CSV file.

If the server has only one site (the default site), the user is created and added to the site. If the server has multiple sites, the user is created but is not added to any site. To add users to a site, use [createsiteusers](#).

If you have a user-based server installation, and if the command creates a new user but you have already reached the limit on the number of licenses for your users, the user is added as an unlicensed user.

Local authentication

If the server is configured to use local authentication, the information in the CSV file is used to create users.

Active Directory authentication

If the server is configured to use Active Directory authentication, user information is imported from Active Directory, and password and friendly name information in the CSV file is ignored. Further, if a user is specified in the CSV file but no corresponding user exists in Active Directory, the user is not added to Tableau Server. For Active Directory users, because the user name is not guaranteed to be unique across domains, you must include the domain as part of the user name. You can specify this as either `domain/username` or `username@domain.com`; however, we recommend using the `domain/username` format. For more information, see [User Management in Deployments with External Identity Stores](#).

Example

```
tabcmd createusers "users.csv" --role "ServerAdministrator"
```

```
tabcmd createusers "users.csv"
```

Options

```
--admin-type
```

Deprecated. Use the `--role` option instead.

```
--complete
```

Requires that all rows be valid for any change to succeed. This is the default setting.

```
--no-complete
```

Specifies that the command should make changes on the server even if not all rows contain valid information. Rows that contain invalid information are skipped.

```
--no-publisher
```

Deprecated. Use the `--role` option instead.

```
--nowait
```

Do not wait for asynchronous jobs to complete.

```
--publisher
```

Deprecated. Use the `--role` option instead.

```
-r, --role
```

Specifies a site role for all users in the `.csv` file. When you want to assign site roles using the `--role` option, create a separate CSV file for each site role.

Valid values are `ServerAdministrator`, `SiteAdministratorCreator`, `SiteAdministratorExplorer`, `Creator`, `ExplorerCanPublish`, `Explorer`, `Viewer`, `ReadOnly`, and `Unlicensed`.


On a multi-site server, the command does not assign the user to a site. Therefore, the only site roles the command can successfully assign are `ServerAdministrator` and `Unlicensed`. If you specify any other site role, the command assigns the `Unlicensed` role.

On a single-site server, the user is created and added to the default site using the role that you specify.

If you have a user-based server installation, and if the command creates a new user but you have already reached the limit on the number of licenses for your users, the user is added as an unlicensed user.

`--silent-progress`

Do not display progress messages for the command.

[-xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand") Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) :::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p`, `--password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t`, `--site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: ::: :::

[**\[icon--med-lg icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[#{#decryptextracts_tabcmd}decryptextracts**](#)

Decrypt all extracts on a site. If no site is specified, extracts on the default site will be decrypted. For more information, see [Extract Encryption at Rest](#).

Depending on the number and size of extracts, this operation may consume significant server resources. Consider running this command outside of normal business hours.

Example

```
tabcmd decryptextracts "West Coast Sales"
```

[icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"] Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{sr-only}](#) :::

`-s, --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u, --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: ::: :::

[\[!\[\]\(5361750c22c4e047a52f4eac1ec2d4cc_img.jpg\) !\[\]\(f276343e5e0d2402c20fdc9e8443c0dd_img.jpg\) **heading-item** !\[\]\(f63d0a0c6c21d1cd8465081c8a0d79d6_img.jpg\)\]{.heading-item_link .print-hidden} \[!\[\]\(c7aa0a73772f58306e4c9858ef30418b_img.jpg\)#idfdf59712-84ed-4590-9471-541d316917a6\]delete *workbook-name* or *datasource-name* {#delete-workbookname-or-datasourcename}](#)

Deletes the specified workbook or data source from the server.

This command takes the name of the workbook or data source as it is on the server, not the file name when it was published.

Example

```
tabcmd delete "Sales_Analysis"
```

Options

```
-r, --project
```

The name of the project containing the workbook or data source you want to delete. If not specified, the "Default" project is assumed.

```
--parent-project-path
```

Specifies the name of the parent project for the nested project as specified with the `-r` option. For example, to specify a project called "Nested" that exists in a "Main" project, use the following syntax: `--parent-project-path "Main" -r "Nested"`.

```
--workbook
```

The name of the workbook you want to delete.

```
--datasource
```

The name of the data source you want to delete.

```
{icon--xl .accordion__icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options ::
```

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. ::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. ::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. ...

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ..

[\[!\[\]\(6bb0e4f14c4133b37d2887cb37e67ddd_img.jpg\) !\[\]\(5677a36a9444aca55c9ef7a9b7d8dd5c_img.jpg\) **heading-item** !\[\]\(678dcfc0c73e5cf2048495727be3f5de_img.jpg\)\]{.heading-item_link .print-hidden} \[!\[\]\(d0b071b2af484162c8e7863e10859500_img.jpg\)#id5a3316ed-45bb-4da4-b557-2222222d4ac8\]deleteextracts](#)

Deletes extracts for a published workbook or data source.

Options

`-d, --datasource`

The name of the target data source for extract deletion.

`--embedded-datasources`

A space-separated list of embedded data source names within the target workbook. Enclose data source names with double quotes if they contain spaces. Only available when deleting extracts for a workbook.

`--encrypt`

Create encrypted extract.

`--include-all`

Include all embedded data sources within target workbook.

`--parent-project-path`

Path of the project that is the parent of the project that contains the target resource. Must specify the project name with `--project`.

`--project`

The name of the project that contains the target resource. Only necessary if `--workbook` or `--datasource` is specified. If unspecified, the default project 'Default' is used.

`-u , -url`

The canonical name for the resource as it appears in the URL.

`-w , -workbook`

The name of the target workbook for extract deletion.

`[{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options :::`

The following options are used by all `tabcmd` commands. The `--server` , `--user` , and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h , --help`

Displays the help for the command.

`-c , --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) :::

`-s , --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u , --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p , --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t , --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x , --proxy`

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::

[\[icon--med-lg .icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#id0d009916-bee3-4ef0-a6ac-22188c0e7f30}deletegroup group-name {#deletegroup-groupname}\]](#)

Deletes the specified group from the server.

Example

```
tabcmd deletegroup "Development"
```

[icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"] Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#) ::

`-s , --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u , --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p , --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t , --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x , --proxy`

Host:Port

Uses the specified HTTP proxy. ::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. ::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. ::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

--

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ::

`[]{.icon--med-lg .icon--arrow-up .heading-item _icon){.heading-item _link .print-hidden} []{#iddeleteproject_project-name}deleteproject project-name {#deleteproject}`

Deletes the specified project from the server.

Using `tabcmd`, you can specify only a top-level project in a project hierarchy. To automate tasks you want to perform on a project within a parent project, use the equivalent Tableau [REST API\[\(Link opens in a new window\)\]{.sr-only}](#) call.

Example

```
tabcmd deleteproject "Designs"
```

Option

`--parent-project-path`

Specifies the name of the parent project for the nested project as specified with the command. For example, to specify a project called "Designs" that exists in a "Main" project, use the following syntax: `--parent-project-path "Main" "Designs"`.

`[]{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand") Global options ::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) ::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ::

[[icon--med-lg](#) [icon--arrow-up](#) [.heading-item](#) [icon](#)]{.heading-item_link .print-hidden} [[#id54a7f404-5d1b-452e-8273-0ab8396da641](#)]{deletesite *site-name* {#deletesite-sitename}}

...

Deletes the specified site from the server.

Example

```
tabcmd deletesite "Development"
```

[[icon--xl](#) [.accordion_icon](#) [icon--chevron-right2](#) role="button" tabindex="0" aria-expanded="false" aria-label="Expand") Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#) ::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: ::: :::

[\[!\]{.icon--med-lg .icon--arrow-up .heading-item _icon}{.heading-item _link .print-hidden} \[!\]{#deletesiteusers}deletesiteusers *filename.csv* {#deletesiteusers-filenamecsv}](#)

Removes users from the site that you are logged in to. The users to be removed are specified in a file that contains a simple list of one user name per line. (No additional information is required beyond the user name.)

By default, if the server has only one site, or if the user belongs to only one site, the user is also removed from the server. On a Tableau Server Enterprise installation, if the server contains multiple sites, users who are assigned the site role of **Server Administrator** are removed from the site but are not removed from the server.

If the user owns content, the user's role is change to **Unlicensed**, but the user is not removed from the server or the site. The content is still owned by that user. To remove the user completely, you must change the owner of the content and then try removing the user again.

If the user was imported from Active Directory, the user is removed from the site and possibly from the server. However, the user is not deleted from Active Directory.

Example

```
tabcmd deletesiteusers "users.csv"
```

Improving performance for large CSV files

A server administrator can use the `tabadmin set` command to enable settings that help to improve performance for large CSV files. For more information, see [Improve performance for large CSV files passed through tabcmd](#) in the CSV Import File Guidelines topic.

```
{{icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}} Global options ::
```

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#) ::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::

`[]{.icon--med-lg .icon--arrow-up .heading-item icon}{.heading-item _link .print-hidden} []{#id6a8ef3d6-d17b-4c31-be47-7b09437ecec0}deleteusers filename.csv {#deleteusers-filenamecsv}`

Deletes the users listed in the specified comma-separated values (`.csv`) file.

The `.csv` file should contain a simple list of one user name per line.

Example

```
tabcmd deleteusers "users.csv"
```

Options

```
--[no-]complete
```

When set to `--complete` this option requires that all rows be valid for any change to succeed. If not specified, `--complete` is used.

`[]{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}` Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) ::

`-s, --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u, --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. ::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. ::

`--no-certcheck`

When specified, `tabcmd` (the client) does not validate the server's SSL certificate. ::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... :: ...

[\[!{.icon--med-lg .icon--arrow-up .heading-item _icon}{.heading-item _link .print-hidden} \[!{#editdoma}editdomain](#)

...

Changes the nickname or full domain name of an Active Directory domain on the server. A domain "nickname" is the Windows NetBIOS domain name.

You can modify the nickname for any domain the server is using. In general, you can modify the full domain name for any domain except the one that you used to sign in. However, if the user name that you are currently signed in with exists in both the current domain and the new domain, you can modify the full name for the current domain.

To ensure that Tableau Server can connect to other Active Directory domains, you must also specify secondary domains that Tableau Server connects to by setting the `wgserver.domain.whitelist` option with TSM. For more information about secondary domains and configuring the connection, see [wgserver.domain.whitelist](#).

Review [User Management in Deployments with External Identity Stores](#) to understand how multiple domains, domain name mapping, and user names interact with Tableau Server.

To see a list of domains, use [listdomains](#).

Examples

```
tabcmd editdomain --id 2 --nickname "new-nickname"
```

```
tabcmd editdomain --id 3 --name "new-name"
```

Options

`--id`

The ID of domain to change. To get a list of domain IDs, use [listdomains](#).

`--name`

The new name for the domain.

`--nickname`

The new nickname for the domain.

`[]{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options ::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

`-s, --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u, --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. ::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::...

[\[!{.icon--med-lg .icon--arrow-up .heading-item _icon}{.heading-item _link .print-hidden} \[!{#id06d8e2e0-d7a1-4733-b0df-d1e02f66919b}editsite *site-name* {#editsite-sitename}](#)

...

Changes the name of a site or its web folder name. You can also use this command to allow or deny site administrators the ability to add and remove users, or prevent users from running certain tasks manually. If site administrators have user management rights, you can specify how many users they can add to a site.

Examples

```
tabcmd editsite wc_sales --site-name "West Coast Sales"
```

```
tabcmd editsite wc_sales --site-id "wsales"
```

```
tabcmd editsite wsales --status ACTIVE
```

```
tabcmd editsite wsales --user-quota 50
```

Options

```
--site-name
```

The name of the site that's displayed.

```
--site-id
```

Used in the URL to uniquely identify the site.

```
--user-quota
```

Maximum number of users who can be members of the site.

```
--[no-]site-mode
```

Allow or prevent site administrators from adding users to the site.

```
--status
```

Set to `ACTIVE` to activate a site, or to `SUSPENDED` to suspend a site.

```
--storage-quota
```

In MB, the amount of workbooks, extracts, and data sources that can be stored on the site.

```
--extract-encryption-mode
```

The extract encryption mode for the site can be **enforced**, **enabled** or **disabled**. For more information, see [Extract Encryption at Rest](#). Depending on the number and size of extracts, this operation may consume significant server resources.

```
--run-now-enabled
```

Allow or deny users from running extract refreshes, flows, or schedules manually. **true** to allow users to run tasks manually or **false** to prevent users from running tasks manually. For more information, see [Server Settings \(General and Customization\)](#).

[[{icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) :::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t`, `--site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x`, `--proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... :: ...

`[]{.icon--med-lg .icon--arrow-up .heading-item _icon}{.heading-item _link .print-hidden} []{#encryptextracts_tabcmd}encryptextracts`

Encrypt all extracts on a site. If no site is specified, extracts on the default site will be encrypted. For more information, see [Extract Encryption at Rest](#).

Depending on the number and size of extracts, this operation may consume significant server resources. Consider running this command outside of normal business hours.

Example

```
tabcmd encryptextracts "West Coast Sales"
```

`{{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}}` Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) :::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

Exports a view or workbook from [Tableau Server] and saves it to a file. This command can also export just the data used for a view.

Note the following when you use this command:

- **Permissions:** To export, you must have the [Export Image] permission. By default, this permission is Allowed or Inherited for all roles, although permissions can be set per workbook or view.
- **Exporting data:** To export just the data for a view, use the `--csv` option. This exports the summary data used in a view to a .csv file.
- **Specifying the view, workbook, or data to export:**
 - Use part of the URL to identify what to export, specifically the `"workbook/view"` string as it appears in the URL for the workbook or view. Do not use the "friendly name," and exclude the `:iid=<n>` session ID at the end of the URL.

For example, the Tableau sample view *Global Temperatures* in the *Regional* workbook has a URL similar to this: `<server_name>/#/views/Regional/GlobalTemperatures?:iid=3`

To export the *Global Temperatures* view, use the string `Regional/GlobalTemperatures`.

Do *not* use `Regional/Global Temperatures`, or `Regional/GlobalTemperatures?:iid=3`.

- If the server is running multiple sites and the view or workbook is on a site other than Default, Use `-t <site_id>`.
- To export a workbook, get the URL string by opening a view in the workbook, and include the view in the string you use.

In the above example, to export the *Regional* workbook, use the string

```
Regional/GlobalTemperatures .
```

- To export a workbook, it must have been published with [Show Sheets as Tabs] selected in the Tableau Desktop Publish dialog box.

Note: The Tableau workbook that contains the [administrative views](#)[\[\(Link opens in a new window\)\]](#) `{.sr-only}` cannot be exported.

- [The saved file's format]: Your format options depend on what's being exported. A workbook can only be exported as a PDF using the `--fullpdf` argument. A view can be exported as a PDF (`--pdf`) or a PNG (`--png`).
- **The saved file's name and location** (optional): If you don't provide a name, it will be derived from the view or workbook name. If you don't provide a location, the file will be saved to your current working directory. Otherwise, you can specify a full path or one that's relative to your current working directory.

Note: You must include a file name extension such as `.csv` or `.pdf` . The command does not automatically add an extension to the file name that you provide.
- **Dashboard web page objects not included in PDF exports:** A dashboard can optionally include a web page object. If you are performing an export to PDF of a dashboard that includes a web page object, the web page object won't be included in the PDF.
- **Non-ASCII and non-standard ASCII characters and PDF exports:** If you are exporting a view or workbook with a name that includes a character outside the ASCII character set, or a non-standard ASCII character set, you need to URL encode (percent-encode) the character.

For example if your command includes the city `Zürich` , you need to URL encode it as `Z%C3%BCrich` :

```
tabcmd export "/Cities/Sheet1?locationCity=Z%C3%BCrich" -fullpdf
```

Clearing the Cache to Use Real-Time Data

You can optionally add the URL parameter `?:refresh=yes` to force a fresh data query instead of pulling the results from the cache. If you are using `tabcmd` with your own scripting and the `refresh` URL parameter is being used a great deal, this can have a negative impact on performance. It's recommended that you use `refresh` only when real-time data is required---for example, on a single dashboard instead of on an entire workbook.

Examples

Views

```
tabcmd export "Q1Sales/Sales_Report" --csv -f "Weekly-Report.csv"
```

```
tabcmd export -t Sales "Sales/Sales_Analysis" --pdf -f "C:\Tableau_Workbooks\Weekly-Reports.pdf"
```

```
tabcmd export "Finance/InvestmentGrowth" --png
```

```
tabcmd export "Finance/InvestmentGrowth?:refresh=yes" --png
```

Workbooks

```
tabcmd export "Q1Sales/Sales_Report" --fullpdf
```

```
tabcmd export "Sales/Sales_Analysis" --fullpdf --pagesize tabloid -f
"C:\Tableau_Workbooks\Weekly-Reports.pdf"
```

Options

`-f, --filename`

Saves the file with the given filename and extension.

`--csv`

View only. Export the view's data (summary data) in `.csv` format.

`--pdf`

View only. Export as a PDF.

`--png`

View only. Export as an image in `.png` format.

`--fullpdf`

Workbook only. Export as a PDF. The workbook must have been published with [Show Sheets as Tabs] enabled.

`--pagelayout`

Sets the page orientation (`landscape` or `portrait`) of the exported PDF. If not specified, its Tableau Desktop setting will be used.

`--pagesize`

Sets the page size of the exported PDF as one of the following: `unspecified`, `letter`, `legal`, `note folio`, `tabloid`, `ledger`, `statement`, `executive`, `a3`, `a4`, `a5`, `b4`, `b5`, or `quarto`. Default is `letter`.

`--width`

Sets the width in pixels. Default is 800 px.

`--height`

Sets the height in pixels. Default is 600 px.

`{{icon--xl.accordion__icon.icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}}` Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) ::

`-s, --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u, --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. ::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. ::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. ::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following

example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ..

`[]{.icon--med-lg .icon--arrow-up .heading-item _icon){.heading-item_link .print-hidden} []{#id7e0a0627-ad89-4135-a1c2-85b1d8472568}get url`

Gets the resource from [Tableau Server] that's represented by the specified (partial) URL. The result is returned as a file.

Note the following when you use this command:

- **Permissions:** To get a file, you must have the [Download/Web Save As] permission. By default, this permission is allowed or inherited for all roles, although permissions can be set per workbook or view.
- **Specifying a view or workbook to get:** You specify a view to get using the `"/views/<workbookname>/<viewname>.<extension>"` string, and specify a workbook to get using the `"/workbooks/<workbookname>.<extension>"` string. Replace `<workbookname>` and `<viewname>` with the names of the workbook and view as they appear in the URL when you open the view in a browser and replace `<extension>` with the type of file you want to save. Do not use the session ID at the end of the URL (`?:iid=<n>`) or the "friendly" name of the workbook or view.

For example, when you open a view *Regional Totals* in a workbook named *Metrics Summary*, the URL will look similar to this:

```
/views/MetricsSummary_1/RegionalTotals?:iid=1
```

Use the string `/views/MetricsSummary_1/RegionalTotals.<extension>` to get the view.

Use the string `/workbooks/MetricsSummary_1.<extension>` to get the workbook.

- **File extension:** The URL must include a file extension. The extension determines what's returned. A view can be returned in PDF, PNG, or CSV (summary data only) format. A Tableau workbook is returned as a TWB if it connects to a published data source or uses a live connection, or a TWBX if it connects to a data extract.

Note: If you are downloading a view to a PDF or PNG file, and if you include a `--filename` parameter that includes the .pdf or .png extension, you do not have to include a .pdf or .png extension in the URL.

- **The saved file's name and location** (optional): The name you use for `--filename` should include the file extension. If you don't provide a name and file extension, both will be derived from the URL string. If you don't provide a location, the file is saved to your current working directory. Otherwise, you can specify a full path or one that's relative to your current working directory.
- **PNG size** (optional): If the saved file is a PNG, you can specify the size, in pixels, in the URL.

Clearing the cache to use real-time data

You can optionally add the URL parameter `?:refresh=yes` to force a fresh data query instead of pulling the results from the cache. If you are using `tabcmd` with your own scripting, using the `refresh` parameter a great deal can have a negative impact on performance. It's recommended that you use `refresh` only when real-time data is required---for example, on a single dashboard instead of on an entire workbook.

Examples

Views

```
tabcmd get "/views/Sales_Analysis/Sales_Report.png" --filename "Weekly-Report.png"
```

```
tabcmd get "/views/Finance/InvestmentGrowth.pdf" -f "Q1Growth.pdf"
```

```
tabcmd get "/views/Finance/InvestmentGrowth" -f "Q1Growth.pdf"
```


```
tabcmd get "/views/Finance/InvestmentGrowth.csv"
```

```
tabcmd get "/views/Finance/InvestmentGrowth.png?size=640,480" -f growth.png
```

```
tabcmd get "/views/Finance/InvestmentGrowth.png?refresh=yes" -f growth.png
```

Workbooks

```
tabcmd get "/workbooks/Sales_Analysis.twb" -f "C:\Tableau_Workbooks\Weekly-Reports.twb"
```

[-xl.accordion_icon.icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand")] Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[\(sr-only\)](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[\(sr-only\)](#) :::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p`, `--password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t`, `--site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::

[\[icon--med-lg icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#initialu}initialuser](#)

...

Create the initial administrative user on a server that does not have an initial administrative user defined.

Note: The `tabcmd initialuser` command does not require authentication to Tableau Server, but you must run the command on the initial server node.

Examples

```
tabcmd initialuser --username "admin" --password "password" --server http://localhost
```

```
tabcmd initialuser --username "admin" --password "password" --friendly "Tableau Admin"
--server http://localhost
```

To prompt for the password in the shell, do not include the `--password` parameter in the command. For example:

```
tabcmd initialuser --username "admin" --server http://localhost
```

Options

```
-f, --friendly
```

Creates the initial administrative user with the display name.

```
[icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"] Global options ::
```

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: :::

`[]{{.icon--med-lg .icon--arrow-up .heading-item _icon}}{{.heading-item _link .print-hidden} listdomains`

:::

Displays a list of the Active Directory domains that are in use on the server, along with their nicknames and IDs. If the server is configured to use local authentication, the command returns only the domain name `local`.

Example

```
tabcmd listdomains
```

`[]{{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}} Global options :::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c , --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) :::

```
-s , --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u , --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p , --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t , --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x , --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

--

Specifies the end of options on the command line. You can use -- to indicate to tabcmd that anything that follows -- should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use -- in a tabcmd command, where -430105/Sheet1 is a required value for the export command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... :: ...

[\[icon--med-lg .icon--arrow-up .heading-item _icon\]{.heading-item_link .print-hidden} \[{#idc7467cb6-6cef-49bf-9358-a3e4addd5fa0}\]listsites](#)

...

Returns a list of sites to which the logged in user belongs.

Example

```
tabcmd listsites --username adam --password mypassword
```

Options

--get-extract-encryption-mode

The extract encryption mode for the site can be **enforced**, **enabled** or **disabled**. For more information, see [Extract Encryption at Rest](#).

[icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"] Global options ::

The following options are used by all tabcmd commands. The --server, --user, and --password options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

-h, --help

Displays the help for the command.

-c, --use-certificate

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) ::

-s, --server

The [Tableau Server] URL, which is required at least once to begin session.

```
-u , --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p , --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t , --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x , --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: ::: :::

login

Logs in a [Tableau Server] user.

Use the `--server`, `--site`, `--username`, `--password` global options to create a session.

Note: When you use the **tabcmd login** command, you cannot use SAML single sign-on (SSO), even if the server is configured to use SAML. To log in, you must pass the user name and password of a user who has been created on the server. You will have the permissions of the Tableau Server user that you're signed in as. For more information, see [Set Users' Site Roles](#) and [Permissions](#).

If you want to log in using the same information you've already used to create a session, just specify the `--password` option. The server and user name stored in the cookie will be used.

If the server is using a port other than 80 (the default), you will need to specify the port.

You need the `--site` (`-t`) option only if the server is running multiple sites and you are logging in to a site other than the Default site. If you do not provide a password you will be prompted for one. If the `--no-prompt` option is specified and no password is provided the command will fail.

Once you log in, the session will continue until it expires on the server or the `logout` command is run.

Example

Logs user jsmith in to the [Tableau Server] running on their local machine:

```
tabcmd login -s http://localhost -u jsmith -p password
```

Logs administrator in to the Sales site on sales-server:

```
tabcmd login -s http://sales-server -t Sales -u administrator -p password
```

```
tabcmd login -s http://sales-server:8000 -t Sales -u administrator -p password
```

Logs administrator in to the Sales site on sales-server using SSL, but does not validate the server's SSL certificate:

```
tabcmd login --no-certcheck -s https://sales-server -t Sales -u administrator -p password
```

Establishes a forward proxy and port for localhost:

```
tabcmd login --proxy myfwdproxyserver:8888 -s http://localhost -u jsmith -p password
```

Logs user jsmith in to the reverse proxy using SSL:

```
tabcmd login -s https://myreverseproxy -u jsmith -p password :::
```

Options

```
-s, --server
```

If you are running the command from a Tableau Server computer that's on your network, you can use `http://localhost`. Otherwise, specify the computer's URL, such as `http://bigbox.myco.com` or `http://bigbox`.

For Tableau Online specify the URL `https://online.tableau.com`.

`-t, --site`

Include this option if the server has multiple sites, and you are logging in to a site other than the default site.

The site ID is used in the URL to uniquely identify the site. For example, a site named West Coast Sales might have a site ID of west-coast-sales.

`-u, --username`

The user name of the user logging in. For Tableau Online, the user name is the user's email address.

`-p, --password`

Password for the user specified for `--username`. If you do not provide a password you will be prompted for one.

`--password-file`

Allows the password to be stored in the given `filename.txt` file rather than the command line, for increased security.

`-x, --proxy`

Use to specify the HTTP proxy server and port (Host:Port) for the `tabcmd` request.

`--no-prompt`

Do not prompt for a password. If no password is specified, the `login` command will fail.

`--no-proxy`

Do not use an HTTP proxy server. :::

`--cookie`

Saves the session ID on login. Subsequent commands will not require a login. This value is the default for the command.

`--no-cookie`

Do not save the session ID information after a successful login. Subsequent commands will require a login.

`--timeout SECONDS`

The number of seconds the server should wait before processing the `login` command. Default: 30 seconds.

`[{.icon--xl .accordion__icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options :::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h, --help`

Displays the help for the command.

`-c, --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[}{.sr-only}](#) ::

`-s , --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u , --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p , --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t , --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x , --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

--

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ::

[\[!\[\]\(e2376d476d06eb31946dc01a69a4403a_img.jpg\).icon--med-lg .icon--arrow-up .heading-item _icon\){.heading-item _link .print-hidden} \[{#id8f512aec-57a4-4ed4-94c4-86e91ea9cc9c}\]logout](#)

Logs out of the server.

Example

```
tabcmd logout
```

[\[!\[\]\(0b5e7e25e8775f7e7e80906ada4f0021_img.jpg\).icon--med-lg .icon--arrow-up .heading-item _icon\){.heading-item _link .print-hidden} \[{#id8f512aec-57a4-4ed4-94c4-86e91ea9cc9c}\]publish *filename.twb\(x\)*, *filename.tds\(x\)*, or *filename.hyper* {#publish-filenametwbx-filenametdsx-or-filenamehyper}](#)

Publishes the specified workbook (.twb(x)), data source (.tds(x)), or extract (.hyper) to [Tableau Server].

If you are publishing a workbook, by default, all sheets in the workbook are published without database user names or passwords.

The permissions initially assigned to the workbook or data source are copied from the project that the file is published to. Permissions for the published resource can be changed after the file has been published.

If the workbook contains user filters, one of the thumbnail options must be specified.

Example

```
tabcmd publish "analysis.twbx" -n "Sales_Analysis" --db-username "jsmith" --db-password "secret-password"
```

```
tabcmd publish "analysis_sfdc.hyper" -n "Sales Analysis" --oauth-username "user-name" --save-oauth
```

If the file is not in the same directory as `tabcmd`, include the full path to the file.

Example

```
tabcmd publish "\\computer\volume\Tableau Workbooks\analysis.twbx" -n "Sales_Analysis" --db-username "jsmith" --db-password "secret-password"
```

```
tabcmd publish "\\computer\volume\Tableau Workbooks\analysis_sfdc.hyper" -n "Sales Analysis" --oauth-username "username" --save-oauth
```

Options

`-n , --name`

Name of the workbook or data source on the server. If omitted, the workbook, data source, or data extract will be named after filename.

`-o , --overwrite`

Overwrites the workbook, data source, or data extract if it already exists on the server.

`-r , --project`

Publishes the workbook, data source, or data extract into the specified project. Publishes to the "Default" project if not specified.

`--parent-project-path`

Specifies the name of the parent project for the nested project as specified with the `-r` option. For example, to specify a project called "Nested" that exists in a "Main" project, use the following syntax: `--parent-project-path "Main" -r "Nested"`.

`--db-username`

Use this option to publish a database user name with the workbook, data source, or data extract.

`--db-password`

Use this option to publish a database password with the workbook, data source, or extract.

`--save-db-password`

Stores the provided database password on the server.

`--oauth-username`

The email address of the user account. Connects the user through a preconfigured OAuth connection, if the user already has a saved access token for the cloud data source specified in `--name`. Access tokens are managed in user preferences.

For existing OAuth connections to the data source, use this option instead of `--db-username` and `--db-password`.

`--save-oauth`

Saves the credential specified by `--oauth-username` as an embedded credential with the published workbook or data source.

Subsequently, when the publisher or server administrator signs in to the server and edits the connection for that workbook or data source, the connection settings will show this OAuth credential as embedded in the content.

If you want to schedule extract refreshes after publishing, you must include this option with `--oauth-username`. This is analogous to using `--save-db-password` with a traditional database connection.

`--thumbnail-username`

If the workbook contains user filters, the thumbnails will be generated based on what the specified user can see. Cannot be specified when `--thumbnail-group` option is set.

`--thumbnail-group`

If the workbook contains user filters, the thumbnails will be generated based on what the specified group can see. Cannot be specified when `--thumbnail-username` option is set.

`--tabbed`

When a workbook with tabbed views is published, each sheet becomes a tab that viewers can use to navigate through the workbook. Note that this setting will override any sheet-level security.

`--append`

Append the extract file to the existing data source.

`--replace`

Use the extract file to replace the existing data source.

`--disable-uploader`

Disable the incremental file uploader.

`--restart`

Restart the file upload.

`--encrypt-extracts`

Encrypt extracts when you publish a workbook, data source, or extract to the server. For more information, see [Extract Encryption at Rest](#).

Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#) (Link opens in a new window) {.sr-only}.
- **Linux:** [Configure Mutual SSL](#) (Link opens in a new window) {.sr-only} ::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p, --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: :::

[\[\]{.icon--med-lg .icon--arrow-up .heading-item icon}{.heading-item__link .print-hidden} \[\]{#publishsamples}publishsamples](#)

Description

Publishes Tableau Sample workbooks to the specified project. Any existing samples will be overwritten.

Syntax

```
tabcmd publishsamples -n [project name] [Global options]
```

Example

Publish samples to the Inside Sales project on the Default site, as user jsmith.

```
tabcmd publishsamples -n "Inside Sales" -t "" -s localhost --username "jsmith" --password "secret-password"
```

Options

`-n`, `--name`

Required. Publishes the Tableau samples into the specified project. If the project name includes spaces, enclose the entire name in quotes.

`--parent-project-path`

Specifies the name of the parent project for the nested project as specified with the `-n` option. For example, to specify a project called "Nested" that exists in a "Main" project, use the following syntax: `--parent-project-path "Main" -n "Nested"`.

[`{icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}`] Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#) ::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p`, `--password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t, --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x, --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... :: ...

`[]{.icon--med-lg .icon--arrow-up .heading-item _icon}{.heading-item _link .print-hidden} []{#reencryptextracts _tabcmd}reencryptextracts`

Reencrypt all extracts on a site with new encryption keys. This command will regenerate the key encryption key and data encryption key. You must specify a site. For more information, see [Extract Encryption at Rest](#).

Depending on the number and size of extracts, this operation may consume significant server resources. Consider running this command outside of normal business hours.

Examples

```
tabcmd reencryptextracts "Default"
```

```
tabcmd reencryptextracts "West Coast Sales"
```

[[icon--xl](#) [.accordion_icon](#) [.icon--chevron-right2](#) role="button" tabindex="0" aria-expanded="false" aria-label="Expand")} Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#) [\(Link opens in a new window\)](#) [{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#) [\(Link opens in a new window\)](#) [{.sr-only}](#) :::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... :::

`[]{.icon--med-lg .icon--arrow-up .heading-item _icon){.heading-item _link .print-hidden} [{#{id4cdb3410-1c41-4dad-b1d2-306542ac9b32}refreshextracts workbook-name or datasource-name {#refreshextracts-workbookname-or-datasourcename}`

Performs a full or incremental refresh of extracts belonging to the specified workbook or data source.

This command takes the name of the workbook or data source as it appears on the server, not the file name when it was published. Only an administrator or the owner of the workbook or data source is allowed to perform this operation.

Note: This method will fail and result in an error if your Server Administrator has disabled the **RunNow** setting for the site. For more information, see [Tableau Server Settings](#)[\(Link opens in a new window\)](#)[{sr-only}](#).

Examples

```
tabcmd refreshextracts --datasource sales_ds
```

```
tabcmd refreshextracts --project "Sales External" --datasource sales_ds
```

```
tabcmd refreshextracts --workbook "My Workbook"
```

```
tabcmd refreshextracts --url SalesAnalysis
```

```
tabcmd refreshextracts --workbook "My Workbook" --addcalculations
```

```
tabcmd refreshextracts --datasource sales_ds --removecalculations
```

Options

`--incremental`

Runs the incremental refresh operation.

`--synchronous`

Adds the full refresh operation to the queue used by the Backgrounder process, to be run as soon as a Backgrounder process is available. If a Backgrounder process is available, the operation is run immediately. The refresh operation appears on the Background Tasks report.

During a synchronous refresh, `tabcmd` maintains a live connection to the server while the refresh operation is underway, polling every second until the background job is done.

`--workbook`

The name of the workbook containing extracts to refresh. If the workbook has spaces in its name, enclose it in quotes.

`--datasource`

The name of the data source containing extracts to refresh.

`--project`

Use with `--workbook` or `--datasource` to identify a workbook or data source in a project other than *Default*. If not specified, the Default project is assumed.

`--parent-project-path`

Specifies the name of the parent project for the nested project as specified with the `--project` option. For example, to specify a project called "Nested" that exists in a "Main" project, use the following syntax: `--parent-project-path "Main" --project "Nested"`.

`--url`

The name of the workbook as it appears in the URL. A workbook published as "Sales Analysis" has a URL name of "SalesAnalysis".

`--addcalculations`

Use with `--workbook` to materialize calculations in the embedded extract of the workbook or `--datasource` to materialize calculations in the extract data source. Adds the operation to the queue used by the Backgrounder process. If a Backgrounder process is available, the operation runs immediately. This operation appears on the [Background Tasks for Extracts](#) administrative view.

`--removecalculations`

Use with `--workbook` or `--datasource` to remove calculations that were previously materialized. Adds the operation to the queue used by the Backgrounder process. If a Backgrounder process is available, the operation runs immediately. This operation appears on the [Background Tasks for Extracts](#) administrative view.

`{{icon--xl.accordion_icon.icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"}}` Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h , --help`

Displays the help for the command.

`-c , --use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

`-s , --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u , --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p , --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t , --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x , --proxy`

Host:Port

Uses the specified HTTP proxy. ::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. ::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. ::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

:: ::

[\[{.icon--med-lg .icon--arrow-up .heading-item _icon}\]{.heading-item _link .print-hidden} \[{#reset_sub}reset_openid_sub {#resetopenidsub}\]](#)

Clears OpenID Connect identifiers (sub values) that have already been associated with Tableau Server identities. See [Changing IdPs in Tableau Server for OpenID Connect](#).

Example

```
tabcmd reset_openid_sub --target-username jsmith
```

Options

`--target-username`

Clears sub value for the specified individual user.

`--all`

Clears sub values for all users.

[\[{.icon--xl .accordion__icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options ::](#)

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#) [\(Link opens in a new window\)](#) [\[.sr-only\]](#).

- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{sr-only}](#) :::

`-s , --server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u , --user`

The [Tableau Server] username, which is required at least once to begin session.

`-p , --password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t , --site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x , --proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.





`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following

example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

⋮ ⋮ ⋮

[  [.heading-item](#) ]{.heading-item_link .print-hidden} [ [#id5cc30cba-44b8-48b0-93d6-5707938d157a](#)]{removeusers *group-name* {#removeusers-groupname}}

Removes users from the specified group.

Example

```
tabcmd removeusers "Development" --users "users.csv"
```

Options




`--users`

Remove the users in the given `.csv` file from the specified group. The file should be a simple list with one user name per line.

If you use this command with large `.csv` files on Tableau Server, a server administrator can enable settings that help to improve performance. For information, see [Improve performance for large CSV files passed through tabcmd](#)

`--[no-]complete`

Requires that all rows be valid for any change to succeed. If not specified `--complete` is used.

[   role="button" tabindex="0" aria-expanded="false" aria-label="Expand"] Global options ⋮

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) ⋮

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... ::

[\[!\[\]\(066cb4a00c9d9f40edb6f87372ec6f08_img.jpg\) !\[\]\(24377e79ecb79b4f251fbfab58d46b4d_img.jpg\) **heading-item** !\[\]\(bd6b375b1716b423b5f6fb61d8fe86ac_img.jpg\)\]{.heading-item_link .print-hidden} \[!\[\]\(d50b9adee98e60c04f0c793558bc61dd_img.jpg\)#idd9d99c44-c9be-4191-9191-](#)

402341775a3d}runschedule *schedule-name* {#runschedule-schedulename}

Runs the specified schedule.

This command takes the name of the schedule as it is on the server.

This command is not available for Tableau Online.

Note: This method will fail and result in an error if your Server Administrator has disabled the **RunNow** setting for the site. For more information, see [Tableau Server Settings](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).

Example

```
tabcmd runschedule "5AM Sales Refresh"
```

`[icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"]` Global options ::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) ::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or "") or use

Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

...:::

[\[icon--med-lg icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#idfe12acaf-ed64-4f0c-8eb8-b83c9de12382}\]set setting](#)

...

Enables the specified setting on the server. Details about each setting can be seen on the Maintenance page on the server.

Use an exclamation mark in front of the setting name to disable the setting. You can enable or disable the following settings:

- `allow_scheduling`
- `embedded_credentials`

- `remember_passwords_forever`

Example

```
tabcmd set embedded_credentials
```

`[]{.icon--xl .accordion__icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options :::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#).
- **Linux:** [Configure Mutual SSL\[\(Link opens in a new window\)\]{.sr-only}](#) :::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or "") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

```
--no-certcheck
```

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

```
--[no-]cookie
```

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

```
--timeout
```

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

```
--
```

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

::: ::: :::

[\[icon--med-lg icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#ide6a39f29-77ff-44f6-b946-c2b56b31a2f9}syncgroup group-name {#syncgroup-groupname}](#)

:::

Synchronizes a Tableau Server group with an Active Directory group. If the Tableau Server group does not already exist, it is created and synchronized with the specified Active Directory group.

If the group name itself includes an "@" (other than as the domain separator) you need to refer to the symbol using the hex format "\0x40".

Example

```
tabcmd syncgroup "Development"
```

```
tabcmd syncgroup "Dev\0x40West"
```

Note: If you synchronize a group that you are a member of, changes that you make using this command do not apply to your user. For example, if you use this command to remove the administrator right from users in a group that you are a member of, you are still an administrator when the command finishes.

Options

```
--grant-license-mode <grant-license-mode>
```

Specifies whether a role should be granted on sign in. Default is `on-sync`. Valid values are `on-login`, `on-sync`. If no value is specified, `on-sync` is assumed and the default role will be granted when the group is synchronized. For more information, see [Modifying user roles with Grant role on sign in](#).

`--no-publisher`

Deprecated. Use the `--role` option instead.

`--overwritesiterole`

Allows a user's site role to be overwritten with a less privileged one when using `--role`. By default, a user site role can be promoted when using `--role`, but cannot be demoted. Because the `--overwritesiterole` option will demote user site roles, use it with caution.

`--publisher`

Deprecated. Use the `--role` option instead.

`-r`, `--role`

Specifies a site role for users in the group. The default is `Unlicensed`.

`--silent-progress`

Do not display progress messages for the command.

`[{.icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"} Global options :::`

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

`-h`, `--help`

Displays the help for the command.

`-c`, `--use-certificate`

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) :::

`-s`, `--server`

The [Tableau Server] URL, which is required at least once to begin session.

`-u`, `--user`

The [Tableau Server] username, which is required at least once to begin session.

`-p`, `--password`

The [Tableau Server] password, which is required at least once to begin session.

`--password-file`

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

`-t`, `--site`

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

`-x`, `--proxy`

Host:Port

Uses the specified HTTP proxy. :::

`--no-prompt`

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

`--no-proxy`

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. :::

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```

... :: ...

[\[icon--med-lg icon--arrow-up .heading-item icon\]{.heading-item_link .print-hidden} \[{#id825f5d18-529c-408a-b876-57693195bbdd}version](#)

Displays the version information for the current installation of the tabcmd utility.

Example


```
tabcmd version
```

[icon--xl .accordion_icon .icon--chevron-right2 role="button" tabindex="0" aria-expanded="false" aria-label="Expand"] Global options :::

The following options are used by all `tabcmd` commands. The `--server`, `--user`, and `--password` options are required at least once to begin a session. An authentication token is stored so subsequent commands can be run without including these options. This token remains valid for five minutes after the last command that used it.

```
-h, --help
```

Displays the help for the command.

```
-c, --use-certificate
```

Use client certificate to sign in. Required when mutual SSL is enabled.

For information about configuring the certificate, start with the following topic appropriate for your Tableau Server OS:

- **Windows:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#).
- **Linux:** [Configure Mutual SSL](#)[\(Link opens in a new window\)](#)[{.sr-only}](#) :::

```
-s, --server
```

The [Tableau Server] URL, which is required at least once to begin session.

```
-u, --user
```

The [Tableau Server] username, which is required at least once to begin session.

```
-p, --password
```

The [Tableau Server] password, which is required at least once to begin session.

```
--password-file
```

Allows the password to be stored in the given `.txt` file rather than the command line for increased security.

```
-t, --site
```

Indicates that the command applies to the site specified by the [Tableau Server] site ID, surrounded by single quotes or double quotes. To specify the Default site, use either an empty string with single or double quotes (" or ") or use Default in double quotes ("Default"). Site ID is case-sensitive when using a cached authentication token. If you do not match case you may be prompted for a password even if the token is still valid.

```
-x, --proxy
```

Host:Port

Uses the specified HTTP proxy. :::

```
--no-prompt
```

When specified, the command will not prompt for a password. If no valid password is provided the command will fail.

```
--no-proxy
```

When specified, an HTTP proxy will not be used. :::

`--no-certcheck`

When specified, tabcmd (the client) does not validate the server's SSL certificate. ...

`--[no-]cookie`

When specified, the session ID is saved on login so subsequent commands will not need to log in. Use the `no-` prefix to not save the session ID. By default the session is saved.

`--timeout`

Waits the specified number of seconds for the server to complete processing the command. By default the process will timeout in 30 seconds.

`--`

Specifies the end of options on the command line. You can use `--` to indicate to `tabcmd` that anything that follows `--` should not be interpreted as an option setting and can instead be interpreted as a value for the command. This is useful if you need to specify a value in the command that includes a hyphen. The following example shows how you might use `--` in a `tabcmd` command, where `-430105/Sheet1` is a required value for the `export` command.

```
tabcmd export --csv -f "D:\export10.csv" -- -430105/Sheet1
```