

PUU Monitoring - Production SQL

NILAMS (nilams @ antartika.uitm.edu.my, MariaDB 10.11) - branch puu_monitoring - prepared 25 Sep 2026

Summary

#	Change	Type
1	tbl_vetting_documents: add risk_classification, document_compliance_status	2 new columns (nullable)
2	tbl_puu_sla_configs + 11 SLA values	New table + rows
3	tbl_puu_pic_reminder_logs	New table
4	tbl_asl_cycle_idx, tbl_adsl_cycle_idx on the two status log tables	2 new indexes
5	5 permissions in tbl_permissions	New rows
6	Role grants in tbl_role_has_permissions	New rows

Before you run: an account with CREATE, ALTER, INDEX and INSERT on nilams is needed (effendy is SELECT-only). Run all six steps **before** the code is deployed. Every statement is safe to run twice, and no existing row or column is changed or removed. The same SQL is in NILAM-PUU-Monitoring-Production-SQL-2026-09-25.sql next to this PDF - run that file rather than copying from the PDF.

Current state - checked 25 Sep 2026, 11:38

Read-only check of both databases before this document was written.

Item	Dev (nilamsdev)	Production (nilams)
2 columns on tbl_vetting_documents	Present	Missing - Step 1
tbl_puu_sla_configs	Present, 12 rows (11 + 1 unused)	Missing - Step 2
tbl_puu_pic_reminder_logs (with kind)	Present, 3 rows	Missing - Step 3
tbl_asl_cycle_idx, tbl_adsl_cycle_idx	Present	Missing - Step 4
5 PUU permissions	5 of 5	0 of 5 - Step 5
Role grants	14 of 14	0 of 14 - Step 6
tbl_puu_holidays (retired design)	Absent	Absent - nothing to drop

Nothing from PUU Monitoring needs to be removed on production. The only leftover is one unused setting row on nilamsdev (see "Development database cleanup").

Step 0 - Pre-check (read-only)

```
-- Read-only. Run first to confirm nothing is installed yet.
SELECT DATABASE(); -- expect: nilams
SHOW COLUMNS FROM tbl_vetting_documents LIKE 'risk_classification';
SHOW COLUMNS FROM tbl_vetting_documents LIKE 'document_compliance_status';
SHOW TABLES LIKE 'tbl_puu_%';
SHOW INDEX FROM tbl_application_status_logs WHERE Key_name = 'tbl_asl_cycle_idx';
SHOW INDEX FROM tbl_application_document_status_logs WHERE Key_name = 'tbl_adsl_cycle_idx';
SELECT name FROM tbl_permissions
WHERE name IN ('view_selfmonitorings','view_assignmentmonitorings',
              'view_managementmonitorings','view_puureports','export_puureports');
-- As checked on 25 Sep 2026 11:38: every query above except the first returns 0 rows.
```

Step 1 - Final Draft Assessment columns

Adds two nullable columns to an existing table. Existing rows get NULL; no data is changed. **Required:** without them vetters cannot save comments/uploads and the MEU Pending and LPU Approval print pages fail.

```
ALTER TABLE `tbl_vetting_documents`
  ADD COLUMN IF NOT EXISTS `risk_classification`
    VARCHAR(20) NULL AFTER `pic_comment`,
  ADD COLUMN IF NOT EXISTS `document_compliance_status`
    VARCHAR(50) NULL AFTER `risk_classification`;
```

Step 2 - SLA configuration table

New table holding the SLA thresholds (all values are working days), plus its 11 default rows. PUU changes the values afterwards in **Parameter Setup** → **PUU Monitoring**; re-running this step never overwrites a value that has been changed there.

```
CREATE TABLE IF NOT EXISTS `tbl_puu_sla_configs` (  
  `id`          BIGINT(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `key`         VARCHAR(50)          NOT NULL,  
  `value`       SMALLINT(5) UNSIGNED NOT NULL,  
  `label`       VARCHAR(150)         NOT NULL,  
  `updated_by`  BIGINT(20) UNSIGNED  NULL DEFAULT NULL,  
  `created_at`  TIMESTAMP             NULL DEFAULT NULL,  
  `updated_at`  TIMESTAMP             NULL DEFAULT NULL,  
  PRIMARY KEY (`id`),  
  UNIQUE KEY `tbl_puu_sla_configs_key_unique` (`key`),  
  KEY `tbl_puu_sla_configs_updated_by_foreign` (`updated_by`),  
  CONSTRAINT `tbl_puu_sla_configs_updated_by_foreign`  
    FOREIGN KEY (`updated_by`) REFERENCES `tbl_users` (`id`)  
) ENGINE = InnoDB DEFAULT CHARSET = utf8mb4 COLLATE = utf8mb4_unicode_ci;  
  
INSERT INTO `tbl_puu_sla_configs`  
  (`key`, `value`, `label`, `updated_by`, `created_at`, `updated_at`)  
VALUES  
(  
  'assignment_sla_days', 14,  
  'SLA 1 - max working days for the Legal Advisor to assign a Drafter/Vetter',  
  NULL, NOW(), NOW()),  
(  
  'feedback_sla_days', 21,  
  'SLA 2 - max working days for a Drafter/Vetter to return feedback to the PIC',  
  NULL, NOW(), NOW()),  
(  
  'rag_green_max', 6,  
  'Assignment cycle - maximum working days classified as On track',  
  NULL, NOW(), NOW()),  
(  
  'rag_amber_max', 10,  
  'Assignment cycle - maximum working days classified as Due soon',  
  NULL, NOW(), NOW()),  
(  
  'rag_watch_at', 11,  
  'Assignment cycle - first working day classified as Critical',  
  NULL, NOW(), NOW()),  
(  
  'vetting_on_track_max', 10,  
  'Vetting cycle - maximum working days classified as On track',  
  NULL, NOW(), NOW()),  
(  
  'vetting_due_soon_max', 14,  
  'Vetting cycle - maximum working days classified as Due soon',  
  NULL, NOW(), NOW()),  
(  
  'stale_after_working_days', 90,  
  'Working days after which an open cycle counts as abandoned, not late',  
  NULL, NOW(), NOW()),  
(  
  'pic_on_track_max', 8,  
  'PIC turn - maximum working days with the PIC classified as On track',  
  NULL, NOW(), NOW()),  
(  
  'pic_due_soon_max', 15,  
  'PIC turn - maximum working days with the PIC classified as Due soon',  
  NULL, NOW(), NOW()),  
(  
  'pic_turn_sla_days', 21,  
  'PIC turn - working days with the PIC after which the document counts as overdue',  
  NULL, NOW(), NOW())  
ON DUPLICATE KEY UPDATE  
  -- Only the description is refreshed. Values are edited by PUU in  
  -- Parameter Setup -> PUU Monitoring and must survive a re-run.  
  `label` = VALUES(`label`);
```

Step 3 - PIC reminder email history table

New table recording each reminder email sent to a PIC. kind is return (Awaiting PIC) or execution (Not Executed Yet).

```
CREATE TABLE IF NOT EXISTS `tbl_puu_pic_reminder_logs` (  
  `id` BIGINT(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `application_id` BIGINT(20) UNSIGNED NOT NULL,  
  `kind` VARCHAR(20) NOT NULL DEFAULT 'return',  
  `sent_by` BIGINT(20) UNSIGNED NOT NULL,  
  `recipients` TEXT NOT NULL,  
  `sent_at` TIMESTAMP NOT NULL DEFAULT CURRENT_TIMESTAMP,  
  PRIMARY KEY (`id`),  
  KEY `tbl_puu_pic_reminder_logs_application_sent_idx`  
    (`application_id`, `sent_at`),  
  KEY `tbl_puu_pic_reminder_logs_sent_by_foreign` (`sent_by`),  
  CONSTRAINT `tbl_puu_pic_reminder_logs_application_foreign`  
    FOREIGN KEY (`application_id`) REFERENCES `tbl_applications` (`id`),  
  CONSTRAINT `tbl_puu_pic_reminder_logs_sent_by_foreign`  
    FOREIGN KEY (`sent_by`) REFERENCES `tbl_users` (`id`)  
) ENGINE = InnoDB DEFAULT CHARSET = utf8mb4 COLLATE = utf8mb4_unicode_ci;
```

Step 4 - Indexes on existing log tables

Speeds up the SLA calculations. Built online (reads and writes continue), on about 69,000 and 33,000 rows - a few seconds each. No data is changed.

```
CREATE INDEX IF NOT EXISTS `tbl_asl_cycle_idx`  
  ON `tbl_application_status_logs`  
  (`application_id`, `application_status_id`, `created_at`)  
  ALGORITHM = INPLACE LOCK = NONE;  
  
CREATE INDEX IF NOT EXISTS `tbl_adsl_cycle_idx`  
  ON `tbl_application_document_status_logs`  
  (`application_id`, `document_status_id`, `created_at`)  
  ALGORITHM = INPLACE LOCK = NONE;
```

Step 5 - Permissions

Five new permissions. tbl_permissions has no unique key on name, so each row is only inserted if it does not already exist.

```
INSERT INTO `tbl_permissions` (`name`, `guard_name`, `created_at`, `updated_at`)  
SELECT requested.`name`, 'web', NOW(), NOW()  
FROM (  
  SELECT 'view_selfmonitorings' AS `name`  
  UNION ALL SELECT 'view_assignmentmonitorings'  
  UNION ALL SELECT 'view_managementmonitorings'  
  UNION ALL SELECT 'view_puureports'  
  UNION ALL SELECT 'export_puureports'  
) AS requested  
WHERE NOT EXISTS (  
  SELECT 1 FROM `tbl_permissions` existing  
  WHERE existing.`name` = requested.`name`  
  AND existing.`guard_name` = 'web'  
)  
);
```

Step 6 - Role grants

Admin, Assistant Superadmin and Legal Advisor: assignment, management, reports, export. Drafter/Vetter: self monitoring and reports. All four roles exist on production.

```
INSERT IGNORE INTO `tbl_role_has_permissions` (`permission_id`, `role_id`)
SELECT p.`permission_id`, r.`id`
FROM (
  SELECT MIN(`id`) AS `permission_id`, `name`
  FROM `tbl_permissions`
  WHERE `guard_name` = 'web'
  AND `name` IN ('view_selfmonitorings', 'view_assignmentmonitorings',
                'view_managementmonitorings', 'view_puureports',
                'export_puureports')
  GROUP BY `name`
) AS p
JOIN `tbl_roles` r ON r.`guard_name` = 'web'
WHERE (r.`name` IN ('Admin', 'Assistant Superadmin', 'Legal Advisor')
  AND p.`name` IN ('view_assignmentmonitorings', 'view_managementmonitorings',
                  'view_puureports', 'export_puureports'))
OR (r.`name` = 'Drafter/Vetter'
  AND p.`name` IN ('view_selfmonitorings', 'view_puureports'));
```

Verification (read-only)

Expected results are shown after each query.

```
SHOW COLUMNS FROM tbl_vetting_documents
WHERE Field IN ('risk_classification', 'document_compliance_status'); -- 2 rows

SHOW TABLES LIKE 'tbl_puu_%'; -- tbl_puu_pic_reminder_logs, tbl_puu_sla_configs

SELECT COUNT(*) FROM tbl_puu_sla_configs; -- 11

SHOW INDEX FROM tbl_application_status_logs
WHERE Key_name = 'tbl_asl_cycle_idx'; -- 3 rows
SHOW INDEX FROM tbl_application_document_status_logs
WHERE Key_name = 'tbl_adsl_cycle_idx'; -- 3 rows

SELECT r.name AS role, p.name AS permission
FROM tbl_role_has_permissions rp
JOIN tbl_roles r ON r.id = rp.role_id
JOIN tbl_permissions p ON p.id = rp.permission_id
WHERE p.name IN ('view_selfmonitorings', 'view_assignmentmonitorings',
                'view_managementmonitorings', 'view_puureports',
                'export_puureports')
ORDER BY r.name, p.name; -- 14 rows
```

After the SQL - on the application server

```
php artisan permission:cache-reset # required: permissions were inserted by SQL
php artisan view:clear
php artisan puu:verify # read-only check; expect "puu:verify passed."
```

Without permission:cache-reset, users see 403 errors or no PUU menu for up to 24 hours. The server also needs outbound HTTPS to api.uitm.edu.my (working-day calendar and staff photos) and working SMTP settings (PIC reminder emails).

Development database cleanup (nilamsdev only)

Leftovers that exist only on nilamsdev. They are not in the production .sql file.

```
-- nilamsdev ONLY. Do not run on production (this row never existed there).

-- Unused SLA setting left over from development; no code reads it.
DELETE FROM `tbl_puu_sla_configs` WHERE `key` = 'assignment_metric_shown';

-- Check: expect 11 rows, all keys listed in Step 2.
SELECT `key`, `value` FROM `tbl_puu_sla_configs` ORDER BY `key`;
```

Rollback (only if needed)

```
-- Only if the release has to be withdrawn. Run in this order.
DELETE rp FROM tbl_role_has_permissions rp
  JOIN tbl_permissions p ON p.id = rp.permission_id
 WHERE p.guard_name = 'web'
    AND p.name IN ('view_selfmonitorings', 'view_assignmentmonitorings',
                  'view_managementmonitorings', 'view_puureports',
                  'export_puureports');
DELETE FROM tbl_permissions
 WHERE guard_name = 'web'
    AND name IN ('view_selfmonitorings', 'view_assignmentmonitorings',
                'view_managementmonitorings', 'view_puureports',
                'export_puureports');
DROP INDEX tbl_asl_cycle_idx ON tbl_application_status_logs;
DROP INDEX tbl_adsl_cycle_idx ON tbl_application_document_status_logs;
DROP TABLE IF EXISTS tbl_puu_pic_reminder_logs;
DROP TABLE IF EXISTS tbl_puu_sla_configs;
-- Removes any final draft assessments saved since go-live:
ALTER TABLE tbl_vetting_documents
  DROP COLUMN IF EXISTS document_compliance_status,
  DROP COLUMN IF EXISTS risk_classification;
```