

Outline-OPS-002：下载功能和图片展示失效

Runbook

Metadata

- 环境: 生产
- 服务名称: Outline
- 告警名称: 302 Found
- 负责人: @sre-oncall
- 最后更新: 2026-08-04
- 下次演练: xxx
- 预计耗时: 5-20 分钟
- 严重级别: P1 (全量不可用)

触发条件

- ☒ 用户反馈：Outline Web页面无法展示图片、下载功能失败

快速诊断

步骤1：查看开发者工具Network

outline中显示图片错误: Request URL
https://outline.tian-power.cloud/api/attachments.redirect?id=58bf62e6-3086-44be-af7a-b050fd4491c7
Request Method
GET
Status Code
302 Found (from disk cache)
Remote Address
192.168.13.23:443
Referrer Policy
no-referrer

步骤2：查看容器运行状态

```
# docker ps
```

CONTAINER ID	IMAGE	COMMAND
CREATED	STATUS	PORTS
		NAMES
7b5ec0edc477	outlinewiki/outline:1.9.2	"docker-entrypoint.s..."
7 minutes ago	Up 7 minutes (healthy)	0.0.0.0:3000->3000/tcp, :::3000->3000/tcp
7d3abef791d1	keycloak/keycloak:26.1.4	"/opt/bitnami/script..."
10 days ago	Up 10 days	8443/tcp, 0.0.0.0:8080->8080/tcp, :::8080->8080/tcp, 9000/tcp
a54b1beb1879	postgres:15.12	"docker-entrypoint.s..."
4 months ago	Up 8 weeks	0.0.0.0:5432->5432/tcp, :::5432->5432/tcp
3bbedc2c930d	minio/minio:RELEASE.2025-03-12T18-04-18Z	"/usr/bin/docker-ent..."
4 months ago	Up 8 weeks	0.0.0.0:29000->9000/tcp, :::29000->9000/tcp, 0.0.0.0:29001->9001/tcp, :::29001->9001/tcp
97782cbe3025	redis:7.4.2-alpine	"docker-entrypoint.s..."
16 months ago	Up 8 weeks	0.0.0.0:6379->6379/tcp, :::6379->6379/tcp

步骤3：分析

```
docker run -d -p 80:3000 --name outline_1.9.2 --network keycloak-network -v ~/docker-data/outline-data:/var/lib/outline/data -e DATABASE_URL=postgres://iotcloud:iotcloud@postgres/outline2 -e REDIS_URL=redis://:iotcloud@192.168.13.23:6379/0 -e PGSSLMODE=disable -e FORCE_HTTPS=true -e SECRET_KEY=22a3dbd6fd96864cb125504826b153cf60a454e43a019afe4692e06f6cacd700 -e UTILS_SECRET=11121c684ca0dc0352bf7567db9aaf9bc26c45fc34cacd5dbe883c086d7c7e00 -e URL=https://outline.tian-power.cloud -e OIDC_CLIENT_ID=outline -e OIDC_CLIENT_SECRET=y3WktIycbXAYnmYu7zPXnpOceY034EOn -e OIDC_AUTH_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-connect/auth -e OIDC_TOKEN_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-connect/token -e OIDC_USERINFO_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-connect/userinfo -e OIDC_LOGOUT_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-connect/logout?redirect_uri=http%3A%2F%2F192.168.13.23 -e OIDC_USERNAME_CLAIM=preferred_username -e OIDC_DISPLAY_NAME=keycloak -e OIDC_SCOPES="openid profile email" -e AWS_ACCESS_KEY_ID=iotcloud -e AWS_SECRET_ACCESS_KEY=iotcloud@2025 -e AWS_S3_UPLOAD_BUCKET_URL=http://192.168.13.23:29000 -e AWS_S3_UPLOAD_BUCKET_NAME=outline -e AWS_REGION=cn-homelab-1 -e FILE_STORAGE_UPLOAD_MAX_SIZE=5621440000 -e AWS_S3_FORCE_PATH_STYLE=true -e AWS_S3_ACL=private -e SMTP_HOST=smtp.exmail.qq.com -e SMTP_PORT=465 -e SMTP_USERNAME=iot-cloud@tian-power.com -e SMTP_PASSWORD=Vb4Ca8H0fi3l6AE -e SMTP_FROM_EMAIL=iot-cloud@tian-power.com -e EMAIL_ENABLED=true -e GITLAB_CLIENT_ID=43c97e179744f685cd6528e35ad5352b1e9c37dcf9790679476a537635176c08 -e GITLAB_CLIENT_SECRET=gloas-988dd8d9d59aa6f6f0fd0c5e3a30f0d98e997752995174b4469ad83658d4adec -e GITLAB_BASE_URL=https://gitlab.tian-power.cloud -e DEFAULT_LANGUAGE=zh_CN -e WEB_CONCURRENCY=256 -e ALLOWED_PRIVATE_IP_ADDRESSES=192.168.13.76 outlinewiki/outline:1.9.2
```

根据部署配置，问题很可能出在 `AWS_S3_UPLOAD_BUCKET_URL` 使用了内网 IP 地址。

Outline 的图片加载流程是：

浏览器请求 `/api/attachments.redirect?id=...`

Outline 验证用户身份（通过 `Cookie/Session`）后，返回 `302` 重定向到实际的 S3 存储地址（即您配置的 `AWS_S3_UPLOAD_BUCKET_URL` 加上签名参数）。

浏览器随后请求该重定向地址获取图片。

如果重定向后的地址是 `http://192.168.13.23:29000/outline/...`，

步骤4：解决办法

nginx做反向代理到minio容器

```
# vim minio.conf
server {
    listen 80;
    server_name minio.tian-power.cloud;
    # 如果需要 HTTP 重定向到 HTTPS，可以单独配置或在这里处理
    return 301 https://$server_name$request_uri;
}
```

```

server {
    listen 443 ssl;
    server_name minio.tian-power.cloud;

    # SSL 证书（请替换为您的实际证书路径）
    ssl_certificate      /etc/nginx/conf.d/ssl/tian-power.cloud.pem;
    ssl_certificate_key  /etc/nginx/conf.d/ssl/tian-power.cloud.key;

    # SSL 安全设置（建议）
    ssl_protocols TLSv1.2 TLSv1.3;
    ssl_ciphers HIGH:!aNULL:!MD5;
    ssl_prefer_server_ciphers on;

    # 日志（可选）
    access_log /data/wwwlog/minio_access.log;
    error_log  /data/wwwlog/minio_error.log;

    # 最大上传大小（与 Outline 的 FILE_STORAGE_UPLOAD_MAX_SIZE 保持一致）
    client_max_body_size 5G;

    location / {
        # 代理到 MinIO 服务（内网地址）
        proxy_pass http://192.168.13.23:29000;

        # 传递必要的头部
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;

        # 禁用缓存（可选）
        proxy_buffering off;

        # 超时设置（大文件上传可能需要）
        proxy_connect_timeout 300;
        proxy_send_timeout 300;
        proxy_read_timeout 300;
        send_timeout 300;
    }
}

```

outline启动命令参数修改

```
# 修改变量AWS_S3_UPLOAD_BUCKET_URL=https://minio.tian-power.cloud 和
OIDC_LOGOUT_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-
connect/logout?redirect_uri=http%3A%2F%2Foutline.tian-power.cloud
docker run -d      -p 3000:3000      --name outline_1.9.2-1      --network keycloak-
network      -v ~/docker-data/outline-data:/var/lib/outline/data      -e
DATABASE_URL=postgres://iotcloud:iotcloud@postgres/outline2      -e
REDIS_URL=redis://:iotcloud@192.168.13.23:6379/0      -e PGSSLMODE=disable      -e
FORCE_HTTPS=true      -e
SECRET_KEY=22a3dbd6fd96864cb125504826b153cf60a454e43a019afe4692e06f6cacd700      -
e UTILS_SECRET=11121c684ca0dc0352bf7567db9aaf9bc26c45fc34cacd5dbe883c086d7c7e00
      -e URL=https://outline.tian-power.cloud      -e OIDC_CLIENT_ID=outline      -e
OIDC_CLIENT_SECRET=y3WktIycbXAYnmYu7zPxNpOcEy034EOn      -e
OIDC_AUTH_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-
connect/auth      -e
OIDC_TOKEN_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-
connect/token      -e
OIDC_USERINFO_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-
connect/userinfo      -e
OIDC_LOGOUT_URI=http://192.168.13.23:8080/realms/outline/protocol/openid-
connect/logout?redirect_uri=http%3A%2F%2Foutline.tian-power.cloud      -e
OIDC_USERNAME_CLAIM=preferred_username      -e OIDC_DISPLAY_NAME=keycloak      -e
OIDC_SCOPES="openid profile email"      -e AWS_ACCESS_KEY_ID=iotcloud      -e
AWS_SECRET_ACCESS_KEY=iotcloud@2025      -e
AWS_S3_UPLOAD_BUCKET_URL=https://minio.tian-power.cloud      -e
AWS_S3_UPLOAD_BUCKET_NAME=outline      -e AWS_REGION=cn-homelab-1      -e
FILE_STORAGE_UPLOAD_MAX_SIZE=5621440000      -e AWS_S3_FORCE_PATH_STYLE=true      -
e AWS_S3_ACL=private      -e SMTP_HOST=smtp.exmail.qq.com      -e SMTP_PORT=465
-e SMTP_USERNAME=iot-cloud@tian-power.com      -e SMTP_PASSWORD=Vb4Ca8H0fi3l6AE
      -e SMTP_FROM_EMAIL=iot-cloud@tian-power.com      -e EMAIL_ENABLED=true      -e
GITLAB_CLIENT_ID=43c97e179744f685cd6528e35ad5352b1e9c37dcf9790679476a537635176c08
-e GITLAB_CLIENT_SECRET=gloas-
988dd8d9d59aa6f6f0fd0c5e3a30f0d98e997752995174b4469ad83658d4adec -e
GITLAB_BASE_URL=https://gitlab.tian-power.cloud -e DEFAULT_LANGUAGE=zh_CN -e
WEB_CONCURRENCY=256 -e ALLOWED_PRIVATE_IP_ADDRESSES=192.168.13.76
outlinewiki/outline:1.9.2
```

步骤5: 验证

outline.tian-power.cloud登录

检查浏览器开发者工具的 **Network** 面板:

点击图片请求, 查看重定向后的 **URL** 是否变成了可访问的域名。

- 1、图片正常展示
- 2、文件可正常下载
- 3、上传图片和文件正常
- 4、`docker logs --tail 10 <outline_container>`查看日志无报错