# HBase at JD

HBaseCon Asia 2017 xingbo peng & bang wen



### 主要内容

- 规模现状
- 应用的业务场景
- 高可用改进
- 运维实践
- 未来展望



#### 规模现状

- 4个数据中心
- 3000+台服务器
- 30+个集群,单集群最大规模400+
- 业务实例600+
- 用户1000+



### 基础版本

■ 0.92-><del>0.94</del> -> 0.96 -> 0.98 -> 1.0 ->1.1




#### 应用业务场景

- 罗盘(商家、供应商、品牌)
- 个性化推荐
- 商品评价/会员PLUS
- 风控/白条/支付/资管(金融)
- 订单/青龙
- MDC/UMP/CAP/JDH/监控大屏



#### 应用业务场景-商智

- 数据罗盘
- 存储600T
- 表620+
- 类sql查询
- 1100w/tps





### 应用业务场景-推荐


- 首页、商详、 购物车
- 存储130T
- 表700+
- TP999<200ms
- 300w/tps





#### 应用业务场景-MDC

- 统一监控平台
- 物理机5.8w, 容器近10w
- 用户2700+
- Metric 5大类,31小类
- 日增量1.6 TB





### 应用业务场景-监控大屏






### 高可用改进

- RSGroup
- Security
- Replication
- Client
- Tuning
- Other



### **RS** Group

- HBASE-6721 RSGROUP
- 多租户业务分级(独立、共享)
- 差异化配置管理
- 移动分组滚动重启
- 资源弹性管理
- 成本核算







Home

Table Details

Local Logs

Log Level Debug Dump

Metrics Dump

HBase Configuration

#### **RS** Group


Group	Region Server Num	Table Num	Region Num	Load average	RequestPerSecond	StoreFile Size
pop_oplog	6	3	5584	930.67	18756	36971404
monitor	3	73	177	59.00	31859	730262
mdc	50	13	18484	369.68	29941	259529530
sd	30	35	9069	302.30	45132	78942185
friendsgo	3	29	663	221.00	866	4096335
ai_image	15	5	25	1.67	41	297
ptcp_jiaoyi_usertracer	30	11	25175	839.17	98560	172758503
tmp_qianyi	113	6	2881	25.50	12124	19880602
default	30	248	4782	159.40	40252	30802246
sr_mon	3	10	334	111.33	28093	1932907
fdm	20	105	5542	277.10	23239	26606976

### Security

- Hadoop集群安全
  - JDHadoop 版本
  - Whitelist, Blacklist, Otherlist
  - SecurityPathLists
- HBase权限
  - 服务端:认证、授权, SASL+IP 实现
  - 客户端: InstanceID+AccessKey



#### HBase鉴权流程图





#### Replication

- HBASE-13153 Bulk Loaded HFile Replication
- HBASE-15809 Basic Replication WebUI
- HBASE-16447 Replication by namespaces config in peer
- HBASE-11393 Replication TableCfs should be a PB object rather than a string
- HBASE-17698 ReplicationEndpoint choosing sinks




#### Client

- 一键切换
  - 主库异常,服务故障转移
  - 数据迁移
  - 秒级切换
  - 集群、分组、实例



#### 一键切换-架构





### 一键切换-迁移





プJD.京东 COM

### Tuning

- Compaction 优化
- Hlogs参数优化
- 堆外内存
- 读写队列分离
- GC参数优化
- Quota
- 分布式Log Replay



#### other

- HBASE-14644 Region in transition metric is broken
- HBASE-14963 Remove use of Guava Stopwatch from HBase client code
- HBASE-15319 clearJmxCache does not take effect actually



### 运维实践




#### 监控

- Mummut监控
  - 目标:集群jmx、日志、服务器运行指标等信息
  - 处理能力: 秒级8Kw
  - 架构实现: tcollector + celery + redis + tsdb + granfa + bdp\_phoenix
- 其它监控
  - ganglia mdc ops ump
- 巡检

基础服务、磁盘健康、SWOP、连接数、僵尸进程、集群配置




### 监控-Mammut





### 监控-Mammut




#### 告警

- 报警方式:
  - 短信、邮件、咚咚
  - 监控中心7x24小时,方法性能调用次数、可用率
- Metric:
  - AverageLoad, sizeOfLogQueue, ritCount, DeadRegionServer, numActiveHandler, numCallGeneralQueue



### 集群迁移


**0.94->1.1** 






### 集群迁移

**1**.1->1.1





### 管理平台





### JDHBase生态



### 未来展望




#### Phoenix

- 版本: 4.10
- Patch
  - PHOENIX-3757 System mutex table not being created in SYSTEM namespace when namespace mapping is enabled
  - PHOENIX-3756 Users lacking ADMIN on 'SYSTEM' HBase namespace can't connect to Phoenix
- 改进
  - 适配jdhbase认证机制
  - 支持多用户同时登陆,改造cache用户逻辑



#### Phoenix





### 容器化部署

■ k8s, 预发布环境



## 感谢!

#### 我们联系方式,hbase@jd.com

# 急平台强 618平台保障来护航 饕

