

	60 km/h $\mu = 1.0$	100 km/h $\mu = 1.0$	130 km/h $\mu = 1.0$	60 km/h $\mu = 0.5$	100 km/h $\mu = 0.5$	130 km/h $\mu = 0.5$
TTC 10 s	S S S S S	S S S S S	S S S S S	S S S S S	S S S S S	S S S S S
TTC 7 s	S S S S S	S S S S S	S S S S S	S S S S S	S S S S S	P P P S P
TTC 5 s	P P P S P	P P P P P	P P P P P	P P P S P	P P P P P	U P P P P
TTC 3 s	P P P P P	P P P P P	U U U P P	U U U P P	U U U U U	U U U U U
TTC 2 s	U U U P P	U U U U U	U U U U U	U U U U U	U U U U U	U U U U U
	P0-E P0-U P1 P2-E P2-U	P0-E P0-U P1 P2-E P2-U	P0-E P0-U P1 P2-E P2-U	P0-E P0-U P1 P2-E P2-U	P0-E P0-U P1 P2-E P2-U	P0-E P0-U P1 P2-E P2-U

□ S = ROBUSTLY SATISFIED

■ U = ROBUSTLY UNSATISFIED

▒ P = PARAMETER-SENSITIVE

▢ thick outline: changes to PARAMETER-SENSITIVE with t1 upper bound 4 s (supplement, sensitivity only)

Branches are counterfactual model branches, not observed D003 automation: P0 hold, P1 passive drag, P2 supported deceleration;
 -E authority at effective control, -U uncertain authority (f.t1). Classification by time margins with $\varepsilon = 0.01$ s; no case lies within ± 0.01 s of the boundary.