Extension: extensions/vla_handover_feasibility (v0.2.0) | Genuine AutoVLA Inference (Qwen2.5-VL-3B + 2048 Physical Action Tokens)

Original 42 Claims Frozen & Unmodified | 11-Point Provenance Verified

VLA-Informed Handover Feasibility Analysis — Research Evaluation Dashboard

Central Research Question: Under what conditions do VLA-generated driving trajectories violate specified vehicle-dynamics constraints, and how does the available braking-only human fallback margin change under explicitly defined takeover-request timing assumptions?

Model: AutoVLA (ucla-mobility/AutoVLA)
Checkpoint: `Zewei-Zhou/AutoVLA/AutoVLA_PDMS_89.ckpt`
Dataset: nuPlan / OpenScene / NAVSIM Mini (7 Real Scenes)
Manifest SHA-256: `8b8d77f168cda99a...`
Predicts Takeover Request?: No (False — Evaluated Counterfactually)

---

1. Genuine VLA Trajectory Source (Phase B)
All 7 trajectories are decoded from real AutoVLA forward passes on 12-frame multi-view camera history and ego kinematics. AutoVLA does not output a takeover request signal.

2. Independent Trajectory Verifier (Phase C)
Evaluates continuity, speed, acceleration, braking, yaw rate, Kamm friction circle, and initial-state acceleration consistency (C1–C10) on the 0.5 s grid. Passing checks does *not* establish safety.

3. Counterfactual R3B Fallback (Phase D/E)
Connects ego states to frozen R3B braking-only bounds across transition policies P0 (hold speed), P1 (passive drag), and P2 (supported decel 1–3 m/s²). Any state with an assumed obstacle distance d_0 or $\tau_{req} > 0$ is explicitly badged as counterfactual/hypothetical.

4. Explicit Insufficient-Evidence Boundaries
TTC is never inferred from images alone. Open-road scenes without an assumed d_0, stationary ego scenes ($v_0 \leq 0.05$ m/s), and turning trajectories leaving the ±1.75 m corridor return `INSUFFICIENT_EVIDENCE_OR_NOT_APPLICABLE`.

EXECUTIVE RESEARCH SUMMARY

Key Empirical Findings Across the 7 Real nuPlan / NAVSIM Driving Scenes (Click Any Finding to Inspect)

7 Genuine VLA Predictions • 1,011 Parameter-Sweep Rows (Counterfactual Grid, Not 1,011 Independent Scenes)

Finding 1 — High-Speed & Arterial Accuracy

EXT-VLA-C01

In steady forward cruising (**Scene 01**, v_0 = 13.58 m/s; **Scene 04**, v_0 = 6.21 m/s) and intersection turns (**Scene 06**, v_0 = 8.78 m/s), AutoVLA satisfies all C1–C10 checks with **ADE = 0.36–0.66 m** and **FDE = 0.76–2.09 m**.

Finding 2 — Active-Braking Prompt Norm Limitation

EXT-VLA-C03

In **Scene 05** (observed $a_{x,0}$ = −1.5525 m/s²), AutoVLA's prompt passes unsigned norm `1.56 m/s²`. After Step 1 (−0.88 m/s²), the plan reverses to **+1.5442 m/s² at Step 3**, violating `C10` ($|a_{lon,3} - a_{x,0}|$ = 3.10 m/s² > 2.50 m/s², **FDE = 12.90 m**).

Finding 3 — Wet-Road Lateral & Timing Erosion

EXT-VLA-C04

In **Scene 02** (v_0 = 6.95 m/s, observed stationary obstacle d_0 = 55.49 m), wet-road urban turning bound is violated ($|a_{lat}|$ = 2.27 m/s² > 2.0 m/s²). Across scenes, delaying τ_{req} erodes R3B margins from positive to violated (P0 fails earliest; P2 preserves margin longest).

Finding 4 — Explicit Evidence Boundaries

EXT-VLA-C05

R3B evaluation is withheld in open-road observed mode (**Scene 01, 05, 06**), stationary ego baseline (**Scene 07**, v_0 = 0.0019 m/s), and turning states exiting the ±1.75 m / ±0.35 rad 1D corridor (**Scene 02** $\tau_{req} \geq 1.5$ s, **Scene 06** $\tau_{req} \geq 2.0$ s).

Methodological Limitation — Driving-Command Conditioning & Future-Displacement Leakage Risk (EXT-VLA-C06): In **Scene 02** (`scene_02_stationary_lead_obstacle`, $y_{GT}(3.0\text{ s})$ = +4.51 m, $y_{GT}(5.0\text{ s})$ = +16.67 m) and **Scene 06** (`scene_06_intersection_turn_maneuver`, $y_{GT}(3.0\text{ s})$ = +4.09 m, $y_{GT}(5.0\text{ s})$ = +8.35 m), the effective `"turn left"` prompt command corresponds to future ground-truth lateral displacement rather than an independent pre-trip navigation signal (and when an unknown raw command is resolved from future lateral displacement, this constitutes future-information leakage). Recorded inference inputs are preserved unmodified for provenance integrity, and affected ADE/FDE metrics are bounded as command-conditioned evaluations rather than strictly leakage-free blind predictions.

1. Driving Scenario & Genuine VLA Prediction (7 Scenes)

scene_05_active_braking_deceleration (v0=4.31 m/s, FDE=12.90 m)

2. Obstacle Distance Source & Provenance Mode (Phase D/E)

Counterfactual Assumption: Stationary d0 = 20.00 m

3. Road Friction (μ)

μ = 1.0 (Dry — 9.81 m/s²)

4. Takeover Request τ_{req}: **1.5 s**

0.0s (t_0) 1.5s 3.0s

Active Selection: `scene_05_active_braking_deceleration` nuPlan Token: `b49c80be2d0d5bb9` (idx 181)

| Ego t_0: v_0 = 4.31 m/s, $a_{x,0}$ = -1.55 m/s² (Prompt $\|a_0\|$ = 1.56 m/s²)

Obstacle Mode: COUNTERFACTUAL ASSUMPTION (Assumed Stationary Obstacle d0 = 20.00 m) | μ = 1.0 | τ_{req} = 1.5 s

Multi-View Camera Observations at Evaluation Timestamp t_0 = 0.0 s

`us-nv-las-vegas-strip | log-0019-scene-0006 | token=b49c80be2d0d5bb9`

Front-Left (CAM_L0)

CAM_L0 (Front-Left @ t0) token=b49c80be2d0d5bb9

scene_05_active_braking_deceleration

SHA-256: e628817b34646fd14e61... (225.9 KB)

Input: 4 frames @ 2.0 Hz (100,352 px/frame)

nuPlan / OpenScene Sensor Provenance Verified

Raw camera JPEG excluded from Git redistribution
(CC BY-NC-SA 4.0 — stream via extract_navsim_scenes.py)

Front Center (CAM_F0)

CAM_F0 (Front-Center @ t0) token=b49c80be2d0d5bb9

scene_05_active_braking_deceleration

SHA-256: 867ef25e02fd43108ae3... (198.7 KB)

Input: 4 frames @ 2.0 Hz (100,352 px/frame)

nuPlan / OpenScene Sensor Provenance Verified

Raw camera JPEG excluded from Git redistribution
(CC BY-NC-SA 4.0 — stream via extract_navsim_scenes.py)

Front-Right (CAM_R0)

CAM_R0 (Front-Right @ t0) token=b49c80be2d0d5bb9

scene_05_active_braking_deceleration

SHA-256: d7257674a885200b5a6a... (222.0 KB)

Input: 4 frames @ 2.0 Hz (100,352 px/frame)

nuPlan / OpenScene Sensor Provenance Verified

Raw camera JPEG excluded from Git redistribution
(CC BY-NC-SA 4.0 — stream via extract_navsim_scenes.py)

Active longitudinal deceleration scene; evaluates whether AutoVLA continues or relaxes deceleration and how reduced future speed along the VLA trajectory alters delayed takeover braking margins.

Genuine AutoVLA Output & Observed t_0 State

10/10 Action Tokens Verified

Observed Speed v_0 **4.31 m/s (15.5 km/h)**	Observed $a_{x,0}$ / Prompt $\|a_0\|$ **-1.55 / 1.56 m/s²**	Driving Command **KEEP FORWARD**
Observed 3D Corridor Lead **None in +-1.75m corridor**	ADE / FDE vs. Logged GT **6.25 m / 12.90 m**	Inference Latency **37861 ms (MPS)**

Exact Input Prompt & Raw AutoVLA Action Tokens (10 steps, Δt = 0.5 s):

```
Prompt: Suppose you are driving, and I'm providing you with the image captured by the car's <FRONT VIEW>, <FRONT LEFT VIEW>, <FRONT RIGHT VIEW>,
theego velocity is 4.31 m/s, the ego acceleration is 1.56 m/s^2, and the driving command is keep forward. Generate the planned trajectory for the
next 5 seconds.

Generated Output:
<think>
This is a straightforward scenario, and a direct decision can be made.
</think>
<answer>
```

```
The final output action is: <action_30><action_189><action_66><action_145><action_626><action_147><action_88><action_1497><action_1172><action_42>
</answer>
```

Apple M5 (arm64) | PyTorch 2.14.1 | transformers 5.19.0

Codebook IDs: [30, 189, 66, 145, 626, 147, 88, 1497, 1172, 42]

Priority 3 Deep-Dive — Scene 05 Active-Braking Finding & Controlled Signed-Acceleration Prompt Ablation

Distinguishing Input-Representation Limitation ($\|a(0)\| = 1.56$ m/s²) from Causal Attribution ($a_x(0) = -1.5525$ m/s²)

`CURRENTLY SELECTED SCENE: scene_05_active_braking_deceleration`

---

1. Logged Ground Truth

Brakes 4.31 → 2.29 m/s (t ≤ 2.5 s)

Observed $a_x(0) = -1.5525$ m/s², $a_y(0) = +0.1831$ m/s². Decelerates to x = 6.92 m at t = 2.5 s, then gently accelerates to x = 15.65 m at t = 5.0 s.

2. Standard AutoVLA (Unsigned Norm)

Prompt: "1.56 m/s^2" ($\|a\| = 1.5633$)

Step 1 decelerates ($a_{lon,1} = -0.8841$ m/s²), then reverses at Step 2 (+0.7917 m/s²) and peaks at **Step 3 (+1.5442 m/s²)**, reaching $x_{10} = 28.53$ m (**ADE = 6.25 m, FDE = 12.90 m**).


3. Controlled OOD Signed Ablation

Prompt: "−1.55 m/s^2" (Signed $a_{x,0}$)

Identical images & v_0: sustains braking across Steps 1–7 ($a_{lon} \in [-1.39, -0.88]$ m/s²) to standstill at **$x_{10} = 6.93$ m** (0–2 s braking ADE = **0.14 m**; 5 s ADE = **2.42 m**).

Mandatory Scientific Boundary on Causal Attribution: (1) Passing a negative acceleration string (`−1.55 m/s^2`) is an *out-of-distribution (OOD) prompt intervention* relative to AutoVLA's training interface (`np.linalg.norm(acceleration) ≥ 0`) and is *not* a validated model upgrade. (2) Even under the standard unsigned prompt (`1.56 m/s^2`), Step 1 still decelerates at −0.8841 m/s² from multi-frame visual cues before the trajectory reverses at Steps 2–3. (3) Under the OOD signed prompt, once the vehicle reaches standstill at t = 3.5 s (x = 6.98 m), Step 9 emits a 5.8 cm backward jitter token (`<action_126>`). Thus, unsigned acceleration encoding is a verified **input-representation limitation** and strong contributing factor in Scene 05, not a single-cause deterministic law.

Scene 05 Longitudinal Position x(t) [m] — Standard Unsigned vs. Signed Ablation vs. Logged GT


30m
20m
10m
0m
Unsigned Prompt ("1.56 m/s²", x_10=28.5m)
Signed OOD Ablation ("-1.55 m/s²", x_10=6.9m)
Logged GT (Brakes to 6.9m @ 2.5s, then 15.6m)
0.0s
1.0s
2.0s
3.0s
4.0s
5.0s


PHASE B & C — INDEPENDENT TRAJECTORY FEASIBILITY VERIFIER

VLA Trajectory Geometry & Physical Dynamics Checks (C1–C10)

CONSTRAINTS_VIOLATED


Bird's-Eye View Trajectory in Ego Frame (+x Forward [m], +y Left [m])


1D R3B Corridor: ±1.75 m | Horizon: 5.0 s



Implied Speed Profile v(t) [m/s] vs. Time t [s]

Implied Accel $a_{lon}(t)$ & $|a_{tot}(t)|$ [m/s²] vs. Time t [s]





Physical Constraint Violations Detected (μ = 1.0):

- Longitudinal acceleration state-consistency violation at steps [3, 4]: max |a_lon(t) - a_x(0)|=3.10 m/s^2 > 2.50 m/s^2 (observed a_x(0)=-1.55 m/s^2, step 1 a_lon=-0.88 m/s^2, peak a_lon=+1.54 m/s^2).

Explicit Trajectory Constraint Checks (C1–C10)

Check ID & Condition	Measured Value	Threshold	Status
C1_TIMESTAMP_AND_HORIZON_CONTINUITY Uniform timestamp spacing dt=0.5s across 10 steps num_waypoints=10	0 s	0.002 s	PASS
C2_COORDINATE_AND_UNIT_CONSISTENCY Ego-local frame consistency (+x forward m, +y left m, heading in [-pi, pi] rad, no reverse jumps) Checks min forward body step dx_m and heading bounds.	1.9341 m	−0.08 m	PASS
C3_IMPLIED_SPEED_LIMIT Implied longitudinal speed within [0.0, 35.0] m/s	7.0503 m/s	35 m/s	PASS
C4_LONGITUDINAL_ACCELERATION_LIMIT Longitudinal forward acceleration a_lon <= 4.0 m/s^2	1.5442 m/s^2	4 m/s^2	PASS

Check ID & Condition	Measured Value	Threshold	Status
C5_BRAKING_DEMAND_PLANNING_LIMIT Longitudinal braking demand <= nominal planning bound (4.0 m/s^2)	0.8841 m/s^2	4 m/s^2	PASS
C6_BRAKING_DEMAND_PHYSICAL_LIMIT Longitudinal braking demand <= physical vehicle limit (8.0 m/s^2)	0.8841 m/s^2	8 m/s^2	PASS
C7_LATERAL_ACCELERATION_LIMIT Lateral centripetal acceleration |a_lat| <= 4.5 m/s^2	0.3562 m/s^2	4.5 m/s^2	PASS
C8_YAW_RATE_LIMIT Yaw rate |dpsi/dt| <= 0.75 rad/s	0.0554 rad/s	0.75 rad/s	PASS
C9_FRICTION_CIRCLE_LIMIT Combined horizontal acceleration sqrt(a_lon^2 + a_lat^2) <= mu*g (9.81 m/s^2 at mu=1.0)	1.5442 m/s^2	9.81 m/s^2	PASS
C10_LONGITUDINAL_ACCEL_STATE_CONSISTENCY Active-motion longitudinal acceleration deviation |a_lon(t) - a_x(0)| <= 2.5 m/s^2 (observed a_x(0)=-1.55 m/s^2) step_1 a_lon=-0.8841 m/s^2, peak a_lon=+1.5442 m/s^2; detects active-braking to positive-acceleration reversals.	3.0967 m/s^2	2.5 m/s^2	VIOLATED (steps 3,4)

Trajectory Demand vs. Road-Friction Cap (μ·g [m/s²])

Friction μ	μ·g Cap	Max Braking	Max $\|a_{tot}\|$	Kamm Friction-Circle Status
μ = 1.00	9.81 m/s²	0.88 m/s²	1.54 m/s²	WITHIN CAP (+8.27 m/s²)
μ = 0.70	6.87 m/s²	0.88 m/s²	1.54 m/s²	WITHIN CAP (+5.32 m/s²)
μ = 0.50	4.91 m/s²	0.88 m/s²	1.54 m/s²	WITHIN CAP (+3.36 m/s²)
μ = 0.35	3.43 m/s²	0.88 m/s²	1.54 m/s²	WITHIN CAP (+1.89 m/s²)

PHASE D & E — COUNTERFACTUAL R3B BRAKING-ONLY FALLBACK ADAPTER

Recoverability Margin Across Takeover Request Timing τ_{req}

COUNTERFACTUAL ASSUMPTION (Assumed Stationary Obstacle d0 = 20.00 m)

At τ_{req} = 1.5 s: Hypothetical VLA + Assumed Obstacle (d_0)

x=6.58m, v=5.04m/s, d_{rem}=13.42m, TTC=2.66s

P0 (Hold Speed in t1)
M_d: [−9.2, 3.3] m
M_t: [−1.82, 0.65] s
PARAMETER_SENSITIVE


P1 (Passive Drag in t1)
M_d: [−8.0, 3.6] m
M_t: [−1.59, 0.71] s
PARAMETER_SENSITIVE

P2 (Supported Decel 1–3 m/s²)
M_d: [−0.7, 7.2] m
M_t: [−0.14, 1.43] s
PARAMETER_SENSITIVE

Braking-Only Distance Margin M_d [m] vs. Takeover Request Time τ_{req} [s]

Road Friction mu = 1.0

Shared R3B latency box: $t_1 \in [1.15, 3.00]$ s (TOR → effective braking), $t_2 \in [0.05, 0.17]$ s, $t_3 \in [0.30, 1.20]$ s, $a_{max} \in [6.43, 9.10]$ m/s² capped by μ·g.



Complete Scenario State Provenance Notice: At tau_req = 1.5 s, ego position and speed are derived from the hypothetical VLA-predicted trajectory AND the stationary obstacle distance (d0 = 20.00 m) is a COUNTERFACTUAL ASSUMPTION. (Code token: `HYPOTHETICAL_VLA_STATE_PLUS_ASSUMED_OBSTACLE_D0`)

Takeover Timing & Pre-Control Transition Policy Comparison (P0 / P1 / P2)

Cells show [conservative, optimistic] distance margin [m] and time margin [s]

τ_{req}	Complete Scenario State Provenance	$v(\tau_{req})$	d_{rem}	TTC	P0 (Hold Speed)	P1 (Passive Drag)	P2 (Supported Decel)
0.0s	Observed Ego (t_0) + Assumed Obstacle (d_0)	4.31 m/s	20.00 m	4.64 s	[0.7, 11.2] m [0.16, 2.60] s	[1.8, 11.5] m [0.42, 2.67] s	[8.7, 14.9] m [2.03, 3.46] s
0.5s	Hypothetical VLA + Assumed Obstacle (d_0)	3.87 m/s	18.07 m	4.67 s	[0.7, 10.1] m [0.18, 2.60] s	[1.8, 10.4] m [0.46, 2.68] s	[8.5, 13.6] m [2.19, 3.51] s
1.0s	Hypothetical VLA + Assumed Obstacle (d_0)	4.26 m/s	15.93 m	3.74 s	[-3.2, 7.2] m [-0.74, 1.69] s	[-2.1, 7.5] m [-0.49, 1.77] s	[4.8, 10.9] m [1.14, 2.56] s
1.5s	Hypothetical VLA + Assumed Obstacle (d_0)	5.04 m/s	13.42 m	2.66 s	[-9.2, 3.3] m [-1.82, 0.65] s	[-8.0, 3.6] m [-1.59, 0.71] s	[-0.7, 7.2] m [-0.14, 1.43] s
2.0s	Hypothetical VLA + Assumed Obstacle (d_0)	5.56 m/s	10.63 m	1.91 s	[-14.4, -0.5] m [-2.58, -0.10] s	[-13.2, -0.2] m [-2.37, -0.03] s	[-5.7, 3.6] m [-1.02, 0.64] s
2.5s	Hypothetical VLA + Assumed Obstacle (d_0)	5.75 m/s	7.76 m	1.35 s	[-18.1, -3.8] m [-3.15, -0.66] s	[-16.9, -3.4] m [-2.94, -0.59] s	[-9.3, 0.4] m [-1.62, 0.07] s
3.0s	Hypothetical VLA + Assumed Obstacle (d_0)	6.06 m/s	4.73 m	0.78 s	[-22.6, -7.4] m [-3.73, -1.23] s	[-21.4, -7.1] m [-3.53, -1.17] s	[-13.6, -3.1] m [-2.25, -0.51] s

Cross-Scenario Provenance & Evaluation Overview (All 7 Real Scenes)

Click any row to load scenario

Scene ID & nuPlan Token	v_0 / $a_{x,0}$	ADE / FDE	Dry (μ=1.0)	Wet (μ=0.5)	3D Corridor Lead
scene_01_high_speed_open_road token=5143e810d84656d0 | cmd='keep forward'	13.58 m/s −0.15 m/s²	0.36 m FDE 0.76 m	CONSTRAINTS_SATISFIED	CONSTRAINTS_SATISFIED	None (Open Road)
scene_02_stationary_lead_obstacle token=3cacb287d398542f | cmd='turn left'	6.95 m/s +1.30 m/s²	2.42 m FDE 3.47 m	CONSTRAINTS_SATISFIED	CONSTRAINTS_VIOLATED	55.49 m (v=0.0 m/s)
scene_03_close_urban_lead_following token=7a524614561c54ef | cmd='keep forward'	13.05 m/s +0.09 m/s²	1.03 m FDE 2.27 m	CONSTRAINTS_SATISFIED	CONSTRAINTS_SATISFIED	37.30 m (v=4.6 m/s)
scene_04_fast_arterial_lead_vehicle token=c48640204ad758c4 | cmd='keep forward'	6.21 m/s −0.07 m/s²	0.54 m FDE 2.09 m	CONSTRAINTS_SATISFIED	CONSTRAINTS_SATISFIED	68.00 m (v=14.0 m/s)
scene_05_active_braking_deceleration token=b49c80be2d0d5bb9 | cmd='keep forward'	4.31 m/s −1.55 m/s²	6.25 m FDE 12.90 m	CONSTRAINTS_VIOLATED	CONSTRAINTS_VIOLATED	None (Open Road)
scene_06_intersection_turn_maneuver token=c9d4d04945e85ef8 | cmd='turn left'	8.78 m/s −0.40 m/s²	0.66 m FDE 1.88 m	CONSTRAINTS_SATISFIED	CONSTRAINTS_SATISFIED	None (Open Road)

Scene ID & nuPlan Token	v_0 / $a_{x,0}$	ADE / FDE	Dry (μ=1.0)	Wet (μ=0.5)	3D Corridor Lead
scene_07_stationary_ego_baseline token=e9138a74627452c2 | cmd='keep forward'	0.00 m/s −0.02 m/s²	3.93 m FDE 10.10 m	INSUFFICIENT_EVIDENCE_OR_NOT_APPLICABLE	INSUFFICIENT_EVIDENCE_OR_NOT_APPLICABLE	None (Open Road)

Independent Extension Evidence Register (EXT-VLA-C01 – EXT-VLA-C05)

ID	Category	Verified Finding & Scope Boundary
EXT-VLA-C01 **VERIFIED**	**GENUINE_VLA_EXECUTION** Phase A/B	AutoVLA (Zewei-Zhou/AutoVLA AutoVLA_PDMS_89.ckpt, 825 tensors on Qwen2.5-VL-3B-Instruct + 2048 physical action tokens) executes genuine multi-view camera + kinematics trajectory inference locally on Apple M5 after mapping legacy transformers 4.49 state_dict keys (autovla.vlm.model.* -> model.language_model.*, autovla.vlm.visual.* -> model.visual.*) with strict=True. *Scope & Boundaries:* Verified on 7 completed genuine nuPlan/NAVSIM mini scene prediction(s) (e.g. scene_01 fast latency=162954.86 ms, scene_03 ADE=1.0267 m vs human log). AutoVLA outputs 10 ego-frame poses over 5.0 s (dt=0.5 s) and does not output a takeover request. Prompts are conditioned on NAVSIM/OpenScene driving commands (see EXT-VLA-C06 on future-displacement command leakage).
EXT-VLA-C02 **VERIFIED**	**CANDIDATE_MODEL_BLOCKER** Phase A	OpenDriveVLA (DriveVLA/OpenDriveVLA-0.5B/3B/7B) is blocked for unauthenticated local Apple Silicon execution due to gated Hugging Face checkpoint access (HTTP 401) and mandatory NVIDIA CUDA C++ Deformable Attention ops (mmcv-full==1.7.2, mmdet3d==1.0.0rc6) plus pre-extracted UniAD 3D queries. *Scope & Boundaries:* Documented in Phase A feasibility audit; AutoVLA was selected as the publicly accessible, runnable driving VLA.
EXT-VLA-C03 **VERIFIED**	**TRAJECTORY_FEASIBILITY_VERIFIER** Phase C	AutoVLA's prompt interface encodes ego acceleration as an unsigned 2D Euclidean norm (||a|| = 1.5633 m/s^2 -> '1.56 m/s^2' in scene_05_active_braking_deceleration where observed a_x(0) = -1.5525 m/s^2). After Step 1 deceleration (-0.8841 m/s^2), the predicted trajectory reverses into positive acceleration at Step 2 (+0.7917 m/s^2) and peaks at Step 3 (+1.5442 m/s^2), violating C10 longitudinal acceleration state consistency (|a_lon(3) - a_x(0)| = 3.0967 m/s^2 > 2.50 m/s^2, ADE = 6.25 m, FDE = 12.90 m); under wet-road limits (mu = 0.5) scene_02 violates C7 lateral acceleration bounds (2.2721 m/s^2 > 2.0 m/s^2).

ID	Category	Verified Finding & Scope Boundary
EXT-VLA-C04 **VERIFIED**	**TAKEOVER_TIMING_SENSITIVITY** Phase D/E	*Scope & Boundaries:* A controlled single-variable OOD prompt ablation ('-1.55 m/s^2') on scene_05 restores sustained braking across Steps 1-7 to standstill (x_10 = 6.93 m, ADE = 2.42 m), confirming prompt sign sensitivity while showing that visual context still drives Step 1 and OOD negative prompting is a single-scene diagnostic rather than a validated model fix. Under the counterfactual assumption that the ego vehicle follows the VLA-predicted trajectory until a delayed takeover request time tau_req > 0, forward ego progress reduces remaining obstacle distance d(tau_req) = d0 - x_VLA(tau_req), shifting R3B braking-only recoverability margins from UNIFORMLY_POSITIVE at tau_req = 0.0 s to PARAMETER_SENSITIVE and UNIFORMLY_VIOLATED at later request times, with P0 (constant-speed pre-control) and wet road (mu=0.5) violating earliest. *Scope & Boundaries:* Counterfactual analytical bound reusing frozen R3B equations. Future states along VLA trajectories are hypothetical predictions, not observed vehicle motion or empirical human braking responses.
EXT-VLA-C05 **VERIFIED**	**INSUFFICIENT_EVIDENCE_BOUNDARIES** Phase C/D/E	Evaluation explicitly withholds R3B recoverability claims (returning INSUFFICIENT_EVIDENCE_OR_NOT_APPLICABLE) in three distinct regimes: (1) open-road scenes without an observed 3D in-lane obstacle when no counterfactual d0 is assumed, (2) stationary ego scenes (v0 <= 0.05 m/s) where braking-only stopping bounds are not applicable, and (3) turning maneuvers once hypothetical lateral displacement |y(tau_req)| > 1.75 m or heading |psi(tau_req)| > 0.35 rad departs the 1D longitudinal corridor. *Scope & Boundaries:* Demonstrated on real scenes scene_01_high_speed_open_road, scene_02_stationary_lead_obstacle, scene_07_stationary_ego_baseline (v0=0.0019 m/s), and scene_06_intersection_turn_maneuver (cmd='turn left').
EXT-VLA-C06 **VERIFIED**	**COMMAND_LEAKAGE_METHODOLOGICAL_BOUNDARY** Phase B/E	In scene_02_stationary_lead_obstacle (y_GT(3.0s) = +4.5128 m, y_GT(5.0s) = +16.6678 m) and scene_06_intersection_turn_maneuver (y_GT(3.0s) = +4.0889 m, y_GT(5.0s) = +8.3498 m), the effective 'turn left' driving command reflects future ground-truth lateral displacement rather than an independent pre-trip navigation command. Resolving an unknown command from future ground-truth displacement—or conditioning on NAVSIM/OpenScene future-displacement-derived commands—constitutes future-information leakage for trajectory-prediction evaluation. *Scope & Boundaries:* Recorded inference inputs are preserved unmodified for provenance integrity, but ADE/FDE metrics on command-conditioned scenes (especially scene_02 and scene_06) must not be interpreted as strictly leakage-free blind trajectory predictions.