RAJALAKSHMI ENGINEERING COLLEGE

Fenulin E 251701012-2025-CSD F2

Started on	Monday, 28 September 2026, 10:21 PM
State	Finished
Completed on	Monday, 28 September 2026, 10:30 PM
Time taken	8 mins 26 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int majority(int a[],int l,int r)
{
    if(l==r)
    {
        return a[l];
    }
    int mid=(l+r)/2;
    int x=majority(a,l,mid);
    int y=majority(a,mid+1,r);
    if(x==y)
    {
        return x;
    }
    int cx=0,cy=0;
    for(int i=l;i<=r;i++)
    {
        if(a[i]==x)
        {
            cx++;
        }
        if(a[i]==y)
        {
            cy=0;
        }
    }
    if(cx>cy)
    {
        return x;
    }
    else
    {
        return y;
    }
```

```
}
int main()
{
    int a;
    scanf("%d",&a);
    int arr[a];
    for(int i=0;i<a;i++)
    {
        scanf("%d",&arr[i]);
    }
    printf("%d",majority(arr,0,a-1));
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course