




REFERENCE DOCUMENTS

P&ID LEGEND	PRO13-ING-PRO0
PROCESS FLOW DIAGRAM	21044-PR-PID-00000
UTILITY FLOW DIAGRAM	PRO10-ING-PR01/02/03/04
MATERIAL SELECTION DIAGRAM	21044-PR-PFD-00001
	PRO10-ING-PR11
	21044-PR-UFD-00001
	PRO08-ING-FR01
	21044-PR-MSD-00001

INSTRUMENT SUPPLY AIR

ISA 0X

NOTES:

----- TAM SUPPLY LIMIT

1	25 Mar 2026	ISSUE FOR COMMISSIONING	TAM (JB)	TAM (MM)	LCAMPLONE
0	08 Jan 2026	AS BUILT	TAM (JB)	LCAMPLONE	W.BOUALALI
Rev.	Date	Description	Draft	Check'd	Approved

Customer: MANAENERGY

Contractor: ITALFLUID

Engineering: ITALFLUID

Technology Vendor: TECHNICAL AMERICA INC

OFFICES: Mahaj Riad Center, Batiment 6, 3eme etage, Avenue Al Az, Hay Ryad, 10100 Rabat, Morocco

OFFICES: VIA VVALDI,4 MONTESILVANO (ITALY) Tel.+39 085 4224374 fax+39 085 4220742

OFFICES: VIA VVALDI,4 MONTESILVANO (ITALY) Tel.+39 085 4224374 fax+39 085 4220742


OFFICES: 301 N Smith Avenue, 92880 Corona, California (USA) Ph.+1 951 272 9540

TITLE: LNG TENDRARA PLANT

OBJECT: P&ID PACKAGE PK-351-6 (UNIT 350)

TYPE	SCALE	DOCUMENTS ID:	VENDOR DOC CODE:	SHEET/OF
A1	N/A	PRO13-ING-PR18	21044-PR-PID-35006	1/3

C-351H-6		MC-351H-6	
MR COMPRESSOR HP 6		MR COMPRESSOR HP MOTOR 6	
SPEED	2950 rpm	SPEED	2950 rpm
SWEEP VOLUME	1997 m3/h	RATED POWER	560 kW
VI	2.2	VOLTAGE	690 Vdc
MODEL	WP-W36S-28	FREQUENCY	50 Hz
MANUFACTURER	GEA	STARTING	VFD
CASING DESIGN PRESSURE	28 barg	ENCLOSURE PROTECTION	IP55
CASING DESIGN TEMPERATURE	-60/120 °C	STD	IEC
CASING MATERIAL	CAST IRON	FRAME SIZE	355L



REFERENCE DOCUMENTS


P&ID LEGEND	PRO13-ING-PRO0
PROCESS FLOW DIAGRAM	21044-PR-PID-00000
UTILITY FLOW DIAGRAM	PRO10-ING-PR01/02/03/04
MATERIAL SELECTION DIAGRAM	21044-PR-PFD-00001
	PRO10-ING-PR11
	21044-PR-UFD-00001
	PRO08-ING-FR01
	21044-PR-MSD-00001

INSTRUMENT SUPPLY AIR

NOTES:

----- TAM SUPPLY LIMIT

1	25 Mar 2026	ISSUE FOR COMMISSIONING	TAM (JB)	TAM (MM)	LCAMPLONE
0	08 Jan 2026	AS BUILT	TAM (JB)	LCAMPLONE	W.BOUALALI
Rev.	Date	Description	Draft	Check'd	Approved
Customer: MANAENERGY			Offices: Mahaj Riad Center, Batiment 6, 3eme etage, Avenue Al Az, Hay Ryad, 10100 Rabat, Morocco		
Contractor: ITALFLUID			Offices: VIA VVALDI,4 MONTESILVANO (ITALY) Tel.+39 085 4224374 fax+39 085 4220742		
Engineering: ITALFLUID			Offices: VIA VVALDI,4 MONTESILVANO (ITALY) Tel.+39 085 4224374 fax+39 085 4220742		
Technology Vendor: TECHNICAL AMERICA INC			Offices: 301 N Smith Avenue, 92880 Corona, California (USA) Ph.+1 951 272 9540		
TITLE: LNG TENDRARA PLANT			OBJECT: P&ID PACKAGE PK-351-6 (UNIT 350)		
TYPE	SCALE	DOCUMENTS ID:	VENDOR DOC CODE:		SHEET/OF
A1	N/A	PRO13-ING-PR18	21044-PR-PID-35006		2/3



REFERENCE DOCUMENTS

P&ID LEGEND	PRO13-ING-PROO
PROCESS FLOW DIAGRAM	21044-PR-PID-00000
UTILITY FLOW DIAGRAM	PRO10-ING-PRO1/02/03/04
MATERIAL SELECTION DIAGRAM	21044-PR-PFD-00001
	PRO10-ING-PR11
	21044-PR-UFD-00001
	PRO08-ING-FR01
	21044-PR-MSD-00001

V-351-6

OIL SEPARATOR

DESIGN PRESSURE	28 bar g
DESIGN TEMPERATURE	-15/120 °C
VOLAGE	965 00 mm
DIAMETER	5000 mm
SM TO SM	0 mm
CORROSION ALLOWANCE	0 mm
INSULATION	NO
LINING/CLADDING	N.A.
MATERIAL	CS
INTERNAL VOLUME	3.4 m3
INTERNAL ELEMENTS	COALESCEERS

MP-351-6

OIL PUMP ELECTRIC MOTOR

SPEED	1450 rpm
RATED POWER	4 kW
VOLAGE	690 Vac
FREQUENCY	50 Hz
STARTING	DOL
ENCLOSURE PROTECTION	IP55
STD	IEC
FRAME SIZE	112

F-351-6A/B

HP COMP. MAIN OIL FILTER

DESIGN PRESSURE	34 bar g
DESIGN TEMPERATURE	-15/120 °C
DIAMETER	8" NPS
SM TO SM	600 mm
CORROSION ALLOWANCE	0 mm
INSULATION	NO
LINING/CLADDING	N.A.
MATERIAL	CS
INTERNAL VOLUME	0.01 m3
INTERNAL ELEMENTS	PARTICULATE FILTER

MF-351-6-1...10

OIL COOLER FAN ELECTRIC MOTORS

SPEED	1450 rpm
RATED POWER	4 kW
VOLAGE	400/3 Vac
FREQUENCY	50 Hz
STARTING	DOL
ENCLOSURE PROTECTION	IP55
STD	IEC
FRAME SIZE	112M

F-351-6-1...10

FAN

SPEED	1450 rpm
RATED CAPACITY	27634 m3/h
ABSORBED POWER	3 kW

P-351-6

OIL PUMP

SPEED	1450 rpm
RATED CAPACITY	110 l/min
HEAD	4 bar
TYPE	VOLUMETRIC
MANUFACTURER	KRACHT
CASING DESIGN PRESSURE	34 barg
CASING DESIGN TEMPERATURE	-15/120 °C
MODEL	KF80
MOTOR POWER	4 kW
CASING MATERIAL	CI

X-351-6

OIL HEATER

RATED POWER	2.25 (3x 0.75) kW
SUPPLY VOLTAGE	690 Vac-50Hz-3ph

F-351-6

OIL COOLER

DESIGN DUTY	380 kW
DESIGN PRESSURE	28 / 34 bar g
DESIGN TEMP.	-15/120 °C
MATERIAL	AS304 / A1 in
CORR. ALL.	0 mm
FAN Qty	10
FAN ABS POWER each	3 kW
SURFACE AREA	4304 m2

F-351-6C/D

LP COMP. MAIN OIL FILTER

DESIGN PRESSURE	28 bar g
DESIGN TEMPERATURE	-15/120 °C
DIAMETER	8" NPS
SM TO SM	1000 mm
CORROSION ALLOWANCE	0 mm
INSULATION	NO
LINING/CLADDING	N.A.
MATERIAL	CS
INTERNAL VOLUME	0.033 m3
INTERNAL ELEMENTS	PARTICULATE FILTER

NOTES:

OIL COOLER CAN BE SPLIT IN 2 SEPARATE OIL COOLERS OR COMBINED IN ONE OIL COOLER WITH SEPARATE CIRCUIT.

Customer:

MANAENERGY

Contractor:

ITALFLUID

Engineering:

ITALFLUID

Technology Vendor:

TECHNICAL AMERICA INC

OFFICES:

Manajir Rad Center, Batiment 6, 3eme etage, Avenue Al Az, Hay Ryad, 10100 Rabat, Morocco

OFFICES:

VIA VIVALDI,4 MONTESILVANO (ITALY)

Tel.+39 085 4224374 fax+39 085 4220742

OFFICES:

VIA VIVALDI,4 MONTESILVANO (ITALY)

Tel.+39 085 4224374 fax+39 085 4220742

OFFICES:

301 N Smith Avenue, 92880 Corona, California (USA)

Ph.+1 951 272 9540

TITLE:

LNG TENDRARA PLANT

OBJECT:

P&ID PACKAGE PK-351-6 (UNIT 350)

TYPE

A1

SCALE

N/A

DOCUMENTS ID:

PRO13-ING-PR18

VENDOR DOC CODE:

21044-PR-PID-35006

SHEET/OF

3/3