EXTENSION LADDERS

LOUISVILLE.

FE3200 Series Fiberglass Channel Extension Ladder

Type 1A

- The extra heavy duty, channel extension ladder for lighter industrial use
- Full channel non-conductive side rails
- Designed for 300 lb. workload when set at the proper working angle
- D-shaped rungs
- Swivel safety shoes
- Outside slide guides
- Mar-resistant rail end caps
- Quicklatch™

SPECIFICATIONS						
SIZES	RAIL DEPTH	STACK HEIGHT	INSIDE BASE	WIDTH FLY	OUTSIDE BASE	WIDTH FLY
16' - 28'	3-1/4"	5-3/4"	14-11/16"	13-11/16"	17-1/16"	16-1/16"
32 - 40'	3-15/16"	6-1/8"	15-5/16"	14-5/16"	17-11/16	16-11/16"

PART NO.	SIZE	STEP SIZE	BOTTOM WIDTH	SPREAD
FE3220	20'	10"	17"	42"
FE3224	24'	12"	21"	52"
FE3228	28'	14"	25"	58"
FE3232	32'	16"	29"	70"
FE3236	36'	18"	32"	79"
FE3240	40'	20''	35"	93"

LOUISVILLE.

FE7000 Series Fiberglass Plate Connect Extension Ladder

Type 1A

- For all industrial needs
- Full channel non-conductive side rails
- Designed for a 300 lb. workload when set at the proper working angle
- Full metal Boot™
- D-shaped rungs
- Swivel safety shoes
- Outside slide guides
- Mar-resistant rail end caps
- Aluminum plate coonection rungs
- Quicklatch™

SPECIFICATIONS						
SIZES	RAIL DEPTH	STACK HEIGHT	INSIDE BASE	WIDTH FLY	OUTSIDE BASE	WIDTH FLY
16' - 28'	3-1/4"	5-3/4"	14-11/16"	13-11/16"	17-1/16"	16-1/16"
32 - 40'	3-15/16"	6-1/8"	15-5/16"	14-5/16"	17-11/16	16-11/16"

PART NO.	SIZE	STEP SIZE	BOTTOM WIDTH	SPREAD
FE7216	20'	10'	17"	42"
FE7220	24'	12"	21"	52"
FE7224	28'	14"	25"	58"
FE7240	32'	16"	29"	70"

WERNER

Fiberglass D-Rung Extension Ladder

- Exclusive ALFLO® rung joint means TWIST-PROOF® performance
- 1-5/8" slip-resistant TRACTION-TRED® D-rungs
- Smooth operating pulley with polypropylene rope
- Interlocking side rails with internal rail guides on bottom of fly section securely connect rails

PART NO.	SIZE	REACH HEIGHT	MAX. WORKING LENGTH	WEIGHT
D6220-2	20''	19'	17'	44.5 lb.
D6224-2	24'	23'	21'	52 lb.
D6228-2	28'	27'	25'	59.5 lb.
D6232-2	32'	31'	29'	71.5 lb.
D6240-2	40'	37'	35'	195.1 lb.