

Loctite PL 400 VOC Compliant Subfloor & Deck Adhesive

- For all heavy-duty interior or exterior construction
- Bonds dry, wet, frozen and treated lumber to most b uilding materials
- Strong, fast set
- VOC compliant

PART NO.	DESCRIPTION
56668972	10 oz. tube
56668903	28 oz. tube

LOCTITE PL200 VOC CONSTRUCTION ADHESIVE LATEX WHITE

- Formulated for use on drywall, wood paneling and wood or metal studs
- Water based
- Low odor
- Bonds to most building materialsPaintable and water resistant
- Water clean up

PART NO.	DESCRIPTION
56668646	10 oz.
56668648	28 oz.

Liquid Nails

- Will not attack foam insulation
- No harmful fumes
- Water cleanup
- VOC compliant

PART NO.	DESCRIPTION
49607705	Liquid Nails - 10.5 fl. oz.

3M

Super 77™ Multi-Purpose Spray Adhesive

- Finger-touch, targeted control
- Low soak-in for high coverage and strong, long-lasting bond
- High initial grab and aggressive tack
- Bonds quickly in 15 seconds
- Low viscosity formula stays in place with little to no run or migration

PART NO.	DESCRIPTION
49492157	Multi-Purpose Spray Adhesive

3M 90 14.6 OZ HI-STRENGTH 90 SPRAY ADHESIVE

- High contact bond strength
- One-minute dry time
- High temperature resistance
- Non-misting, precise spray control

PART NO.	DESCRIPTION
49492159	14.6 OZ HI-STRENGTH 90 SPRAY ADHESIVE

OSI Quad Max White Elastomeric Polymers Door Siding and Window Sealant 9.5 oz

- Apply in temperature range of 0°F-140°F
- Will not shrink as it cures
- Resists damage from UV exposure
- Does not collect dust and dirt
- Fast 24-hour cure and paintable in 1 hour
- Resistant to bubbling
- GreenGuard® certified

PART NO.	DESCRIPTION
78000	Clear 9 oz Tube
78001	White 9.5 oz Tube

Loctite Power Grab Ultimate Construction Adhesive, Versatile High Strength- 9 fl oz

- Strong and Versatile: Works in all conditions and on most materials, including wet surfaces and can even bond two non-porous surfaces
- Professional Choice: High-quality, easy-to-use construction adhesive for bonding most common construction materials such as wood, plywood, MDF, tile, and more
- Tough Against Weather: Strong adhesion with no shrinkage that's waterproof and resistant against extreme temperatures from 40°F to 104°F for interior and exterior project

PART NO.	DESCRIPTION
76415	Power Grab Ultimate 9 oz Tube

6/15/24 12:52 PM