METACAULK® FIRESTOP SEALANTS

Metacaulk® 1000

Intumescent, Water-Based Firestop Sealant

RECTORSEAL

Features and Benefits:

- Prevents spread of fire through joint openings and through-penetrations
- No dilution or mixing required
- For areas under constant vibration and movement or fire-rated gypsum wallboard partitions, concrete walls or floors, wood floors and concrete or corrugated steel deck floor/ceiling assemblies
- Excellent freeze-thaw
- For interior use - paintable
- VOC compliant
- 3 year shelf life
- UL Classified systems up to 4 hrs.
- Complies to UL required Accelerated Aging and High Humidity Testing
- STC rating 62
- **Test Standards:** ASTM E814 (UL 1479) & ASTM E1966 (UL 2079), Mold inhibitor tested to ASTM G21

Applications:

- Metal pipes
- Insulated pipes
- Fiberglass & plastic pipes
- Wall construction joints
- Power & telephone cables

PART NO.	DESCRIPTION	QTY
66640	10.3 oz. cartridge	12
66303	30 oz. cartridge	12
66312	20.2 oz. foil pack	12
66305	1 gal.	4
66307	2 gal.	1
66309	5 gal.	1

Metacaulk® MC 150+

General Purpose Firestop Sealant

Features and Benefits:

- One component, general purpose fire-rated sealant and smoke seal for construction joints and through-penetrations on both horizontal and vertical surfaces
- Non-sag caulking grade sealant that is easy to apply as well as to retrofit
- Can be used in areas under constant vibration or movement
- Flexible
- Non-sag
- UL Classified up to 4 hrs.
- 3 year shelf life
- Color: Red
- STC rating 65
- **Test Standards:** ASTM E814 (UL 1479) & ASTM E1966 (UL 2079), Mold inhibitor tested to ASTM G21

Applications:

- Metal pipes
- Insulated pipes
- Fiberglass and plastic pipes
- Wall construction joints
- Power and telephone cables

PART NO.	DESCRIPTION	QTY
66648	10.3 oz. cartridge	12
66383	30 oz. cartridge	12
66385	20.2 oz. foil pack	12
66389	5 gal.	1

Metacaulk® 350i

Intumescent Firestop Sealant

Features and Benefits:

- One component, general purpose sealant and smoke seal
- Intumescent, water-based, non-sag caulking grade sealant that is easy to apply and great for retrofits
- Suitable for dynamic movement
- Flexible
- Excellent freeze-thaw
- For interior use - paintable
- 3 year shelf life
- Complies to UL required
- Accelerated Aging and High
- Humidity Testing
- Color: Red
- STC rating 53
- **Test Standards:** ASTM E814 (UL 1479) & ASTM E1966 (UL 2079)

Applications:

- Metal pipes
- Insulated pipes
- Fiberglass & plastic pipes
- Wall construction joints
- Power & telephone cables

PART NO.	DESCRIPTION	QTY
66648	10.3 oz. cartridge	12
66383	30 oz. cartridge	12
66385	20.2 oz. foil pack	12
66389	5 gal.	1

STANLEY_SUPPLY.indd 172-173