RECTORSEAL

METACAULK® FIRESTOP SEALANTS

Metacaulk® 835+

Elastomeric, Silicone Firestop Sealant

Features and Benefits:

- For systems where dynamic movement is expected
- Resistant to chemical exposure
- Exterior / interior use
- Weather/chemical resistant
- Excellent moisture resistance
- 2 year shelf life
- Color: Gray
- STC rating 55
- Meets ASTM C920, Type S, Grade NS, Class 25, Use NT, M, G, A, O
- **Test Standards:** ASTM E814 (UL 1479) & ASTM E1966 (UL 2079)

PART NO.	DESCRIPTION	QTY
66645	10.15 oz. cartridge	12
66019	5 gal.	1
66300	20.2 oz caulk grade	12
66301	20.2 oz self-leveling	12

Applications:

- Cable and cable trays and EMT
- Insulated/uninsulated steel pipe
- Construction / control joints
- Interior expansion joints

Metacaulk® 950

Non-Combustible Firestop Sealant

Features and Benefits:

- Formulated with inorganic materials
- Not for use in vibration or wet environments
- Gas/Smokeless under fire exposure
- Hardened cure
- Interior application
- 2 year shelf life
- Color: Beige
- **Test Standards:** ASTM E814 (UL 1479) & ASTM E1966 (UL 2079)

Applications:

- Cable and cable trays
- EMT
- Insulated and uninsulated steel pipe
- Construction and control joints
- Interior expansion joints

PART NO.	DESCRIPTION	QTY
66643	10.3 oz. cartridge	12

Metacaulk® 1200

Spray & Caulk Firestop Mastic

Features and Benefits:

- Cures to an elastomeric membrane seal suitable for dynamic movement
- Mastic spray for fast, economical installation on long joint runs
- Flexible with freeze-thaw
- 3 year shelf life
- Color: Red or White
- STC rating 65
- UL Classified up to 4 hrs
- **Test Standards:** ASTM E814 (UL 1479) & ASTM E1966 (UL 2079), Mold inhibitor tested to ASTM G21

Applications:

- Construction joints such as: top of the wall, curtain wall perimeter, expansion, and control
- Cable trays
- HVAC Ductwork
- Deflection
- Track Wall Systems

PART NO.	DESCRIPTION	COLOR	QTY
66379	5 gal. spray	Red	1
66292	20.2 oz. caulk grade	Red	12
66015	30 oz. caulk grade	Red	12
66387	5 gal. caulk grade	Red	1
66529	5 gal. spray (USA)	Red	1

PART NO.	DESCRIPTION	COLOR	QTY
66527	5 gal. spray	White	1
66294	20.2 caulk grade	White	12
66525	30 oz. caulk grade	White	12
66526	5 gal. spray (USA)	White	1
66386	5 gal caulk grade	White	1

C70 Industrial Coating

Acrylic Latex for Power Cables

Features and Benefits:

- Acrylic latex heavy duty spray coating designed to prevent vertical and horizontal spread of fire along grouped or single communication or power cables
- Compatible with and adheres to typical cable jacketing materials
- No cable derating
- Interior use
- Easy to apply
- Cures to a flexible seal
- 2 year shelf life
- Color: Gray or White

Applications:

- Suitable for areas of limited movement

PART NO.	DESCRIPTION	QTY
50250	5 gal. gray	1
50253	5 gal. white	1