FLUSH ACCESS DOORS

UF-5000 Universal Flush

- One piece trim flange will not rack, sag or distort
- Unique continuous concealed hinge will not bind
- Door panel has rounded safety corners providing an architecturally pleasing appearance
- **Applications:** Installation in drywall, paster, masonry, tile or any flush surface

SPECIFICATIONS	
Door:	Flush to frame with rounded safety corners
Finish:	Steel: 5-stage iron phosphate preparation with prime-coat of White alkyd baking enamel OR Stainless Steel: Type 304 - #4 satin polish
Hinge:	Continuous, concealed
Material:	Up to 16" X 16" - 16 gage, 18 gage mounting frame, over 16" X 16" - 14 gage door, 16 gage mounting frame
Mounting:	Frame: One piece outer flange welded to mounting frame
Optional Latches/Locks	Cylinder lock and key, allen head cam latch, spanner head cam latch
Standard Latch:	Stainless steel screwdriver operated cam latch

NOMINAL DOOR SIZE (W X H)	NO. OF LATCHES	WEIGHT
6" x 6"	1	2 lb.
8" x 8"	1	2.7 lb.
8" x 12"	1	3.6 lb.
10" x 10"	1	3.6 lb.
12" x 12"	1	4.7 lb.
12" x 16"	2	6 lb.
12" x 18"	2	7 lb.
12" x 24"	2	8.5 lb.
14" x 14"	1	6.2 lb.
16" x 16"	2	7.6 lb.
16" x 24"	2	12.5 lb.
18" x 18"	2	11.2 lb.
18" x 24"	2	15 lb.
22" x 22"	4	16.3 lb.
22" x 30	5	21 lb.
22" x 36"	5	26 lb.
24" x 24"	4	18 lb.
24" x 30"	5	22.5 lb.
24" x 36"	5	26.6 lb.
24" x 48"	5	38 lb.
30" x 30"	5	27.5 lb.
36" x 36"	5	39 lb.

DW-5040 Flush for Drywall

- Formed door panel with flanges on four sides
- Unique concealed hinge, door flange is a perforated taping bead with pre-punched hole
- **Applications:** Designed specifically for installation in drywall walls and ceilings after the drywall has been installed

SPECIFICATIONS	
Door:	Formed door panel, flanged on four sides, Integral perforated taping bead adds extra rigidity
Finish:	5 stage iron phosphate preparation with white baked-on polyester powder coat on door panel. Frame to be mill finish
Hinge:	Concealed
Material:	20 gauge galvanized formed door panel, 26 gauge galvanized frame
Standard Latch:	Slot screwdriver operated cam latch Optional Latches/Locks: Cylinder lock & key; allen head cam latch; spanner head cam latch, torx

NOMINAL DOOR SIZE (W X H)	NO. OF LATCHES	WEIGHT
6" x 6"	1	3 lb.
8" x 8"	1	3.5 lb.
10" x 10"	1	4.5 lb.
12" x 12"	1	6 lb.
14" x 14"	1	7.5 lb.
16" x 16"	2	9.5 lb.
18" x 18"	2	11.5 lb.
22" x 22"	4	15 lb.
24" x 24"	4	19 lb.
24" x 36"	5	28 lb.
30" x 30"	5	27.5 lb.
36" x 36"	5	39 lb.

6/15/24 12:51 PM