Legs®

Wallboard Anchor

Expansion anchor
Pierce point; no pre-drilling

Wallboard

Zinc plated carbon steel

LEGS WALLBOARD ANCHOR

CAT.NO.	DESCRIPTION	PACK	CTN
02336-PWR	Legs Wallboard Anchor	100	1000
02335-PWR	Legs Anchor w/ No.8 x 1" Screw	100	1000

MASTER PACK

CAT #	DESCRIPTION	MASTER CTN
02338-PWR	Legs Wallboard Anchor	5000

Zip-All®

Wallboard Anchor

Self drilling
Use No. 6 or No. 8 screws

Wallboard

Zamac alloy

ZIP-ALL

CAT #	WALL THICKNESS	DESCRIPTION	PACK	CTN
02297-PWR	3/8" to 1"	Zinc - with screws	100	1000

Fluted Plastic Anchor

Plastic Wall Anchor

Light duty
Use with sheet metal or wood screw

Normal-weight concrete

Engineered plastic

FLUTED PLASTIC ANCHOR

CAT #	SIZE	COLOR	DRILL DIAMETER	PACK	CTN
07500-PWR	#4-#6 x 1"	White	3/16"	100	5,000
07510-PWR	#10-#12 x 1"	Green	1/4"	100	5,000
07515-PWR	#10-#12 x 1-1/4"	Green	1/4"	100	1,000
07520-PWR	#10-#12 x 1-1/2"	Green	1/4"	100	1,000
07530-PWR	#14 x 1-1/2"	Blue	5/16"	100	1,000

Strap-Toggle™

Hollow Wall Anchor

Federal GSA Specification – Meets the descriptive requirements of FF-B-588D Type V for a captive toggle (superseded)

Heavy duty
Small installation hole; removable
Accommodates range of wall thicknesses

Wallboard hollow concrete masonry

Engineered plastic and carbon steel wings

STRAP-TOGGLE (not packed with screws)

CAT #	SIZE	DRILL DIAMETER	WALL THICKNESS	PACK	CTN
04052-PWR	3/16" x 4	1/2"	3/8" - 2-1/2"	50	300
04054-PWR	1/4" x 4-1/2"	1/2"	3/8" - 2-1/2"	50	300
04056-PWR	3/8" x 4"	3/4"	3/8" - 2-1/2"	25	150

STRAP-TOGGLE INSTALLATION