Drive & Head Styles	HWH Hex Washer Head	TFH Phillips Trimfit Flat Head	PFH Phillips Flat Head
Drive	3/8" Hex	#3 Bit Drive	#3 Bit Drive
Washer Face Dia.	0.520"	NA	NA
Head Dia.		0.400"	0.460"
Head Height	0.240"	0.158"	0.210"
Flare	-	80°	80°

Cat #	Length	Drive Size	Drill Bit Size	Box Qty*	Box Wt
#14 Diameter, Hex Washer Head - Stalgard® SUB Silver (2,000 Hour)					
EMR155	1-3/4"	3/8" hex	7/32"	1,000	36
EMR165	2-1/4"	3/8" hex	7/32"	1,000	30
EMR175	2-3/4"	3/8" hex	7/32"	800	25
EMR185	3-1/4"	3/8" hex	7/32"	500	23
EMR195	3-3/4"	3/8" hex	7/32"	500	21
#14 Phillips Flat Head - Silver Stalgard® (1,000 Hr)					
EMR110	1-3/4"	#3 Phillips	7/32"	2,000	44
EMR120	2-1/4"	#3 Phillips	7/32"	1,500	35
EMR130	2-3/4"	#3 Phillips	7/32"	1,000	30
EMR140	3-1/4"	#3 Phillips	7/32"	1,000	26
EMR150	3-3/4"	#3 Phillips	7/32"	500	23
#14 TrimFit Flat Head - Silver Stalgard® (1,000 Hr)					
EMR113	1-3/4"	#3 Phillips	7/32"	2,000	51
EMR123	2-1/4"	#3 Phillips	7/32"	1,500	40
EMR133	2-3/4"	#3 Phillips	7/32"	1,000	31
EMR143	3-1/4"	#3 Phillips	7/32"	1,000	27
EMR153	3-3/4"	#3 Phillips	7/32"	500	25
#14 TrimFit Flat Head - White Stalgard® (1,000 Hr)					
EMR124	2-1/4"	#3 Phillips	7/32"	1,500	40
EMR134	2-3/4"	#3 Phillips	7/32"	1,000	33
EMR144	3-1/4"	#3 Phillips	7/32"	1,000	27

Note: Length measured under head for hex head anchors, total length for flat head and trim flat head anchors. See diagram above.

Masonry Drill Bits

Drill Bit	Drill Diameter	Overall Length	Usable Bit Length	Drill Bit Shank Type
EMC100	7/32" ANSI	4-1/2"	2-3/4"	Tanged
EMC110		5-1/2"	4"	
EMC130		7"	4"	Hex SDS

RapidSet® Tools

The fastest, easiest and most reliable way to install machine screw anchors

Efficient RapidSet® tools eliminate clumsy hammer and -setting processes or expensive, slow expander tools.*

Specifications

- For machine screw anchor sizes #10, 1/4" and 3/8"
- Designed for use with power tools, including battery impact drivers
- MAXX model allows placement of 1/4" anchors at various depths (up to 2") below the surface

Features & Benefits

- Power tool does all the work – no pounding with setting tools
- Automatically sets anchor just below the surface
- Maximizes expansion of bottom portion of lead sleeve, which results in consistently high pull-out values

Cat #	For Insert-Anchor Size
Standard RapidSet tool	
EZB790	#10-24
EZB800	1/4-20
EZB820	3/8-16
RapidSet MAXX tool	
EZB810	1/4-20
Repair Kits	
EZB811	Repair Kit for EZB810 (Rapidset MAXX Tool)
EZB801	Repair Kit for EZB800 (Rapidset Tool for 1/4-20 Inserts)

* Note: RapidSet tools draw the anchor's internal insert up into the anchor's outer sleeve; this installation process eliminates the need to maintain a back bearing surface (required by hammer setting tools).

STANLEY_SUPPLY.indd 38-39