HDU AND HDQ HOLDOWNS

SIMPSON Strong-Tie

HDQ, HDU and HD series

- Supplied with Strong-Drive® SDS screws

PRODUCT NO.	DESCRIPTION
HD3B	HD3B BOLTED HOLDOWN
HD5B	HD5B BOLTED HOLDOWN
HD7B	HD7B BOLTED HOLDOWN
HD9B	HD9B BOLTED HOLDOWN
HD12	HD12 BOLTED HOLDOWN
HD19	HD19 BOLTED HOLDOWN
HDU2	HDU2 SDS2.5 W/SCREWS
HDU4	HDU4 SDS2.5 W/SCREWS
HDU5	HDU5 SDS2.5 W/SCREWS
HDU8	HDU8 SDS2.5 W/SCREWS
HDU11	HDU11 SDS2.5 W/SCREWS
HDU14	HDU14 SDS2.5 W/SCREWS
HDQ8SDS3	HDQ8 SDS3 W/SCREWS
DTT2Z	MULTIPURPOSE HOLDOWN

⚠ WARNING ⚠
Cancer Harm - **www.P65Warnings.ca.gov**

STC ROOF TRUSS CLIPS

SIMPSON Strong-Tie

For alignment control between a roof truss and nonbearing walls

- 1-1/2" slot permits vertical truss chord movement when loads are applied
- 18 gauge
- Galvanized finish

PRODUCT NO.
STC

A34 FRAMING ANCHOR

SIMPSON Strong-Tie

- Use with 8, 8d x 1-1/2" nails
- Sold as 100 per pack (priced per unit)

PRODUCT NO.
A34

GABLE END WALL CONNECTOR

SIMPSON Strong-Tie

Attaches to gable trusses and provides good lateral wind resistance

- Zinc galvanized finish containing 0.90 ounces of zinc per square foot of surface area
- Includes: 10 gusset angles, 40 SDS 1/4" x 1-1/2" screws and 40 SDS 1/4" x 3" screws

PRODUCT NO.
HGA10KT

A35 FRAMING ANCHOR

SIMPSON Strong-Tie

Instant, accurate field bends for all two- and three-way ties

- Use with 9d/12d x 1-1/2" nails
- Sold as 100 per pack (priced per piece)

PRODUCT NO.	FINISH
A35Z	HOT DIP GALVANIZED
A35	ZINC GALVANIZED FINISH

DOUBLE-SHEAR JOIST HANGER

SIMPSON Strong-Tie

Allows for fewer nails and fast installation

- Double-shear nailing distributes the load for greater strength
- Use 10d common nails for header and joist
- Codes: ICC-ES ESR, City of L.A., Florida

PRODUCT NO.	SIZE	GAUGE
HUS18110	1-3/16" X 8-7/8" X 3"	14
LUS282	3-1/8" X 7-3/16" X 2"	14
HUS410	3-9/16" X 8-15/16" X 2"	14
HUS412	3-9/16" X 10-1/2" X 2"	14
HUS26	1-5/8" X 5-3/8" X 3"	16
LUS24	1-9/16" 3-1/8" 1-3/4"	18
LUS26	1-9/16" X 4-3/4" X 1-3/4"	18
LUS28	1-9/16" X 6-5/8" X 1-3/4"	18
LUS210	1-9/16" X 7-13/16" X 1-3/4"	18
LUS2102	3-1/8" X 9" X 2"	18
LUS46	3-9/16" X 4-3/4" X 2"	18

LSSJ FIELD-ADJUSTABLE JACK HANGER

SIMPSON Strong-Tie

Accommodates roof pitches from 0:12 to 12:12

- Versatile hinged swivel seat adjusts easily and provides more support ot joist for higher loads
- Straightforward design makes installation quick and intuitive
- Flange design for easy skew adjustment from 0° to 45°
- ZMAX® coating
- Can be installed as a retrofit

PRODUCT NO.	DESCRIPTION
LSSJ210RZ	1-9/16" X 8" RIGHT-SIDE SKEWED
LSSJ210LZ	1-9/16" X 8" LEFT-SIDE SKEWED

URFP RETROFIT FOUNDATION PLATES

SIMPSON Strong-Tie

Increased load while maintaining adjustability during installation

- Longitudinal embossments, stiffening darts, and scalloped slotted holes
- Allows for one-for-one replacement of 1/2" or 5/8" mudsill anchors
- 14-gauge galvanized steel

Includes: 1/4" x 3" SDS heavy-duty connector screws

PRODUCT NO.	DESCRIPTION
URFPSDS3	W/SDS SCREWS
URFPSDS3B	W/SDS SCREWS - BULK (570CT)

⚠ WARNING ⚠
Cancer Harm - **www.P65Warnings.ca.gov**