MALLEABLE

DROP-FORGED

METHODS OF APPLICATION:

1. Turn back the specified amount of rope from the thimble. Apply the first clip one base width from the dead end of the wire rope.

2. Apply the next clip as near the loop as possible. Turn on the nuts but do not tighten.

3. Space additional clips equally between the first two. Take up rope slack. Tighten all nuts evenly on all clips.

MALLEABLE & DROP-FORGED WIRE ROPE CLIPS

SIZE	MALLEABLE, ZINC PLATED					DROP-FORGED, HOT GALVANIZED				
	STOCK NUMBER	WEIGHT/ 100 PCS. (LBS.)	MIN. CLIPS REQ'D	TORQUE IN LBS. FT.*	TURN BACK LENGTH	STOCK NUMBER	WEIGHT/ 100 PCS. (LBS.)	MIN. CLIPS REQ'D	TORQUE IN LBS. FT.*	TURN BACK LENGTH
1/16"	MWRC062	3	3	2	3"	-	-	-	-	-
1/8"	MWRC125	4	3	3	4 3/4"	DFWRC125	5	2	4.5	3 1/4"
3/16"	MWRC187	7	3	4.5	5 1/2"	DFWRC187	10	2	7.5	3 1/4"
1/4"	MWRC250	14	3	15	7"	DFWRC250	18	2	15	4 3/4"
5/16"	MWRC312	15	3	15	7 3/4"	DFWRC312	31	2	30	5 1/4"
3/8"	MWRC375	21	3	30	9 1/2"	DFWRC375	46	2	45	6 1/2"
7/16"	MWRC437	37	4	40	10 1/4"	DFWRC437	73	3	65	7"
1/2"	MWRC500	38	4	45	15 1/4"	DFWRC500	73	3	65	11 1/2"
9/16"	MWRC562	59	4	50	16"	DFWRC562	96	3	95	12"
5/8"	MWRC625	59	4	75	16"	DFWRC625	104	3	95	12"
3/4"	MWRC750	84	5	75	22 1/4"	DFWRC750	150	4	130	18"
7/8"	MWRC875	125	5	130	23 1/2"	DFWRC875	244	4	225	19"
1"	MWRC100	166	6	130	31"	DFWRC100	270	5	225	26"
1 1/8"	MWRC1125	211	7	200	39 1/2"	DFWRC1125	310	6	225	34"
1 1/4"	-	-	-	-	-	DFWRC1250	460	7	360	44"
1 3/8"	-	-	-	-	-	DFWRC1375	520	7	360	44"
1 1/2"	-	-	-	-	-	DFWRC1500	590	8	360	54"
1 3/4"	-	-	-	-	-	DFWRC1750	980	8	590	58"

Torque values shown are based on clean, unlubricated threads. Wire rope clips are not designed for load carrying purposes, therefore working load limits have not been established.

Note: Malleable Wire Rope Clips made according to Federal Specification FF-C-450 D, Type 1, Class 2. Forged Wire Rope Clips made according to Federal Specification FF-C-450 D, Type 1, Class 1.
All parts are Hot Dip Galvanized. The U Bolt is Hot Dip Galvanized, then Powder Coated.

STAINLESS STEEL

DOUBLE GRIP

316 STAINLESS STEEL

SIZE	STOCK NUMBER	WT./ 100 PCS.	MIN. CLIPS REQ'D	TURN BACK LENGTH
1/16"	SWRC062	2	2	2 1/2"
1/8"	SWRC125	5	2	3 1/4"
3/16"	SWRC187	11	3	3 3/4"
1/4"	SWRC250	19	3	4 3/4"
5/16"	SWRC312	30	3	5 1/4"
3/8"	SWRC375	46	3	6 1/2"
1/2"	SWRC500	68	3	11 1/2"
5/8"	SWRC625	92	3	12"
3/4"	SWRC750	104	4	18"
7/8"	SWRC875	168	4	19"
1"	SWRC100	186	5	26"

DOUBLE GRIP - HOT GALVANIZED

SIZE	STOCK NUMBER	WT./ 100 PCS.	MIN. CLIPS REQ'D	TURN BACK LENGTH
1/4"	FIST250	18.5	2	4"
5/16"	FIST312	28	2	5"
3/8"	FIST375	40	2	5 1/2"
7/16"	FIST437	70	2	6 1/2"
1/2"	FIST500	75	3	11"
9/16"	FIST562	100	3	12 3/4"
5/8"	FIST625	100	3	13 1/2"
3/4"	FIST750	175	3	16"

STANLEY_SUPPLY.indd 164-165