Tractel Group

FEATURES

- Working Load Limit: 1,500 lbs. / 3/4 Ton
- Lengths Available: 5, 10, 15, 20, 30 Feet Lift
- Load Chain Size : 6 x 18 mm
- Number of Falls: 1
- Effort on lever at capacity: 44 lbs. / 20 kg
- 360° swivel hook with overload opening indicators
- Removable large-opening swivel hook with large latch marked with working load limit of the hoist
- Five sprocket load wheel with closed bearings
- Free wheel safety device activates braking mechanism when load applied in neutral position
- The hoist and its components are made of high tensile alloy steel
  - Anti-corrosion treated lifting and handling line
  - Operates in temperatures between -40 and 140°F (-40 and 60°C)
- Wind-through chain system for fast hook positioning
- Automatic brake with double ratchet

bravo™ Lever Chain Hoist - 3/4 Ton / 1 500 lbs

19669	bravo™ Lever Chain Hoist 3/4 Ton - 5 Ft. Lift
19670	bravo™ Lever Chain Hoist 3/4 Ton - 10 Ft. Lift
19671	bravo™ Lever Chain Hoist 3/4 Ton - 15 Ft. Lift
19672	bravo™ Lever Chain Hoist 3/4 Ton - 20 Ft. Lift
19673	bravo™ Lever Chain Hoist 3/4 Ton - 30 Ft. Lift

Tractel Group

Griphoist Manual Wire Rope Hoist, 2,000 lb. 1 Ton

PART NO.	
00869912430K	griphoist® Wire Rope Hoist 1 Ton - 30 Ft. Assembly -
00869912460K	griphoist® Wire Rope Hoist 1 Ton - 60 Ft. Assembly -
008699124100K	griphoist® Wire Rope Hoist 1 Ton - 100 Ft. Assembly -
008699124150K	griphoist® Wire Rope Hoist 1 Ton - 150 Ft. Assembly -
008699124200K	griphoist® Wire Rope Hoist 1 Ton - 200 Ft. Assembly -
008699124250K	griphoist® Wire Rope Hoist 1 Ton - 250 Ft. Assembly -

Tractel Group

Chain Hoists

- FEATURES
- Operates in temperatures between -40 and 140°F (-40 and 60°C)
- Working load limit (WLL) of 500 to 40,000 lbs. (1/4 to 20 t)
- 360° swivel hook with overload opening indicators
- Automatic brake with double pawl system
- Tested to 150% of WLL
- Heavy duty construction: hoist body constructed with six through
- bolts and rugged cover
- Standard lift: 10 ft., 15 ft., 20 ft. (others available)
- Alloy load hook enables user to see if hook is deformed by overload
- Extra large hook latch
- Bolted hook latch
- Improved chain stop
- Anti-corrosion treated lifting and handling line
- Grade 80 chain

MODEL	¼t	½t	1 t	1½t	2 t	3 t	5 t	10 t	20 t
Capacity	500 lbs. (250 kg)	1,000 lbs. (500 kg)	2,000 lbs. (1,000 kg)	3,000 lbs. (1,500 kg)	4,000 lbs. (2,000 kg)	6,000 lbs. (3,000 kg)	10,000 lbs. (5,000 kg)	20,000 lbs. (10,000 kg)	40,000 lbs. (20,000 kg)
Standard lift	Lengths available: 10, 15, 20, 30 and 40 ft.								
Number of falls	1	1	1	1	1	2	2	4	8

STANLEY_SUPPLY.indd 92-93