FLEXVOLT™ 60V MAX* BRUSHLESS 7-1/4" WORM DRIVE STYLE SAW

DEWALT FLEXVOLT BRUSHLESS MOTOR

5,800 rpm, 2-7/16" cut capacity at 90°, direct drive motor

- Rear-handle and left-oriented blade for easy line of sight
- Bevel capacity of 53° with stops at 45° and 22.5°
- Integrated dust blower to clear line of sight
- Electronic brake stops blade when trigger released
- Durable, high-grade magnesium shoe and efficient brushless motor for smooth, accurate cuts and long runtime
- Onboard blade wrench storage and integrated rafter hook

Includes: 20V MAX fan corded fast charger, 1 FLEXVOLT™ 9.0 Ah battery, (1) 7-1/4" FLEXVOLT™ carbide-tipped circular saw blade, blade wrench, user manual, contractor bag

PRODUCT NO.	DESCRIPTION
DCS577B	BARE TOOL
DCS577X1	60V FRAME SAW KIT

⚠ WARNING ⚠
Cancer and Reproductive Harm - **www.P65Warnings.ca.gov**

FLEXVOLT™ 20V/60V MAX* LITHIUM-ION 9.0AH BATTERY

DEWALT FLEXVOLT

Powers all 20V Max, 60V Max, and 120V Max tools

- LED state of charge display
- 9.0 Ah capacity when used with 20V Max tool
- Compatible with all 20V Max tools

PRODUCT NO.	DESCRIPTION
DCB6092	9.0AH 2-PACK
DCB609	9.0AH 1-PACK

⚠ WARNING ⚠
Cancer and Reproductive Harm - **www.P65Warnings.ca.gov**

FLEXVOLT™ 20V/60V MAX* 6.0 AH BATTERY

DEWALT FLEXVOLT

Powers a new line of 60V MAX and 120V MAX tools, compatible with the 20V MAX* system of tools and chargers

- 3-LED fuel gauge
- One piece cell holder construction
- Shipping Cap for use when shipping converts battery pack to 3 x 40Whr configuration
- 3X power compared to DC9096 18V battery, 4X runtime compared to DCB201 1.5Ah battery pack
- Weighs 2.3 lbs.

PRODUCT NO.	DESCRIPTION
DCB6062	2-PACK BATTERIES
DCB606	BATTERY

⚠ WARNING ⚠
Cancer and Reproductive Harm - **www.P65Warnings.ca.gov**

DEWALT

NEW

DCS692X2

60V MAX* BRUSHLESS CORDLESS 9" CUT-OFF SAW (9.0 Ah) (2 BATTERY KIT)

- Rotatable, 5-position guard for optimized approach angle and improved visibility versus fixed guard.
- 3-1/4" (83 mm) depth of cut for single pass in pavestones, rebar cutting, and concrete scoring.
- All-metal drivetrain for durability and efficiency.
- Latched battery box protects against airborne dust and water.
- Dual-sided water delivery system for optimal dust management when cutting concrete.
- Tool Connect™ System TAG READY - Track This Tool™
- New Battery Door Designed to fit DCB615 (15.0 Ah battery) for extended run time.
- Wireless Tool Control - Tool activated remote control for water management.
- 2-stage trigger required to meet safety requirements.

TOOL CONNECT™ | 60V MAX* BRUSHLESS | POWERED BY FLEX VOLT™

Maximum initial battery voltage (measured without a workload) is 20 and 60 volts. Nominal voltage is 18 and 54. All amp hours (Ah) shown with 60V MAX products are measured in 20V MAX* mode.

GDS/22-2911636

6/15/24 12:52 PM