CHARGERS

20V MAX* CHARGERS

12V-20V/60V MAX* Dual Port Charger

DCB102

12V 20V 60V

SPECIFICATIONS	
Compatibility	12V MAX*, 20V MAX*, 20V/60V MAX*
Output Current	4 Amps per Port
Wall Mountable	No
Handle	No
Tool Connect Tag Ready™	No
USB Outlets	Yes
Fan Cooled	No

12V-20V/60V MAX* Vehicle Charger

DCB119

12V 20V 60V

SPECIFICATIONS	
Compatibility	12V MAX*, 20V MAX*, 20V/60V MAX*
Output Current	4 Amps
Wall Mountable	No
Handle	No
Tool Connect Tag Ready™	No
USB Outlets	No
Fan Cooled	No

12V-20V-60V MAX* Charger

DCB115

12V 20V 60V

SPECIFICATIONS	
Compatibility	12V MAX*, 20V MAX*, 20V/60V MAX*
Output Current	4 Amps
Wall Mountable	Yes
Handle	No
Tool Connect Tag Ready™	No
USB Outlets	No
Fan Cooled	No

20V MAX* Fast Charger

DCB118

20V 60V

SPECIFICATIONS	
Compatibility	12V MAX*, 20V MAX*, 20V/60V MAX*
Output Current	4 Amps
Wall Mountable	Yes
Handle	No
Tool Connect Tag Ready™	No
USB Outlets	No
Fan Cooled	Yes

1800 Watt Portable Power Station™ and Simultaneous Charger

DCB1800B

SPECIFICATIONS	
Output	120V MAX*
Compatibility	20V MAX* Lithium Ion Batteries and 20V/60V MAX* FLEXVOLT® Lithium Ion Batteries
Max AC Output	3600 Watts Peak
Rated AC Output	1800 Watts Continuous
Power Source	Extension cord, and batteries sold separately.

20V 60V

Simultaneous Four-Port Fast Charger

DCB104

12V 20V 60V

SPECIFICATIONS	
Compatibility	12V MAX*, 20V MAX*, 20V/60V MAX*
Output Current	8 Amps per Port (4 Ports)
Wall Mountable	Yes
Handle	Yes
Tool Connect Tag Ready™	Yes
*TOUGH*SYSTEM® Compatible	Yes
USB Outlets	No
Fan Cooled	No

Combination Dual Port Charger

DCB103

12V 18 VOLT 20V 60V

SPECIFICATIONS	
Compatibility	7.2V-18V, 12V MAX*, 20V MAX*, 20V/60V MAX*
Output Current	2.5 Amps, 4 Amps
Wall Mountable	No
Handle	No
Tool Connect Tag Ready™	No
USB Outlets	No
Fan Cooled	No

20V MAX* BATTERY ACCESSORIES

18V to 20V MAX* Adapter

DCA1820

18 VOLT 20V

SPECIFICATIONS	
Voltage	18V to 20V MAX*
Not For Use With	DEWALT 18V Nailers, DEWALT Charger / Radios, DCS370 Band Saw

AVAILABLE	
DCA1820	Battery Adapter Only.
DCA2203C	Also Includes: (2) 20V MAX* Lithium Ion Batteries (2.0 Ah) and Charger

USB Power Source

DCB090

12V 20V 60V

SPECIFICATIONS	
Voltage	12V MAX*, 20V MAX*, 20V/60V MAX*
USB Ports	2
State of Charge Indicator	Yes
Tool Weight (Tool only)	0.5 lbs

6/15/24 12:52 PM