Milwaukee

Shear Pin and Clutch Models

- Two speed Dymodrill Motors for use with Vac-U-Rig and Dymorig Diamond Core Rigs
- Triple reduction gearing on all models
- Built-in water swivel on all models
- All ball and roller bearings
- Shear Pin Protection protects gears and motor against overload; Shear pins easily replaced; Extra pins included with each unit
- Clutch Protection protects gears and motor against overload; Set to specifications at factory, no adjustment necessary

15 AMP MODELS

PART NO.	AMP	SPINDLE	RPM	SUGGESTED DIA./MED. AGGREGATE	TYPE
4090	15	1-1/4-7	375-750	5" - 8" / 2-1/2 "- 5"	Shear Pin
4092-20	15	1-1/4-7	375-750	5" - 8" / 2-1/2" - 5"	Clutch
4097-20	15	1-1/4-7	500-1000	3" - 5" / 1-1/4" - 3"	Clutch

20 AMP MODELS

PART NO.	AMP	SPINDLE	RPM	SUGGESTED DIA./MED. AGGREGATE	TYPE
4079	20	1-1/4-7	300-600	7" - 14" / 4" - 7"	Shear Pin
4004-20	20	1-1/4-7	300-600	7" - 14" / 4" - 7"	Clutch
4094	20	1-1/4-7	450-900	6" - 10" / 2 "- 6"	Shear Pin
4005	20	1-1/4-7	600-1200	4" - 7" / 3/4" - 4"	Clutch

Milwaukee

Contractor Series Drilling Rig Base Stands

- Cast aluminum base with four leveling screws for fast accurate leveling adjustment
- Durable precision-ground 2-1/2 in. steel column, 43-1/2 in. high
- Rear mounted rack and pinion feed
- Jackscrew for ceiling and backwall bracing

PART NO.	DESCRIPTION
4115	Diamond Coring Small Base Stand
4120	Diamond Coring Large Base Stand
4120-22	Diamond Coring Rig with Large Base Stand, Vac-U-Rig® Kit, Meter Box and Diamond Coring Motor
4115-22	Diamond Coring Rig with Small Base Stand, Vac-U-Rig® Kit, Meter Box and Diamond Coring Motor

Milwaukee

Diamond Coring Rig w/ Large Base Stand, Vac-U-Rig® Kit & Meter Box

- Cast aluminum base with four leveling screws for fast accurate leveling adjustment
- Adjustable, tilting 2-7/8" × 43-1/2" steel column
- Four speed wheel feed control
- Motor mount cradle, bubble level and jackscrew

PART NO.	DESC.	COLUMN HT.	NET WT.	SHIP WT.
4136	Rig	47"	106 lb.	129 lb.
4130	Stand	47"	82.5 lb.	103.5 lb.

DIAMOND PRODUCTS

CB733 3-Speed Motor Core Rig

- 115/20 amp electric motor with on/off switch (no need for control panel)
- Up to 16" bit capacity (when mounted on M-2, M-5 or M-5 PRO)
- Extra high efficiency 3000W motor in aluminum housing for better cooling and durability
- LED light lets the operator easily know that the motor is near overload conditions
- 1.250"-7 threaded spindle with anti-seize ring to keep Core Bore® bits from getting stuck

PART NO.	DESCRIPTION
M1C	TOOL ONLY

DIAMOND PRODUCTS

M-2 Core Drilling Rig

- Complete rigs include: Dual switch/outlet control panel and amp meter
- 4 spoke handle, 6" wheels
- 2-1/2" square column
- 10" bit capacity, 14" with one spacer, accepts bits 22" overall
- 20 amp Milwaukee motor: 600/1200 RPM, slip clutch safety overide

PART NO.	DESCRIPTION
4241049	TOOL ONLY