TYPE 1 THIN HIGH SPEED CUT-OFF - .045"

A60S
General Purpose

- Thin .045 width
- Use with reusable 5/8-11 adaptor to fit angle grinders
- Extremely fast cutting with long life

METAL Ferrous and/or non-ferrous metals (iron, steel, welds, etc.)

StackPack

SAIT.M.X.™ *(Ferrous Metals)*

- Special bond for cutting sheet metal and other thin gauge metals
- Fast, burr-free cutting

METAL Ferrous metals (carbon steel, etc.)

STAINLESS Stainless steel

A46N - Aluminum
(Non-Ferrous Metals)

- Aluminum oxide grain
- Soft bond for aggressive cutting without loading
- Use with reusable 5/8-11 adaptor to fit angle grinders

ALUMINUM Non-ferrous metals (aluminum, copper, brass, etc.)

XA46R

- Specially formulated for nuclear and food processing plants
- Free of iron, chlorine and sulphur compounds (Fe + Cl + S < 0.1%)
- All wheels are 1/16" thick

STAINLESS Stainless steel and other high tensile alloys

SIZE (IN.) A DIA.	B WID.	C BORE	MAX RPM	GRADES AVAILABLE PART NO. A60S	SAIT. M.X.	A46N	QTY/ BOX	QTY/ CTN	LB./ BOX
4	.045	5/8	19,000	**23099**	-	-	50	200	4
4-1/2	.045	7/8	13,300	**23101**	**23604**	**23314**	50	200	4
5	.045	7/8	12,200	**23103**	**23605**	-	50	200	6
6	.045	5/8	10,200	**23105**	-	-	50	200	8
6	.045	7/8	10,200	**23106**	**23606**	**23316**	50	200	8
7	.045	5/8	8,500	**23107**	-	-	50	200	14

Note: Reusable 5/8-11 adaptor for use on Type 1 and Type 27 reinforced wheels with a 7/8 arbor, a max. diameter of 5" and a wheel thickness of .045 to 1/8"

SIZE (IN.) A DIA.	B WID.	C BORE	MAX RPM	PART NO. XA46R	QTY/ BOX	QTY/ CTN	LB./ BOX
4-1/2	1/16	7/8	13,300	**24251**	50	200	7
5	1/16	7/8	12,200	**24252**	50	200	7
6	1/16	7/8	10,200	**24253**	50	200	14
7	1/16	7/8	8,500	**24254**	50	200	14

TECH INFO

- Thin cutting wheel in a Type 27 / Type 42 shape makes this perfect for your angle grinder
- Designed to provide very long life for fewer wheel changes and less downtime
- All sizes reinforced with the highest quality fiberglass for maximum safety and performance

Type 27 / Type 42

5/8-11 Hub

Angle Grinder