Multi-Purpose Dry Chemical Extinguishers

- Rechargeable
- Anodized metal & brass valve assemblies for corrosion resistance
- Industrial grade steel and aluminum cylinders with polyester powder coating withstand harsh environments and rough usage
- Color-coded gauges show operating status

PART NO.	BRACKET	CAPACITY	UL RATING
12905	Wall	30 lb.	6-A:80-B:C
12120	Wall	20 lb.	6-A:80-B:C
BK11340	Wall	10 lb.	4-A:80-B:C
BK25614	Vehicle	5 lb.	3-A:40-B:C
10914	Wall	5 lb.	3-A:40-B:C
13315	Vehicle	2.5 lb.	3-A:40-B:C

Fire Extinguisher Vehicle Brackets

- Keeps fire extinguisher secure and readily accessible

Mini-Guard Extinguishers

- Supplies supplementary fire protection for some local and total flood applications
- Available in horizontal and vertical mounts and can be charged with Multipurpose Dry Chemical or Halotron
- Suitable for Class A, B & C Fires
- Not intended as a substitute for automatic sprinkler systems, fixed pre-engineered or engineered extinguishing systems and are not intended to be multiple mounted
- Fitted with a detection sprinkler head that is rated at 165° F
- Typical Uses: Spot type extinguishers act as dedicated protection of specialized equipment used in business or manufacturing processes or for specific fire risk areas such as flammable liquid storage rooms (dry chemical) and small electronic data storage rooms (Halotron)

PART NO.	DESC.	WEIGHT
	VERTICAL	
80250	2.5 lb. ABC	4 lbs.
80501	5 lb. ABC	11 lbs.
81001	10 lb. ABC	19 lbs.
82001	20 lb. ABC	36 lbs.
87100	18 lb. Halotron I	29 lbs.
87200	25 lb. Halotron I	42 lbs.
	HORIZONTAL	
80251	2.5 lb. ABC	4 lbs.
80521	5 lb. ABC	11 lbs.
81021	10 lb. ABC	19 lbs.
82021	20 lb. ABC	36 lbs.
87105	18 lb. Halotron I	29 lbs.
87205	25 lb. Halotron I	42 lbs.

Fire Extinguisher Stand

- Superior chemical and corrosion resistance
- Breakaway acrylic panel with hammer assembly – no glass to shatter
- Environmentally safe sand filled base (10 lb. has 20 lbs. of sand)