REMOVABLE CONCRETE ANCHOR

022-4085

The Removable Concrete Anchor is a compact, durable anchor for repeated use in concrete. Easy installation in seconds with quick trigger removal by hand or optional assist with a simple tap. Secure protection while you work and releases quickly when you need to move on.

- Removable and reusable with reliable durability
- 360° rotating connection point for increased mobility
- Easy trigger provides quick release for repeated use
- Durable cap for optional hammer assisted removal
- For horizontal, vertical and overhead use including with HLLs
- 3/4"x 3" drilled hole required for installation
- Length: 6.5"
- Minimum Breaking Strength:
  - 5,000 lbs. (in 3,000 PSI concrete)
  - 10,000 lbs. (in 4,000 PSI or higher concrete)
- Weight Capacity ANSI 130-310 lbs., OSHA 420 lbs.
- ANSI Z359.18-2017 Type T, OSHA 1926.502, 1910.140, 1910.66

Easy Trigger with Cap

Corrosion-Resistant Materials

360° Rotation

5K Removable Concrete Hole Anchor

FS876

- Removable and reusable with reliable durability
- Easy trigger provides quick release for repeated use
- 3/4"x 3" drilled hole required for installation
- Length: 10.75"
- Minimum Breaking Strength: 5,000 lbs.
- Weight Capacity ANSI 130-310 lbs., OSHA 420 lbs.
- OSHA 1926.502, 1910.140, 1910.66

6/15/24 12:53 PM