5K Swivel Anchor & Concrete Wedge Bolt

021-4054

- 180° / 360° rotating connection point for increased mobility
- Quick temporary or permanent installation
- Versatile vertical or horizontal use
- Fits in 1/2" (12.7mm) concrete hole
- Minimum Breaking Strength: 5,000 lbs.
- Weight Capacity ANSI 130-310 lbs., OSHA 420 lbs.
- ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140, 1910.66

5K Swivel Anchor & Concrete Wedge Bolt Options

Part Number	Description
021-4054	5K Swivel Anchor & Concrete Wedge Bolt
021-4057	5K Replacement Concrete Wedge Bolt

10K Swivel Anchor & Concrete Wedge Bolt

021-4072

- 180° / 360° rotating connection point for increased mobility
- Quick temporary or permanent installation
- Versatile vertical or horizontal use
- Fits in 5/8" (15.9mm) concrete hole
- Minimum Breaking Strength: 10,000 lbs.
- Weight Capacity ANSI 130-310 lbs., OSHA 420 lbs.
- ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140, 1910.66

10K Swivel Anchor & Concrete Wedge Bolt Options

Part Number	Description
021-4072	10K Swivel Anchor & Concrete Wedge Bolt
021-4073	10K Replacement Concrete Wedge Bolt

5K Swivel Anchor & Concrete Bolt

021-4052

- 180° / 360° rotating connection point for increased mobility
- Quick temporary or permanent installation
- Versatile vertical or horizontal use
- Galvanized 0.5" x 6" concrete bolt
- Minimum Breaking Strength: 5,000 lbs.
- Weight Capacity ANSI 130-310 lbs., OSHA 420 lbs.
- ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140, 1910.66

5K Swivel Anchor & Concrete Wedge Bolt Options

Part Number	Description
021-4052	5K Swivel Anchor & Concrete Bolt
021-4053	Replacement Concrete Bolt

STANLEY_SUPPLY.indd 282-283